


OTTOSEAL[®] S 105



		0757
Hermann Otto GmbH Krankenhausstr. 14, 83413 Fridolfing, Germany 2014 OC0105D		
EN 15651 - 1, EN 15651 - 2 EN 15651 - 3 1 component silicone sealant, acetate curing for application in the facade for glazing for application in sanitary areas - Type F EXT-INT CC, G CC, S - Conditioning: Process A - Carrier material: Glass - Pre-treatment: OTTO Cleanprimer 1226		
1/2/3-1	Fire behaviour	E
1/2/3-2	Release of chemicals hazardous to health and/or the environment	NPD
Water- and airtightness		
1/2/3-3	Stability under load	≤ 3 mm
1/2-4	Volume loss	≤ 10 %
3-4	Volume loss	≤ 20 %
1/3-5	Tensile behaviour, i.e. stress expansion under pretensioning after submersion in water	NF
1/2-7	Tensile properties / secant modulus in cold climate (at -30°C)	≤ 0,9 MPa
1/2-8	Tensile properties under pretensioning in a cold climate (at -30°C)	NF
2-10	Adhesive/stress expansion action after the effects of heat, water and artificial light	NF
2-11	Resilience	≥ 60 %
3-12	Microbiological growth	0
1/2/3-20	Durability - adhesive/stress expansion at different temperatures	NF