Printing date 25.04.2023

Version 4 (replaces version 3)

Revision: 25.04.2023

SECTION 1: Identification of the substance/mixture and of the company/ undertaking 1.1 Product identifier Trade name: OTTOSEAL M 350 Application of the substance / the mixture Spacings sealent Sealant/ Adhesive 1.3 Details of the subplier of the safety data sheet Manufacturer/Supplier: Hermann Otto GmbH Krankenhausstraße 14 D-83413 Fridoling Tel:: 0049/(0)8684/908-1840 Further information obtainable from: Tel:: 0049/(0)8684/908-1840 Further information obtainable from: Tel:: 0049/(0)8684/908-1840 Fullis parzingre@public-chemie de 1.4 Emergency telephone number: Tel:: 0049/(0) 859 129 40 (emergency telephone no.) +441 1865 407333 (Carechem 24) SECTION 2: Hazards identification 2.1 Classification according to Regulation (EC) No 1272/2008 The product is not classified, according to the GB CLP regulation. 2.2 Label elements Labelling according to Regulation (EC) No 1272/2008 Void Hazard pictograms Void Hazard pictograms Void Hazard pictograms Void 2.3 Other hazards 2.3 Other hazards During processing and curing of the material, chemical substances are released into the air (see point 11). Therefore, ensure good row ne	Tinting date 25.04.2025		Revision: 25.04.2025
 Trade name: OTTOSEAL M 350 Application of the substance / the mixture Spacings sealent Sealant/ Adhesive 1.3 Details of the supplier of the safety data sheet Manufacturer/Supplier: Hermann Otto GrnbH Krankenhausstraße 14 D-834 13 Fridolfing Tel: : 0049(0)8684/908-0 Fax: : 0049(0)8684/908-1840 Further information obtainable from: Tel: : 0049- (0)8684-908-2363 (-4300) F-Mali: Sion Spazinger@dtoc-chemic.de 1.4 Emergency telephone number: Tel: : 0049- (0)864-908 (discontered to the substance or nixture Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008 The product is not classified, according to the GB CLP regulation. 2.1 Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008 Void Hazard pictograms Void Signal word Void Hazard statements Void Additional information: Ensure good ventilation during application and curing. Contains timethoxyvinyIslane. May produce an allergic reaction. Safety data sheet available on request. 2.3 Other hazards During processing and curing of the material, chemical substances are released into the air (see point 11). Therefore, ensure good room ventilation and, if necessary, exhaust ventilation. Rescuits of PBT and VPVB assessment PBT: Not applicable. SECTION 3: Composition/information on ingredients S.2 Mixtures Description: Adhesive and sealant based on silane-terminated polymers (hybrid) Dangerous components: CAS: 2768-02-7 trimethoxyvinyIslane		n of the substance/mixture ar	nd of the company/
Application of the substance / the mixture Spacings sealent Sealent/Adhesive 1.3 Details of the supplier of the safety data sheet Manufacturer/Supplier: Hermann Otto GmbH Krankenhausstraße 14 D-33413 Fridolling Tel.: 0049/(0)8684/908-1840 Further information obtainable from: Tel.: 0049-(0)8684/908-1840 F-Mail: alios parzinger@otto-chemic.de 1.4 Emergency telephone number: Tel:: 0049-(0)8684-908-2363 (-4300) F-Mail: alios parzinger@otto-chemic.de 1.4 Emergency telephone number: Tel:: 0049-(0) 89-19240 (emergency telephone no.) +44 1865 407333 (Carechem 24) SECTION 2: Hazards identification Classification according to Regulation (EC) No 1272/2008 The product is not classified, according to the GB CLP regulation. 2.2 Label elements Labeling according to Regulation (EC) No 1272/2008 Void Hazard statements Void Additional information: Ensure good ventilation during application and curing. Contains trimethoxyvinylsilane. May produce an allergic reaction. Safety data sheet available on request. 2.3 Other hazards During	· 1.1 Product identifier		
 Manufacturer/Suppier: Hermann Otto GmbH Krankenhausstraße 14 D-83413 Fridolfing Tel:: 0049/(0)8684/908-0 Fax:: 0049/(0)8684/908-1840 Further information obtainable from: Tel:: 0049/(0)8684/908-263 (+300) E-Mail: alois.parzinger@otto-chemie.de 1.4 Emergency telephone number: Tel:: 0049/(0)80-2083 (+300) E-Mail: alois.parzinger@otto-chemie.de 1.4 Emergency telephone number: Tel:: 0049/(0)80-2084 (+300) E-Mail: alois.parzinger@otto-chemie.de 1.4 Emergency telephone number: Tel:: 0049/(0)80-2084 (+300) E-Mail: alois.parzinger@otto-chemie.de 2.1 Classification according to Regulation (EC) No 1272/2008 The product is not classified, according to the GB CLP regulation. 2.2 Label elements 1. Labelling according to Regulation (EC) No 1272/2008 Void Hazard pictograms Void Signal word Void Hazard pictograms Void Signal word Void 1.4 Hazard statements Void 2.3 Other hazards During processing and curing of the material. chemical substances are released into the air (see point 11). Therefore, ensure good room ventilation and, if necessary, exhaust ventilation. Results OFBT and VPJB assessment PBT: Not applicable. VPVB: Not applicable. SECTION 3: Composition/information on ingredients SECTION 3: Composition/information on silane-terminated polymers (hybrid) Dangerous components: ImmethoxyvinyIsilane CAS: 2768-02-7 EiNECS: 220-449-8 Reg.nr: 01-2119513215-52-xxxx TB, H317 Specific concentration limit: Skin Sens. 1B; H317: C ≥ 5 % 	 Application of the substance / Spacings sealent 		
Tel.: 0049- (0)8684- 908- 2363 (-4300) E-Maii: alois.parzinger@otto-chemie.de 1.4 Emergency telephone number: Tel.: 0049- (0) 89- 192 40 (emergency telephone no.) +441 1865 407333 (Carechem 24) SECTION 2: Hazards identification SECTION 2: Hazards identification • 2.1 Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008 The product is not classified, according to the GB CLP regulation. • 2.2 Label elements • Labelling according to Regulation (EC) No 1272/2008 Void • Hazard pictograms Void • Signal word Void • Hazard statements Void • Additional information: Ensure good ventilation during application and curing. Contains trimethoxyvinylsilane. May produce an allergic reaction. Safety data sheet available on request. • 2.3 Other hazards During processing and curing of the material, chemical substances are released into the air (see point 11). Therefore, ensure good rom ventilation and, if necessary, exhaust ventilation. • Results of PBT and vPvB assessment • PBT: Not applicable. • VPvB: Not applicable. • VPvB: Not applicable. • VPvB: Not applicable.	<i>Manufacturer/Supplier:</i> Hermann Otto GmbH Krankenhausstraße 14 D-83413 Fridolfing Tel.: 0049/(0)8684/908-0	he safety data sheet	
 2.1 Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008 The product is not classified, according to the GB CLP regulation. 2.2 Label elements Labelling according to Regulation (EC) No 1272/2008 Void Hazard pictograms Void Signal word Void Hazard statements Void Additional information: Ensure good ventilation during application and curing. Contains trimethoxyvinylsilane. May produce an allergic reaction. Safety data sheet available on request. 2.3 Other hazards During processing and curing of the material, chemical substances are released into the air (see point 11). Therefore, ensure good room ventilation and, if necessary, exhaust ventilation. Results of PBT and vPvB assessment PBT: Not applicable. vPvB: Not applicable. SECTION 3: Composition/information on ingredients Safety case and sealant based on silane-terminated polymers (hybrid) Dangerous components:	Tel.: 0049- (0)8684- 908- 2363 (E-Mail: alois.parzinger@otto-che • 1.4 Emergency telephone nun Tel.: 0049- (0) 89- 192 40 (emer	(-4300) emie.de n ber: rgency telephone no.)	
 2.1 Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008 The product is not classified, according to the GB CLP regulation. 2.2 Label elements Labelling according to Regulation (EC) No 1272/2008 Void Hazard pictograms Void Signal word Void Hazard statements Void Additional information: Ensure good ventilation during application and curing. Contains trimethoxyvinylsilane. May produce an allergic reaction. Safety data sheet available on request. 2.3 Other hazards During processing and curing of the material, chemical substances are released into the air (see point 11). Therefore, ensure good room ventilation and, if necessary, exhaust ventilation. Results of PBT and vPvB assessment PBT: Not applicable. vPvB: Not applicable. SECTION 3: Composition/information on ingredients Safety and sealant based on silane-terminated polymers (hybrid) Dangerous components: CAS: 2768-02.7 trimethoxyvinylsilane Secific concentration limit: Skin Sens. 1B; H317: C ≥ 5 % 			
 3.2 Mixtures Description: Adhesive and sealant based on silane-terminated polymers (hybrid) Dangerous components: CAS: 2768-02-7 EINECS: 220-449-8 Flam. Liq. 3, H226; 	The product is not classified, acc • 2.2 Label elements • Labelling according to Regula • Hazard pictograms Void • Signal word Void • Hazard statements Void • Additional information: Ensure good ventilation during a Contains trimethoxyvinylsilane. I Safety data sheet available on re • 2.3 Other hazards During processing and curing of point 11). Therefore, ensure good • Results of PBT and vPvB asse • PBT: Not applicable.	cording to the GB CLP regulation. ation (EC) No 1272/2008 Void May produce an allergic reaction. equest. The material, chemical substances ar od room ventilation and, if necessary,	
CAS: 2768-02-7 trimethoxyvinylsilane <2.5%	• 3.2 Mixtures • Description: Adhesive and sea		ners (hybrid)
EINECS: 220-449-8 Reg.nr.: 01-2119513215-52-xxxx 1B, H317 Specific concentration limit: Skin Sens. 1B; H317: C ≥ 5 %		trimethoxvvinvlsilane	<2.5%
Specific concentration limit: Skin Sens. 1B; H317: C ≥ 5 %	EINECS: 220-449-8	🚸 Flam. Liq. 3, H226; 🚸 Acute Tox	
	-	Specific concentration limit: Skin Se	

(Contd. on page 2)

Printing date 25.04.2023

Version 4 (replaces version 3)

Revision: 25.04.2023

(Contd. of page 1)

Trade name: OTTOSEAL M 350

SECTION 4: First aid measures

· 4.1 Description of first aid measures

After inhalation

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

· After skin contact

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· After eye contact

Rinse opened eye for several minutes under running water. Then consult a doctor.

· After swallowing

Do not induce vomiting; call for medical help immediately. Show container or label.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

· Suitable extinguishing agents

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

- · 5.3 Advice for firefighters
- · Protective equipment:

Mount respiratory protective device.

Do not inhale explosion gases or combustion gases.

SECTION 6: Accidental release measures

• **6.1 Personal precautions, protective equipment and emergency procedures** Wear protective equipment. Keep unprotected persons away. Ensure adequate ventilation

· 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.

- 6.3 Methods and material for containment and cleaning up:
- Dispose contaminated material as waste according to item 13.

• 6.4 Reference to other sections See Section 8 for information on personal protection equipment.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. see item 8: Personal protective equipment
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage
- Requirements to be met by storerooms and receptacles: Prevent any seepage into the ground.
- · Information about storage in one common storage facility: Store away from foodstuffs.
- Further information about storage conditions: Store in cool, dry conditions in well sealed receptacles. Protect from heat and direct sunlight.

(Contd. on page 3)

Printing date 25.04.2023

Version 4 (replaces version 3)

Revision: 25.04.2023

Trade name: OTTOSEAL M 350

(Contd. of page 2)

8.1 Control parameters			
Ingredients with limit values that requir			
CAS No. Designation of material %			
	it Values for possible hazards during processing:		
67-56-1 methanol			
WEL Short-term value: 333 mg/m ³ , 250 pp			
Long-term value: 266 mg/m³, 200 pp	om		
Sk Additional information. The lists valid du	uring the making ware used on head		
Additional information: The lists valid du	ining the making were used as basis.		
8.2 Exposure controls			
Appropriate engineering controls No ful			
Individual protection measures, such a General protective and hygienic measu			
The usual precautionary measures are to be adhered to when handling chemicals. Wash hands before breaks and at the end of work.			
Avoid contact with the eyes and skin.			
Respiratory protection:			
	nditions of poor ventilation unless a protective mask with		
an appropriate gas filter (i.e.type ABEK ac	cording to standard EN 14387) is used.		
Hand protection Protective gloves.			
Material of gloves	not only depend on the meterial but also an further man		
of quality and varies from manufacturer to	not only depend on the material, but also on further mar manufacturer		
Recommended glove types: nitrile rubber	manaradurer.		
Recommended thickness of the material: >	>0.4 mm		
Recommended thickness of the material: > Penetration time of glove material Break Eye/face protection Safety glasses Body protection: Protective work clothing	kthrough time: 10 - 30 min		
Penetration time of glove material Break Eye/face protection Safety glasses	kthrough time: 10 - 30 min g.		
Penetration time of glove material Bread Eye/face protection Safety glasses Body protection: Protective work clothing SECTION 9: Physical and chemic 9.1 Information on basic physical and c	kthrough time: 10 - 30 min g. cal properties		
Penetration time of glove material Bread Eye/face protection Safety glasses Body protection: Protective work clothing SECTION 9: Physical and chemic 9.1 Information on basic physical and c General Information	kthrough time: 10 - 30 min g. <mark>cal properties</mark> chemical properties		
Penetration time of glove material Break Eye/face protection Safety glasses Body protection: Protective work clothing SECTION 9: Physical and chemic 9.1 Information on basic physical and c General Information Physical state	kthrough time: 10 - 30 min g. cal properties chemical properties Solid.		
Penetration time of glove material Bread Eye/face protection Safety glasses Body protection: Protective work clothing SECTION 9: Physical and chemic 9.1 Information on basic physical and c General Information Physical state Colour:	kthrough time: 10 - 30 min g. cal properties chemical properties Solid. According to product specification		
Penetration time of glove material Break Eye/face protection Safety glasses Body protection: Protective work clothing SECTION 9: Physical and chemic 9.1 Information on basic physical and c General Information Physical state Colour: Odour:	kthrough time: 10 - 30 min g. cal properties chemical properties Solid. According to product specification Characteristic		
Penetration time of glove material Break Eye/face protection Safety glasses Body protection: Protective work clothing SECTION 9: Physical and chemic 9.1 Information on basic physical and c General Information Physical state Colour: Odour: Melting point/freezing point:	kthrough time: 10 - 30 min g. cal properties chemical properties Solid. According to product specification Characteristic undetermined		
Penetration time of glove material Break Eye/face protection Safety glasses Body protection: Protective work clothing SECTION 9: Physical and chemic 9.1 Information on basic physical and c General Information Physical state Colour: Odour: Melting point/freezing point: Boiling point or initial boiling point and	kthrough time: 10 - 30 min g. cal properties chemical properties Solid. According to product specification Characteristic undetermined		
Penetration time of glove material Break Eye/face protection Safety glasses Body protection: Protective work clothing SECTION 9: Physical and chemic 9.1 Information on basic physical and c General Information Physical state Colour: Odour: Melting point/freezing point: Boiling point or initial boiling point and boiling range	kthrough time: 10 - 30 min g. cal properties chemical properties Solid. According to product specification Characteristic undetermined		
Penetration time of glove material Bread Eye/face protection Safety glasses Body protection: Protective work clothing SECTION 9: Physical and chemic 9.1 Information on basic physical and c General Information Physical state Colour: Odour: Melting point/freezing point: Boiling point or initial boiling point and boiling range Lower and upper explosion limit	kthrough time: 10 - 30 min g. cal properties chemical properties Solid. According to product specification Characteristic undetermined		
Penetration time of glove material Bread Eye/face protection Safety glasses Body protection: Protective work clothing SECTION 9: Physical and chemic 9.1 Information on basic physical and c General Information Physical state Colour: Odour: Melting point/freezing point: Boiling point or initial boiling point and boiling range Lower and upper explosion limit Lower: Upper:	kthrough time: 10 - 30 min g. cal properties chemical properties Solid. According to product specification Characteristic undetermined undetermined Not determined. Not determined.		
Penetration time of glove material Break Eye/face protection Safety glasses Body protection: Protective work clothing SECTION 9: Physical and chemic 9.1 Information on basic physical and c General Information Physical state Colour: Odour: Melting point/freezing point: Boiling point or initial boiling point and boiling range Lower and upper explosion limit Lower: Upper: Flash point:	kthrough time: 10 - 30 min g. cal properties chemical properties Solid. According to product specification Characteristic undetermined undetermined Not determined. Not determined. undetermined		
Penetration time of glove material Break Eye/face protection Safety glasses Body protection: Protective work clothing SECTION 9: Physical and chemic 9.1 Information on basic physical and c General Information Physical state Colour: Odour: Melting point/freezing point: Boiling point or initial boiling point and boiling range Lower and upper explosion limit Lower: Upper: Flash point: Decomposition temperature:	kthrough time: 10 - 30 min g. cal properties chemical properties Solid. According to product specification Characteristic undetermined undetermined Not determined. Not determined. Not determined. Not determined. Not determined. Not determined.		
Penetration time of glove material Break Eye/face protection Safety glasses Body protection: Protective work clothing SECTION 9: Physical and chemic 9.1 Information on basic physical and c General Information Physical state Colour: Odour: Melting point/freezing point: Boiling point or initial boiling point and boiling range Lower and upper explosion limit Lower: Upper: Flash point: Decomposition temperature: pH	kthrough time: 10 - 30 min g. cal properties chemical properties Solid. According to product specification Characteristic undetermined undetermined Not determined. Not determined. Not determined. Not determined. Not determined. Not determined. Not determined. Not determined.		
Penetration time of glove material Break Eye/face protection Safety glasses Body protection: Protective work clothing SECTION 9: Physical and chemic 9.1 Information on basic physical and c General Information Physical state Colour: Odour: Melting point/freezing point: Boiling point or initial boiling point and boiling range Lower and upper explosion limit Lower: Upper: Flash point: Decomposition temperature: pH Viscosity:	kthrough time: 10 - 30 min g. cal properties chemical properties Solid. According to product specification Characteristic undetermined undetermined Not determined. Not determined. Not determined. Not determined. Not determined. Not determined.		
Penetration time of glove material Break Eye/face protection Safety glasses Body protection: Protective work clothing SECTION 9: Physical and chemic 9.1 Information on basic physical and c General Information Physical state Colour: Odour: Melting point/freezing point: Boiling point or initial boiling point and boiling range Lower and upper explosion limit Lower: Upper: Flash point: Decomposition temperature: pH Viscosity: Solubility	kthrough time: 10 - 30 min g. cal properties chemical properties Solid. According to product specification Characteristic undetermined undetermined Not determined. Not determined.		
Penetration time of glove material Break Eye/face protection Safety glasses Body protection: Protective work clothing SECTION 9: Physical and chemic 9.1 Information on basic physical and c General Information Physical state Colour: Odour: Melting point/freezing point: Boiling point or initial boiling point and boiling range Lower and upper explosion limit Lower: Upper: Flash point: Decomposition temperature: pH Viscosity: Solubility Water:	kthrough time: 10 - 30 min g. cal properties chemical properties Solid. According to product specification Characteristic undetermined undetermined Not determined. Not determined.		
Penetration time of glove material Break Eye/face protection Safety glasses Body protection: Protective work clothing SECTION 9: Physical and chemic 9.1 Information on basic physical and c General Information Physical state Colour: Odour: Melting point/freezing point: Boiling point or initial boiling point and boiling range Lower and upper explosion limit Lower: Upper: Flash point: Decomposition temperature: pH Viscosity: Solubility Water: Partition coefficient n-octanol/water (lo	kthrough time: 10 - 30 min g. cal properties chemical properties Solid. According to product specification Characteristic undetermined undetermined Not determined. Not determined.		
Penetration time of glove material Break Eye/face protection Safety glasses Body protection: Protective work clothing SECTION 9: Physical and chemic 9.1 Information on basic physical and c General Information Physical state Colour: Odour: Melting point/freezing point: Boiling point or initial boiling point and boiling range Lower and upper explosion limit Lower: Upper: Flash point: Decomposition temperature: pH Viscosity: Solubility Water: Partition coefficient n-octanol/water (low	kthrough time: 10 - 30 min g. cal properties chemical properties Solid. According to product specification Characteristic undetermined undetermined Not determined. Not determined. Not determined. Not determined. Not determined. Not determined. Not determined. Not determined. Not determined. Not determined.		
Penetration time of glove material Break Eye/face protection Safety glasses Body protection: Protective work clothing SECTION 9: Physical and chemic 9.1 Information on basic physical and c General Information Physical state Colour: Odour: Melting point/freezing point: Boiling point or initial boiling point and boiling range Lower and upper explosion limit Lower: Upper: Flash point: Decomposition temperature: pH Viscosity: Solubility Water: Partition coefficient n-octanol/water (low value) Vapour pressure:	kthrough time: 10 - 30 min g. cal properties chemical properties Solid. According to product specification Characteristic undetermined undetermined Not determined. Not determined.		
Penetration time of glove material Break Eye/face protection Safety glasses Body protection: Protective work clothing SECTION 9: Physical and chemic 9.1 Information on basic physical and c General Information Physical state Colour: Odour: Melting point/freezing point: Boiling point or initial boiling point and boiling range Lower and upper explosion limit Lower: Upper: Flash point: Decomposition temperature: pH Viscosity: Solubility Water: Partition coefficient n-octanol/water (lo	kthrough time: 10 - 30 min g. cal properties chemical properties Solid. According to product specification Characteristic undetermined undetermined Not determined. Not determined. Not determined. Not determined. Not determined. Not determined. Not determined. Not determined. Not determined. Not determined.		

Printing date 25.04.2023

Version 4 (replaces version 3)

Revision: 25.04.2023

Trade name: OTTOSEAL M 350

Vapour density Particle characteristics	(Contd. of page 3 Not applicable. undetermined	
9.2 Other information Form:	nontre la contre de	
Auto-ignition temperature:	pasty Product is not selfigniting.	
Explosive properties:	Product is not scringing. Product is not explosive. However, formation of explosive air/vapour mixtures are possible.	
Information with regard to physica classes	l hazard	
Aerosols	Void	
Flammable liquids	Void	

SECTION 10: Stability and reactivity

• 10.1 Reactivity No further relevant information available.

10.2 Chemical stability

• **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications. Avoid strong heating.

· 10.3 Possibility of hazardous reactions No dangerous reactions known

10.6 Hazardous decomposition products: see item 5.2

SECTION 11: Toxicological information

• 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

• Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:

2768-02-7 trimethoxyvinylsilane

Oral LD50 7,100 mg/kg (rat)

Dermal LD50 3,200 mg/kg (rab)

Inhalative LC50/4 h 16.8 mg/l (rat)

- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation
- dermal: not sensitizing

Source: test report OECD 406

Test report according to OECD Guideline 406 (Guinea Pigs)

Based on available data, the classification criteria are not met.

- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.

· Reproductive toxicity Based on available data, the classification criteria are not met.

· STOT-single exposure Based on available data, the classification criteria are not met.

- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

• Other information (about experimental toxicology):

Product hydrolyses under formation of methanol (CAS no. 67-56-1). Methanol is toxic by inhalation, in contact with skin and if swallowed. Methanol causes damage to organs. Methanol is highly flammable. Inhalation of aerosol spray may damage health.

· 11.2 Information on other hazards

· Endocrine disrupting properties

None of the ingredients is listed.

(Contd. on page 5)

Printing date 25.04.2023

Version 4 (replaces version 3)

Revision: 25.04.2023

Trade name: OTTOSEAL M 350

(Contd. of page 4)

SECTION 12: Ecological information

- · 12.2 Persistence and degradability
- · Other information: Product is not biodegradable.
- · 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties
- The product does not contain substances with endocrine disrupting properties.
- 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

Do not allow product to reach ground water, water course or sewage system.

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

Recommendation

Observe local by-laws.

Already cured material can be disposed of with the domestic or commercial waste. Unconsumed material (fluid, paste-like) is to dispose of as hazardous waste.

- · Uncleaned packaging:
- · Recommendation:

Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

SECTION 14: Transport information

 14.1 UN number or ID number ADR, ADN, IMDG, IATA 14.2 UN proper shipping name ADR, ADN, IMDG, IATA 14.3 Transport hazard class(es) 	Void Void
· ADR, ADN, IMDG, IATA · Class · 14.4 Packing group	Void
• ADR, IMDG, IATA • 14.5 Environmental hazards: • Marine pollutant:	Void No
 14.6 Special precautions for user 14.7 Maritime transport in bulk according IMO instruments 	Not applicable. to Not applicable.
· Transport/Additional information:	Not dangerous according to the above specifications.
· UN "Model Regulation":	Void

(Contd. on page 6)

Printing date 25.04.2023

Version 4 (replaces version 3)

Revision: 25.04.2023

Trade name: OTTOSEAL M 350

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · National regulations
- · Waterhazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.
- · Details of international registration status: Listed on or in accordance with the following inventories: UK REACH - Europe listed AICS - Australia listed DSL- Canada listed IECSC - China listed ENCS - Japan listed PICCS - Philippines listed NZIoC - New Zealand not listed ECL - Korea listed TSCA - USA listed TCSI - Taiwan not listed · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship. This Safety Data Sheets is in compliance with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

· Relevant phrases

H226 Flammable liquid and vapour. H317 May cause an allergic skin reaction. H332 Harmful if inhaled.

- · Department issuing SDS: Tel.: 0049- (0)8684- 908- 2363
- · Contact: Tel.: 0049- (0)8684- 908- 2363 (-4300)

 Abbreviations and acronyms: ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 3: Flammable liquids - Category 3 Acute Tox. 4: Acute toxicity – Category 4 Skin Sens. 1B: Skin sensitisation – Category 1B ** Data compared to the previous version altered.