Printing date 08.02.2023

Version 3 (replaces version 2)

Revision: 08.02.2023

undertaking	
1.1 Product identifier	
Trade name: OTTOSEAL S	18
	e / the mixture Silicone sealant
1.3 Details of the supplier o	f the safety data sheet
Manufacturer/Supplier: Hermann Otto GmbH	
Krankenhausstraße 14	
D-83413 Fridolfing	
Tel.: 0049/(0)8684/908-0 Fax.: 0049/(0)8684/908-1840	
Further information obtaina	
Tel.: 0049- (0)8684- 908- 236	
E-Mail: alois.parzinger@otto-	
1.4 Emergency telephone n Tel.: 0049- (0) 89- 192 40 (en	
+44 1865 407333 (Carechem	
SECTION 2: Hazards id	lentification
2.1 Classification of the sub	ostance or mixture
	Regulation (EC) No 1272/2008
	according to the GB CLP regulation.
U	
Keep out of the reach of child Avoid contact with skin. Contains 3-aminopropyltriethor reaction. Safety data sheet available or 2.3 Other hazards During the application and cu	cide 2-octyl-2H-isothiazol-3-one to protect against mould infestation. Fren. Dxysilane, 2-octyl-2H-isothiazol-3-one. May produce an allergic In request. Fring process of the material chemicals are released as vapour (see bod ventilation or exhaustion if necessary.
Hazard statements Void Additional information: Ensure good ventilation during Contains the active agent biod Keep out of the reach of child Avoid contact with skin. Contains 3-aminopropyltriethe reaction. Safety data sheet available of 2.3 Other hazards During the application and cur item 11). Therefore ensure go Results of PBT and vPvB as PBT: Not applicable. vPvB: Not applicable.	cide 2-octyl-2H-isothiazol-3-one to protect against mould infestation. Fren. Dxysilane, 2-octyl-2H-isothiazol-3-one. May produce an allergic In request. Fring process of the material chemicals are released as vapour (see bod ventilation or exhaustion if necessary.
Hazard statements Void Additional information: Ensure good ventilation during Contains the active agent biod Keep out of the reach of child Avoid contact with skin. Contains 3-aminopropyltriethor reaction. Safety data sheet available of 2.3 Other hazards During the application and cur item 11). Therefore ensure go Results of PBT and vPvB as PBT: Not applicable. vPvB: Not applicable. SECTION 3: Compositi	cide 2-octyl-2H-isothiazol-3-one to protect against mould infestation. ren. oxysilane, 2-octyl-2H-isothiazol-3-one. May produce an allergic in request. ring process of the material chemicals are released as vapour (see bod ventilation or exhaustion if necessary. ssessment
Hazard statements Void Additional information: Ensure good ventilation during Contains the active agent biod Keep out of the reach of child Avoid contact with skin. Contains 3-aminopropyltriethor reaction. Safety data sheet available of 2.3 Other hazards During the application and cur- item 11). Therefore ensure go Results of PBT and vPvB as PBT: Not applicable. vPvB: Not applicable. SECTION 3: Composition 3.2 Mixtures Description: Polydimethylsido	cide 2-octyl-2H-isothiazol-3-one to protect against mould infestation. ren. oxysilane, 2-octyl-2H-isothiazol-3-one. May produce an allergic in request. ring process of the material chemicals are released as vapour (see bod ventilation or exhaustion if necessary. ssessment
Hazard statements Void Additional information: Ensure good ventilation during Contains the active agent biod Keep out of the reach of child Avoid contact with skin. Contains 3-aminopropyltriethor reaction. Safety data sheet available of 2.3 Other hazards During the application and cur item 11). Therefore ensure go Results of PBT and vPvB as PBT: Not applicable. vPvB: Not applicable. SECTION 3: Compositi 3.2 Mixtures	cide 2-octyl-2H-isothiazol-3-one to protect against mould infestation. Tren. Doxysilane, 2-octyl-2H-isothiazol-3-one. May produce an allergic on request. Tring process of the material chemicals are released as vapour (see bod ventilation or exhaustion if necessary. Ssessment Con/information on ingredients Doxane, filler, auxiliaries and oximosilane crosslinker
Hazard statements Void Additional information: Ensure good ventilation during Contains the active agent biod Keep out of the reach of child Avoid contact with skin. Contains 3-aminopropyltriethor reaction. Safety data sheet available of 2.3 Other hazards During the application and cur item 11). Therefore ensure go Results of PBT and vPvB as PBT: Not applicable. vPvB: Not applicable. SECTION 3: Compositi 3.2 Mixtures Description: Polydimethylsilo Dangerous components:	cide 2-octyl-2H-isothiazol-3-one to protect against mould infestation. ren. bxysilane, 2-octyl-2H-isothiazol-3-one. May produce an allergic in request. ring process of the material chemicals are released as vapour (see bod ventilation or exhaustion if necessary. ssessment con/information on ingredients bxane, filler, auxiliaries and oximosilane crosslinker 2-Pentanone, O,O',O''-(methylsilylidyne)trioxime \$\sum{30}\$ Acute Tox. 4, H302; Eye Irrit. 2, H319
Hazard statements Void Additional information: Ensure good ventilation during Contains the active agent biod Keep out of the reach of child Avoid contact with skin. Contains 3-aminopropyltriethor reaction. Safety data sheet available of 2.3 Other hazards During the application and cur- item 11). Therefore ensure go Results of PBT and vPvB as PBT: Not applicable. vPvB: Not applicable. vPvB: Not applicable. SECTION 3: Compositi 3.2 Mixtures Description: Polydimethylsilo Dangerous components: CAS: 37859-55-5 ELINCS: 484-460-1 Reg.nr.: 01-2120004323-76-x CAS: 128446-60-6	cide 2-octyl-2H-isothiazol-3-one to protect against mould infestation. ren. bxysilane, 2-octyl-2H-isothiazol-3-one. May produce an allergic in request. ring process of the material chemicals are released as vapour (see bod ventilation or exhaustion if necessary. ssessment con/information on ingredients con/information on ingredients bxane, filler, auxiliaries and oximosilane crosslinker 2-Pentanone, O,O',O''-(methylsilylidyne)trioxime () Acute Tox. 4, H302; Eye Irrit. 2, H319 () Silsesquioxanes, 3-aminopropyl Me, ethoxy-terminated <2.5
Hazard statements Void Additional information: Ensure good ventilation during Contains the active agent biod Keep out of the reach of child Avoid contact with skin. Contains 3-aminopropyltriethor reaction. Safety data sheet available of 2.3 Other hazards During the application and cur- item 11). Therefore ensure go Results of PBT and vPvB as PBT: Not applicable. vPvB: Not applicable. SECTION 3: Compositi 3.2 Mixtures Description: Polydimethylsilo Dangerous components: CAS: 37859-55-5 ELINCS: 484-460-1 Reg.nr.: 01-2120004323-76-x	cide 2-octyl-2H-isothiazol-3-one to protect against mould infestation. ren. oxysilane, 2-octyl-2H-isothiazol-3-one. May produce an allergic in request. ring process of the material chemicals are released as vapour (see bod ventilation or exhaustion if necessary. ssessment oxane, filler, auxiliaries and oximosilane crosslinker 2-Pentanone, O,O´,O´´-(methylsilylidyne)trioxime (Acute Tox. 4, H302; Eye Irrit. 2, H319

(Contd. on page 2) GB

Printing date 08.02.2023

Version 3 (replaces version 2)

Revision: 08.02.2023

Trade name: OTTOSEAL S 18

	(Contd. c	of page 1)
CAS: 870-08-6	dioctyltin oxide	<1%
EINECS: 212-791-1	🚸 STOT SE 2, H371	
CAS: 919-30-2	3-aminopropyltriethoxysilane	<1%
EINECS: 213-048-4 Reg.nr.: 01-2119480479-24-XX	♦ Skin Corr. 1B, H314; (1) Acute Tox. 4, H302; Skin Sens. 1B, H317	
-	Specific concentration limit: Skin Sens. 1B; H317: $C \ge 3$ %	
CAS: 26530-20-1	2-octyl-2H-isothiazol-3-one	<0.1%
EINECS: 247-761-7		
	Aquatic Acute 1, H400 (M=100); Aquatic Chronic 1,	
	H410 (M=100); 🕦 Skin Sens. 1A, H317, EUH071	
	ATE: LD50 oral: 125 mg/kg	
	LD50 dermal: 311 mg/kg LC50/4 h inhalative: 0.27 mg/l	
	Specific concentration limit: Skin Sens. 1A; H317: C ≥ 0.0015 %	

• Additional information For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

- · General information Take affected persons out into the fresh air.
- · After inhalation

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

- After skin contact Immediately wash with water and soap and rinse thoroughly. If skin irritation continues, consult a doctor.
- · After eye contact
- Rinse opened eye for several minutes under running water. Then consult a doctor.
- After swallowing
- Do not induce vomiting; call for medical help immediately. Show container or label.
- Information for doctor

Symptomatic treatment (decontamination, vital functions), no specific antidote known.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents
- CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- 5.2 Special hazards arising from the substance or mixture
- Formation of toxic gases is possible during heating or in case of fire.
- 5.3 Advice for firefighters
- · Protective equipment:
- Mount respiratory protective device.

Do not inhale explosion gases or combustion gases.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Ensure adequate ventilation
- · 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up: Dispose contaminated material as waste according to item 13.

(Contd. on page 3)

- GB

Printing date 08.02.2023

Version 3 (replaces version 2)

Revision: 08.02.2023

Trade name: OTTOSEAL S 18

(Contd. of page 2) • 6.4 Reference to other sections See Section 8 for information on personal protection equipment.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. see item 8: Personal protective equipment
- · 7.2 Conditions for safe storage, including any incompatibilities
- [.] Storage
- · Requirements to be met by storerooms and receptacles: Prevent any seepage into the ground.
- *Information about storage in one common storage facility:* Store away from foodstuffs. • *Further information about storage conditions:*
- Store in cool, dry conditions in well sealed receptacles. Protect from heat and direct sunlight.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

- Ingredients with limit values that require monitoring at the workplace:
- · Additional information:

The lists valid during the making were used as basis. Reaction product 2-Pentanoneoxime CAS: 623-40-5 DNEL (Data for WORKERS) INHALATION Exposure Systemic Effects Long-term: (DNEL) 8,3 mg/m3 Acute/ short term: (DNEL) 24,9 mg/m3 Source: ECHA

- · 8.2 Exposure controls
- Appropriate engineering controls No further data; see item 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures

The usual precautionary measures are to be adhered to when handling chemicals. Wash hands before breaks and at the end of work. Avoid contact with the eyes and skin.

· Respiratory protection:

This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e.type ABEK according to standard EN 14387) is used.

- · Hand protection Protective gloves.
- Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

Recommended glove types: nitrile rubber

Recommended thickness of the material: >0,4 mm

- · Penetration time of glove material Breakthrough time: 10 30 min
- · Eye/face protection Safety glasses
- · Body protection: Protective work clothing.
- **SECTION 9: Physical and chemical properties**
- 9.1 Information on basic physical and chemical properties
- · General Information
- Physical state
- · Colour:
- · Odour:

Solid. According to product specification Characteristic

(Contd. on page 4)

GB

Printing date 08.02.2023

Version 3 (replaces version 2)

Revision: 08.02.2023

Trade name: OTTOSEAL S 18

	(Contd. of page 3)
 Melting point/freezing point: 	undetermined
 Boiling point or initial boiling point and 	
boiling range	undetermined
• Lower and upper explosion limit	
· Lower:	not applicable
· Upper:	not applicable
· Flash point:	Not applicable
 Decomposition temperature: 	Not determined.
· pH	Not determined.
· Viscosity:	Not determined.
· Solubility	
· Water:	Insoluble
 Partition coefficient n-octanol/water (log 	
value)	Not determined.
· Vapour pressure:	Not determined.
Density and/or relative density	
[.] Density:	see technical datasheet
[.] Relative density	Not determined.
· Vapour density	Not applicable.
9.2 Other information	
· Form:	pastv
· Auto-ignition temperature:	Product is not selfigniting.
• Explosive properties:	Product does not present an explosion hazard.
Information with regard to physical hazar	d
classes	
Aerosols	Void
· Flammable liquids	Void

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

10.2 Chemical stability

• **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications. Avoid strong heating.

• **10.6 Hazardous decomposition products:** Tests on representative products have shown that above temperatures of 150° C small quantities of formaldehyde are split off. see item 5.2

SECTION 11: Toxicological information

 \cdot 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

- Acute toxicity Based on available data, the classification criteria are not met.
- LD/LC50 values relevant for classification:

37859-55-5 2-Pentanone, O,O´,O´´-(methylsilylidyne)trioxime

Oral LD50 1,234 mg/kg (rat)

870-08-6 dioctyltin oxide

Oral LD50 2,500 mg/kg (rat)

919-30-2 3-aminopropyltriethoxysilane

Oral LD50 1,570 mg/kg (rat)

Dermal LD50 4,290 mg/kg (rab)

(Contd. on page 5)

GB

Printing date 08.02.2023

Version 3 (replaces version 2)

Revision: 08.02.2023

(Contd. of page 4)

Trade name: OTTOSEAL S 18

26530-20-1 2-octyl-2H-isothiazol-3-one

Oral LD50 125 mg/kg (ATE)

Dermal LD50 311 mg/kg (ATE)

Inhalative LC50/4 h 0.27 mg/l (ATE)

• Skin corrosion/irritation Based on available data, the classification criteria are not met.

· Serious eye damage/irritation Based on available data, the classification criteria are not met.

- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.
- Other information (about experimental toxicology): During the application of the product 2-Pentanonoxim (CAS: 623-40-5) is released. 2-Pentanonoxim
- is harmful if swallowed, causes serious eye irritation, may cause damage to organs through prolonged or repeated exposure and is harmful to aquatic life with long lasting effects.

Additional toxicological information:

26530-20-1 2-octyl-2H-isothiazol-3-one

Oral Acute toxicity estimate (ATE mix) 125 mg/kg (rat)

Dermal Acute toxicity estimate (ATE mix) 311 mg/kg (rat)

- 11.2 Information on other hazards
- · Endocrine disrupting properties

870-08-6 dioctyltin oxide: List II

SECTION 12: Ecological information

- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties

For information on endocrine disrupting properties see section 11.

- · 12.7 Other adverse effects
- Additional ecological information:
- · General notes:

Do not allow product to reach ground water, water course or sewage system.

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Observe local by-laws.

Already cured material can be disposed of with the domestic or commercial waste. Unconsumed material (fluid, paste-like) is to dispose of as hazardous waste.

- · Uncleaned packaging:
- · Recommendation:

Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

(Contd. on page 6)

GB

Printing date 08.02.2023

Version 3 (replaces version 2)

Revision: 08.02.2023

Trade name: OTTOSEAL S 18

(Contd. of page 5)

SECTION 14: Transport information	tion
· 14.1 UN number or ID number	
· ADR, ADN, IMDG, IATA	Void
• 14.2 UN proper shipping name	
· ADR, ADN, IMDG, IATA	Void
 14.3 Transport hazard class(es) 	
· ADR, ADN, IMDG, IATA	
Class	Void
[.] 14.4 Packing group	
· ADR, IMDG, IATA	Void
14.5 Environmental hazards:	
· Marine pollutant:	No
 14.6 Special precautions for user 	Not applicable.
 14.7 Maritime transport in bulk accordi 	ing to
IMO instruments	Not applicable.
· Transport/Additional information:	Not dangerous according to the above specifications.
· UN "Model Regulation":	Void

SECTION 15: Regulatory information

• 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· National regulations

- · Waterhazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.
- Details of international registration status:

Listed on or in accordance with the following inventories:

TCSI - Taiwan not listed UK REACH - Europe listed AICS - Australia not listed DSL - Canada not listed IECSC - China not listed ENCS - Japan not listed NZIoC - New Zealand not listed PICCS - Philippines not listed ECL - Korea not listed TSCA - USA not listed · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

- H226 Flammable liquid and vapour.
- H301 Toxic if swallowed.
- H302 Harmful if swallowed.
- H311 Toxic in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation. H330 Fatal if inhaled.

(Contd. on page 7)

Printing date 08.02.2023

Version 3 (replaces version 2)

Revision: 08.02.2023

Trade name: OTTOSEAL S 18

H271 May agues domage to expens	(Contd. of page 6)
H371 May cause damage to organs.	
H400 Very toxic to aquatic life.	
H410 Very toxic to aquatic life with long lasting effects.	
EUH071 Corrosive to the respiratory tract.	
· Department issuing SDS: Tel.: 0049- (0)8684- 908- 2363	
· Contact: Tel.: 0049- (0)8684- 908- 2363 (-4300)	
· Abbreviations and acronyms:	
ADR: Accord relatif au transport international des marchandises dangereuses par route (Europea	an Agreement Concerning
the International Carriage of Dangerous Goods by Road)	
IMDG: International Maritime Code for Dangerous Goods	
IATA: International Air Transport Association	
GHS: Globally Harmonised System of Classification and Labelling of Chemicals	
EINECS: European Inventory of Existing Commercial Chemical Substances	
ELINCS: European List of Notified Chemical Substances	
CAS: Chemical Abstracts Service (division of the American Chemical Society)	
LC50: Lethal concentration, 50 percent	
LD50: Lethal dose, 50 percent	
PBT: Persistent, Bioaccumulative and Toxic	
vPvB: very Persistent and very Bioaccumulative	
Flam. Liq. 3: Flammable liquids – Category 3	
Acute Tox. 3: Acute toxicity – Category 3	
Acute Tox. 4: Acute toxicity – Category 4	
Acute Tox. 2: Acute toxicity – Category 2	
Skin Corr. 1: Skin corrosion/irritation – Category 1	
Skin Corr. 1B: Skin corrosion/irritation – Category 1B	
Skin Irrit. 2: Skin corrosion/irritation – Category 2	
Eye Dam. 1: Serious eye damage/eye irritation – Category 1	
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2	
Skin Sens. 1A: Skin sensitisation – Category 1A	
Skin Sens. 1B: Skin sensitisation – Category 1B	
STOT SE 2: Specific target organ toxicity (single exposure) – Category 2	
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1	1
Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category	1
* * Data compared to the previous version altered.	
	GB