Revision: 25.04.2024

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 25.04.2024

Version 4 (replaces version 3)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name: OTTOSEAL S 50

· Application of the substance / the mixture Silicone sealant

· 1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Hermann Otto GmbH Krankenhausstraße 14 D-83413 Fridolfing Tel.: 0049/(0)8684/908-0

Tel.: 0049/(0)8684/908-0 Fax.: 0049/(0)8684/908-1840

· Further information obtainable from:

Tel.: 0049- (0)8684- 908- 2363 (-4300) E-Mail: alois.parzinger@otto-chemie.de • 1.4 Emergency telephone number:

Tel.: 0049- (0) 89- 192 40 (emergency telephone no.)

+44 1865 407333 (Carechem 24)

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

The product is not classified, according to the GB CLP regulation.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008 Void
- · Hazard pictograms Void
- · Signal word Void
- · Hazard statements Void
- · Additional information:

Ensure good ventilation during application and curing.

EUH210 Safety data sheet available on request.

· 2.3 Other hazards

During processing and curing of the material, chemical substances are released into the air (see point 11). Therefore, ensure good room ventilation and, if necessary, exhaust ventilation.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Determination of endocrine-disrupting properties

This product does not contain components that are endocrine disruptors according to UK REACH Article 57(f) or Commission Delegated Regulation (EU) 2017/2100 or Commission Delegated Regulation (EU) 2018/605 in quantities of 0.1% or more.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description: Polydimethylsiloxane, filler, auxiliaries and acetoxysilane crosslinker
- Dangerous components:

CAS: 68855-24-3 EINECS: 272-472-8 benzene, C14-30-alkyl derivs. Aquatic Chronic 4, H413 <25%

(Contd. on page 2)

Printing date 25.04.2024 Version 4 (replaces version 3) Revision: 25.04.2024

Trade name: OTTOSEAL S 50

(Contd. of page 1)

CAS: 17689-77-9 ethyltriacetoxysilane <2.5%

♦ Skin Corr. 1B, H314; ◆ Acute Tox. 4, H302, EUH014 EINECS: 241-677-4 Reg.nr.: 01-2119881778-15-xxxx Specific concentration limits: Skin Irrit. 2; H315: C ≥ 5 % Eye Irrit. 2; H319: C ≥ 5 %

CAS: 4253-34-3 <2.5% methylsilanetriyl triacetate

EINECS: 224-221-9 ♦ Skin Corr. 1B, H314; ♦ Acute Tox. 4, H302, EUH014 Reg.nr.: 01-2119962266-32-xxxx Specific concentration limits: Skin Irrit. 2; H315: C ≥ 5 % Eye Irrit. 2; H319: C ≥ 5 %

· Additional information

For the wording of the listed hazard phrases refer to section 16.

Particulate raw materials with risk of inhalation are inextricably bound in the product and therefore does not trigger classification of the product for inhalation hazards. Due to the product's physical properties, particulate inhalation exposure is not possible.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

· After skin contact

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· After eye contact

Rinse opened eye for several minutes under running water. Then consult a doctor.

· After swallowing

Do not induce vomiting; call for medical help immediately. Show container or label.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- · Suitable extinguishing agents

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

- · 5.3 Advice for firefighters
- Protective equipment:

Mount respiratory protective device.

Do not inhale explosion gases or combustion gases.

SECTION 6: Accidental release measures

- · 6.1 Personal precautions, protective equipment and emergency procedures Ensure adequate ventilation
- · 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to section 13.

• 6.4 Reference to other sections See Section 8 for information on personal protection equipment.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

see item 8: Personal protective equipment

(Contd. on page 3)

Printing date 25.04.2024 Version 4 (replaces version 3) Revision: 25.04.2024

Trade name: OTTOSEAL S 50

(Contd. of page 2)

- · 7.2 Conditions for safe storage, including any incompatibilities
- Storage
- · Requirements to be met by storerooms and receptacles: Prevent any seepage into the ground.
- Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- Ingredients with limit values that require monitoring at the workplace:
- · DNELs

17689-77-9 ethyltriacetoxysilane

Inhalative Worker, local (long term) 32.5 mg/m3 (rat)
Consumer, local (acute) 65 mg/m3 (rat)

4253-34-3 methylsilanetriyl triacetate

Consumer, local (long term)

Dermal Worker, systemic (long term) 14.5 mg/kg/Tag (rat)

Consumer, systemic (long term) 7.2 mg/kg/Tag (rat)

Inhalative Worker, systemic (long term) 25 mg/m3 (rat)

Consumer, local (long term) 5.1 mg/m3 (rat)

CAS No. Designation of material % Type Value Unit

Additional Occupational Exposure Limit Values for possible hazards during processing:

10.8 mg/m3 (rat)

64-19-7 acetic acid

OEL Short-term value: 50 mg/m³, 20 ppm Long-term value: 25 mg/m³, 10 ppm WEL Short-term value: 50 mg/m³, 20 ppm Long-term value: 25 mg/m³, 10 ppm

· Additional information: The lists valid during the making were used as basis.

- · 8.2 Exposure controls
- Appropriate engineering controls No further data; see section 7.
- Individual protection measures, such as personal protective equipment
- General protective and hygienic measures

The usual precautionary measures are to be adhered to when handling chemicals.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Respiratory protection:

This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e.type ABEK according to standard EN 14387) is used.

· Hand protection Protective gloves.

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

Recommended glove types: nitrile rubber

Recommended thickness of the material: >0,4 mm

- · Penetration time of glove material Breakthrough time: 10 30 min
- · Eye/face protection Safety glasses
- · Body protection: Protective work clothing.

– gl

Printing date 25.04.2024 Version 4 (replaces version 3) Revision: 25.04.2024

Trade name: OTTOSEAL S 50

(Contd. of page 3)

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

Physical state
Colour:
Odour:
Melting point/freezing point:

Fluid
Clear
after vinegar
undetermined

· Boiling point or initial boiling point and

boiling range undetermined

· Lower and upper explosion limit

Lower: not applicable
Upper: not applicable
Flash point: undetermined
Decomposition temperature: Not determined.
pH Not determined.
Viscosity: Not determined.

Solubility

· Water: Insoluble

· Partition coefficient n-octanol/water (log

value) Not determined.
Vapour pressure: Not determined.

Density and/or relative density

Density: see technical data sheet

Relative density
 Vapour density
 Particle characteristics
 Not determined.
 Not applicable.
 undetermined

· 9.2 Other information

· Form: pasty

· Ignition temperature: Not determined. · Explosive properties: Not determined.

· Information with regard to physical hazard

classes

· Aerosols Void · Flammable liquids Void

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

Avoid strong heating.

· 10.6 Hazardous decomposition products:

Tests on representative products have shown that above temperatures of 150° C small quantities of formaldehyde are split off.

see item 5.2

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.
- LD/LC50 values relevant for classification:

68855-24-3 benzene, C14-30-alkyl derivs.

Oral LD50 >5,000 mg/kg (rat)

(Contd. on page 5)

Printing date 25.04.2024 Version 4 (replaces version 3) Revision: 25.04.2024

Trade name: OTTOSEAL S 50

(Contd. of page 4)

Dermal LD50 >3,000 mg/kg (rab)

17689-77-9 ethyltriacetoxysilane

Oral LD50 1,460 mg/kg (rat)

Skin corrosion/irritation

not irritating Source: ECHA

Test in accordance with: OECD Guideline 404 (rabbit). Based on available data, the classification criteria are not met.

Serious eye damage/irritation

not irritating Source: ECHA

Test in accordance with: OECD Guideline 405 (rabbit).

Based on available data, the classification criteria are not met.

- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.
- · Other information (about experimental toxicology):

In curing the material splits off acetic acid as damp. This may cause irritating effects to skin, eyes or respiratory system.

- · 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

- 12.2 Persistence and degradability
- · Other information: Product is not biodegradable.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties

This product does not contain components that are endocrine disruptors according to UK REACH Article 57(f) or Commission Delegated Regulation (EU) 2017/2100 or Commission Delegated Regulation (EU) 2018/605 in quantities of 0.1% or more.

- · 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

Do not allow product to reach ground water, water course or sewage system.

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

Recommendation

Observe local by-laws.

Already cured material can be disposed of with the domestic or commercial waste. Unconsumed material (fluid, paste-like) is to dispose of as hazardous waste.

- · Uncleaned packaging:
- Recommendation:

Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.

(Contd. on page 6)

Printing date 25.04.2024 Version 4 (replaces version 3) Revision: 25.04.2024

Trade name: OTTOSEAL S 50

(Contd. of page 5)

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

SECTION 14: Transport information

· 14.1 UN number or ID number

· ADR, IMDG, IATA Void

· 14.2 UN proper shipping name

ADR, ADN, IMDG, IATA Void

· 14.3 Transport hazard class(es)

· ADR, ADN, IMDG, IATA

Void · Class

· 14.4 Packing group

Void · ADR, IMDG, IATA

· 14.5 Environmental hazards: Not applicable. · 14.6 Special precautions for user Not applicable.

· 14.7 Maritime transport in bulk according to

IMO instruments Not applicable.

· Transport/Additional information: Not dangerous according to the above

specifications.

Void UN "Model Regulation":

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Poisons Act
- · Regulated explosives precursors

None of the ingredients is listed.

Regulated poisons

None of the ingredients is listed.

Reportable explosives precursors

None of the ingredients is listed.

Reportable poisons

None of the ingredients is listed.

- Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment - Annex II

None of the ingredients is listed.

- · REGULATION (EU) 2019/1148
- · Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

- · National regulations
- · Waterhazard class; Water hazard class 2 (Self-assessment): hazardous for water.
- · Details of international registration status:

Listed on or in accordance with the following inventories:

UK REACH - Europe listed AICS - Australia not listed

DSL- Canada listed IECSC - China listed

(Contd. on page 7)

Printing date 25.04.2024 Version 4 (replaces version 3) Revision: 25.04.2024

Trade name: OTTOSEAL S 50

(Contd. of page 6)

ENCS - Japan not listed
NZIOC - New Zealand listed
PICCS - Philippines listed
ECL - Korea listed
TCSI - Taiwan listed
TSCA - USA listed

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship. This Safety Data Sheets is in compliance with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

· Relevant phrases

H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H413 May cause long lasting harmful effects to aquatic life.

EUH014 Reacts violently with water.

Department issuing SDS: Tel.: 0049- (0)8684- 908- 2363

· Contact: Tel.: 0049- (0)8684- 908- 2363 (-4300)

Date of previous version: 20.10.2022
 Version number of previous version: 3

· Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning

the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (UK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Acute Tox. 4: Acute toxicity - Category 4

Skin Corr. 1B: Skin corrosion/irritation - Category 1B

Aquatic Chronic 4: Hazardous to the aquatic environment - long-term aquatic hazard - Category 4

* Data compared to the previous version altered.

gb