Printing date 09.08.2022 Version 3 (replaces version 2) Revision: 09.08.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: OTTOSEAL S 140
- · Application of the substance / the mixture Silicone sealant
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Hermann Otto GmbH Krankenhausstraße 14 D-83413 Fridolfing Tel.: 0049/(0)8684/908-0

Tel.: 0049/(0)8684/908-0 Fax.: 0049/(0)8684/908-1840

· Further information obtainable from:

Tel.: 0049- (0)8684- 908- 2363 (-4300) E-Mail: alois.parzinger@otto-chemie.de • 1.4 Emergency telephone number:

Tel.: 0049- (0) 89- 192 40 (emergency telephone no.)

+44 1865 407333 (Carechem 24)

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

The product is not classified, according to the GB CLP regulation.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008 Void
- · Hazard pictograms Void
- · Signal word Void
- · Hazard statements Void
- · Additional information:

Ensure good ventilation during application and curing.

Contains the active agent biocide Silver phosphate glass to protect against mould infestation. Contains the active agent biocide 2-octyl-2H-isothiazol-3-one to protect against mould infestation. Keep out of the reach of children.

Avoid contact with skin.

Contains 3-aminopropyltriethoxysilane, 2-octyl-2H-isothiazol-3-one. May produce an allergic reaction.

Safety data sheet available on request.

2.3 Other hazards

During the application and curing process of the material chemicals are released as vapour (see item 11). Therefore ensure good ventilation or exhaustion if necessary.

- Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description: Polydimethylsiloxane, filler, auxiliaries and oximosilane crosslinker
- Dangerous components:

CAS: 37859-55-5 2-Pentanone, O,O´,O´´-(methylsilylidyne)trioxime <5%

Reg.nr.: 01-2120004323-76-xxxx

CAS: 919-30-2 3-aminopropyltriethoxysilane <1%

Reg.nr.: 01-2119480479-24-XX 1B, H317

Specific concentration limit: Skin Sens. 1B; H317: C ≥ 3 %

(Contd. on page 2)

Printing date 09.08.2022 Version 3 (replaces version 2) Revision: 09.08.2022

Trade name: OTTOSEAL S 140

(Contd. of page 1)

CAS: 26530-20-1

2-octyl-2H-isothiazol-3-one

< 0.1%

Aquatic Acute 1, H400 (M=100); Aquatic Chronic 1, H410 (M=100); Skin Sens. 1A, H317, EUH071

ATE: LD50 oral: 125 mg/kg LD50 dermal: 311 mg/kg LC50/4 h inhalative: 0.27 mg/l

Specific concentration limit: Skin Sens. 1A; H317: C ≥

0.0015 %

· Additional information For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- After inhalation

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

After skin contact

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· After eye contact

Rinse opened eye for several minutes under running water. Then consult a doctor.

· After swallowing

Do not induce vomiting; call for medical help immediately. Show container or label.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- Suitable extinguishing agents

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

- 5.3 Advice for firefighters
- · Protective equipment:

Mount respiratory protective device.

Do not inhale explosion gases or combustion gases.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Ensure adequate ventilation
- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to item 13.

• 6.4 Reference to other sections See Section 8 for information on personal protection equipment.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

see item 8: Personal protective equipment

(Contd. on page 3)

Printing date 09.08.2022 Version 3 (replaces version 2) Revision: 09.08.2022

Trade name: OTTOSEAL S 140

(Contd. of page 2)

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage
- · Requirements to be met by storerooms and receptacles: Prevent any seepage into the ground.
- · Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:
- · Additional information:

The lists valid during the making were used as basis. Reaction product 2-Pentanoneoxime CAS: 623-40-5

DNEL (Data for WORKERS)
INHALATION Exposure
Systemic Effects

Long-term: (DNEL) 8,3 mg/m3

Acute/ short term: (DNEL) 24,9 mg/m3

Source: ECHA

- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see item 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures

The usual precautionary measures are to be adhered to when handling chemicals.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· Respiratory protection:

This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e.type ABEK according to standard EN 14387) is used.

- · Hand protection Protective gloves.
- · Material of gloves

Natural rubber, NR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

Recommended glove types: nitrile rubber

Recommended thickness of the material: >0,4 mm

- Penetration time of glove material Breakthrough time: 10 30 min
- · Eye/face protection Safety glasses
- Body protection: Protective work clothing.

SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information

· Physical state Solid.

· Colour: According to product specification

Odour: CharacteristicMelting point/freezing point: undetermined

· Boiling point or initial boiling point and

boiling range Not applicable.

· Lower and upper explosion limit

Lower: not applicableUpper: not applicableFlash point: Not applicable

(Contd. on page 4)

Printing date 09.08.2022 Version 3 (replaces version 2) Revision: 09.08.2022

Trade name: OTTOSEAL S 140

(Contd. of page 3)

Decomposition temperature: Not determined.
 pH Not applicable.
 Viscosity: Not determined.

Solubility

· Water: Insoluble

· Partition coefficient n-octanol/water (log

value) Not determined.
• Vapour pressure: Not applicable.

· Density and/or relative density

· Density: see technical datasheet

Relative density
 Vapour density
 Relative gas density
 Not determined.
 Not applicable.
 undetermined

· 9.2 Other information

· Form: pasty

· Auto-ignition temperature: Product is not selfigniting.

• Explosive properties: Product does not present an explosion hazard.

· Information with regard to physical hazard

classes
· Aerosols Void
· Flammable liquids Void

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

Avoid strong heating.

- · 10.3 Possibility of hazardous reactions No dangerous reactions known
- · 10.6 Hazardous decomposition products:

Tests on representative products have shown that above temperatures of 150° C small quantities of formaldehyde are split off.

see item 5.2

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity
- · LD/LC50 values relevant for classification:

37859-55-5 2-Pentanone, O,O´,O´´-(methylsilylidyne)trioxime

Oral LD50 1,234 mg/kg (rat) 919-30-2 3-aminopropyltriethoxysilane

Oral LD50 1,570 mg/kg (rat) Dermal LD50 4,290 mg/kg (rab) **26530-20-1 2-octyl-2H-isothiazol-3-one**

Oral LD50 125 mg/kg (ATE)
Dermal LD50 311 mg/kg (ATE)
Inhalative LC50/4 h 0.27 mg/l (ATE)

Other information (about experimental toxicology):

During the application of the product 2-Pentanonoxim (CAS: 623-40-5) is released. 2-Pentanonoxim is harmful if swallowed, causes serious eye irritation, may cause damage to organs through prolonged or repeated exposure and is harmful to aquatic life with long lasting effects.

(Contd. on page 5)

Printing date 09.08.2022 Version 3 (replaces version 2) Revision: 09.08.2022

Trade name: OTTOSEAL S 140

(Contd. of page 4)

· Additional toxicological information:

26530-20-1 2-octyl-2H-isothiazol-3-one

Acute toxicity estimate (ATE mix) 125 mg/kg (rat)

Dermal Acute toxicity estimate (ATE mix) 311 mg/kg (rat)

- 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- · 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

Do not allow product to reach ground water, water course or sewage system.

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Observe local by-laws.

Already cured material can be disposed of with the domestic or commercial waste. Unconsumed material (fluid, paste-like) is to dispose of as hazardous waste.

- · Uncleaned packaging:
- · Recommendation:

Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

SECTION 14: Transport information

· 14.1 UN number or ID number

· ADR, ADN, IMDG, IATA Void

· 14.2 UN proper shipping name

· ADR, ADN, IMDG, IATA Void

· 14.3 Transport hazard class(es)

· ADR, ADN, IMDG, IATA

· Class Void

· 14.4 Packing group

· ADR, IMDG, IATA Void

· 14.5 Environmental hazards:

· Marine pollutant: No

· 14.6 Special precautions for user Not applicable.

· 14.7 Maritime transport in bulk according to

Not applicable. IMO instruments

· Transport/Additional information: Not dangerous according to the above

specifications.

(Contd. on page 6)

Printing date 09.08.2022 Version 3 (replaces version 2) Revision: 09.08.2022

Trade name: OTTOSEAL S 140

· UN "Model Regulation": Void

(Contd. of page 5)

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · National regulations
- · Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.
- · Details of international registration status:

Listed on or in accordance with the following inventories:

UK REACH - Europe listed
AICS - Australia not listed
DSL - Canada not listed
IECSC - China not listed
ENCS - Japan not listed
NZIOC - New Zealand listed

NZIOC - New Zealand listed
PICCS - Philippines not listed
ECL - Korea not listed
TSCA - USA not listed
TCSI - Taiwan not listed

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H301 Toxic if swallowed.

H302 Harmful if swallowed.

H311 Toxic in contact with skin.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H330 Fatal if inhaled.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

EUH071 Corrosive to the respiratory tract.

Department issuing SDS: Tel.: 0049- (0)8684- 908- 2363

Contact: Tel.: 0049- (0)8684- 908- 2363 (-4300)

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Acute Tox. 3: Acute toxicity - Category 3

Acute Tox. 4: Acute toxicity - Category 4

Acute Tox. 2: Acute toxicity – Category 2

Skin Corr. 1: Skin corrosion/irritation – Category 1

Skin Corr. 1B: Skin corrosion/irritation – Category 1B

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

(Contd. on page 7)

Page 7/7

(Contd. of page 6)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 09.08.2022 Version 3 (replaces version 2) Revision: 09.08.2022

Trade name: OTTOSEAL S 140

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

Skin Sens. 1A: Skin sensitisation – Category 1A
Skin Sens. 1B: Skin sensitisation – Category 1B
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

* Data compared to the previous version altered.