

# The professionals for all floors



## OTTOSEAL® S125

The floor silicone OTTOSEAL® S125 is also approved for use in sanitary areas and offers a large selection of colours, also in matte.

## OTTOSEAL® S51

The synthetic flooring professional convinces with its large selection of colours to choose from and is also suitable for special requirements, such as escape routes, due to the building material class B1 testing.

## OTTOSEAL® S34

Due to its extreme resilience, OTTOSEAL® S34 is the first choice when it comes to heavily trafficked joints or joints exposed to high chemical stresses.

## OTTOSEAL® M390

The all-rounder combines a lot of product advantages and can be used for many floor and connection joints. It is also ideal for wood floors with its sandability and paintability.

## OTTOSEAL® A221 Parkett

The proven parquet joint compound impresses with its sandability and paintability as well as the availability in many common parquet colours.



### Searching for the right colour for your hard joint?

Use our colour recommendations on our website or in the OTTO app. Please use the latest colour tables of our premium silicones for your own colour comparisons.



For information relating to certification marks, please see [www.otto-chemie.com](http://www.otto-chemie.com) under the heading „Information on Certification Marks“. The requirements and test criteria of the DGNB and LEED can be found on [www.dgnb.de](http://www.dgnb.de) and [www.german-gba.org](http://www.german-gba.org). Please note that these companies do not evaluate our individual products, but the sustainability as a whole of each complete building project.

The information in the present document corresponds to the status quo on going to print, refer to the index. With a new edition this edition becomes invalid. Due to the many possible influences during and after application, the customer always has to carry out trials first. Please observe the respective technical data sheet! This information is available on the Internet at [www.otto-chemie.com](http://www.otto-chemie.com). Errors and typographical errors are excepted.

**Hermann Otto GmbH**  
Krankenhausstr. 14  
83413 Fridolfing, Germany  
Tel.: +49 8684 908-0  
[info@otto-chemie.com](mailto:info@otto-chemie.com)  
[www.otto-chemie.com](http://www.otto-chemie.com)



OTTO product information

# OTTOSEAL® S125

The low-odour floor and  
sanitary silicone

Quality creates cohesion

- ✓ **Low odour**
- ✓ Resistant to mould
- ✓ Durable joint

Index: 9999492-GB | 10.02.2022 | © Hermann Otto GmbH 2022



# Matte colours are trendy

## 1-component silicone sealant based on alkoxy, neutral cross-linking

for internal and external use



### Matte or gloss? The choice is yours!

The low-odour floor and bathroom silicone OTTOSEAL® S 125 is best-suited for different applications indoors and outdoors. OTTOSEAL® S 125 can be used to make durable, mould-resistant seals on floor and connection joints on plastic and design floor coverings made of rubber, linoleum, vinyl and PVC, as well as for different connection joints in sanitary areas. Thanks to its availability in many different colours, the silicone sealant creates a cohesive overall look. OTTOSEAL® S 125 is also available in matte colour tones. Thanks to the ISEGA clearance certificate, OTTOSEAL® S 125 has been tested and approved for use in the food-related sector and is therefore perfect for these applications.



### The OTTO processor tip

We recommend smoothing a joint that was designed with matte colours only once with smoothing agent. The more often the surface is reworked with smoothing agent, the more the matte effect is lost and the joint becomes glossier. You will find the right OTTO smoothing agent in our OTTO product range.



Low odour



Resistant to mould



Durable joint



Boden- und Sanitär-Silikon

Floor and sanitary silicone  
Silicone pour joints de sol  
et pour sanitaires  
Vloer- en sanitairsilicone

- ✓ Sicher gegen Schimmel
- ✓ Langlebige Fuge

**OTTO**  
DICHTEN & KLEBEN

Floor and connection joints for plastic and design floor coverings made of rubber, linoleum, vinyl and PVC



Connection joints in sanitary areas



Connection joints on windows and doors



Sealing of joints on facades



External sealing of mirrors



## The applications at a glance



Floor and connection joints for plastic and design floor coverings made of rubber, linoleum, vinyl and PVC



Connection joints in sanitary areas



Connection joints on windows and doors



### Find out more about OTTOSEAL® S 125

You can find more information about the product on our website [www.otto-chemie.com](http://www.otto-chemie.com) or in the OTTO app.

