# **OTTO Smoothing Agent**

# The smoothing agent

Aquaeous solution of surface-active substances

For indoor and outdoor application

GL

#### **Characteristics**

- > Aquaeous solution of surface-active substances
- Dermatologically tested ingredients
- > Does not dry out the skin
- > Dilutable with water; 2 (smoothing agent): 1 (water)
- > Keeps the shine of the sealant surface intact
- > Colouring pigments of the sealant are not washed off
- > Not suitable for marble and other natural stones

# Fields of application

 Smoothing of sealant surfaces including silicone, polyurethane and MS hybrid polymer sealants

#### Standards and tests

Due to the results of the in-vivo compatibility test (test report of Institute Fresenius, 65232 Taunusstein, Germany) the OTTO Smoothing Agent is classified as harmless in terms of a potential skin irritating effect





## **Technical properties**

Storage temperature from/to [°C]	0 / + 35
Shelf life at 20 °C/50 % RH [months]	121

1) Frost-free storage

### **Application information**

For applications in combination with marble and other natural stones we recommend OTTO Marble Silicone Smoothing Agent GLM.

If using smoothing agent remove the emerging water streaks immediately after sealing. If the surfaces are cleaned at a later time, permanent streaks may remain.

Smoothing agent must not remain on the sealant joint and on adjacent surfaces, because dried residual sealant might cause optical impairmentes (dull/light spots).

As a matter of principle it is advisable to use the smoothing agent as sparingly as possible, for example by only slightly moistening the smoothing tools or applying the smoothing agent directly to the surface of the sealant with a clean paintbrush. Residual smoothing agent must be removed using clear water before it dries.

Please check compatibility to adjacent surfaces, e.g. coated wood, before use by making preliminary tests. 5 I and 10 I canisters are equipped with "Anti-bubble system".

Due to the many possible influences during and after application, the customer always has to carry out trials first. Please observe the recommended shelf life which is printed on the packaging.

#### **Packaging**

#### Hermann Otto GmbH

Krankenhausstr. 14 | 83413 Fridolfing, Germany & +49 8684 908-0 | @ info@otto-chemie.de www.otto-chemie.com

Application advice 449 8684 908-4300 atae@otto-chemie.de



Technical datasheet OTTO Smoothing Agent

	250 ml plastic bottle	1,000 ml plastic bottle	5 I plastic canister	10 l plastic canister	60 I plastic drum	200 I plastic drum with tap hole*
colourless	GL-52	GL-57	GL-59	GL-61	GL-65	on request
Pieces per packaging unit	1	1	1	1	1	1
Pieces per pallet			90	30	6	2

<sup>\*</sup> OTTO Drain cock 2" with venting (AERO-FLOW) sold separately

#### Safety precautions

Please observe the material safety data sheet.

# **Disposal**

Information about disposal: Please refer to the material safety data sheet.

# Warranty information

The above information and our technical application advice, whether verbal, in writing or by means of tests, are provided to the best of our knowledge, but are non-binding, including with regard to any third-party property rights. The information in this publication does not exempt the processor from carrying out their own tests on our products with regard to their suitability for the intended processes and purposes. The application, use and processing of our products and the products manufactured on the basis of our technical application advice are beyond our control and are therefore the sole responsibility of the processor. If the application for which our products are used is subject to an official authorisation requirement, the user is responsible for obtaining these authorisations. We reserve the right to adapt the product to technical progress and new developments. For the rest, we refer to our General Terms and Conditions, in particular with regard to any liability for defects. You can find our GTC at www.otto-chemie.de.