

OTTOFLEX® Protective tape

The cut-resistant protective tape

One-sided self-adhesive tape with polyamide fabric

For indoor and outdoor application

OFSCHUTZ

Characteristics

- ▶ Self-adhesive protective tape, tight-edged woven with double fabric with cut-resistant effect
- ▶ Protection of the compound seal (e.g. OTTOFLEX® sealing tape) against inadvertent separation in a sanitation case
- ▶ Textile made from polyamide and high molecular weight polyethylene with self-adhesive strip and peel-off foil
- ▶ Thin overall thickness to ensure it doesn't come across as too thick underneath the tile
- ▶ Flexible for easy processing
- ▶ Resistant to aging

Fields of application

- ▶ Self-adhesive protective tape as a supplement for sealing tapes for use in the areas of silicone joints
- ▶ All joint areas which need to be cut-proof. Wall joint, floor joint, bath and shower edge

Standards and tests

- ▶ Cut resistance passed according to EN 388
- ▶ UV-resistance according to DIN EN ISO 4892-2 at least 200 hours

Technical properties

| | |
|--------------------------------------|------------|
| Colour | white |
| Total thickness [mm] | 0,75 |
| Total width [mm] | 50 |
| Wide cut protection zone [mm] | 40 |
| Temperature resistance from/to [°C] | - 5 / + 60 |
| Wide cut protection zone [mm] | 10 |
| Shelf life at 23 °C/50 % RH [months] | 18 |

These data are not suitable for the issue of specifications. Please contact OTTO-CHEMIE before issuing specifications.

Application information

Once the peel-off foil has been removed from the rear, the tape is applied to the self-adhesive side on the sealing tape to be protected.

Please also see our user videos on our homepage (otto-chemie.de/anwendungsvideos).

Due to the many possible influences during and after application, the customer always has to carry out trials first.

Packaging

| Width | Order unit (OU) | Order code |
|-------|-------------------|------------|
| 5 cm | 1 roll, each 10 m | OFSCHUTZ10 |

Hermann Otto GmbH

Krankenhausstr. 14 | 83413 Fridolfing, Germany
 ☎ +49 8684 908-0 | @ info@otto-chemie.de
www.otto-chemie.com

💡 Application advice

☎ +49 8684 908-4300
 @ tae@otto-chemie.de



SEALING & BONDING

5 cm

1 roll, each 25 m

OFSCHUTZ25

Disposal

Product residues can be disposed of along with industrial waste as mixed plastics. Packaging materials (cardboard boxes, foils) are recyclable and hence should be recycled.

Warranty information

The above information and our technical application advice, whether verbal, in writing or by means of tests, are provided to the best of our knowledge, but are non-binding, including with regard to any third-party property rights. The information in this publication does not exempt the processor from carrying out their own tests on our products with regard to their suitability for the intended processes and purposes. The application, use and processing of our products and the products manufactured on the basis of our technical application advice are beyond our control and are therefore the sole responsibility of the processor. If the application for which our products are used is subject to an official authorisation requirement, the user is responsible for obtaining these authorisations. We reserve the right to adapt the product to technical progress and new developments. For the rest, we refer to our General Terms and Conditions, in particular with regard to any liability for defects. You can find our GTC at www.otto-chemie.de.