

OTTOSEAL® S 120



757

Hermann Otto GmbH
Krankenhausstr. 14, 83413 Fridolfing, Germany
 2014
 OC0120B

EN 15651 - 1, EN 15651 - 2
EN 15651 - 3, EN 15651 - 4

1-component silicone sealant, neutral curing
 for application in the facade
 for glazing
 for application in the sanitary area
 for pedestrian walkways

- Type F EXT-INT CC, G CC, S, PW INT
- Conditioning: Process A
- Carrier material: glass
- Pretreatment: OTTO Cleanprimer 1226

| | |
|---|-------------|
| Fire behaviour | Class E |
| Release of chemicals hazardous to health and/or the environment | evaluated |
| Water- and airtightness | |
| a) Tensile behaviour under pretensioning | passed (NF) |
| b) Stability under load | ≤ 3 mm |
| c) Volume loss | ≤ 10 % |
| d) Tearing strength | passed (NF) |
| e) Tensile behaviour, i.e. stress expansion under pretensioning after submersion in water | passed (NF) |
| f) Adhesive/stress expansion action after the effects of heat, water and artificial light | passed (NF) |
| g) Resilience | ≥ 70 % |
| h) Tensile properties / secant modulus in cold climate (at -30°C) | ≤ 0.9 MPa |
| i) Tensile properties under pretensioning in a cold climate (at -30°C) | passed (NF) |
| j) Microbiological growth | 0 |
| Durability | passed (NF) |