

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 30.11.2022

Version 5 (replaces version 4)

Revision: 30.11.2022

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name: OTTOSEAL S 105**
- **Application of the substance / the mixture** Silicone sealant
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
Hermann Otto GmbH  
Krankenhausstraße 14  
D-83413 Fridolfing  
Tel.: 0049/(0)8684/908-0  
Fax.: 0049/(0)8684/908-1840
- **Further information obtainable from:**  
Tel.: 0049- (0)8684- 908- 2363 ( -4300 )  
E-Mail: alois.parzinger@otto-chemie.de
- **1.4 Emergency telephone number:**  
Tel.: 0049- (0) 89- 192 40 (emergency telephone no.)  
+44 1865 407333 (Carechem 24)

### SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**  
The product is not classified, according to the GB CLP regulation.
- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008** Void
- **Hazard pictograms** Void
- **Signal word** Void
- **Hazard statements** Void
- **Additional information:**  
Ensure good ventilation during application and curing.  
Contains the active agent biocide 2-octyl-2H-isothiazol-3-one to protect against mould infestation.  
Keep out of the reach of children.  
Avoid contact with skin.  
Contains 2-octyl-2H-isothiazol-3-one. May produce an allergic reaction.  
Safety data sheet available on request.
- **2.3 Other hazards**  
During the application and curing process of the material chemicals are released as vapour (see item 11). Therefore ensure good ventilation or exhaustion if necessary.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

### SECTION 3: Composition/information on ingredients

- **3.2 Mixtures**
  - **Description:** Polydimethylsiloxane, filler, auxiliaries and acetoxysilane crosslinker
  - **Dangerous components:**
- |                                  |   |       |
|----------------------------------|---|-------|
| CAS: 17689-77-9                  | ethyltriacetoxysilane                                       | <2.5% |
| EINECS: 241-677-4                | ⚠ Skin Corr. 1A, H314; Eye Dam. 1, H318; ⚠ Acute Tox.       |       |
| Reg.nr.: 01-2119881778-15-xxxx4, | H302, EUH014, EUH071  |       |
|                                  | Specific concentration limits: Skin Irrit. 2; H315: C ≥ 5 % |       |
|                                  | Eye Irrit. 2; H319: C ≥ 5 %                                 |       |
| <br>                             |   |       |
| CAS: 4253-34-3                   | methylsilanetriyl triacetate                                | <2.5% |
| EINECS: 224-221-9                | ⚠ Skin Corr. 1C, H314; Eye Dam. 1, H318; ⚠ Acute Tox.       |       |
| Reg.nr.: 01-2119962266-32-xxxx4, | H302, EUH014  |       |
|                                  | Specific concentration limits: Skin Irrit. 2; H315: C ≥ 5 % |       |
|                                  | Eye Irrit. 2; H319: C ≥ 5 %                                 |       |

(Contd. on page 2)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 30.11.2022

Version 5 (replaces version 4)

Revision: 30.11.2022

**Trade name: OTTOSEAL S 105**

(Contd. of page 1)

CAS: 26530-20-1  
EINECS: 247-761-7

2-octyl-2H-isothiazol-3-one <0.1%  
 ⚠ Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 2, H330; ⚠ Skin Corr. 1, H314; Eye Dam. 1, H318;  
 ⚠ Aquatic Acute 1, H400 (M=100); Aquatic Chronic 1, H410 (M=100); ⚠ Skin Sens. 1A, H317, EUH071  
 ATE: LD50 oral: 125 mg/kg  
 LD50 dermal: 311 mg/kg  
 LC50/4 h inhalative: 0.27 mg/l  
 Specific concentration limit: Skin Sens. 1A; H317: C ≥ 0.0015 %

· **Additional information** For the wording of the listed hazard phrases refer to section 16.

### SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **General information** Take affected persons out into the fresh air.
- **After inhalation**  
Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.
- **After skin contact**  
Immediately wash with water and soap and rinse thoroughly.  
If skin irritation continues, consult a doctor.
- **After eye contact**  
Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing**  
Do not induce vomiting; call for medical help immediately. Show container or label.  
Rinse out mouth and then drink plenty of water in small amounts (if person is conscious).

### SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents**  
CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **5.2 Special hazards arising from the substance or mixture**  
Formation of toxic gases is possible during heating or in case of fire.
- **5.3 Advice for firefighters**
- **Protective equipment:**  
Mount respiratory protective device.  
Do not inhale explosion gases or combustion gases.

### SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**  
Particular danger of slipping on leaked/spilled product.  
Wear protective equipment. Keep unprotected persons away.  
Ensure adequate ventilation
- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**  
Dispose contaminated material as waste according to item 13.
- **6.4 Reference to other sections** See Section 8 for information on personal protection equipment.

### SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**  
Ensure good ventilation/exhaustion at the workplace.

(Contd. on page 3)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 30.11.2022

Version 5 (replaces version 4)

Revision: 30.11.2022

Trade name: OTTOSEAL S 105

(Contd. of page 2)

see item 8: Personal protective equipment

### 7.2 Conditions for safe storage, including any incompatibilities

#### Storage

Requirements to be met by storerooms and receptacles: Prevent any seepage into the ground.

Information about storage in one common storage facility: Store away from foodstuffs.

#### Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

CAS No.	Designation of material	%	Type	Value	Unit
<b>Additional Occupational Exposure Limit Values for possible hazards during processing:</b>					
<b>64-19-7 acetic acid</b>					
OEL Short-term value: 50 mg/m <sup>3</sup> , 20 ppm					
Long-term value: 25 mg/m <sup>3</sup> , 10 ppm					
WEL Short-term value: 50 mg/m <sup>3</sup> , 20 ppm					
Long-term value: 25 mg/m <sup>3</sup> , 10 ppm					
Additional information: The lists valid during the making were used as basis.					

### 8.2 Exposure controls

Appropriate engineering controls No further data; see item 7.

Individual protection measures, such as personal protective equipment

#### General protective and hygienic measures

The usual precautionary measures are to be adhered to when handling chemicals.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

#### Respiratory protection:

This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type ABEK according to standard EN 14387) is used.

Hand protection Protective gloves.

#### Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

Recommended glove types: nitrile rubber

Recommended thickness of the material: >0,4 mm

Penetration time of glove material Breakthrough time: 10 - 30 min

Eye/face protection Safety glasses

Body protection: Protective work clothing.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

#### General Information

Physical state

Fluid

Colour:

According to product specification

Odour:

Pungent

Melting point/freezing point:

undetermined

Boiling point or initial boiling point and boiling range

undetermined

Lower and upper explosion limit

Lower:

not applicable

Upper:

not applicable

Flash point:

Not applicable

(Contd. on page 4)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 30.11.2022

Version 5 (replaces version 4)

Revision: 30.11.2022

Trade name: OTTOSEAL S 105

(Contd. of page 3)

- **Decomposition temperature:** Not determined.
- **pH** Not applicable.
- **Viscosity:** Not determined.
- **Solubility**
- **Water:** Insoluble
- **Partition coefficient n-octanol/water (log value)** Not determined.
- **Vapour pressure:** Not determined.
- **Density and/or relative density**
- **Density:** see technical datasheet
- **Relative density** Not determined.
- **Vapour density** Not applicable.
- **9.2 Other information**
- **Form:** pasty
- **Auto-ignition temperature:** Product is not selfigniting.
- **Explosive properties:** Product does not present an explosion hazard.
- **Information with regard to physical hazard classes**
- **Aerosols** Void
- **Flammable liquids** Void

### SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**  
No decomposition if used according to specifications.  
Avoid strong heating.
- **10.6 Hazardous decomposition products:**  
Tests on representative products have shown that above temperatures of 150° C small quantities of formaldehyde are split off.  
see item 5.2

### SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity**
- **LD/LC50 values relevant for classification:**
- 17689-77-9 ethyltriacetoxysilane**  
Oral LD50 1,460 mg/kg (rat)
- 26530-20-1 2-octyl-2H-isothiazol-3-one**  
Oral LD50 125 mg/kg (ATE)  
Dermal LD50 311 mg/kg (ATE)  
Inhalative LC50/4 h 0.27 mg/l (ATE)
- **Skin corrosion/irritation**  
not irritating  
Source: ECHA  
Test in accordance with: OECD Guideline 404 (rabbit).
- **Serious eye damage/irritation**  
not irritating  
Source: ECHA  
Test in accordance with: OECD Guideline 405 (rabbit).
- **Other information (about experimental toxicology):**  
In curing the material splits off acetic acid as damp. This may cause irritating effects to skin, eyes or respiratory system.

(Contd. on page 5)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 30.11.2022

Version 5 (replaces version 4)

Revision: 30.11.2022

Trade name: OTTOSEAL S 105

(Contd. of page 4)

- **Additional toxicological information:**

- **26530-20-1 2-octyl-2H-isothiazol-3-one**

- Oral Acute toxicity estimate (ATE mix) 125 mg/kg (rat)

- Dermal Acute toxicity estimate (ATE mix) 311 mg/kg (rat)

- **11.2 Information on other hazards**

- **Endocrine disrupting properties**

- None of the ingredients is listed.

### SECTION 12: Ecological information

- **12.2 Persistence and degradability**

- **Other information:** Product is not biodegradable.

- **12.5 Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

- **12.6 Endocrine disrupting properties**

- The product does not contain substances with endocrine disrupting properties.

- **12.7 Other adverse effects**

- **Additional ecological information:**

- **General notes:**

- Do not allow product to reach ground water, water course or sewage system.

- Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water.

### SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**

- **Recommendation**

- Observe local by-laws.

- Already cured material can be disposed of with the domestic or commercial waste. Unconsumed material (fluid, paste-like) is to dispose of as hazardous waste.

- **Uncleaned packaging:**

- **Recommendation:**

- Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.

- Packagings that may not be cleansed are to be disposed of in the same manner as the product.

### SECTION 14: Transport information

- **14.1 UN number or ID number**

- **ADR, ADN, IMDG, IATA**

Void

- **14.2 UN proper shipping name**

- **ADR, ADN, IMDG, IATA**

Void

- **14.3 Transport hazard class(es)**

- **ADR, ADN, IMDG, IATA**

Void

- **Class**

Void

- **14.4 Packing group**

- **ADR, IMDG, IATA**

Void

- **14.5 Environmental hazards:**

- **Marine pollutant:**

No

- **14.6 Special precautions for user**

Not applicable.

- **14.7 Maritime transport in bulk according to IMO instruments**

Not applicable.

- **Transport/Additional information:**

- Not dangerous according to the above specifications.

(Contd. on page 6)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 30.11.2022

Version 5 (replaces version 4)

Revision: 30.11.2022

Trade name: OTTOSEAL S 105

· UN "Model Regulation":

Void

(Contd. of page 5)

### SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **National regulations**
- **Waterhazard class:** Water hazard class 1 (Self-assessment): slightly hazardous for water.
- **Details of international registration status:**  
**Listed on or in accordance with the following inventories:**
  - ECL - Korea listed
  - TCSI - Taiwan listed
  - AICS - Australia not listed
  - NZIoC - New Zealand not listed
  - UK REACH - Europe listed
  - DSL - Canada listed
  - IECSC - China listed
  - NZIoC - New Zealand listed
  - ENCS - Japan not listed
  - PICCS - Philippines listed
  - TSCA - USA listed
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

*This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.*

- **Relevant phrases**

- H301 Toxic if swallowed.
- H302 Harmful if swallowed.
- H311 Toxic in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H330 Fatal if inhaled.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- EUH014 Reacts violently with water.
- EUH071 Corrosive to the respiratory tract.

- **Department issuing SDS:** Tel.: 0049- (0)8684- 908- 2363

- **Contact:** Tel.: 0049- (0)8684- 908- 2363 ( -4300 )

- **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)  
 IMDG: International Maritime Code for Dangerous Goods  
 IATA: International Air Transport Association  
 GHS: Globally Harmonised System of Classification and Labelling of Chemicals  
 EINECS: European Inventory of Existing Commercial Chemical Substances  
 ELINCS: European List of Notified Chemical Substances  
 CAS: Chemical Abstracts Service (division of the American Chemical Society)  
 LC50: Lethal concentration, 50 percent  
 LD50: Lethal dose, 50 percent  
 PBT: Persistent, Bioaccumulative and Toxic  
 vPvB: very Persistent and very Bioaccumulative  
 Acute Tox. 3: Acute toxicity – Category 3  
 Acute Tox. 4: Acute toxicity – Category 4  
 Acute Tox. 2: Acute toxicity – Category 2  
 Skin Corr. 1: Skin corrosion/irritation – Category 1  
 Skin Corr. 1A: Skin corrosion/irritation – Category 1A

(Contd. on page 7)

**Safety data sheet**  
**according to 1907/2006/EC, Article 31**

Printing date 30.11.2022

Version 5 (replaces version 4)

Revision: 30.11.2022

**Trade name: OTTOSEAL S 105**

(Contd. of page 6)

*Skin Corr. 1C: Skin corrosion/irritation – Category 1C**Eye Dam. 1: Serious eye damage/eye irritation – Category 1**Skin Sens. 1A: Skin sensitisation – Category 1A**Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1**Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1***\* Data compared to the previous version altered.**

GB