Revision: 27.03.2025

Safety data sheet according to UK REACH

Printing date 27.03.2025

Version 5 (replaces version 4)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: OTTOSEAL S 125
- 1.2 Relevant identified uses of the substance or mixture and uses advised against
- · Application of the substance / the mixture Silicone sealant
- · Uses advised against Observe the information in the technical data sheet
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Hermann Otto GmbH Krankenhausstraße 14 D-83413 Fridolfing Tel.: 0049/(0)8684/908-0

Fax.: 0049/(0)8684/908-1840

· Further information obtainable from:

Tel.: 0049- (0)8684- 908- 2363 (-4300)

E-Mail: msds@otto-chemie.de

1.4 Emergency telephone number:

Tel.: 0049- (0) 89- 192 40 (emergency telephone no.)

+44 1865 407333 (Carechem 24)

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

The product is not classified, according to the GB CLP regulation.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008 Void
- · Hazard pictograms Void
- · Signal word Void
- · Hazard statements Void
- · Additional information:

Ensure good ventilation during application and curing.

Contains the active agent biocide 2-octyl-2H-isothiazol-3-one to protect against mould infestation. Keep out of the reach of children.

Avoid contact with skin.

EUH208 Contains trimethoxyvinylsilane, 3-aminopropyltriethoxysilane, 2-octyl-2H-isothiazol-3-one. May produce an allergic reaction.

EUH210 Safety data sheet available on request.

2.3 Other hazards

During processing and curing of the material, chemical substances are released into the air (see point 11). Therefore, ensure good room ventilation and, if necessary, exhaust ventilation.

- Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- Determination of endocrine-disrupting properties

This product does not contain components that are endocrine disruptors according to UK REACH Article 57(f) or Commission Delegated Regulation (EU) 2017/2100 or Commission Delegated Regulation (EU) 2018/605 in quantities of 0.1% or more.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description: Polydimethylsiloxane, filler, auxiliaries, alkoxysilane crosslinker
- Dangerous components:

CAS: 128446-60-6 EC number: 603-274-5 Reg.nr.: Polymer (REACH) Silsesquioxanes, 3-aminopropyl Me, ethoxy-terminated

♦ Flam. Liq. 3, H226; ♦ Eye Dam. 1, H318; ♦ Skin Irrit.

2. H315

(Contd. on page 2)

<5%

Printing date 27.03.2025 Version 5 (replaces version 4) Revision: 27.03.2025

Trade name: OTTOSEAL S 125

(Contd. of page 1)

CAS: 2768-02-7 trimethoxyvinylsilane

<2.5%

Reg.nr.: 01-2119513215-52-xxxx 1B, H317

CAS: 919-30-2 3-aminopropyltriethoxysilane <1%

Reg.nr.: 01-2119480479-24-XX 1B, H317

CAS: 26530-20-1 2-octyl-2H-isothiazol-3-one <0.1%

H330; ♠ Skin Corr. 1, H314; Eye Dam. 1, H318; ♠ Aquatic Acute 1, H400 (M=100); Aquatic Chronic 1, H410 (M=100); ♠ Skin Sens. 1A, H317, EUH071

ATE: LD50 oral: 125 mg/kg LD50 dermal: 311 mg/kg LC50/4 h inhalative: 0.27 mg/l

Specific concentration limit: Skin Sens. 1A; H317: C ≥

0.0015 %

· Additional information

For the wording of the listed hazard phrases refer to section 16.

Particulate raw materials with risk of inhalation are inextricably bound in the product and therefore does not trigger classification of the product for inhalation hazards. Due to the product's physical properties, particulate inhalation exposure is not possible.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

· After skin contact

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· After eye contact

Rinse opened eye for several minutes under running water. Then consult a doctor.

After swallowing

Do not induce vomiting; call for medical help immediately. Show container or label.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

- 5.3 Advice for firefighters
- Protective equipment:

Mount respiratory protective device.

Do not inhale explosion gases or combustion gases.

gb ·

Printing date 27.03.2025 Version 5 (replaces version 4) Revision: 27.03.2025

Trade name: OTTOSEAL S 125

(Contd. of page 2)

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures

 Ensure adequate ventilation
- · 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up:

 Dispose contaminated material as waste according to section 13.
- 6.4 Reference to other sections See Section 8 for information on personal protection equipment.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace. see item 8: Personal protective equipment

- 7.2 Conditions for safe storage, including any incompatibilities
- · Storage
- · Requirements to be met by storerooms and receptacles: Prevent any seepage into the ground.
- · Information about storage in one common storage facility: Store away from foodstuffs.
- Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- Ingredients with limit values that require monitoring at the workplace:
- CAS No. Designation of material % Type Value Unit
- · Additional Occupational Exposure Limit Values for possible hazards during processing:

67-56-1 methanol

WEL Short-term value: 333 mg/m³, 250 ppm Long-term value: 266 mg/m³, 200 ppm

Sk

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see section 7.
- Individual protection measures, such as personal protective equipment
- General protective and hygienic measures

The usual precautionary measures are to be adhered to when handling chemicals.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

- · Hand protection Protective gloves.
- · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

Recommended glove types: nitrile rubber

Recommended thickness of the material: >0,4 mm

- Penetration time of glove material Breakthrough time: 10 30 min
- Eye/face protection Safety glasses
- · Body protection: Protective work clothing.

-gb

Printing date 27.03.2025 Version 5 (replaces version 4) Revision: 27.03.2025

Trade name: OTTOSEAL S 125

(Contd. of page 3)

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Physical state Liquid

· Colour: According to product specification

Odour: CharacteristicMelting point/freezing point: undetermined

· Boiling point or initial boiling point and

boiling range undetermined

· Lower and upper explosion limit

Lower: not applicable
Upper: not applicable
Flash point: undetermined
Decomposition temperature: Not determined.
pH Not determined.
Viscosity: Not determined.

Solubility

· Water: Insoluble

· Partition coefficient n-octanol/water (log

value) Not determined.
• Vapour pressure: Not determined.

Density and/or relative density

Density: see technical data sheet

Relative density
 Vapour density
 Relative gas density
 Particle characteristics
 Not determined.
 Not applicable.
 undetermined
 undetermined

· 9.2 Other information

· Form: pasty

· Ignition temperature: Product is not selfigniting.

• Explosive properties: Product is not explosive. However, formation of

explosive air/vapour mixtures are possible.

· Information with regard to physical hazard

classes

· Aerosols Void · Flammable liquids Void

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

Avoid strong heating.

· 10.3 Possibility of hazardous reactions

Contact with humidity, water and protic agents produces ethanol.

Contact with humidity, water and protic agents produces methanol.

- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products:

see item 5.2

Tests on representative products have shown that above temperatures of 150° C small quantities of formaldehyde are split off.

gb

Printing date 27.03.2025 Version 5 (replaces version 4) Revision: 27.03.2025

Trade name: OTTOSEAL S 125

(Contd. of page 4)

SECTION 11: Toxicological information

- 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.
- LD/LC50 values relevant for classification:

2768-02-7 trimethoxyvinylsilane

Oral LD50 7,100 mg/kg (rat)
Dermal LD50 3,200 mg/kg (rab)
Inhalative LC50/4 h 16.8 mg/l (rat)

919-30-2 3-aminopropyltriethoxysilane

Oral LD50 1,570 mg/kg (rat)
Dermal LD50 4,290 mg/kg (rab)
26530-20-1 2-octyl-2H-isothiazol-3-one

Oral LD50 125 mg/kg (ATE) Dermal LD50 311 mg/kg (ATE) Inhalative LC50/4 h 0.27 mg/l (ATE)

- · Primary irritant effect:
- Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation

dermal: not sensitizing

Source: Conclusion by analogy

Test report according to OECD Guideline 406 (Guinea Pigs)

Based on available data, the classification criteria are not met.

- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.
- · Other information (about experimental toxicology):

Ethanol is released upon contact with water (humidity). According to literature, ethanol (67-17-5) irritates the mucous membranes, slightly irritates the skin, degreases the skin, is narcotic and may cause liver damage.

Product hydrolyses under formation of methanol (CAS no. 67-56-1). Methanol is toxic by inhalation, in contact with skin and if swallowed. Methanol causes damage to organs. Methanol is highly flammable. Inhalation of aerosol spray may damage health.

· Additional toxicological information:

26530-20-1 2-octyl-2H-isothiazol-3-one

Oral Acute toxicity estimate (ATE mix) 125 mg/kg (rat)

Dermal Acute toxicity estimate (ATE mix) 311 mg/kg (rat)

- 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

- · 12.1 Toxicity No further relevant information available
- · 12.2 Persistence and degradability No further relevant information available.
- · Other information: Product is not biodegradable.
- · 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.

(Contd. on page 6)

Printing date 27.03.2025 Version 5 (replaces version 4) Revision: 27.03.2025

Trade name: OTTOSEAL S 125

(Contd. of page 5)

- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties

For information on endocrine disrupting properties see section 11.

- · 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

Do not allow product to reach ground water, water course or sewage system.

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Observe local by-laws.

Already cured material can be disposed of with the domestic or commercial waste. Unconsumed material (fluid, paste-like) is to dispose of as hazardous waste.

- · Uncleaned packaging:
- Recommendation:

Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

SECTION 14: Transport information

· 14.1 UN number or ID number

· ADR, ADN, IMDG, IATA Void

· 14.2 UN proper shipping name

· ADR, ADN, IMDG, IATA Void

· 14.3 Transport hazard class(es)

· ADR, ADN, IMDG, IATA

· Class Void

14.4 Packing group

· ADR, IMDG, IATA Void

· 14.5 Environmental hazards:

· Marine pollutant: No

• 14.6 Special precautions for user Not applicable.

14.7 Maritime transport in bulk according to

IMO instruments Not applicable.

• Transport/Additional information: Not dangerous according to the above

specifications.

· UN "Model Regulation": Void

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Poisons Act
- Regulated explosives precursors

None of the ingredients is listed.

Regulated poisons

None of the ingredients is listed.

· Reportable explosives precursors

None of the ingredients is listed.

(Contd. on page 7)

(Contd. of page 6)

Safety data sheet according to UK REACH

Printing date 27.03.2025 Version 5 (replaces version 4) Revision: 27.03.2025

Trade name: OTTOSEAL S 125

· Reportable poisons

None of the ingredients is listed.

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

- · REGULATION (EU) 2019/1148
- Annex I RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

- · National regulations
- · Waterhazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.
- · Details of international registration status:

Listed on or in accordance with the following inventories:

UK REACH - Europe listed
AICS - Australia listed
DSL - Canada not listed
IECSC - China listed
ENCS - Japan listed
NZIOC - New Zealand not listed
PICCS - Philippines listed
ECL - Korea listed

TSCA - USA listed
TCSI - Taiwan not listed

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship. This Safety Data Sheets is in compliance with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

· Relevant phrases

H226 Flammable liquid and vapour.

H301 Toxic if swallowed. H302 Harmful if swallowed.

H311 Toxic in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H330 Fatal if inhaled.

H332 Harmful if inhaled.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

EUH071 Corrosive to the respiratory tract.

- Date of previous version: 27.03.2025
- · Version number of previous version: 4

(Contd. on page 8)

Printing date 27.03.2025

Version 5 (replaces version 4)

Trade name: OTTOSEAL S 125

(Contd. of page 7)

Revision: 27.03.2025

· Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

ATE: Acute toxicity estimate values

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 3: Acute toxicity – Category 3 Acute Tox. 2: Acute toxicity – Category 2

Acute Tox. 2. Acute toxicity – Category 2
Acute Tox. 4: Acute toxicity – Category 4

Skin Corr. 1: Skin corrosion/irritation – Category 1 Skin Corr. 1B: Skin corrosion/irritation – Category 1B Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Skin Sens. 1A: Skin sensitisation – Category 1A Skin Sens. 1B: Skin sensitisation – Category 1B

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

* Data compared to the previous version altered.

gb