Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.11.2024

Version 4 (replaces version 3)

Revision: 11.11.2024

SECTION 1: Identification of the substance/mixture and of the company/ undertaking 1.1 Product identifier Trade name: OTTO Primer 1102 UF: 3XT0-108X-P00K-M680 Product category PC9a Coatings and paints, thinners, paint removers Application of the substance / the mixture Priming 1.3 Details of the supplier of the safety data sheet Maundacturer/Supplier: Hermann Otto GmbH Krankenhausstraße 14 D-83413 Fridofing Tat: 0049/(0)8684/908-0 Fax:: 0049/(0)8684/908-1840 Further information obtainable from: Tel:: 0049-(0)888-2083 (-300) E-Mail: alois, parzinger@otto-chemie.de 1.4 Emergency telephone number: Tel:: 0049-(0) 889-303 (-300) E-Mail: alois, parzinger@otto-chemie.de 1.4 Emergency telephone number: Tel:: 0049-(0) 889-303 (-300) E-Mail: alois, parzinger@otto-chemie.de 1.4 Emergency telephone number: Tel:: 0049-(0) 889-192-40 (emergency telephone no.) Tel:: 0049-101 89-192 40 (emergency telephone no.) Tel:: 0049-101 89-192 40 (emergency telephone no.) Tel:: 0049-101 80-192 5 Highthy flammable liquid and vapour. Skin Intit. J. H315 Causes skini initation. <t< th=""></t<>
 Trade name: OTTO Primer 1102 UFF: 3XTO-106X-PROK-M680 Product category PC/S8 Coatings and paints, thinners, paint removers Application of the substance / the mixture Priming 1.3 Details of the supplier of the safety data sheet Manufacturer/Supplier: Hermann Otto GmbH Krankenhausstraße 14 D-83413 Fridolfing Tel:: 0049/(0)8684/908-1840 Further information obtainable from: Tel:: 0049/(0)8684/908-1840 Further information obtainable from: Tel:: 0049-(0)8684/908-1840 Further information obtainable from: Tel:: 0049-(0)8684/908-2363 (-4300) E-Mali: alois parzinger@otto-chemie.de 1.4 Emergency telephone number: Tel:: 0049-(0) 89-192 40 (emergency telephone no.) Tel:: 0049-(0) 89-192 40 (emergency telephone no.) Tel:: 0049-(0) 89-192 40 (emergency telephone no.) Tel:: 0049-(0) 89-193 23 (BASF Plant fine brigade) +44 1865 407333 (Carechem 24) SECTION 2: Hazards identification SteCTION 2: Hazards identification Storm: L. H315 Causes skin iritation. Eye Inti. 2. H312 May cause downses or dizziness. STOT RE 2 H338 May cause downsees or dizziness. STOT SE 3 H336 May cause downsees or dizziness. STOT SE 2 H336 May cause downsees or dizziness. STOT SE 2 H336 May cause downsees or dizziness. STOT SE 2 H336 May cause downsees or dizziness. STOT SE 2 H336 May cause downsees or dizziness. STOT SE 2 H336 May cause downsees or dizziness. STOT SE 2 H336 May cause downsees or dizziness. STOT RE 2 H336 May cause downsees or dizziness. STOT RE 2 H336 May cause downsees or dizziness. STOT RE 2 H336 May cause downsees or dizziness. STOT SE 2 H336 May cause downsees or dizziness. STOT SE 3 H396 Cause skin iritation. Hazard pictograms Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP regulation. H326 Ka
 UF: 3XT0-105X-POK-M680 Product category PC98 Coatings and paints, thinners, paint removers Application of the substance / the mixture Priming 1.3 Details of the supplier of the safety data sheet Mauntacturer/Supplier: Hermann Otto GmbH Krankenhausstraße 14 D-83413 Fridolfing Tel:: 0049/(0)8684908-1840 Further information obtainable from: Tel:: 0049/(0)8684908-1840 Further information obtainable from: Tel:: 0049/(0)8684908-1840 Further information obtainable from: Tel:: 0049/(0)8684908-2836 (-4800) E-Mail: alois parzinger@otto-chemie.de 1.4 Emergency telephone number: Tel:: 0049/621/60-43333 (EASF Plant fire brigade) +44 1865 407333 (Carechem 24) SECTION 2: Hazards identification 2.1 Classification of the substance or mixture Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008 Fiam. Lig. 2 H225 Highly flammable liquid and vapour. Skin Irrit. 2: H315 Causes skin irritation. Eyr Irrit. 2: H315 Causes skin irritation. STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure. Ap. Tox. 1: Have fatal if swallowed and enters airways. 2.2 Label elements Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP regulation. Hazard pictograms Signal word Danger Hazard determining components of labelling: acetone xylene (mix) elements Hazard determining components of labelling: acetone xylene (mix) elements Hazard statements <l< td=""></l<>
• Manufacturer/Supplier: Herman Otto GmbH Krankenhaussträle 14 D-83413 Fridölfing Tel:: 0049/(0)8684/908-100 Fax:: 0049/(0)8684/908-1840 • Jutther information obtainable from: Tel:: 0049 (0) 8684-908-2863 (-4300) E-Mali: alois.parzinger@otto-chemie.de 1.4 Emergency telephone number: Tel:: 0049-(0) 80-192-40 (emergency telephone no.) Tel:: 0049-(0) 80-192-40 (emergency telephone no.) Tel:: 0049-(0) 80-192-40 (emergency telephone no.) Tel:: 0049-621/80-43333 (BASF Plant fire brigade) +44 1865 407333 (Carechem 24) SECTION 2: Hazards identification 2.1 Classification of the substance or mixture • Classification according to Regulation (EC) No 1272/2008 Flam: Li, 2. H225 Highly flammable liquid and vapour. Skin Irrit. 2 H315 Causes skin irritation. Eye Irrit. 2 H315 Causes skin irritation. STOT SE 3 H336 May cause drowsiness or dizziness. STOT RE 2 H373 May cause drowsiness or dizziness. STOT SE 3 H386 Hay to Eatel if swallowed and enters airways. • 2.2 Label elements Labeling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP regulation. • Hazard pictograms • Gause Jamage to Jamage I • Hazard determining components of labelling: acetone xylene (mix) ethylbenzene • Hazard statements H225 Highly flammable liquid and vapour. H315 Causes skin irritation. H326 May cause drowsiness or dizziness. H326 May cause drowsiness or dizziness. H326 May cause drowsiness or dizziness. H336 May cause drowsiness or dizziness. H334 May cause drowsiness or dizziness. H334 May cause drowsiness or dizziness. H334 May cause drowsines
Tel: 0049- (0)8684-908-2863 (-4300) E-Mail: alois.parzinger@otto-chemie.de 1.4 Emergency telephone number: Tel: 0049-(0) 89- 192 40 (emergency telephone no.) Tel: 0049-(0) 89- 192 40 (emergency telephone no.) Tel: 0049/621/60-43333 (BASF Plant fire brigade) +44 1865 407333 (Carechem 24) SECTION 2: Hazards identification 2.1 Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008 Flam. Liq. 2 H225 Highly flammable liquid and vapour. Skin Irrit. 2 H315 Causes skin irritation. Eye Irrit. 2 H315 Causes serious eye irritation. STOT SE 3 H336 May cause drowsiness or dizziness. STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure. Asp. Tox. 1 H304 May be fatal if swallowed and enters airways. 2.2 Labeling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP regulation. Hazard pictograms 5.5 GHS02 GHS07 GHS08 5.5 GHS02 GHS07 GHS08 5.5 Ginal word Danger Hazard-determining components of labelling: acetone xylene (mix) ethylbenzene Hazard statements H225 Highly flammable liquid and vapour. H316 Causes skin irritation. H336 May cause drowsiness or dizziness. H334 May cause drowsiness or dizziness. H334 May cause drowsiness or dizziness. H334 May cause drowsines or dizzines. H334 May cause drowsines or dizzines.
2.1 Classification of the substance or mixtureClassification according to Regulation (EC) No 1272/2008Flam. Liq. 2 H225 Highly flammable liquid and vapour.Skin Irrit. 2H315 Causes skin irritation.Eye Irrit. 2H319 Causes serious eye irritation.STOT SE 3 H336 May cause drowsiness or dizziness.STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.Asp. Tox. 1 H304 May be fatal if swallowed and enters airways. 2.1 Label elements1.2 Label elements1.2 Label ferments1.2 Label ferments1.2 Label ferments1.2 Label for gray and the ferminity of the CEO No 1272/2008 The product is classified and labelled according to the GB CLP regulation.Hazard pictograms (Fig.) (Fig.) (Fig.) (Fig.)(Fig.) (Fig.) (Fig.)(Fig.)
• Classification according to Regulation (EC) No 1272/2008 Flam. Liq. 2 H225 Highly flammable liquid and vapour. Skin Irrit. 2 H315 Causes skin irritation. Eye Irrit. 2 H319 Causes serious eye irritation. STOT SE 3 H336 May cause drowsiness or dizziness. STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure. Asp. Tox. 1 H304 May be fatal if swallowed and enters airways. • 2.2 Label elements • Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP regulation. • Hazard pictograms • GHS02 GHS07 GHS08 • Signal word Danger • Hazard-determining components of labelling: acetone xylene (mix) ethylbenzene • Hazard statements H225 Highly flammable liquid and vapour. H315 Causes skin irritation. H319 Causes serious eye irritation. H336 May cause domage to organs through prolonged or repeated exposure. H374 May be fatal if swallowed and enters airways.
 Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP regulation. Hazard pictograms Image: Image: Image
 Signal word Danger Hazard-determining components of labelling: acetone xylene (mix) ethylbenzene Hazard statements H225 Highly flammable liquid and vapour. H315 Causes skin irritation. H319 Causes serious eye irritation. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness. H373 May cause damage to organs through prolonged or repeated exposure. H304 May be fatal if swallowed and enters airways.
 Hazard-determining components of labelling: acetone xylene (mix) ethylbenzene Hazard statements H225 Highly flammable liquid and vapour. H315 Causes skin irritation. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness. H373 May cause damage to organs through prolonged or repeated exposure. H304 May be fatal if swallowed and enters airways.
 Hazard-determining components of labelling: acetone xylene (mix) ethylbenzene Hazard statements H225 Highly flammable liquid and vapour. H315 Causes skin irritation. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness. H373 May cause damage to organs through prolonged or repeated exposure. H304 May be fatal if swallowed and enters airways.
• •
(Contd. on page 2)

according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.11.2024

Version 4 (replaces version 3)

Revision: 11.11.2024

Trade name: OTTO Primer 1102

	(Contd. of pa
Precautionary P102	Keep out of reach of children.
P210	
F210	Keep away from heat, hot surfaces, sparks, open flames and other ignition
0074	sources. No smoking.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves / eye protection / face protection.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
	31 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P302+P352	IF ON SKIN: Wash with plenty of soap and water.
P304+P312	IF INHALED: Call a POISON CENTER/doctor if you feel unwell.
P305+P351+P3	38 IF IN EYES: Rinse cautiously with water for several minutes. Remove contac
	lenses, if present and easy to do. Continue rinsing. Get medical advice/attent
Additional info	rmation:
EUH066 Repea	ted exposure may cause skin dryness or cracking.
	s: Reportable explosives precursors. Making available, introduction, possession
	Regulation (EU) 2019/1148, Article 9.
	ckages where the contents do not exceed 125 ml
Hazard pictogr	
nazara protogr	
\wedge	
\sim	
GHS02 GHS0)7 GHS08
Signal word Da	anger
Hazard-determ	ining components of labelling:
acetone	ining components of labeling.
vulana (miv)	
xylene (mix)	
ethylbenzene	
ethylbenzene Hazard statem	
ethylbenzene Hazard statem H336 May caus	e drowsiness or dizziness.
ethylbenzene Hazard statem H336 May caus H373 May caus	e drowsiness or dizziness. e damage to organs through prolonged or repeated exposure.
ethylbenzene Hazard statem H336 May caus H373 May caus H304 May be fa	e drowsiness or dizziness. e damage to organs through prolonged or repeated exposure. tal if swallowed and enters airways.
ethylbenzene Hazard statem H336 May caus H373 May caus	e drowsiness or dizziness. e damage to organs through prolonged or repeated exposure. tal if swallowed and enters airways.
ethylbenzene Hazard statem H336 May caus H373 May caus H304 May be fa Precautionary	e drowsiness or dizziness. e damage to organs through prolonged or repeated exposure. tal if swallowed and enters airways. statements
ethylbenzene Hazard statem H336 May caus H373 May caus H304 May be fa Precautionary P102 Kee	e drowsiness or dizziness. e damage to organs through prolonged or repeated exposure. tal if swallowed and enters airways. statements ep out of reach of children.
ethylbenzene Hazard statem H336 May caus H373 May caus H304 May be fa Precautionary P102 Kee P210 Kee	e drowsiness or dizziness. e damage to organs through prolonged or repeated exposure. tal if swallowed and enters airways. statements ep out of reach of children. ep away from heat, hot surfaces, sparks, open flames and other ignition sources.
ethylbenzene Hazard statem H336 May caus H373 May caus H304 May be fa Precautionary P102 Kee P210 Kee smo	e drowsiness or dizziness. e damage to organs through prolonged or repeated exposure. tal if swallowed and enters airways. statements ep out of reach of children. ep away from heat, hot surfaces, sparks, open flames and other ignition sources. oking.
ethylbenzene Hazard statem H336 May caus H373 May caus H304 May be fa Precautionary P102 Kee P210 Kee Sm P280 We	e drowsiness or dizziness. e damage to organs through prolonged or repeated exposure. tal if swallowed and enters airways. statements ep out of reach of children. ep away from heat, hot surfaces, sparks, open flames and other ignition sources. oking. ar protective gloves / eye protection.
ethylbenzene Hazard statem H336 May caus H373 May caus H304 May be fa Precautionary P102 Kee P210 Kee Sm P280 We P301+P310 IF S	e drowsiness or dizziness. e damage to organs through prolonged or repeated exposure. tal if swallowed and enters airways. statements ep out of reach of children. ep away from heat, hot surfaces, sparks, open flames and other ignition sources. oking. ar protective gloves / eye protection. SWALLOWED: Immediately call a POISON CENTER/ doctor.
ethylbenzene Hazard statem H336 May caus H373 May caus H304 May be fa Precautionary P102 Kee P210 Kee Sm P280 We P301+P310 IF S P331 Do	e drowsiness or dizziness. e damage to organs through prolonged or repeated exposure. tal if swallowed and enters airways. statements ep out of reach of children. ep away from heat, hot surfaces, sparks, open flames and other ignition sources. oking. ar protective gloves / eye protection. SWALLOWED: Immediately call a POISON CENTER/ doctor. NOT induce vomiting.
ethylbenzene Hazard statem H336 May caus H373 May caus H304 May be fa Precautionary P102 Kee P210 Kee P210 Kee P280 We P301+P310 IF S P331 Do 2.3 Other haza	e drowsiness or dizziness. e damage to organs through prolonged or repeated exposure. tal if swallowed and enters airways. statements ep out of reach of children. ep away from heat, hot surfaces, sparks, open flames and other ignition sources. oking. ar protective gloves / eye protection. SWALLOWED: Immediately call a POISON CENTER/ doctor. NOT induce vomiting. rds
ethylbenzene Hazard statem H336 May caus H373 May caus H304 May be fa Precautionary P102 Kee P210 Kee P210 Kee P301+P310 IF S P331 Do 2.3 Other hazan Results of PBT	e drowsiness or dizziness. e damage to organs through prolonged or repeated exposure. tal if swallowed and enters airways. statements ep out of reach of children. ep away from heat, hot surfaces, sparks, open flames and other ignition sources. oking. ar protective gloves / eye protection. SWALLOWED: Immediately call a POISON CENTER/ doctor. NOT induce vomiting. rds and vPvB assessment
ethylbenzene Hazard statem H336 May caus H373 May caus H304 May be fa Precautionary P102 Kee P210 Kee P210 Kee P280 We P301+P310 IF S P331 Do 2.3 Other haza Results of PB1 PBT: Not applic	e drowsiness or dizziness. e damage to organs through prolonged or repeated exposure. tal if swallowed and enters airways. statements ep out of reach of children. ep away from heat, hot surfaces, sparks, open flames and other ignition sources. oking. ar protective gloves / eye protection. SWALLOWED: Immediately call a POISON CENTER/ doctor. NOT induce vomiting. rds ' and vPvB assessment able.
ethylbenzene Hazard statem H336 May caus H373 May caus H304 May be fa Precautionary P102 Kee P210 Kee P210 Kee P280 We P301+P310 IF S P331 Do 2.3 Other hazau Results of PBT PBT: Not applic vPvB: Not applic	e drowsiness or dizziness. e damage to organs through prolonged or repeated exposure. tal if swallowed and enters airways. statements ep out of reach of children. ep away from heat, hot surfaces, sparks, open flames and other ignition sources. oking. ar protective gloves / eye protection. SWALLOWED: Immediately call a POISON CENTER/ doctor. NOT induce vomiting. rds and vPvB assessment able. cable.
ethylbenzene Hazard statem H336 May caus H373 May caus H304 May be fa Precautionary P102 Kee P210 Kee P210 Kee P280 We P301+P310 IF S P331 Do 2.3 Other hazau Results of PBT PBT: Not applic vPvB: Not applic	e drowsiness or dizziness. e damage to organs through prolonged or repeated exposure. tal if swallowed and enters airways. statements ep out of reach of children. ep away from heat, hot surfaces, sparks, open flames and other ignition sources. oking. ar protective gloves / eye protection. SWALLOWED: Immediately call a POISON CENTER/ doctor. NOT induce vomiting. rds ' and vPvB assessment able.
ethylbenzene Hazard statem H336 May caus H373 May caus H304 May be fa Precautionary P102 Kee P210 Kee P210 Kee P280 We P301+P310 IF S P331 Do 2.3 Other hazar Results of PBT PBT: Not applic VPvB: Not applic Determination	e drowsiness or dizziness. e damage to organs through prolonged or repeated exposure. tal if swallowed and enters airways. statements ep out of reach of children. ep away from heat, hot surfaces, sparks, open flames and other ignition sources. oking. ar protective gloves / eye protection. SWALLOWED: Immediately call a POISON CENTER/ doctor. NOT induce vomiting. rds and vPvB assessment able. cable.
ethylbenzene Hazard statem H336 May caus H373 May caus H304 May be fa Precautionary P102 Kee P210 Kee P210 Kee P210 Kee P301+P310 IF S P331 Do 2.3 Other hazar Results of PBT PBT: Not applic vPvB: Not applic Determination This product do	e drowsiness or dizziness. e damage to organs through prolonged or repeated exposure. tal if swallowed and enters airways. statements ep out of reach of children. ep away from heat, hot surfaces, sparks, open flames and other ignition sources. oking. ar protective gloves / eye protection. SWALLOWED: Immediately call a POISON CENTER/ doctor. NOT induce vomiting. rds rand vPvB assessment able. cable. of endocrine-disrupting properties es not contain components that are endocrine disruptors according to UK REAC
ethylbenzene Hazard statem H336 May caus H373 May caus H304 May be fa Precautionary P102 Kee P210 Kee P210 Kee P280 We P301+P310 IF S P331 Do 2.3 Other hazal Results of PB1 PBT: Not applic vPvB: Not applic Determination This product do Article 57(f) or C	e drowsiness or dizziness. e damage to organs through prolonged or repeated exposure. tal if swallowed and enters airways. statements ep out of reach of children. ep away from heat, hot surfaces, sparks, open flames and other ignition sources. oking. ar protective gloves / eye protection. SWALLOWED: Immediately call a POISON CENTER/ doctor. NOT induce vomiting. rds and vPvB assessment able. cable. of endocrine-disrupting properties es not contain components that are endocrine disruptors according to UK REAC Commission Delegated Regulation (EU) 2017/2100 or Commission Delegated
ethylbenzene Hazard statem H336 May caus H373 May caus H304 May be fa Precautionary P102 Kee P210 Kee P210 Kee P280 We P301+P310 IF S P331 Do 2.3 Other hazal Results of PB1 PBT: Not applic vPvB: Not applic Determination This product do Article 57(f) or C	e drowsiness or dizziness. e damage to organs through prolonged or repeated exposure. tal if swallowed and enters airways. statements ep out of reach of children. ep away from heat, hot surfaces, sparks, open flames and other ignition sources. oking. ar protective gloves / eye protection. SWALLOWED: Immediately call a POISON CENTER/ doctor. NOT induce vomiting. rds rand vPvB assessment able. cable. of endocrine-disrupting properties es not contain components that are endocrine disruptors according to UK REAC
ethylbenzene Hazard statem H336 May caus H373 May caus H304 May be fa Precautionary P102 Kee P210 Kee P210 Kee P280 We P301+P310 IF S P331 Do 2.3 Other hazal Results of PB1 PBT: Not applic vPvB: Not applic Determination This product do Article 57(f) or C	e drowsiness or dizziness. e damage to organs through prolonged or repeated exposure. tal if swallowed and enters airways. statements ep out of reach of children. ep away from heat, hot surfaces, sparks, open flames and other ignition sources. oking. ar protective gloves / eye protection. SWALLOWED: Immediately call a POISON CENTER/ doctor. NOT induce vomiting. rds and vPvB assessment able. cable. of endocrine-disrupting properties es not contain components that are endocrine disruptors according to UK REAC Commission Delegated Regulation (EU) 2017/2100 or Commission Delegated
ethylbenzene Hazard statem H336 May caus H373 May caus H373 May caus P102 Kee P210 Kee P210 Kee P210 Kee P210 Kee P301+P310 IF S P331 Do 2.3 Other haza Results of PB1 PBT: Not applic vPvB: Not applic Determination This product do Article 57(f) or C Regulation (EU)	e drowsiness or dizziness. e damage to organs through prolonged or repeated exposure. tal if swallowed and enters airways. statements ep out of reach of children. ep away from heat, hot surfaces, sparks, open flames and other ignition sources. oking. ar protective gloves / eye protection. SWALLOWED: Immediately call a POISON CENTER/ doctor. NOT induce vomiting. rds and vPvB assessment able. cable. of endocrine-disrupting properties es not contain components that are endocrine disruptors according to UK REAC Commission Delegated Regulation (EU) 2017/2100 or Commission Delegated

· Description: Solvent mixture with additives.

• Dangerous components: CAS: 67-64-1 EINECS: 200-662-2 Reg.nr.: 01-2119471330-49-0000

acetone 50-100% ♦ Flam. Liq. 2, H225; ♦ Eye Irrit. 2, H319; STOT SE 3, H336, EUH066

(Contd. on page 3)

according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.11.2024

Version 4 (replaces version 3)

Revision: 11.11.2024

Trade name: OTTO Primer 1102

	(Col	ntd. of page 2)
CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32-	xylene (mix) Flam. Liq. 3, H226; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H312; Acute Tox. 4, H332;	
0000	Skin Irrit. Ž, H315; Eye Irrit. 2, H319; STOT SE 3, H335	
CAS: 78-93-3 EINECS: 201-159-0 Reg.nr.: 01-2119457290-43	butanone ♦ Flam. Liq. 2, H225; ♦ Eye Irrit. 2, H319; STOT SE 3 H336, EUH066	<10% 3,
CAS: 100-41-4 EINECS: 202-849-4 Reg.nr.: 01-2119489370-35	ethylbenzene ♦ Flam. Liq. 2, H225; ♦ STOT RE 2, H373; Asp. Tox. 1, H304; ♦ Acute Tox. 4, H332; Aquatic Chronic 3, H412	<5%
CAS: 71-36-3 EINECS: 200-751-6 Reg.nr.: 01-2119484630-38	butanol � Flam. Liq. 3, H226; � Eye Dam. 1, H318; � Acute Tox. 4, H302; Skin Irrit. 2, H315; STOT SE 3, H335- H336	<2.5%

· Additional information For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

• 4.1 Description of first aid measures

· General information

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- After inhalation Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.
- After skin contact Immediately wash with water and soap and rinse thoroughly. If skin irritation continues, consult a doctor.
- · After eye contact
- Rinse opened eye for several minutes under running water. Then consult a doctor. After swallowing
- Do not induce vomiting; call for medical help immediately. Show container or label.
- 4.2 Most important symptoms and effects, both acute and delayed
- Headache
- Dizziness
- Dizziness
- Nausea

• **4.3 Indication of any immediate medical attention and special treatment needed** If swallowed or in case of vomiting, danger of entering the lungs

SECTION 5: Firefighting measures

· Suitable extinguishing agents

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents Water with full jet.
- 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

5.3 Advice for firefighters

· Protective equipment: Do not inhale explosion gases or combustion gases.

· Additional information Cool endangered receptacles with water spray.

(Contd. on page 4)

 ^{5.1} Extinguishing media

according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.11.2024

Version 4 (replaces version 3)

Revision: 11.11.2024

Trade name: OTTO Primer 1102

(Contd. of page 3)

SECTION 6: Accidental release measures

• 6.1 Personal precautions, protective equipment and emergency procedures Ensure adequate ventilation

Keep away from ignition sources

. 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to section 13.

6.4 Reference to other sections See Section 8 for information on personal protection equipment.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. see item 8: Personal protective equipment
- Information about fire and explosion protection: Protect against electrostatic charges. Traces of flammable substances may collect in the steam chamber of enclosed systems. Keep clear ofignition sources. Highly volatile, flammable constituents are released during processing.

Flammable gas-air mixtures may form in empty receptacles.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage
- Requirements to be met by storerooms and receptacles: Provide solvent resistant, sealed floor. Prevent any seepage into the ground.
- · Information about storage in one common storage facility: Store away from foodstuffs.
- **Further information about storage conditions:** Store in cool, dry conditions in well sealed receptacles. Protect from heat and direct sunlight.
- Store receptacle in a well ventilated area.
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

67-64-1 acetone

WEL Short-term value: 3620 mg/m³, 1500 ppm Long-term value: 1210 mg/m³, 500 ppm

78-93-3 butanone

WEL Short-term value: 899 mg/m³, 300 ppm Long-term value: 600 mg/m³, 200 ppm Sk, BMGV

100-41-4 ethylbenzene

WEL Short-term value: 552 mg/m³, 125 ppm Long-term value: 441 mg/m³, 100 ppm Sk

71-36-3 butanol

WEL Short-term value: 154 mg/m³, 50 ppm Sk

(Contd. on page 5)

gb

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.11.2024

Version 4 (replaces version 3)

Revision: 11.11.2024

Trade name: OTTO Primer 1102

	(Contd. of page
Ingredients with biological limit valu	ues:
78-93-3 butanone	
BMGV 70 μmol/L	
Medium: urine	
Sampling time: post shift	
Parameter: butan-2-one	
Additional information: The lists vali	id during the making were used as basis.
8.2 Exposure controls	
Appropriate engineering controls N	lo further data: see section 7
	ch as personal protective equipment
General protective and hygienic me	
	e to be adhered to when handling chemicals.
Wash hands before breaks and at the	
Avoid contact with the eyes and skin.	
Pregnant women should strictly avoid	inhalation or skin contact.
Respiratory protection:	
	vice when high concentrations are present.
Hand protection Protective gloves.	
Material of gloves	
The selection of the suitable gloves do	pes not only depend on the material, but also on further mark
of quality and varies from manufacture	er to manufacturer.
Recommended glove material: Butyl ru	
Recommended thickness of the mater	rial: >0,4 mm
Penetration time of glove material B	
Eye/face protection Tightly sealed go	oggles.
Body protection: Protective work clot	thing
SECTION 9: Physical and che	
SECTION 9: Physical and che	emical properties
SECTION 9: Physical and che 9.1 Information on basic physical an General Information	emical properties
SECTION 9: Physical and che 9.1 Information on basic physical an General Information Physical state	emical properties nd chemical properties Fluid
SECTION 9: Physical and che 9.1 Information on basic physical ai General Information Physical state Colour:	emical properties nd chemical properties Fluid Colourless
SECTION 9: Physical and che 9.1 Information on basic physical ai General Information Physical state Colour: Odour:	emical properties nd chemical properties Fluid Colourless Characteristic
SECTION 9: Physical and che 9.1 Information on basic physical au General Information Physical state Colour: Odour: Melting point/freezing point:	emical properties nd chemical properties Fluid Colourless Characteristic undetermined
SECTION 9: Physical and che 9.1 Information on basic physical ar General Information Physical state Colour: Odour: Melting point/freezing point: Boiling point or initial boiling point	emical properties nd chemical properties Fluid Colourless Characteristic undetermined and
SECTION 9: Physical and che 9.1 Information on basic physical ar General Information Physical state Colour: Odour: Melting point/freezing point: Boiling point or initial boiling point boiling range	emical properties nd chemical properties Fluid Colourless Characteristic undetermined and 55 °C (Aceton)
SECTION 9: Physical and che 9.1 Information on basic physical an General Information Physical state Colour: Odour: Melting point/freezing point: Boiling point or initial boiling point boiling range Flammability	emical properties nd chemical properties Fluid Colourless Characteristic undetermined and
SECTION 9: Physical and che 9.1 Information on basic physical au General Information Physical state Colour: Odour: Melting point/freezing point: Boiling point or initial boiling point boiling range Flammability Lower and upper explosion limit	emical properties nd chemical properties Fluid Colourless Characteristic undetermined and 55 °C (Aceton) Highly flammable.
SECTION 9: Physical and che 9.1 Information on basic physical an General Information Physical state Colour: Odour: Melting point/freezing point: Boiling point or initial boiling point boiling range Flammability Lower and upper explosion limit Lower:	emical properties nd chemical properties Fluid Colourless Characteristic undetermined and 55 °C (Aceton) Highly flammable. 2.1 Vol % (Aceton)
SECTION 9: Physical and che 9.1 Information on basic physical an General Information Physical state Colour: Odour: Melting point/freezing point: Boiling point or initial boiling point boiling range Flammability Lower and upper explosion limit Lower: Upper:	emical properties nd chemical properties Fluid Colourless Characteristic undetermined and 55 °C (Aceton) Highly flammable. 2.1 Vol % (Aceton) 13 Vol % (Aceton)
SECTION 9: Physical and che 9.1 Information on basic physical an General Information Physical state Colour: Odour: Melting point/freezing point: Boiling point or initial boiling point boiling range Flammability Lower and upper explosion limit Lower: Upper: Flash point:	emical properties nd chemical properties Fluid Colourless Characteristic undetermined and 55 °C (Aceton) Highly flammable. 2.1 Vol % (Aceton) 13 Vol % (Aceton) -17 °C (Aceton)
SECTION 9: Physical and che 9.1 Information on basic physical au General Information Physical state Colour: Odour: Melting point/freezing point: Boiling point or initial boiling point boiling range Flammability Lower and upper explosion limit Lower: Upper: Flash point: Auto-ignition temperature:	emical properties nd chemical properties Fluid Colourless Characteristic undetermined and 55 °C (Aceton) Highly flammable. 2.1 Vol % (Aceton) 13 Vol % (Aceton) -17 °C (Aceton) 465 °C
SECTION 9: Physical and che 9.1 Information on basic physical au General Information Physical state Colour: Odour: Melting point/freezing point: Boiling point or initial boiling point boiling range Flammability Lower and upper explosion limit Lower: Upper: Flash point: Auto-ignition temperature: Decomposition temperature:	emical properties nd chemical properties Fluid Colourless Characteristic undetermined and 55 °C (Aceton) Highly flammable. 2.1 Vol % (Aceton) 13 Vol % (Aceton) -17 °C (Aceton) 465 °C Not determined.
SECTION 9: Physical and che 9.1 Information on basic physical an General Information Physical state Colour: Odour: Melting point/freezing point: Boiling point or initial boiling point boiling range Flammability Lower and upper explosion limit Lower: Upper: Flash point: Auto-ignition temperature: Decomposition temperature: pH	emical properties nd chemical properties Fluid Colourless Characteristic undetermined and 55 °C (Aceton) Highly flammable. 2.1 Vol % (Aceton) 13 Vol % (Aceton) 13 Vol % (Aceton) 465 °C Not determined. Not applicable.
SECTION 9: Physical and che 9.1 Information on basic physical au General Information Physical state Colour: Odour: Melting point/freezing point: Boiling point or initial boiling point boiling range Flammability Lower and upper explosion limit Lower: Upper: Flash point: Auto-ignition temperature: Decomposition temperature: pH Viscosity:	emical properties nd chemical properties Fluid Colourless Characteristic undetermined and 55 °C (Aceton) Highly flammable. 2.1 Vol % (Aceton) 13 Vol % (Aceton) -17 °C (Aceton) 465 °C Not determined.
SECTION 9: Physical and che 9.1 Information on basic physical au General Information Physical state Colour: Odour: Melting point/freezing point: Boiling point or initial boiling point boiling range Flammability Lower and upper explosion limit Lower: Upper: Flash point: Auto-ignition temperature: Decomposition temperature: pH Viscosity: Solubility	emical properties nd chemical properties Fluid Colourless Characteristic undetermined and 55 °C (Aceton) Highly flammable. 2.1 Vol % (Aceton) 13 Vol % (Aceton) 13 Vol % (Aceton) 465 °C Not determined. Not applicable. Not determined.
SECTION 9: Physical and che 9.1 Information on basic physical au General Information Physical state Colour: Odour: Melting point/freezing point: Boiling point or initial boiling point boiling range Flammability Lower and upper explosion limit Lower: Upper: Flash point: Auto-ignition temperature: Decomposition temperature: pH Viscosity: Solubility Water:	emical properties nd chemical properties Fluid Colourless Characteristic undetermined and 55 °C (Aceton) Highly flammable. 2.1 Vol % (Aceton) 13 Vol % (Aceton) 13 Vol % (Aceton) -17 °C (Aceton) 465 °C Not determined. Not applicable. Not determined. Partly miscible
SECTION 9: Physical and che 9.1 Information on basic physical au General Information Physical state Colour: Odour: Melting point/freezing point: Boiling point or initial boiling point boiling range Flammability Lower and upper explosion limit Lower: Upper: Flash point: Auto-ignition temperature: Decomposition temperature: pH Viscosity: Solubility Water: Partition coefficient n-octanol/wated	emical properties nd chemical properties Fluid Colourless Characteristic undetermined and 55 °C (Aceton) Highly flammable. 2.1 Vol % (Aceton) 13 Vol % (Aceton) 13 Vol % (Aceton) -17 °C (Aceton) 465 °C Not determined. Not determined. Not determined. Not determined. Partly miscible r (log
SECTION 9: Physical and che 9.1 Information on basic physical au General Information Physical state Colour: Odour: Melting point/freezing point: Boiling point or initial boiling point boiling range Flammability Lower and upper explosion limit Lower: Upper: Flash point: Auto-ignition temperature: Decomposition temperature: pH Viscosity: Solubility Water: Partition coefficient n-octanol/water value)	emical properties nd chemical properties Fluid Colourless Characteristic undetermined and 55 °C (Aceton) Highly flammable. 2.1 Vol % (Aceton) 13 Vol % (Aceton) 13 Vol % (Aceton) -17 °C (Aceton) 465 °C Not determined. Not applicable. Not determined. Partly miscible r (log Not determined.
SECTION 9: Physical and che 9.1 Information on basic physical au General Information Physical state Colour: Odour: Melting point/freezing point: Boiling point or initial boiling point boiling range Flammability Lower and upper explosion limit Lower: Upper: Flash point: Auto-ignition temperature: Decomposition temperature: pH Viscosity: Solubility Water: Partition coefficient n-octanol/water value)	emical properties nd chemical properties Fluid Colourless Characteristic undetermined and 55 °C (Aceton) Highly flammable. 2.1 Vol % (Aceton) 13 Vol % (Aceton) 13 Vol % (Aceton) -17 °C (Aceton) 465 °C Not determined. Not determined. Not determined. Not determined. Partly miscible r (log
SECTION 9: Physical and che 9.1 Information on basic physical au General Information Physical state Colour: Odour: Melting point/freezing point: Boiling point or initial boiling point boiling range Flammability Lower and upper explosion limit Lower: Upper: Flash point: Auto-ignition temperature: Decomposition temperature: pH Viscosity: Solubility Water: Partition coefficient n-octanol/water value) Vapour pressure at 20 °C: Density and/or relative density	emical properties nd chemical properties Fluid Colourless Characteristic undetermined and 55 °C (Aceton) Highly flammable. 2.1 Vol % (Aceton) 13 Vol % (Aceton) 13 Vol % (Aceton) 13 Vol % (Aceton) 17 °C (Aceton) 465 °C Not determined. Not applicable. Not determined. Partly miscible r (log Not determined. 240 hPa (Aceton)
SECTION 9: Physical and che 9.1 Information on basic physical au General Information Physical state Colour: Odour: Melting point/freezing point: Boiling point or initial boiling point boiling range Flammability Lower and upper explosion limit Lower: Upper: Flash point: Auto-ignition temperature: Decomposition temperature: pH Viscosity: Solubility Water: Partition coefficient n-octanol/water value) Vapour pressure at 20 °C: Density and/or relative density Density:	mical properties and Fluid Colourless Characteristic undetermined and 55 °C (Aceton) Highly flammable. 2.1 Vol % (Aceton) 13 Vol % (Aceton) -17 °C (Aceton) 465 °C Not determined. Not determined. Not determined. Not determined. Partly miscible r (log Not determined. 240 hPa (Aceton) see technical data sheet
SECTION 9: Physical and che 9.1 Information on basic physical au General Information Physical state Colour: Odour: Melting point/freezing point: Boiling point or initial boiling point boiling range Flammability Lower and upper explosion limit Lower: Upper: Flash point: Auto-ignition temperature: Decomposition temperature: pH Viscosity: Solubility Water: Partition coefficient n-octanol/water value) Vapour pressure at 20 °C: Density and/or relative density Density: Relative density	emical properties nd chemical properties Fluid Colourless Characteristic undetermined and 55 °C (Aceton) Highly flammable. 2.1 Vol % (Aceton) 13 Vol % (Aceton) -17 °C (Aceton) 465 °C Not determined. Not applicable. Not determined. Partly miscible r (log Not determined. 240 hPa (Aceton) see technical data sheet Not determined.
SECTION 9: Physical and che 9.1 Information on basic physical au General Information Physical state Colour: Odour: Melting point/freezing point: Boiling point or initial boiling point boiling range Flammability Lower and upper explosion limit Lower: Upper: Flash point: Auto-ignition temperature: Decomposition temperature: pH Viscosity: Solubility Water: Partition coefficient n-octanol/water value) Vapour pressure at 20 °C: Density and/or relative density Density:	mical properties and Fluid Colourless Characteristic undetermined and 55 °C (Aceton) Highly flammable. 2.1 Vol % (Aceton) 13 Vol % (Aceton) -17 °C (Aceton) 465 °C Not determined. Not determined. Not determined. Not determined. Partly miscible r (log Not determined. 240 hPa (Aceton) see technical data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.11.2024

Version 4 (replaces version 3)

Revision: 11.11.2024

(Contd. of page 5)

Trade name: OTTO Primer 1102

- · 9.2 Other information
- · Form:
- · Ignition temperature:
- Explosive properties:

Fluid Product is not selfigniting. Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

- · Information with regard to physical hazard
- classes
- Aerosols
 Flammable liquids

Void Highly flammable liquid and vapour.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications. Avoid strong heating.
- **10.3 Possibility of hazardous reactions** Danger of receptacles bursting because of high vapour pressure when heated Can form explosive mixtures in air if heated above flash point and/or when sprayed or atomised
- 10.5 Incompatible materials: Strong oxidizing agents, alkalis, amines, strong acides
- · 10.6 Hazardous decomposition products: see item 5.2

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.
- · LD/LC50 values relevant for classification:

67-64-1 acetone

Oral LD50 5,800 mg/kg (rat) Dermal LD50 >15,800 mg/kg (rabbit) Inhalative LC50/4 h 76 mg/l (rat)

1330-20-7 xylene (mix)

Oral LD50 3,523 mg/kg (rat) Dermal LD50 >4,200 mg/kg (rabbit) Inhalative LC50/4 h 29.091 mg/l (rat)

78-93-3 butanone

 Oral
 LD50
 2,193 mg/kg (rat) (OECD 423)

 Dermal
 LD50
 >8,100 mg/kg (rabbit)

 71-36-3 butanol Oral
 LD50
 790 mg/kg (rat)

Dermal LD50 3,400 mg/kg (rabbit)

Inhalative LC50/4 h 8,000 mg/l (rat)

· Skin corrosion/irritation Causes skin irritation.

- · Serious eye damage/irritation Causes serious eye irritation.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure May cause drowsiness or dizziness.
- STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure.
- Aspiration hazard May be fatal if swallowed and enters airways.

(Contd. on page 7)

gb

according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.11.2024

Version 4 (replaces version 3)

Revision: 11.11.2024

(Contd. of page 6)

Trade name: OTTO Primer 1102

11.2 Information on other hazards

· Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties
- For information on endocrine disrupting properties see section 11.
- 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

Do not allow product to reach ground water, water course or sewage system. Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation Liquid residues must be specially treated adhering to official regulations.
- · Uncleaned packaging:
- Recommendation:
- Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

SECTION 14: Transport information

 · 14.1 UN number or ID number · ADR, IMDG, IATA · 14.2 UN proper shipping name 	UN1993
ADR	1993 FLAMMABLE LIQUID, N.O.S. (ACETONE, XYLENES)
· IMDG, IATA	FLAMMABLE LIQUID, N.O.S. (ACETONE, XYLENES)
· 14.3 Transport hazard class(es) · ADR	
· Class · Label	3 (F1) Flammable liquids. 3
· IMDG, IATA	
· Class · Label	3 Flammable liquids. 3
· 14.4 Packing group · ADR, IMDG, IATA	// (Contd. on page 8)

Page 8/10 Safety data sheet according to Regulation (EC) No 1907/2006, Article 31 Printing date 11.11.2024 Version 4 (replaces version 3) Revision: 11.11.2024 Trade name: OTTO Primer 1102 (Contd. of page 7) · 14.5 Environmental hazards: · Marine pollutant: No · 14.6 Special precautions for user Warning: Flammable liquids. · Hazard identification number (Kemler code): 33 F-E,S-E · EMS Number: Stowage Category В · 14.7 Maritime transport in bulk according to IMO instruments Not applicable. · Transport/Additional information: · ADR · Limited quantities (LQ) 1L Code: E2 • Excepted quantities (EQ) Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml · Transport category 2 · Tunnel restriction code D/E ·IMDG · Limited quantities (LQ) 1L• Excepted quantities (EQ) Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml • UN "Model Regulation": UN 1993 FLAMMABLE LIQUID, N.O.S. (ACETONE, XYLENES), 3, II SECTION 15: Regulatory information · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture · Poisons Act · Regulated explosives precursors None of the ingredients is listed. · Regulated poisons None of the ingredients is listed. Reportable explosives precursors 67-64-1 acetone: Listed Reportable poisons None of the ingredients is listed. · Directive 2012/18/EU • Qualifying quantity (tonnes) for the application of lower-tier requirements 5.000 t • Qualifying quantity (tonnes) for the application of upper-tier requirements 50.000 t · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3 DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II None of the ingredients is listed. · REGULATION (EU) 2019/1148 Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3)) None of the ingredients is listed. Annex II - REPORTABLE EXPLOSIVES PRECURSORS 67-64-1 acetone <u>Regulation (EC) No 273/2004 on drug precursors</u> 67-64-1 acetone: 3

(Contd. on page 9)

78-93-3 butanone: 3

according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.11.2024

Version 4 (replaces version 3)

Revision: 11.11.2024

Trade name: OTTO Primer 1102

	(Contd. of page 8)
108-88-3 toluene: 3	
 <u>Regulation (EC) No 111/2005 laying down rules for the mor</u> Community and third countries in drug precursors 	nitoring of trade between the
67-64-1 acetone: 3	
78-93-3 butanone: 3	
108-88-3 toluene: 3	
National regulations	
• Information about limitation of use: Employment restrictions concerning juveniles must be observed Employment restrictions concerning pregnant and lactating wor	
 Waterhazard class: Water hazard class 2 (Self-assessment): I Details of international registration status: Listed on or in accordance with the following inventories: TCSI - Taiwan listed UK REACH - Europe listed AICS - Australia listed DSL- Canada listed IECSC - China listed ENCS - Japan listed NZIoC - New Zealand not listed PICCS - Philippines not listed ECL - Korea listed TSCA - USA listed T5.2 Chemical safety assessment: A Chemical Safety Assess 	
SECTION 16: Other information	
This information is based on our present knowledge. However, for any specific product features and shall not establish a legal This Safety Data Sheets is in compliance with Regulation (EC)	y valid contractual relationship.

amended by Regulation (EU) 2020/878.

· Relevant phrases

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H412 Harmful to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

- · Department issuing SDS: Tel.: 0049- (0)8684- 908- 2363
- · Contact: Tel.: 0049- (0)8684- 908- 2363 (-4300)
- Date of previous version: 13.12.2022
- Version number of previous version: 3
- Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

(Contd. on page 10)

gb

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.11.2024

Version 4 (replaces version 3)

Revision: 11.11.2024

Trade name: OTTO Primer 1102

EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids – Category 2 Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 4: Acute toxicity – Category 4 Skin Irrit. 2: Skin corrosion/irritation – Category 1 Eye Dam. 1: Serious eye damage/eye irritation – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2 Asp. Tox. 1: Aspiration hazard – Category 1 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3	(Contd. of page 9)
** Data compared to the previous version altered.	