Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 08.09.2026 Version 7 (replaces version 6) Revision: 08.09.2026

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

· **1.1 Product identifier**

· **Trade name: OTTO Primer 1215**
· **UFI:** H615-U095-A00A-227V
· **1.2 Relevant identified uses of the substance or mixture and uses advised against**
· **Product category** PC9a Coatings and paints, thinners, paint removers
· **Application of the substance / the mixture** Priming
· **Uses advised against** Observe the information in the technical data sheet

· **1.3 Details of the supplier of the safety data sheet**
· **Manufacturer/Supplier:**
Hermann Otto GmbH
Krankenhausstraße 14
D-83413 Fridolfing
Tel.: 0049/(0)8684/908-0
Fax.: 0049/(0)8684/908-1840

· **Further information obtainable from:**
Tel.: 0049- (0)8684- 908- 2363 (-4300)
E-Mail: msds@otto-chemie.de
· **1.4 Emergency telephone number:**
Tel.: 0049/621/60-43333 (BASF Plant fire brigade)
+44 1865 407333 (Carechem 24)
Tel.: 0049- (0) 89- 192 40 (emergency telephone no.)

SECTION 2: Hazards identification

· **2.1 Classification of the substance or mixture**
· **Classification according to Regulation (EC) No 1272/2008**
Flam. Liq. 2 H225 Highly flammable liquid and vapour.
Eye Irrit. 2 H319 Causes serious eye irritation.
STOT SE 3 H336 May cause drowsiness or dizziness.
Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

· **2.2 Label elements**
· **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the CLP regulation.
· **Hazard pictograms**



GHS02 GHS07 GHS08

· **Signal word** Danger

· **Hazard-determining components of labelling:**
acetone
xylene (mix)
ethylbenzene
· **Hazard statements**
H225 Highly flammable liquid and vapour.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H304 May be fatal if swallowed and enters airways.

(Contd. on page 2)

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 08.09.2026 Version 7 (replaces version 6) Revision: 08.09.2026

Trade name: OTTO Primer 1215

(Contd. of page 1)

· **Precautionary statements**

P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves / eye protection.
P301+P330+P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical advice/attention.
P501	Dispose of contents/container in accordance with local regulations.

· **Additional information:**
EUH066 Repeated exposure may cause skin dryness or cracking.
Product contains: Reportable explosives precursors. Making available, introduction, possession and use according to Regulation (EU) 2019/1148, Article 9.

· **Labelling of packages where the contents do not exceed 125 ml**

· **Hazard pictograms**



GHS02 GHS07 GHS08

· **Signal word** Danger

· **Hazard-determining components of labelling:**
acetone
xylene (mix)
ethylbenzene

· **Hazard statements**
H336 May cause drowsiness or dizziness.
H304 May be fatal if swallowed and enters airways.

· **Precautionary statements**

P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P280	Wear protective gloves / eye protection.
P301+P330+P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P501	Dispose of contents/container in accordance with local regulations.

· **2.3 Other hazards**
Product hydrolyses to form ethanol (CAS No. 64-17-5). Ethanol is classified with regard to physical and health hazards. The rate of hydrolysis and thus the relevance for the hazard potential of the product are highly dependent on the specific conditions.

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable

· **vPvB:** Not applicable

· **Determination of endocrine-disrupting properties**
This product does not contain components that are endocrine disruptors according to REACH Article 57(f) or Commission Delegated Regulation (EU) 2017/2100 or Commission Delegated Regulation (EU) 2018/605 in quantities of 0.1% or more.

SECTION 3: Composition/information on ingredients

· **3.2 Mixtures**

· **Description:** Solvent mixture with additives.

(Contd. on page 3)

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 08.09.2026 Version 7 (replaces version 6) Revision: 08.09.2026

Trade name: OTTO Primer 1215

(Contd. of page 2)

· **Dangerous components:**

CAS: 67-64-1 EINECS: 200-662-2 Index number: 606-001-00-8 Reg.nr.: 01-2119471330-49-0000	acetone Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	50-100%
CAS: 1330-20-7 EINECS: 215-535-7 Index number: 601-022-00-9 Reg.nr.: 01-2119488216-32-0000	xylene (mix) Flam. Liq. 3, H226; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	<10%
CAS: 78-10-4 EINECS: 201-083-8 Index number: 014-005-00-0 Reg.nr.: 01-2119496195-28	tetraethyl silicate Flam. Liq. 3, H226; Acute Tox. 4, H332; Eye Irrit. 2, H319; STOT SE 3, H335	<5%
CAS: 100-41-4 EINECS: 202-849-4 Index number: 601-023-00-4 Reg.nr.: 01-2119489370-35	ethylbenzene Flam. Liq. 2, H225; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H332; Aquatic Chronic 3, H412	<5%

SECTION 4: First aid measures

· **4.1 Description of first aid measures**
· **General information**
Immediately remove any clothing soiled by the product.
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
· **After inhalation**
Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.
· **After skin contact**
Immediately wash with water and soap and rinse thoroughly.
If skin irritation continues, consult a doctor.
· **After eye contact** Rinse opened eye for several minutes under running water. Then consult a doctor.
· **After swallowing** Do not induce vomiting; call for medical help immediately. Show container or label.
· **4.2 Most important symptoms and effects, both acute and delayed**
Headache
Dizziness
Dizziness
Nausea
· **4.3 Indication of any immediate medical attention and special treatment needed**
If swallowed or in case of vomiting, danger of entering the lungs

SECTION 5: Firefighting measures

· **5.1 Extinguishing media**
· **Suitable extinguishing agents**
CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
· **For safety reasons unsuitable extinguishing agents** Water with full jet.
· **5.2 Special hazards arising from the substance or mixture**
Formation of toxic gases is possible during heating or in case of fire.
· **5.3 Advice for firefighters**
· **Protective equipment:** Do not inhale explosion gases or combustion gases.

(Contd. on page 4)

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 08.09.2026 Version 7 (replaces version 6) Revision: 08.09.2026

Trade name: OTTO Primer 1215

(Contd. of page 3)

· **Additional information** Cool endangered receptacles with water spray.

SECTION 6: Accidental release measures

· **6.1 Personal precautions, protective equipment and emergency procedures**
Ensure adequate ventilation
Keep away from ignition sources
· **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
· **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to section 13.
· **6.4 Reference to other sections** See Section 8 for information on personal protection equipment.

SECTION 7: Handling and storage

· **7.1 Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
see item 8: Personal protective equipment
· **Information about fire - and explosion protection:**
Protect against electrostatic charges.
Traces of flammable substances may collect in the steam chamber of enclosed systems. Keep clear ofignition sources.
Highly volatile, flammable constituents are released during processing.
Flammable gas-air mixtures may form in empty receptacles.

· **7.2 Conditions for safe storage, including any incompatibilities**
· **Storage**
· **Requirements to be met by storerooms and receptacles:**
Provide solvent resistant, sealed floor.
Prevent any seepage into the ground.
· **Information about storage in one common storage facility:** Store away from foodstuffs.
· **Further information about storage conditions:**
Store in cool, dry conditions in well sealed receptacles.
Protect from heat and direct sunlight.
Store receptacle in a well ventilated area.
· **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

· **8.1 Control parameters**
· **Ingredients with limit values that require monitoring at the workplace:**
· **Regulatory information**

67-64-1 acetone

IOELV Long-term value: 1210 mg/m³, 500 ppm

78-10-4 tetraethyl silicate

IOELV Long-term value: 44 mg/m³, 5 ppm

100-41-4 ethylbenzene

IOELV Short-term value: 884 mg/m³, 200 ppm
Long-term value: 442 mg/m³, 100 ppm
Skin
IOELV: (EU) 2019/1831

(Contd. on page 5)

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

(Contd. of page 4)

· **Additional information:** The lists valid during the making were used as basis.

· **8.2 Exposure controls**
· **Appropriate engineering controls** No further data; see section 7.
· **Individual protection measures, such as personal protective equipment**
· **General protective and hygienic measures**
The usual precautionary measures are to be adhered to when handling chemicals.
Wash hands before breaks and at the end of work.
Avoid contact with the eyes and skin.
Pregnant women should strictly avoid inhalation or skin contact.
· **Respiratory protection:**
Use suitable respiratory protective device when high concentrations are present.
· **Hand protection** Protective gloves.
· **Material of gloves**
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.
Recommended glove material: Butyl rubber, BR
Recommended thickness of the material: >0,4 mm
· **Penetration time of glove material** Breakthrough time: 10 - 30 min
· **Eye/face protection** Tightly sealed goggles.
· **Body protection:** Protective work clothing.

SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**
· **General Information**

· **Physical state**	Liquid
· **Colour:**	Colourless
· **Odour:**	Characteristic
· **Melting point/freezing point:**	undetermined
· **Boiling point or initial boiling point and boiling range**	56 °C
· **Flammability**	Highly flammable.
· **Lower and upper explosion limit**	
· **Lower:**	2.3 Vol % (67-64-1 acetone)
· **Upper:**	13 Vol % (67-64-1 acetone)
· **Flash point:**	<-18 °C (67-64-1 acetone)
· **Auto-ignition temperature:**	465 °C
· **Decomposition temperature:**	Not determined
· **pH**	Not applicable
· **Viscosity:**	Not determined
· **Solubility**	
· **Water:**	Not determined
· **Partition coefficient n-octanol/water (log value)**	Not determined
· **Vapour pressure at 20 °C:**	233 hPa
· **Density and/or relative density**	
· **Density:**	see technical data sheet
· **Relative density**	Not determined
· **Vapour density**	Not determined
· **Particle characteristics**	undetermined

· **9.2 Other information** Hydrolysis products lower the flash point. Explosion limits for released ethanol: 3.5 - 15 vol%.

(Contd. on page 6)

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 08.09.2026 Version 7 (replaces version 6) Revision: 08.09.2026

Trade name: OTTO Primer 1215

(Contd. of page 5)

· **Form:**	Fluid
· **Explosive properties:**	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· **Information with regard to physical hazard classes**	
· **Aerosols**	Void
· **Flammable liquids**	Highly flammable liquid and vapour.

SECTION 10: Stability and reactivity

· **10.1 Reactivity** No further relevant information available.
· **10.2 Chemical stability**
· **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
Avoid strong heating.
· **10.3 Possibility of hazardous reactions**
Danger of receptacles bursting because of high vapour pressure when heated
Can form explosive mixtures in air if heated above flash point and/or when sprayed or atomised
· **10.4 Conditions to avoid** Moisture, heat, naked flames and other sources of ignition.
· **10.5 Incompatible materials:** Water, acids, alkalis (formation of ethanol)
· **10.6 Hazardous decomposition products:** Ethanol

SECTION 11: Toxicological information

· **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
· **Acute toxicity** Based on available data, the classification criteria are not met.
· **LD/LC50 values relevant for classification:**

67-64-1 acetone

Oral	LD50	5,800 mg/kg (rat)
Dermal	LD50	>15,800 mg/kg (rabbit)
Inhalative	LC50/4 h	76 mg/l (rat)

1330-20-7 xylene (mix)

Oral	LD50	3,523 mg/kg (rat)
Dermal	LD50	>4,200 mg/kg (rabbit)
Inhalative	LC50/4 h	29.091 mg/l (rat)

78-10-4 tetraethyl silicate

Oral	LD50	6,270 mg/kg (rat)
Dermal	LD50	5,860 mg/kg (rab)
Inhalative	LC50/4 h	10 mg/l (rat)

· **Primary irritant effect:**
· **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
· **Serious eye damage/irritation** Causes serious eye irritation.
· **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
· **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
· **Carcinogenicity** Based on available data, the classification criteria are not met.
· **Reproductive toxicity** Based on available data, the classification criteria are not met.
· **STOT-single exposure** May cause drowsiness or dizziness.
· **STOT-repeated exposure** Based on available data, the classification criteria are not met.
· **Aspiration hazard** May be fatal if swallowed and enters airways.

(Contd. on page 7)

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 08.09.2026 Version 7 (replaces version 6) Revision: 08.09.2026

Trade name: OTTO Primer 1215

(Contd. of page 6)

· **11.2 Information on other hazards**
· **Endocrine disrupting properties**
None of the ingredients is listed.

SECTION 12: Ecological information

· **12.1 Toxicity** No further relevant information available
· **12.2 Persistence and degradability** No further relevant information available.
· **12.3 Bioaccumulative potential** No further relevant information available.
· **12.4 Mobility in soil** No further relevant information available.
· **12.5 Results of PBT and vPvB assessment**
· **PBT:** Not applicable
· **vPvB:** Not applicable
· **12.6 Endocrine disrupting properties**
This product does not contain components that are endocrine disruptors according to REACH Article 57(f) or Commission Delegated Regulation (EU) 2017/2100 or Commission Delegated Regulation (EU) 2018/605 in quantities of 0.1% or more.
· **12.7 Other adverse effects**
· **Additional ecological information:**
· **General notes:**
Do not allow product to reach ground water, water course or sewage system.
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water.

SECTION 13: Disposal considerations

· **13.1 Waste treatment methods**
· **Recommendation** Liquid residues must be specially treated adhering to official regulations.

· **Uncleaned packaging:**
· **Recommendation:**
Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.
Packagings that may not be cleansed are to be disposed of in the same manner as the product.

SECTION 14: Transport information

· **14.1 UN number or ID number**
· **ADR, IMDG, IATA** UN1993
· **14.2 UN proper shipping name**
· **ADR** 1993 FLAMMABLE LIQUID, N.O.S. (ACETONE, XYLENES)
· **IMDG** FLAMMABLE LIQUID, N.O.S. (ACETONE, XYLENES)
· **IATA** FLAMMABLE LIQUID, N.O.S. (containing ACETONE, XYLENES)

· **14.3 Transport hazard class(es)**

· **ADR**



· **Class** 3 (F1) Flammable liquids.

(Contd. on page 8)

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 08.09.2026 Version 7 (replaces version 6) Revision: 08.09.2026

Trade name: OTTO Primer 1215

(Contd. of page 7)

· **Label** 3

· **IMDG, IATA**



· **Class**	3 Flammable liquids.
· **Label**	3
· **14.4 Packing group**	
· **ADR, IMDG, IATA**	II
· **14.5 Environmental hazards:**	Not applicable
· **14.6 Special precautions for user**	Warning: Flammable liquids.
· **Hazard identification number (Kemler code):**	33
· **EMS Number:**	F-E,S-E
· **Stowage Category**	B
· **14.7 Maritime transport in bulk according to IMO instruments**	Not applicable

· **Transport/Additional information:**

· **ADR**	
· **Limited quantities (LQ)**	1L
· **Excepted quantities (EQ)**	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· **Transport category**	2
· **Tunnel restriction code**	D/E

· **IMDG**	
· **Limited quantities (LQ)**	1L
· **Excepted quantities (EQ)**	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· **UN "Model Regulation":**	UN 1993 FLAMMABLE LIQUID, N.O.S. (ACETONE, XYLENES), 3, II

SECTION 15: Regulatory information

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **Directive 2012/18/EU**
· **Named dangerous substances - ANNEX I** None of the ingredients is listed.
· **Seveso category** P5c FLAMMABLE LIQUIDS
· **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t
· **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t
· **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3
· **DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II**

None of the ingredients is listed.

· **REGULATION (EU) 2019/1148**
· **Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))**

None of the ingredients is listed.

(Contd. on page 9)

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 08.09.2026 Version 7 (replaces version 6) Revision: 08.09.2026

Trade name: OTTO Primer 1215

(Contd. of page 8)

· **Annex II - REPORTABLE EXPLOSIVES PRECURSORS**
67-64-1 acetone
· **Regulation (EC) No 273/2004 on drug precursors**
67-64-1 acetone: 3
· **Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors**
67-64-1 acetone: 3

· **National regulations**

· **Information about limitation of use:**
Employment restrictions concerning juveniles must be observed.
Employment restrictions concerning pregnant and lactating women must be observed.

· **Waterhazard class:** Water hazard class 2 (Self-assessment): hazardous for water.
· **Details of international registration status:**
Listed on or in accordance with the following inventories:

REACH - Europe	listed
AICS - Australia	listed
ENCS - Japan	listed
IECSC - China	listed
DSL- Canada	listed
PICCS - Philippines	listed
TSCA - USA	listed
ECL - Korea	not listed
TCSI - Taiwan	listed
NZIoC - New Zealand	not listed

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.
This Safety Data Sheets is in compliance with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

· **Relevant phrases**
H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H312 Harmful in contact with skin.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H373 May cause damage to organs through prolonged or repeated exposure.
H412 Harmful to aquatic life with long lasting effects.
EUH066 Repeated exposure may cause skin dryness or cracking.
· **Version number of previous version:** 6
· **Abbreviations and acronyms:**
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances

(Contd. on page 10)

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 08.09.2026 *Version 7 (replaces version 6)* *Revision: 08.09.2026*

Trade name: OTTO Primer 1215

(Contd. of page 9)

ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flam. Liq. 2: Flammable liquids – Category 2
Flam. Liq. 3: Flammable liquids – Category 3
Acute Tox. 4: Acute toxicity – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3