

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 02.06.2016

Version 1

Revision: 02.06.2016

### SECTION 1: Identification of the substance/mixture and of the company/ undertaking

- **1.1 Product identifier**
- **Trade name:** **OTTO Primer 1215**
- **Application of the substance / the mixture** Priming
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
Hermann Otto GmbH  
Krankenhausstraße 14  
D-83413 Fridolfing  
Tel.: 0049/(0)8684/908-0  
Fax.: 0049/(0)8684/908-539
- **Further information obtainable from:**  
Tel.: 0049- (0)8684- 908- 641 ( -460 )  
E-Mail: alois.parzinger@otto-chemie.de
- **1.4 Emergency telephone number:**  
Tel.: 0049/621/60-43333 (BASF Plant fire brigade)  
Tel.: 0049- (0) 89- 192 40 (emergency telephone no.)

### SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS08 health hazard

Repr. 2 H361d Suspected of damaging the unborn child.  
STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.  
Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.  
Eye Irrit. 2 H319 Causes serious eye irritation.  
STOT SE 3 H336 May cause drowsiness or dizziness.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**  
The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms** GHS02, GHS07, GHS08
- **Signal word** Danger
- **Hazard-determining components of labelling:**  
acetone  
toluene
- **Hazard statements**  
H225 Highly flammable liquid and vapour.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H361d Suspected of damaging the unborn child.  
H336 May cause drowsiness or dizziness.

(Contd. on page 2)

GB

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 02.06.2016

Version 1

Revision: 02.06.2016

**Trade name: OTTO Primer 1215**

(Contd. of page 1)

H373 May cause damage to organs through prolonged or repeated exposure.

H304 May be fatal if swallowed and enters airways.

**Precautionary statements**

P102 Keep out of reach of children.

P271 Use only outdoors or in a well-ventilated area.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P280 Wear protective gloves / eye protection / face protection.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P304+P312 IF INHALED: Call a POISON CENTER/doctor if you feel unwell.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P301+P330+P331 IF SWALLOWED: rinse mouth. Do NOT induce vomiting.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P313 Get medical advice/attention.

**Additional information:**

EUH066 Repeated exposure may cause skin dryness or cracking.

Contains Zirconiumbutanolat. May produce an allergic reaction.

**2.3 Other hazards****Results of PBT and vPvB assessment**• **PBT:** Not applicable.• **vPvB:** Not applicable.

### SECTION 3: Composition/information on ingredients

**3.2 Chemical characterisation: Mixtures**• **Description:** Solvent mixture with additives.**Dangerous components:**

CAS: 67-64-1	acetone	50- 100%
EINECS: 200-662-2	☠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336	
CAS: 108-88-3	toluene	< 25%
EINECS: 203-625-9	☠ Flam. Liq. 2, H225; ☠ Repr. 2, H361d; STOT RE 2, H373; Asp. Tox. 1, H304; ⚠ Skin Irrit. 2, H315; STOT SE 3, H336	
CAS: 78-10-4	tetraethyl silicate	< 2.5%
EINECS: 201-083-8	☠ Flam. Liq. 3, H226; ⚠ Acute Tox. 4, H332; Eye Irrit. 2, H319; STOT SE 3, H335	
CAS: 1071-76-7	Zirconiumbutanolat	< 1%
EINECS: 213-995-3	☠ Flam. Liq. 3, H226; ⚠ Eye Irrit. 2, H319; Skin Sens. 1B, H317	

• **Additional information** For the wording of the listed hazard phrases refer to section 16.

### SECTION 4: First aid measures

**4.1 Description of first aid measures****General information**

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

**After inhalation**

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

**After skin contact**

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

**After eye contact**

Rinse opened eye for several minutes under running water. Then consult a doctor.

(Contd. on page 3)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 02.06.2016

Version 1

Revision: 02.06.2016

**Trade name: OTTO Primer 1215**

(Contd. of page 2)

- **After swallowing**  
Do not induce vomiting; call for medical help immediately. Show container or label.
- **4.2 Most important symptoms and effects, both acute and delayed**  
Headache  
Disziness  
Disziness  
Nausea
- **4.3 Indication of any immediate medical attention and special treatment needed**  
If swallowed or in case of vomiting, danger of entering the lungs  
No further relevant information available.

### SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents**  
CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents** Water with full jet.
- **5.2 Special hazards arising from the substance or mixture**  
During heating or in case of fire poisonous gases are produced.  
Formation of toxic gases is possible during heating or in case of fire.
- **5.3 Advice for firefighters**
- **Protective equipment:** Do not inhale explosion gases or combustion gases.
- **Additional information** Cool endangered receptacles with water spray.

### SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**  
Ensure adequate ventilation  
Keep away from ignition sources
- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose contaminated material as waste according to item 13.
- **6.4 Reference to other sections** See Section 8 for information on personal protection equipment.

### SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**  
Ensure good ventilation/exhaustion at the workplace.  
see item 8: Personal protective equipment
- **Information about fire - and explosion protection:**  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.  
Traces of flammable substances may collect in the steam chamber of enclosed systems. Keep clear of ignition sources.  
Highly volatile, flammable constituents are released during processing.  
Flammable gas-air mixtures may form in empty receptacles.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage**
- **Requirements to be met by storerooms and receptacles:**  
Provide solvent resistant, sealed floor.  
Prevent any seepage into the ground.
- **Information about storage in one common storage facility:** Store away from foodstuffs.
- **Further information about storage conditions:**  
Store in cool, dry conditions in well sealed receptacles.  
Protect from heat and direct sunlight.

(Contd. on page 4)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 02.06.2016

Version 1

Revision: 02.06.2016

Trade name: OTTO Primer 1215

(Contd. of page 3)

Store receptacle in a well ventilated area.

- **7.3 Specific end use(s)** No further relevant information available.

### SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

- **8.1 Control parameters**

- **Ingredients with limit values that require monitoring at the workplace:**

- **67-64-1 acetone**

- OES Short-term value: 3620 mg/m<sup>3</sup>, 1500 ppm

- Long-term value: 1210 mg/m<sup>3</sup>, 500 ppm

- New, IOELV

- **108-88-3 toluene**

- OES Short-term value: 574 mg/m<sup>3</sup>, 150 ppm

- Long-term value: 191 mg/m<sup>3</sup>, 50 ppm

- Sk

- **78-10-4 tetraethyl silicate**

- OES Short-term value: 260 mg/m<sup>3</sup>, 30 ppm

- Long-term value: 87 mg/m<sup>3</sup>, 10 ppm

- **Additional information:** The lists valid during the making were used as basis.

- **8.2 Exposure controls**

- **Personal protective equipment**

- **General protective and hygienic measures**

- The usual precautionary measures are to be adhered to when handling chemicals.

- Wash hands before breaks and at the end of work.

- Avoid contact with the eyes and skin.

- Pregnant women should strictly avoid inhalation or skin contact.

- **Respiratory protection:**

- Use suitable respiratory protective device when high concentrations are present.

- **Protection of hands:** Protective gloves.

- **Material of gloves**

- The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

- Fluorocarbon rubber (Viton)

- Recommended thickness of the material:  $\geq 0.4$  mm

- **Penetration time of glove material** Breakthrough time: > 60 min

- **Eye protection:** Tightly sealed goggles.

- **Body protection:** Protective work clothing.

### SECTION 9: Physical and chemical properties

- **9.1 Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

- **Form:** Fluid

- **Colour:** Colourless

- **Odour:** Characteristic

- **Odour threshold:** Not determined.

- **pH-value at 20 °C:** 7

- **Change in condition**

- **Melting point/Melting range:** < - 50 °C

- **Boiling point/Boiling range:** 56 °C

- **Flash point:** -18 °C

(Contd. on page 5)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 02.06.2016

Version 1

Revision: 02.06.2016

**Trade name: OTTO Primer 1215**

(Contd. of page 4)

- **Ignition temperature:** 540 °C
- **Self-igniting:** Product is not selfigniting.
- **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
- **Explosion limits:**
  - Lower:** 2.3 Vol %
  - Upper:** 13.0 Vol %
- **Oxidising properties** Not determined.
- **Vapour pressure at 20 °C:** 233 hPa
- **Density at 20 °C:** 0.9 g/cm<sup>3</sup>
- **Vapour density** Not determined.
- **Evaporation rate** Not determined.
- **Solubility in / Miscibility with Water at 20 °C:** 900 g/l
- **Partition coefficient (n-octanol/water):** Not determined.
- **Viscosity at 25 °C:** 1-2 mPa.s (DIN 51562)

### SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**  
No decomposition if used according to specifications.  
Avoid strong heating.
- **10.3 Possibility of hazardous reactions**  
Danger of receptacles bursting because of high vapour pressure when heated  
Can form explosive mixtures in air if heated above flash point and/or when sprayed or atomised
- **10.5 Incompatible materials:** Strong oxidizing agents, alkalis, amines, strong acids
- **10.6 Hazardous decomposition products:**  
Ethanol  
see item 5.2

### SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
  - **Acute toxicity** Based on available data, the classification criteria are not met.
  - **LD/LC50 values relevant for classification:**
- 
- 108-88-3 toluene**
- Oral LD50 5580 mg/kg (rat)  
Dermal LD50 12400 mg/kg (rab)  
Inhalative LC50/4 h 28 mg/l (rat)
- 67-64-1 acetone**
- Oral LD50 5800 mg/kg (rat)  
Dermal LD50 20000 mg/kg (rbt)  
Inhalative LC50/4 h 76 mg/l (rat)
- **Primary irritant effect:**
  - **Skin corrosion/irritation**  
Causes skin irritation.
  - **Serious eye damage/irritation**  
Causes serious eye irritation.
  - **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.

(Contd. on page 6)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 02.06.2016

Version 1

Revision: 02.06.2016

Trade name: OTTO Primer 1215

(Contd. of page 5)

- **Additional toxicological information:**

- Oral Acute toxicity estimate (ATE mix) > 2000 mg/kg (ATE)
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity**  
Suspected of damaging the unborn child.
- **STOT-single exposure**  
May cause drowsiness or dizziness.
- **STOT-repeated exposure**  
May cause damage to organs through prolonged or repeated exposure.
- **Aspiration hazard**  
May be fatal if swallowed and enters airways.

### SECTION 12: Ecological information

- **Additional ecological information:**

- **General notes:**  
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water.  
Do not allow product to reach ground water, water course or sewage system.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

### SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**

- **Recommendation**

Liquid residues must be specially treated adhering to official regulations.  
Observe local by-laws.

- **Uncleaned packaging:**

- **Recommendation:**

Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.  
Packagings that may not be cleansed are to be disposed of in the same manner as the product.

### SECTION 14: Transport information

- **14.1 UN-Number**

- **ADR, IMDG, IATA**

UN1993

- **14.2 UN proper shipping name**

- **ADR**

1993 FLAMMABLE LIQUID, N.O.S. (ACETONE, TOLUENE)

- **IMDG**

FLAMMABLE LIQUID, N.O.S. (ACETONE, TOLUENE)

- **IATA**

Flammable liquid, n.o.s. (Acetone, Toluene)

- **14.3 Transport hazard class(es)**

- **ADR**



- **Class**

3 (F1) Flammable liquids.

(Contd. on page 7)



# Safety data sheet

according to 1907/2006/EC, Article 31


Printing date 02.06.2016

Version 1

Revision: 02.06.2016

Trade name: OTTO Primer 1215

(Contd. of page 6)

· <b>Label</b>	3
· <b>IMDG, IATA</b>	
	
· <b>Class</b>	3 Flammable liquids.
· <b>Label</b>	3
· <b>14.4 Packing group</b>	
· <b>ADR, IMDG, IATA</b>	II
· <b>14.5 Environmental hazards:</b>	
· <b>Marine pollutant:</b>	No
· <b>14.6 Special precautions for user</b>	Warning: Flammable liquids.
· <b>Danger code (Kemler):</b>	33
· <b>EMS Number:</b>	F-E,S-E
· <b>Stowage Category</b>	B
· <b>14.7 Transport in bulk according to Annex II of Marpol and the IBC Code</b>	Not applicable.
· <b>Transport/Additional information:</b>	
· <b>ADR</b>	
· <b>Limited quantities (LQ)</b>	1L
· <b>Excepted quantities (EQ)</b>	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· <b>Transport category</b>	2
· <b>Tunnel restriction code</b>	D/E
· <b>IMDG</b>	
· <b>Limited quantities (LQ)</b>	1L
· <b>Excepted quantities (EQ)</b>	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· <b>UN "Model Regulation":</b>	UN1993, FLAMMABLE LIQUID, N.O.S. (ACETONE, TOLUENE), 3, II

## SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5.000 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50.000 t
- **National regulations**
- **Information about limitation of use:**  
Employment restrictions concerning juveniles must be observed.  
Employment restrictions concerning pregnant and lactating women must be observed.
- **Waterhazard class:** Water hazard class 2 (Self-assessment): hazardous for water.
- **Details of international registration status:**  
**Listed on or in accordance with the following inventories:**

EINECS - Europe	listed
ECL/KECI - Korea	listed
ENCS - Japan	listed
AICS - Australia	listed
IECSC - China	listed

(Contd. on page 8)

GB

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 02.06.2016

Version 1

Revision: 02.06.2016

**Trade name: OTTO Primer 1215**

(Contd. of page 7)

DSL/NDSL - Canada listed  
 PICCS - Philippines listed  
 TSCA - USA listed  
 NECI - Taiwan not listed  
 NZIoC - New Zealand not listed

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H225 Highly flammable liquid and vapour.  
 H226 Flammable liquid and vapour.  
 H304 May be fatal if swallowed and enters airways.  
 H315 Causes skin irritation.  
 H317 May cause an allergic skin reaction.  
 H319 Causes serious eye irritation.  
 H332 Harmful if inhaled.  
 H335 May cause respiratory irritation.  
 H336 May cause drowsiness or dizziness.  
 H361d Suspected of damaging the unborn child.  
 H373 May cause damage to organs through prolonged or repeated exposure.

· **Department issuing MSDS:** Tel.: 0049- (0)8684- 908- 641

· **Contact:** Tel.: 0049- (0)8684- 908- 641 ( -460 )

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)  
 IMDG: International Maritime Code for Dangerous Goods  
 IATA: International Air Transport Association  
 GHS: Globally Harmonised System of Classification and Labelling of Chemicals  
 EINECS: European Inventory of Existing Commercial Chemical Substances  
 ELINCS: European List of Notified Chemical Substances  
 CAS: Chemical Abstracts Service (division of the American Chemical Society)  
 LC50: Lethal concentration, 50 percent  
 LD50: Lethal dose, 50 percent  
 PBT: Persistent, Bioaccumulative and Toxic  
 vPvB: very Persistent and very Bioaccumulative  
 Flam. Liq. 2: Flammable liquids, Hazard Category 2  
 Flam. Liq. 3: Flammable liquids, Hazard Category 3  
 Acute Tox. 4: Acute toxicity, Hazard Category 4  
 Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2  
 Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2  
 Skin Sens. 1B: Sensitisation - Skin, Hazard Category 1B  
 Repr. 2: Reproductive toxicity, Hazard Category 2  
 STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3  
 STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2  
 Asp. Tox. 1: Aspiration hazard, Hazard Category 1

· **\* Data compared to the previous version altered.**

GB