

# Safety data sheet

## according to Regulation (EC) No 1907/2006, Article 31

Printing date 30.04.2026

Version 6 (replaces version 5)

Revision: 30.04.2026

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name: OTTO Primer 1217**
- **UFI: D960-4051-J008-40T7**
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
- **Product category PC9a** Coatings and paints, thinners, paint removers
- **Application of the substance / the mixture** Priming
- **Uses advised against** Observe the information in the technical data sheet
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
Hermann Otto GmbH  
Krankenhausstraße 14  
D-83413 Fridolfing  
Tel.: 0049/(0)8684/908-0  
Fax.: 0049/(0)8684/908-1840
- **Further information obtainable from:**  
Tel.: 0049- (0)8684- 908- 2363 ( -4300 )  
E-Mail: msds@otto-chemie.de
- **1.4 Emergency telephone number:**  
Tel.: 0049/621/60-43333 (BASF Plant fire brigade)  
+44 1865 407333 (Carechem 24)  
Tel.: 0049- (0) 89- 192 40 (emergency telephone no.)

### SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**

Flam. Liq. 2	H225	Highly flammable liquid and vapour.
Skin Irrit. 2	H315	Causes skin irritation.
Eye Irrit. 2	H319	Causes serious eye irritation.
Repr. 2	H361d	Suspected of damaging the unborn child.
STOT SE 3	H336	May cause drowsiness or dizziness.
STOT RE 2	H373	May cause damage to organs through prolonged or repeated exposure.
Asp. Tox. 1	H304	May be fatal if swallowed and enters airways.
Aquatic Chronic 3	H412	Harmful to aquatic life with long lasting effects.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**  
The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms**



GHS02 GHS07 GHS08

- **Signal word** Danger
- **Hazard-determining components of labelling:**  
toluene  
propan-2-ol  
Naphtha (petroleum), light alkylate

(Contd. on page 2)

# Safety data sheet

## according to Regulation (EC) No 1907/2006, Article 31

Printing date 30.04.2026

Version 6 (replaces version 5)

Revision: 30.04.2026

**Trade name: OTTO Primer 1217**

(Contd. of page 1)

**· Hazard statements**

- H225 *Highly flammable liquid and vapour.*
- H315 *Causes skin irritation.*
- H319 *Causes serious eye irritation.*
- H361d *Suspected of damaging the unborn child.*
- H336 *May cause drowsiness or dizziness.*
- H373 *May cause damage to organs through prolonged or repeated exposure.*
- H304 *May be fatal if swallowed and enters airways.*
- H412 *Harmful to aquatic life with long lasting effects.*

**· Precautionary statements**

- P102 *Keep out of reach of children.*
- P210 *Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.  
No smoking.*
- P271 *Use only outdoors or in a well-ventilated area.*
- P280 *Wear protective gloves / eye protection.*
- P301+P330+P331 *IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.*
- P305+P351+P338 *IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical advice/attention.*
- P501 *Dispose of contents/container in accordance with local regulations.*

**· Additional information:**

EUH208 *Contains methyl methacrylate, n-butyl methacrylate. May produce an allergic reaction.*

**· Labelling of packages where the contents do not exceed 125 ml****· Hazard pictograms**

GHS02 GHS07 GHS08

**· Signal word Danger****· Hazard-determining components of labelling:**

toluene  
propan-2-ol  
Naphtha (petroleum), light alkylate

**· Hazard statements**

- H361d *Suspected of damaging the unborn child.*
- H336 *May cause drowsiness or dizziness.*
- H373 *May cause damage to organs through prolonged or repeated exposure.*
- H304 *May be fatal if swallowed and enters airways.*
- H412 *Harmful to aquatic life with long lasting effects.*

**· Precautionary statements**

- P102 *Keep out of reach of children.*
- P210 *Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.  
No smoking.*
- P280 *Wear protective gloves / eye protection.*
- P301+P330+P331 *IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.*
- P501 *Dispose of contents/container in accordance with local regulations.*

**· 2.3 Other hazards****· Results of PBT and vPvB assessment**

- **PBT:** Not applicable
- **vPvB:** Not applicable

**· Determination of endocrine-disrupting properties**

*This product does not contain components that are endocrine disruptors according to REACH Article 57(f) or Commission Delegated Regulation (EU) 2017/2100 or Commission Delegated Regulation (EU) 2018/605 in quantities of 0.1% or more.*

(Contd. on page 3)

# Safety data sheet

## according to Regulation (EC) No 1907/2006, Article 31

Printing date 30.04.2026

Version 6 (replaces version 5)

Revision: 30.04.2026

Trade name: OTTO Primer 1217

(Contd. of page 2)

### SECTION 3: Composition/information on ingredients

#### 3.2 Mixtures

**Description:** Solvent mixture with additives.

#### Dangerous components:

CAS: 67-63-0 EINECS: 200-661-7 Index number: 603-117-00-0 Reg.nr.: 01-2119457558-25-0000	propan-2-ol ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336	<50%
CAS: 108-88-3 EINECS: 203-625-9 Index number: 601-021-00-3 Reg.nr.: 01-2119471310-51-xxxx	toluene ⚠ Flam. Liq. 2, H225; ⚠ Repr. 2, H361d; STOT RE 2, H373; Asp. Tox. 1, H304; ⚠ Skin Irrit. 2, H315; STOT SE 3, H336	<25%
CAS: 64741-66-8 EC number: 921-728-3 Reg.nr.: 01-2119471305-42	Naphtha (petroleum), light alkylate ⚠ Flam. Liq. 2, H225; ⚠ Asp. Tox. 1, H304; ⚠ Aquatic Chronic 2, H411; ⚠ Skin Irrit. 2, H315; STOT SE 3, H336	<25%
CAS: 71-36-3 EINECS: 200-751-6 Index number: 603-004-00-6 Reg.nr.: 01-2119484630-38	butanol ⚠ Flam. Liq. 3, H226; ⚠ Eye Dam. 1, H318; ⚠ Acute Tox. 4, H302; ⚠ Skin Irrit. 2, H315; STOT SE 3, H335; STOT SE 3, H336	<2.5%
CAS: 80-62-6 EINECS: 201-297-1 Index number: 607-035-00-6 Reg.nr.: 01-2119452498-28-0000	methyl methacrylate ⚠ Flam. Liq. 2, H225; ⚠ Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335	<1%
CAS: 97-88-1 EINECS: 202-615-1 Index number: 607-033-00-5 Reg.nr.: 01-2119486394-28-0000	n-butyl methacrylate ⚠ Flam. Liq. 3, H226; ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335	<1%

**Additional information** For the wording of the listed hazard phrases refer to section 16.

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

##### General information

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

##### After inhalation

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

##### After skin contact

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

**After eye contact** Rinse opened eye for several minutes under running water. Then consult a doctor.

**After swallowing** Do not induce vomiting; call for medical help immediately. Show container or label.

#### 4.2 Most important symptoms and effects, both acute and delayed

Headache

Dizziness

Dizziness

Nausea

(Contd. on page 4)

en

# Safety data sheet

## according to Regulation (EC) No 1907/2006, Article 31

Printing date 30.04.2026

Version 6 (replaces version 5)

Revision: 30.04.2026

Trade name: OTTO Primer 1217

(Contd. of page 3)

### · 4.3 Indication of any immediate medical attention and special treatment needed

If swallowed or in case of vomiting, danger of entering the lungs

After exposure, it is recommended that you seek specialist medical advice. Product contains reproductive toxins (may cause harm to the unborn child and /or impairs male or female reproductive function).

## SECTION 5: Firefighting measures

### · 5.1 Extinguishing media

#### · Suitable extinguishing agents

CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

#### · For safety reasons unsuitable extinguishing agents

Water with full jet.

### · 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

### · 5.3 Advice for firefighters

#### · Protective equipment: Do not inhale explosion gases or combustion gases.

#### · Additional information Cool endangered receptacles with water spray.

## SECTION 6: Accidental release measures

### · 6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Keep away from ignition sources

### · 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.

### · 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

### · 6.4 Reference to other sections See Section 8 for information on personal protection equipment.

## SECTION 7: Handling and storage

### · 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

see item 8: Personal protective equipment

#### · Information about fire - and explosion protection:

Protect against electrostatic charges.

Traces of flammable substances may collect in the steam chamber of enclosed systems. Keep clear of ignition sources.

Highly volatile, flammable constituents are released during processing.

Flammable gas-air mixtures may form in empty receptacles.

### · 7.2 Conditions for safe storage, including any incompatibilities

#### · Storage

#### · Requirements to be met by storerooms and receptacles:

Provide solvent resistant, sealed floor.

Prevent any seepage into the ground.

#### · Information about storage in one common storage facility: Store away from foodstuffs.

#### · Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

Store receptacle in a well ventilated area.

(Contd. on page 5)

# Safety data sheet

## according to Regulation (EC) No 1907/2006, Article 31

Printing date 30.04.2026

Version 6 (replaces version 5)

Revision: 30.04.2026

Trade name: OTTO Primer 1217

(Contd. of page 4)

- 7.3 Specific end use(s) No further relevant information available.

### SECTION 8: Exposure controls/personal protection

- **8.1 Control parameters**

- **Ingredients with limit values that require monitoring at the workplace:**

- **108-88-3 toluene**

- IOELV Short-term value: 384 mg/m<sup>3</sup>, 100 ppm

- Long-term value: 192 mg/m<sup>3</sup>, 50 ppm

- Skin

- **80-62-6 methyl methacrylate**

- IOELV Short-term value: 100 ppm

- Long-term value: 50 ppm

- **DNELs**

- **64741-66-8 Naphtha (petroleum), light alkylate**

- Dermal Worker, systemic (long term) 773 mg/kg/Tag (rat)

- Consumer, systemic (long term) 699 mg/kg/Tag (rat)

- Inhalative Worker, systemic (long term) 2,035 mg/m<sup>3</sup> (rat)

- Consumer, systemic (long term) 608 mg/m<sup>3</sup> (rat)

- **Additional information:** The lists valid during the making were used as basis.

- **8.2 Exposure controls**

- **Appropriate engineering controls** No further data; see section 7.

- **Individual protection measures, such as personal protective equipment**

- **General protective and hygienic measures**

- The usual precautionary measures are to be adhered to when handling chemicals.

- Wash hands before breaks and at the end of work.

- Avoid contact with the eyes and skin.

- Pregnant women should strictly avoid inhalation or skin contact.

- **Respiratory protection:**

- Use suitable respiratory protective device when high concentrations are present.

- **Hand protection** Protective gloves.

- **Material of gloves**

- The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

- Recommended glove material: Butyl rubber, BR

- Recommended thickness of the material: >0,4 mm

- **Penetration time of glove material** Breakthrough time: 10 - 30 min

- **Eye/face protection** Tightly sealed goggles.

- **Body protection:** Protective work clothing.

### SECTION 9: Physical and chemical properties

- **9.1 Information on basic physical and chemical properties**

- **General Information**

- **Physical state**

Liquid

- **Colour:**

Colourless

- **Odour:**

Characteristic

- **Melting point/freezing point:**

undetermined

- **Boiling point or initial boiling point and boiling range**

82 °C

(Contd. on page 6)

# Safety data sheet

## according to Regulation (EC) No 1907/2006, Article 31

Printing date 30.04.2026

Version 6 (replaces version 5)

Revision: 30.04.2026

Trade name: OTTO Primer 1217

(Contd. of page 5)

- **Flammability** Highly flammable.
- **Lower and upper explosion limit**
- **Lower:** 2 Vol % (Isopropanol)
- **Upper:** 12 Vol % (Isopropanol)
- **Flash point:** 6 °C
- **Auto-ignition temperature:** 425 °C
- **Decomposition temperature:** Not determined
- **pH** Not determined
- **Viscosity:** Not determined
- **Solubility**
- **Water:** Partly miscible
- **Partition coefficient n-octanol/water (log value)** Not determined
- **Vapour pressure:** Not determined
- **Density and/or relative density**
- **Density:** see technical data sheet
- **Relative density** Not determined
- **Vapour density** Not applicable
- **Particle characteristics** Not determined  
undetermined
  
- **9.2 Other information**
- **Form:** Fluid
- **Ignition temperature:** Product is not selfigniting.
- **Explosive properties:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
  
- **Information with regard to physical hazard classes**
- **Aerosols** Void
- **Flammable liquids** Highly flammable liquid and vapour.

### SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**  
No decomposition if used according to specifications.  
Avoid strong heating.
- **10.3 Possibility of hazardous reactions**  
Danger of receptacles bursting because of high vapour pressure when heated  
Can form explosive mixtures in air if heated above flash point and/or when sprayed or atomised
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** Strong oxidizing agents, alkalis, amines, strong acids
- **10.6 Hazardous decomposition products:** see item 5.2

### SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.
- **LD/LC50 values relevant for classification:**

67-63-0 propan-2-ol

Oral LD50 5,840 mg/kg (rat)

(Contd. on page 7)

en

# Safety data sheet

## according to Regulation (EC) No 1907/2006, Article 31

Printing date 30.04.2026

Version 6 (replaces version 5)

Revision: 30.04.2026

**Trade name: OTTO Primer 1217**

(Contd. of page 6)

Dermal LD50 13,900 mg/kg (rab)

**108-88-3 toluene**

Oral LD50 5,580 mg/kg (rat)

Dermal LD50 12,400 mg/kg (rab)

Inhalative LC50/4 h 28 mg/l (rat)

**64741-66-8 Naphtha (petroleum), light alkylate**

Oral LD50 &gt;5,000 mg/kg (rat)

Dermal LD50 &gt;2,000 mg/kg (rab)

Inhalative LC50/4 h &gt;20 mg/l (rat)

**71-36-3 butanol**

Oral LD50 790 mg/kg (rat)

Dermal LD50 3,400 mg/kg (rabbit)

Inhalative LC50/4 h 8,000 mg/l (rat)

**80-62-6 methyl methacrylate**

Oral LD50 7,870 mg/kg (rat)

Dermal LD50 &gt;5,000 mg/kg (rab)

Inhalative LC50/4 h 78 mg/l (rat)

**97-88-1 n-butyl methacrylate**

Oral LD50 22,600 mg/kg (rat)

Dermal LD50 11,300 mg/kg (rabbit)

Inhalative LC50/4 h 4,910 mg/l (rat)

- **Primary irritant effect:**
- **Skin corrosion/irritation** Causes skin irritation.
- **Serious eye damage/irritation** Causes serious eye irritation.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Suspected of damaging the unborn child.
- **STOT-single exposure** May cause drowsiness or dizziness.
- **STOT-repeated exposure** May cause damage to organs through prolonged or repeated exposure.
- **Aspiration hazard** May be fatal if swallowed and enters airways.
- **11.2 Information on other hazards**
- **Endocrine disrupting properties**

None of the ingredients is listed.

## SECTION 12: Ecological information

- **12.1 Toxicity** No further relevant information available
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable
- **vPvB:** Not applicable
- **12.6 Endocrine disrupting properties**  
This product does not contain components that are endocrine disruptors according to REACH Article 57(f) or Commission Delegated Regulation (EU) 2017/2100 or Commission Delegated Regulation (EU) 2018/605 in quantities of 0.1% or more.

(Contd. on page 8)

en

# Safety data sheet

## according to Regulation (EC) No 1907/2006, Article 31

Printing date 30.04.2026

Version 6 (replaces version 5)

Revision: 30.04.2026

Trade name: OTTO Primer 1217



(Contd. of page 7)

- **12.7 Other adverse effects**
- **Additional ecological information:**
- **General notes:**  
Do not allow product to reach ground water, water course or sewage system.  
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water.

### SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation** Liquid residues must be specially treated adhering to official regulations.
- **Uncleaned packaging:**
- **Recommendation:**  
Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.  
Packagings that may not be cleansed are to be disposed of in the same manner as the product.

### SECTION 14: Transport information

- **14.1 UN number or ID number**
- **ADR, IMDG, IATA** UN1993
- **14.2 UN proper shipping name**
- **ADR** 1993 FLAMMABLE LIQUID, N.O.S. (ISOPROPANOL, TOLUENE)
- **IMDG** FLAMMABLE LIQUID, N.O.S. (ISOPROPANOL, TOLUENE)
- **IATA** FLAMMABLE LIQUID, N.O.S. (containing ISOPROPANOL, TOLUENE)
- **14.3 Transport hazard class(es)**
- **ADR**
- 
- **Class** 3 (F1) Flammable liquids.
- **Label** 3
- **IMDG, IATA**
- 
- **Class** 3 Flammable liquids.
- **Label** 3
- **14.4 Packing group**
- **ADR, IMDG, IATA** II
- **14.5 Environmental hazards:**
- **Marine pollutant:** No
- **14.6 Special precautions for user** Warning: Flammable liquids.
- **Hazard identification number (Kemler code):** 33
- **EMS Number:** F-E, S-E
- **Stowage Category** B

(Contd. on page 9)

en

# Safety data sheet

## according to Regulation (EC) No 1907/2006, Article 31

Printing date 30.04.2026

Version 6 (replaces version 5)

Revision: 30.04.2026

Trade name: OTTO Primer 1217

(Contd. of page 8)

- **14.7 Maritime transport in bulk according to IMO instruments** Not applicable
- **Transport/Additional information:**

---

- **ADR**
- **Limited quantities (LQ)** 1L
- **Excepted quantities (EQ)** Code: E2
- Maximum net quantity per inner packaging: 30 ml*
- Maximum net quantity per outer packaging: 500 ml*
- **Transport category** 2
- **Tunnel restriction code** D/E

---

- **IMDG**
- **Limited quantities (LQ)** 1L
- **Excepted quantities (EQ)** Code: E2
- Maximum net quantity per inner packaging: 30 ml*
- Maximum net quantity per outer packaging: 500 ml*
- **UN "Model Regulation":** UN 1993 FLAMMABLE LIQUID, N.O.S.  
(ISOPROPANOL, TOLUENE), 3, II

### SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category P5c** FLAMMABLE LIQUIDS
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5.000 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50.000 t
- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3, 48
- **DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II**
- None of the ingredients is listed.
- **REGULATION (EU) 2019/1148**
- **Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))**
- None of the ingredients is listed.
- **Annex II - REPORTABLE EXPLOSIVES PRECURSORS**
- None of the ingredients is listed.
- **Regulation (EC) No 273/2004 on drug precursors**
- 108-88-3 toluene: 3
- **Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors**
- 108-88-3 toluene: 3
- **National regulations**
- **Information about limitation of use:**
- Employment restrictions concerning juveniles must be observed.
- Employment restrictions concerning pregnant and lactating women must be observed.
- **Waterhazard class:** Water hazard class 2 (Self-assessment): hazardous for water.

(Contd. on page 10)

# Safety data sheet

## according to Regulation (EC) No 1907/2006, Article 31

Printing date 30.04.2026

Version 6 (replaces version 5)

Revision: 30.04.2026

**Trade name: OTTO Primer 1217**

(Contd. of page 9)

· **Details of international registration status:**

**Listed on or in accordance with the following inventories:**

ENCS - Japan listed  
 REACH - Europe listed  
 AICS - Australia listed  
 DSL - Canada listed  
 IECSC - China listed  
 NZIoC - New Zealand not listed  
 PICCS - Philippines listed  
 ECL - Korea not listed  
 TSCA - USA listed  
 TCSI - Taiwan listed

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship. This Safety Data Sheet is in compliance with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

· **Relevant phrases**

H225 Highly flammable liquid and vapour.  
 H226 Flammable liquid and vapour.  
 H302 Harmful if swallowed.  
 H304 May be fatal if swallowed and enters airways.  
 H315 Causes skin irritation.  
 H317 May cause an allergic skin reaction.  
 H318 Causes serious eye damage.  
 H319 Causes serious eye irritation.  
 H335 May cause respiratory irritation.  
 H336 May cause drowsiness or dizziness.  
 H361d Suspected of damaging the unborn child.  
 H373 May cause damage to organs through prolonged or repeated exposure.  
 H411 Toxic to aquatic life with long lasting effects.

· **Date of previous version:** 23.04.2024

· **Version number of previous version:** 5

· **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)  
 IMDG: International Maritime Code for Dangerous Goods  
 IATA: International Air Transport Association  
 GHS: Globally Harmonised System of Classification and Labelling of Chemicals  
 EINECS: European Inventory of Existing Commercial Chemical Substances  
 ELINCS: European List of Notified Chemical Substances  
 CAS: Chemical Abstracts Service (division of the American Chemical Society)  
 DNEL: Derived No-Effect Level (REACH)  
 LC50: Lethal concentration, 50 percent  
 LD50: Lethal dose, 50 percent  
 PBT: Persistent, Bioaccumulative and Toxic  
 vPvB: very Persistent and very Bioaccumulative  
 Flam. Liq. 2: Flammable liquids – Category 2  
 Flam. Liq. 3: Flammable liquids – Category 3  
 Acute Tox. 4: Acute toxicity – Category 4  
 Skin Irrit. 2: Skin corrosion/irritation – Category 2  
 Eye Dam. 1: Serious eye damage/eye irritation – Category 1  
 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2  
 Skin Sens. 1: Skin sensitisation – Category 1  
 Repr. 2: Reproductive toxicity – Category 2

(Contd. on page 11)

**Safety data sheet**  
according to Regulation (EC) No 1907/2006, Article 31

Printing date 30.04.2026

Version 6 (replaces version 5)

Revision: 30.04.2026

**Trade name: OTTO Primer 1217**

(Contd. of page 10)

*STOT SE 3: Specific target organ toxicity (single exposure) – Category 3**STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2**Asp. Tox. 1: Aspiration hazard – Category 1**Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2**Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3***\* Data compared to the previous version altered.**

en