

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.03.2020

Version 3

Revision: 23.03.2020

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** OTTO Primer 1225
- **UFI:** VSW0-R001-S00W-EFG4
- **Product category** PC9a Coatings and paints, thinners, paint removers
- **Application of the substance / the mixture** Priming
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Hermann Otto GmbH
Krankenhausstraße 14
D-83413 Fridolfing
Tel.: 0049/(0)8684/908-0
Fax.: 0049/(0)8684/908-539
- **Further information obtainable from:**
Tel.: 0049- (0)8684- 908- 641 (-460)
E-Mail: alois.parzinger@otto-chemie.de
- **1.4 Emergency telephone number:**
Tel.: 0049- (0) 89- 192 40 (emergency telephone no.)
Tel.: 0049/621/60-43333 (BASF Plant fire brigade)

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS07

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms** GHS02, GHS07
- **Signal word** Danger
- **Hazard-determining components of labelling:**
ethyl acetate
- **Hazard statements**
H225 Highly flammable liquid and vapour.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
- **Precautionary statements**
P102 Keep out of reach of children.
P210 Keep away from heat. - No smoking.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves / eye protection / face protection.
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P302+P352 IF ON SKIN: Wash with plenty of water.
P304+P312 IF INHALED: Call a POISON CENTER/doctor if you feel unwell.

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.03.2020

Version 3

Revision: 23.03.2020

Trade name: OTTO Primer 1225

(Contd. of page 1)

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical advice/attention.

- **Additional information:**

EUH066 Repeated exposure may cause skin dryness or cracking.

Contains dibutyltin dilaurate. May produce an allergic reaction.

- **2.3 Other hazards**

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

- **3.2 Chemical characterisation: Mixtures**

- **Description:** Solvent mixture with additives.

- **Dangerous components:**

CAS: 141-78-6	ethyl acetate	50-100%
EINECS: 205-500-4	⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336	
Reg.nr.: 01-2119475103-46		
CAS: 67-63-0	propan-2-ol	<10%
EINECS: 200-661-7	⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336	
Reg.nr.: 01-2119457558-25-0000		
CAS: 1330-20-7	xylene (mix)	<10%
EINECS: 215-535-7	⚠ Flam. Liq. 3, H226; ⚠ STOT RE 2, H373; Asp. Tox. 1, H304; ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	
Reg.nr.: 01-2119488216-32-0000		
CAS: 100-41-4	ethylbenzene	<2.5%
EINECS: 202-849-4	⚠ Flam. Liq. 2, H225; ⚠ STOT RE 2, H373; Asp. Tox. 1, H304; ⚠ Acute Tox. 4, H332; Aquatic Chronic 3, H412	
Reg.nr.: 01-2119489370-35		
CAS: 67-56-1	methanol	<1%
EINECS: 200-659-6	⚠ Flam. Liq. 2, H225; ⚠ Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331; ⚠ STOT SE 1, H370	
CAS: 77-58-7	dibutyltin dilaurate	<1%
EINECS: 201-039-8	⚠ Muta. 2, H341; Repr. 1B, H360FD; STOT SE 1, H370; STOT RE 1, H372; ⚠ Skin Corr. 1C, H314; ⚠ Aquatic Acute 1, H400; Aquatic Chronic 1, H410; ⚠ Skin Sens. 1, H317	

- **Additional information** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- **4.1 Description of first aid measures**

- **General information**

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- **After inhalation**

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

- **After skin contact**

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

- **After eye contact**

Rinse opened eye for several minutes under running water. Then consult a doctor.

- **After swallowing**

Do not induce vomiting; call for medical help immediately. Show container or label.

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.03.2020

Version 3

Revision: 23.03.2020

Trade name: OTTO Primer 1225

(Contd. of page 2)

- **4.2 Most important symptoms and effects, both acute and delayed**
Headache
Dizziness
Dizziness
Nausea
- **4.3 Indication of any immediate medical attention and special treatment needed**
If swallowed or in case of vomiting, danger of entering the lungs

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents** CO₂, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents** Water.
- **5.2 Special hazards arising from the substance or mixture**
Formation of toxic gases is possible during heating or in case of fire.
- **5.3 Advice for firefighters**
- **Protective equipment:** Do not inhale explosion gases or combustion gases.
- **Additional information** Cool endangered receptacles with water spray.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Ensure adequate ventilation
Keep away from ignition sources
- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
- **6.4 Reference to other sections** See Section 8 for information on personal protection equipment.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
see item 8: Personal protective equipment
- **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Traces of flammable substances may collect in the steam chamber of enclosed systems. Keep clear of ignition sources.
Highly volatile, flammable constituents are released during processing.
Flammable gas-air mixtures may form in empty receptacles.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage**
- **Requirements to be met by storerooms and receptacles:**
Provide solvent resistant, sealed floor.
Prevent any seepage into the ground.
- **Information about storage in one common storage facility:** Store away from foodstuffs.
- **Further information about storage conditions:**
Store in cool, dry conditions in well sealed receptacles.
Protect from heat and direct sunlight.
Store receptacle in a well ventilated area.
- **7.3 Specific end use(s)** No further relevant information available.

GB

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.03.2020

Version 3

Revision: 23.03.2020

Trade name: OTTO Primer 1225

(Contd. of page 3)

SECTION 8: Exposure controls/personal protection

· **Additional information about design of technical facilities:** No further data; see item 7.

· **8.1 Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

141-78-6 ethyl acetate

WEL Short-term value: 400 ppm

Long-term value: 200 ppm

1330-20-7 xylene (mix)

WEL Short-term value: 441 mg/m³, 100 ppm

Long-term value: 220 mg/m³, 50 ppm

Sk; BMGV

100-41-4 ethylbenzene

WEL Short-term value: 552 mg/m³, 125 ppm

Long-term value: 441 mg/m³, 100 ppm

67-56-1 methanol

WEL Short-term value: 333 mg/m³, 250 ppm

Long-term value: 266 mg/m³, 200 ppm

Sk

· **Additional information:** The lists valid during the making were used as basis.

· **8.2 Exposure controls**

· **Personal protective equipment**

· **General protective and hygienic measures**

The usual precautionary measures are to be adhered to when handling chemicals.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· **Respiratory protection:**

Use suitable respiratory protective device when high concentrations are present.

· **Protection of hands:** Protective gloves.

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

Fluorocarbon rubber (Viton)

Recommended thickness of the material: ≥ 0.4 mm

· **Penetration time of glove material** Breakthrough time: > 30 min

· **Eye protection:** Tightly sealed goggles.

· **Body protection:** Protective work clothing.

SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form: Fluid

Colour: Colourless

· **Odour:** Characteristic

· **Odour threshold:** Not determined.

· **pH-value:** Not determined.

· **Change in condition**

Melting point/freezing point: undetermined

Initial boiling point and boiling range: undetermined

· **Flash point:** -4 °C

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.03.2020

Version 3

Revision: 23.03.2020

Trade name: OTTO Primer 1225

(Contd. of page 4)

- **Ignition temperature:** 425 °C
- **Decomposition temperature:** Not determined.
- **Auto-ignition temperature:** Product is not selfigniting.
- **Explosive properties:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
- **Explosion limits:**
 - Lower: 1.0 Vol %
 - Upper: 7.0 Vol %
- **Oxidising properties** Not determined.
- **Vapour pressure at 20 °C:** 100 hPa
- **Density at 20 °C:** 0.98 g/cm³
- **Vapour density** Not determined.
- **Evaporation rate** Not determined.
- **Solubility in / Miscibility with Water:** Not determined.
- **Partition coefficient: n-octanol/water:** Not determined.
- **Viscosity at 40 °C:** <20.5 mm²/s
Not determined.

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
Avoid strong heating.
- **10.3 Possibility of hazardous reactions**
Danger of receptacles bursting because of high vapour pressure when heated
Can form explosive mixtures in air if heated above flash point and/or when sprayed or atomised
- **10.5 Incompatible materials:** Strong oxidizing agents, alkalis, amines, strong acides
- **10.6 Hazardous decomposition products:** see item 5.2

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.
- **LD/LC50 values relevant for classification:**

141-78-6 ethyl acetate

Oral LD50 >5,000 mg/kg (rat)
Dermal LD50 >5,000 mg/kg (rbt)

67-63-0 propan-2-ol

Oral LD50 5,840 mg/kg (rat)
Dermal LD50 13,900 mg/kg (rab)

1330-20-7 xylene (mix)

Oral LD50 3,523 mg/kg (rat)
Dermal LD50 >4,200 mg/kg (rbt)
Inhalative LC50/4 h 29.091 mg/l (rat)

67-56-1 methanol

Oral LD50 1,187 mg/kg (rat) (ECHA)

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.03.2020

Version 3

Revision: 23.03.2020

Trade name: OTTO Primer 1225

(Contd. of page 5)

Inhalative LC50/4 h 115.9 mg/l (rat) (ECHA)

77-58-7 dibutyltin dilaurate

Oral LD50 2,071 mg/kg (rat)

- **Primary irritant effect:**
- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation**
Causes serious eye irritation.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**
May cause drowsiness or dizziness.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water.
Do not allow product to reach ground water, water course or sewage system.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation** Liquid residues must be specially treated adhering to official regulations.
- **Uncleaned packaging:**
- **Recommendation:**
Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.
Packagings that may not be cleansed are to be disposed of in the same manner as the product.

SECTION 14: Transport information

- **14.1 UN-Number**
- **ADR, IMDG, IATA** UN1993
- **14.2 UN proper shipping name**
- **ADR** 1993 FLAMMABLE LIQUID, N.O.S. (ETHYL ACETATE, ETHYLBENZENE)
- **IMDG, IATA** FLAMMABLE LIQUID, N.O.S. (ETHYL ACETATE, ISOPROPANOL)
- **14.3 Transport hazard class(es)**
- **ADR**
- **Class** 3 (F1) Flammable liquids.



(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31


Printing date 23.03.2020

Version 3

Revision: 23.03.2020

Trade name: OTTO Primer 1225

(Contd. of page 6)

· Label	3
<hr style="border-top: 1px dashed #000;"/>	
· IMDG, IATA	
	
· Class	3 Flammable liquids.
· Label	3
· 14.4 Packing group	
· ADR, IMDG, IATA	II
· 14.5 Environmental hazards:	
· Marine pollutant:	No
· 14.6 Special precautions for user	Warning: Flammable liquids.
· Danger code (Kemler):	33
· EMS Number:	F-E, S-E
· Stowage Category	B
· 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	
<hr style="border-top: 1px dashed #000;"/>	
· ADR	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· Transport category	2
· Tunnel restriction code	D/E
<hr style="border-top: 1px dashed #000;"/>	
· IMDG	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN1993, FLAMMABLE LIQUID, N.O.S. (ETHYL ACETATE, ISOPROPANOL), 3, II

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
 - **Directive 2012/18/EU**
 - **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5.000 t
 - **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50.000 t
 - **Regulation (EU) No 649/2012**
-
- 77-58-7 dibutyltin dilaurate Annex I Part 1
- **National regulations**
 - **Information about limitation of use:**
Employment restrictions concerning juveniles must be observed.
Employment restrictions concerning pregnant and lactating women must be observed.
 - **Waterhazard class:** Water hazard class 2 (Self-assessment): hazardous for water.
 - **Details of international registration status:**
Listed on or in accordance with the following inventories:
REACH - Europe listed
TSCA - USA listed
AICS - Australia listed

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.03.2020

Version 3

Revision: 23.03.2020

Trade name: OTTO Primer 1225

(Contd. of page 7)

IECSC - China listed
 DSL - Canada not listed
 ENCS - Japan not listed
 NZIoC - New Zealand listed
 PICCS - Philippines listed
 ECL - Korea listed
 TCSI - Taiwan listed

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H225 Highly flammable liquid and vapour.
 H226 Flammable liquid and vapour.
 H301 Toxic if swallowed.
 H304 May be fatal if swallowed and enters airways.
 H311 Toxic in contact with skin.
 H312 Harmful in contact with skin.
 H314 Causes severe skin burns and eye damage.
 H315 Causes skin irritation.
 H317 May cause an allergic skin reaction.
 H319 Causes serious eye irritation.
 H331 Toxic if inhaled.
 H332 Harmful if inhaled.
 H335 May cause respiratory irritation.
 H336 May cause drowsiness or dizziness.
 H341 Suspected of causing genetic defects.
 H360FD May damage fertility. May damage the unborn child.
 H370 Causes damage to organs.
 H372 Causes damage to organs through prolonged or repeated exposure.
 H373 May cause damage to the hearing organs through prolonged or repeated exposure.
 H400 Very toxic to aquatic life.
 H410 Very toxic to aquatic life with long lasting effects.
 H412 Harmful to aquatic life with long lasting effects.

· **Department issuing SDS:** Tel.: 0049- (0)8684- 908- 641

· **Contact:** Tel.: 0049- (0)8684- 908- 641 (-460)

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
 IMDG: International Maritime Code for Dangerous Goods
 IATA: International Air Transport Association
 GHS: Globally Harmonised System of Classification and Labelling of Chemicals
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 PBT: Persistent, Bioaccumulative and Toxic
 vPvB: very Persistent and very Bioaccumulative
 Flam. Liq. 2: Flammable liquids – Category 2
 Flam. Liq. 3: Flammable liquids – Category 3
 Acute Tox. 3: Acute toxicity – Category 3
 Acute Tox. 4: Acute toxicity – Category 4
 Skin Corr. 1C: Skin corrosion/irritation – Category 1C
 Skin Irrit. 2: Skin corrosion/irritation – Category 2
 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
 Skin Sens. 1: Skin sensitisation – Category 1
 Muta. 2: Germ cell mutagenicity – Category 2
 Repr. 1B: Reproductive toxicity – Category 1B
 STOT SE 1: Specific target organ toxicity (single exposure) – Category 1

(Contd. on page 9)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 23.03.2020

Version 3

Revision: 23.03.2020

Trade name: OTTO Primer 1225

(Contd. of page 8)

*STOT SE 3: Specific target organ toxicity (single exposure) – Category 3**STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1**STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2**Asp. Tox. 1: Aspiration hazard – Category 1**Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1**Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1**Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3**** Data compared to the previous version altered.**

GB