

Declaration of Performance

LE/DoP no. OC0210A

- 1 Identification code of the product type: OTTOSEAL® A 210
- 2 Ident. no.: Batch number, see product packaging
- 3 Designated use: 1-component acrylic sealant; sealant for application in the facade, type **F INT 7.5 P**, conditioning A, carrier material: Mortar M1, pretreatment: OTTO Primer 1105
- 4 Manufacturer: Hermann Otto GmbH
Krankenhausstraße 14
83413 Fridolfing, Germany
- 5 Authorised representative: -
- 6 System for evaluating reliability of performance: 4 plus 3
- 7 Harmonised standard: EN 15651 - 1: 2012-12
- 8 Notified body: In its capacity as a notified test laboratory, ift Rosenheim GmbH (NB no. 0757) performed the fire-behaviour tests in compliance with EN 13501-1, and class E in compliance with EN 15651.

9 Important characteristics:

Important characteristic	Performance	harmonised technical specification
Fire behaviour	Class E	EN 15651 - 1: 2012-12
Release of chemicals hazardous to health and/or the environment	evaluated	
Water- and airtightness		
a) Stability under load	≤ 3 mm	
b) Volume loss	≤ 25 %	
c) Tensile behaviour, i.e. stress expansion on breakage (at 23°C)	≥ 25 %	
Durability	passed (NF)	

10 The performance of the product in compliance with numbers 1 and 2 corresponds to the declared performance in compliance with number 9.

The manufacturer alone is responsible for preparing the declaration of performance in compliance with number 9.
Signed on behalf of and in the name of the manufacturer by:

Fridolfing, dated 03.04.2014



Frank Bechmann
grad. Chemical Engineer
Applications Technology/Development



Nikolaus Auer
Head of Applications Technology &
Development

[gb]