

Declaration of Performance

LE/DoP-no. OC0350A

- 1** Identification code of the product type: OTTOSEAL® M 350
- 2** Ident. no.: Batch number, see product packaging
- 3** Designated use: 1-component sealant based on MS hybrid polymer, sealant for application in the facade and for glazing, Type **F EXT-INT CC 25 HM** and **G CC 25 HM**, conditioning B, carrier material: anodised aluminium, glass and M1 mortar, pretreatment: OTTO Primer SP 6878 (anodised aluminium) and OTTO Primer SP 6879 (M1 mortar)
- 4** Manufacturer: Hermann Otto GmbH
Krankenhausstraße 14
83413 Fridolfing, Germany
- 5** Authorised representative: -
- 6** System for evaluating reliability of performance: 3 plus 3
- 7** Harmonised standard: EN 15651 - 1: 2012-12, EN 15651 - 2: 2012-12
- 8** Notified body: ift Rosenheim GmbH (NB-no. 0757) - in its capacity as a notified test laboratory in system 3 - carried out the initial tests and wrote the test report.
- 9** Important characteristics:

| Important characteristic | Performance | harmonised technical specification |
|---|-------------|--|
| Fire behaviour | Class E | EN 15651 - 1: 2012-12 EN 15651 - 2: 2012-12 |
| Release of chemicals hazardous to health and/or the environment | evaluated | |
| Water- and airtightness | | |
| a) Stability under load | ≤ 3 mm | |
| b) Volume loss | ≤ 10 % | |
| c) Tensile behaviour, i.e. stress expansion under pretensioning after submersion in water | passed (NF) | |
| d) Adhesive/stress expansion action after the effects of heat, water and artificial light | passed (NF) | |
| e) Resilience | ≥ 60 % | |
| f) Tensile properties under pretensioning in a cold climate (at -30°C) | passed (NF) | |
| Durability | passed (NF) | |

- 10** The performance of the product in compliance with numbers 1 and 2 corresponds to the declared performance in compliance with number 9.

The manufacturer alone is responsible for preparing the declaration of performance in compliance with number 9.
Signed on behalf of and in the name of the manufacturer by:

Fridolfing, dated 05.05.2014



Frank Bechmann
grad. Chemical Engineer
Applications Technology/Development



Nikolaus Auer
Head of Applications Technology &
Development

[gb]