

Declaration of Performance

LE/DoP no. OC0080B

- 1** Identification code of the product type: OTTOSEAL® S 80
- 2** Ident. no.: Batch number, see product packaging
- 3** Designated use: 1-component silicone sealant; neutrally curing, sealant for application in the facade and sanitary area, type **F EXT-INT CC 20 LM** and **XS 1**, conditioning A, carrier material: anodised aluminium, pretreatment: OTTO Primer 1216
- 4** Manufacturer: Hermann Otto GmbH
Krankenhausstraße 14
83413 Fridolfing, Germany
- 5** Authorised representative: -
- 6** System for evaluating reliability of performance: 3 plus 3
- 7** Harmonised standard: EN 15651 - 1: 2012-12, EN 15651 - 3: 2012-12
- 8** Notified body: ift Rosenheim GmbH (NB-no. 0757) as a notified test laboratory in System 3 carried out the initial tests and issued the test and classification reports.
- 9** Important characteristics:

Important characteristic	Performance	harmonised technical specification
Fire behaviour	Class E	EN 15651 - 1: 2012-12 EN 15651 - 3: 2012-12
Release of chemicals hazardous to health and/or the environment	evaluated	
Water- and airtightness		
a) Stability under load	≤ 3 mm	
b) Volume loss	≤ 10 %	
c) Tensile behaviour, i.e. stress expansion under pretensioning after submersion in water	passed (NF)	
d) Microbiological growth	0	
Durability	passed (NF)	

10 The performance of the product in compliance with numbers 1 and 2 corresponds to the declared performance in compliance with number 9.

The manufacturer alone is responsible for preparing the declaration of performance in compliance with number 10.
Signed on behalf of and in the name of the manufacturer by:

Fridolfing, dated 15.12.2015



Frank Bechmann
grad. Chemical Engineer
Applications Technology/Development



Nikolaus Auer
Head of Applications Technology &
Development

[gb]