

Declaration of Performance

LE/DoP-Nr. OC0361A

- 1** Identification code of the product type: OTTOSEAL® M 361
- 2** Ident. no.: Batch number, see product packaging
- 3** Designated use: 1-component sealant based on hybrid polymer; sealant for application in the facade, type **F EXT-INT CC 25 LM**, conditioning B, carrier material: Mortar M1, pretreatment: OTTO Primer 1225
- 4** Manufacturer: Hermann Otto GmbH
Krankenhausstraße 14
83413 Fridolfing, Germany
- 5** Authorised representative: -
- 6** System for evaluating reliability of performance: 3 plus 3
- 7** Harmonised standard: EN 15651 - 1: 2012-12
- 8** Notified body: SKZ - Testing GmbH (NB-no. 1213) - in its capacity as a notified test laboratory in system 3 - carried out the initial tests and wrote the test report.
- 9** Important characteristics:

Important characteristic	Performance	harmonised technical specification
Fire behaviour	Class E	EN 15651 - 1: 2012-12
Release of chemicals hazardous to health and/or the environment	evaluated	
Water- and airtightness		
a) Stability under load	≤ 3 mm	
b) Volume loss	≤ 10 %	
c) Tensile behaviour, i.e. stress expansion under pretensioning after submersion in water	passed (NF)	
d) Tensile properties / secant modulus in cold climate (at -30°C)	≤ 0.9 MPa	
e) Tensile properties under pretensioning in a cold climate (at -30°C)	passed (NF)	
Durability	passed (NF)	

10 The performance of the product in compliance with numbers 1 and 2 corresponds to the declared performance in compliance with number 9.

The manufacturer alone is responsible for preparing the declaration of performance in compliance with number 9.
Signed on behalf of and in the name of the manufacturer by:

Fridolfing, 17.04.2019



Nikolaus Auer
Head of Applications Technology & Development



Christian von Malotki
Group leader construction
Applications Technology &
Development

[gb]