


# OTTOSEAL<sup>®</sup> S 7



		1213
<b>Hermann Otto GmbH</b> <b>Krankenhausstr. 14, 83413 Fridolfing, Germany</b> 2014 OC0007B		
<b>EN 15651 - 1, EN 15651 - 2</b> 1 component silicone sealant, neutral curing for application in the facade for glazing		
<ul style="list-style-type: none"> <li>- Type F EXT-INT CC, G CC</li> <li>- Conditioning: Process A</li> <li>- Carrier material: Glass</li> <li>- Pre-treatment: OTTO Cleanprimer 1226</li> </ul>		
1/2-1	Fire behaviour	E
1/2-2	Release of chemicals hazardous to health and/or the environment	NPD
Water- and airtightness		
1/2-3	Stability under load	≤ 3 mm
1/2-4	Volume loss	≤ 10 %
1-5	Tensile behaviour, i.e. stress expansion under pretensioning after submersion in water	NF
1/2-7	Tensile properties / secant modulus in cold climate (at -30°C)	≤ 0,9 MPa
1/2-8	Tensile properties under pretensioning in a cold climate (at -30°C)	NF
2-10	Adhesive/stress expansion action after the effects of heat, water and artificial light	NF
2-11	Resilience	≥ 60%
1/2-20	Durability - adhesive/stress expansion at different temperatures	NF