

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 27.07.2020

Version 1

Revision: 27.07.2020

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name: OTTOPUR OP 950**
- **UFI: 4281-F0TP-J009-TEDV**
- **Application of the substance / the mixture** Assembly foam
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Hermann Otto GmbH
Krankenhausstraße 14
D-83413 Fridolfing
Tel.: 0049/(0)8684/908-0
Fax.: 0049/(0)8684/908-539
- **Further information obtainable from:**
Tel.: 0049- (0)8684- 908- 641 (-460)
E-Mail: alois.parzinger@otto-chemie.de
- **1.4 Emergency telephone number:**
Tel.: 0049- (0) 89- 192 40 (emergency telephone no.)
Tel.: 0049/621/60-43333 (BASF Plant fire brigade)

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Aerosol 1 H222-H229 *Extremely flammable aerosol. Pressurised container: May burst if heated.*



GHS08 health hazard

Resp. Sens. 1 H334 *May cause allergy or asthma symptoms or breathing difficulties if inhaled.*

Carc. 2 H351 *Suspected of causing cancer.*

STOT RE 2 H373 *May cause damage to organs through prolonged or repeated exposure.*



GHS07

Skin Irrit. 2 H315 *Causes skin irritation.*

Eye Irrit. 2 H319 *Causes serious eye irritation.*

Skin Sens. 1 H317 *May cause an allergic skin reaction.*

STOT SE 3 H335 *May cause respiratory irritation.*

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms** GHS02, GHS07, GHS08
- **Signal word** Danger
- **Hazard-determining components of labelling:**
Diphenylmethandiisocyanat, Isomere und Homologe
- **Hazard statements**
H222-H229 *Extremely flammable aerosol. Pressurised container: May burst if heated.*
H315 *Causes skin irritation.*

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 27.07.2020

Version 1

Revision: 27.07.2020

Trade name: OTTOPUR OP 950

(Contd. of page 1)

- H319 Causes serious eye irritation.
 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
 H317 May cause an allergic skin reaction.
 H351 Suspected of causing cancer.
 H335 May cause respiratory irritation.
 H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

- P102 Keep out of reach of children.
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P211 Do not spray on an open flame or other ignition source.
 P251 Do not pierce or burn, even after use.
 P260 Do not breathe dust/fume/gas/mist/vapours/spray.
 P271 Use only outdoors or in a well-ventilated area.
 P280 Wear protective gloves/protective clothing/eye protection/face protection.
 P304+P341 IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical advice/attention.
 P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Additional information:

Buildup of explosive mixtures possible without sufficient ventilation.

2.3 Other hazards

Information according to REACH- Annex XVII.56

- Persons already sensitised to diisocyanates may develop allergic reactions when using this product.
- Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product.
- This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e.type A1 according to standard EN 14387) is used.

Results of PBT and vPvB assessment

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Chemical characterisation: Mixtures· **Description:** Mixture of substances listed below with nonhazardous additions.**Dangerous components:**

CAS: 13674-84-5 EINECS: 237-158-7 Reg.nr.: 01-2119447716-31-XXXX	tris(2-chlorisopropyl)-phosphate ⚠ Acute Tox. 4, H302	<25%
CAS: 32055-14-4 NLP: 500-079-6	Diphenylmethandiisocyanat, Isomere und Homologe ⚠ Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373; ⚠ Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335	<25%
CAS: 115-10-6 EINECS: 204-065-8 Reg.nr.: 01-2119472128-37	dimethyl ether ⚠ Flam. Gas 1, H220; Press. Gas (Comp.), H280	<25%
CAS: 75-28-5 EINECS: 200-857-2 Reg.nr.: 01-2119485395-27	isobutane ⚠ Flam. Gas 1, H220; Press. Gas (Comp.), H280	<25%
CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 01-2119486944-21	propane ⚠ Flam. Gas 1, H220; Press. Gas (Comp.), H280	<10%

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 27.07.2020

Version 1

Revision: 27.07.2020

Trade name: OTTOPUR OP 950

(Contd. of page 2)

- **Additional information** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· **General information**

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· **After inhalation**

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

· **After skin contact**

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· **After eye contact**

Rinse opened eye for several minutes under running water. Then consult a doctor.

· **After swallowing**

Do not induce vomiting; call for medical help immediately. Show container or label.

· 4.2 Most important symptoms and effects, both acute and delayed

After inhalation: dry throat/neck pain. Cough. Irritation of the respiratory tract. Irritation of the nasal mucous membranes. Running of the nose. CONSEQUENTIAL SYMPTOMS MAY OCCURE:

Possible inflammation of the respiratory tract. Pulmonary edema possible. Difficulty breathing. After skin contact: Tingles/irritation of the skin. After eye contact: Irritation of the eye tissue. Lachrymal flow.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

· **Suitable extinguishing agents**

CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· **For safety reasons unsuitable extinguishing agents** Water with full jet.

· 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

· 5.3 Advice for firefighters

· **Protective equipment:**

Mount respiratory protective device.

Do not inhale explosion gases or combustion gases.

· **Additional information** Cool endangered receptacles with water spray.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Keep away from ignition sources

· 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to item 13.

Allow to solidify. Pick up mechanically.

· 6.4 Reference to other sections See Section 8 for information on personal protection equipment.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 27.07.2020

Version 1

Revision: 27.07.2020

Trade name: OTTOPUR OP 950

(Contd. of page 3)

- see item 8: Personal protective equipment
- **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Fumes can combine with air to form an explosive mixture.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage**
- **Requirements to be met by storerooms and receptacles:**
Observe official regulations on storing packagings with pressurised containers.
Prevent any seepage into the ground.
- **Information about storage in one common storage facility:**
Store away from oxidising agents.
Store away from foodstuffs.
- **Further information about storage conditions:**
Protect from heat and direct sunlight.
Store in a cool place. Heat will increase pressure and may lead to the receptacle bursting.

SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.
- **8.1 Control parameters**
- **Ingredients with limit values that require monitoring at the workplace:**
- 115-10-6 dimethyl ether (<25%)
WEL Short-term value: 958 mg/m³, 500 ppm
Long-term value: 766 mg/m³, 400 ppm
- **Additional information:** The lists valid during the making were used as basis.
- **8.2 Exposure controls**
- **Personal protective equipment**
- **General protective and hygienic measures**
The usual precautionary measures are to be adhered to when handling chemicals.
Wash hands before breaks and at the end of work.
Avoid contact with the eyes and skin.
- **Respiratory protection:**
This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e.type A1 according to standard EN 14387) is used.
- **Protection of hands:** Protective gloves.
- **Material of gloves**
Recommended glove types: nitrile rubber
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.
Recommended thickness of the material: ≥ 0.7 mm
- **Penetration time of glove material** Breakthrough time: > 480 min
- **Eye protection:** Safety glasses
- **Body protection:** Protective work clothing.

SECTION 9: Physical and chemical properties

- **9.1 Information on basic physical and chemical properties**
- **General Information**
- **Appearance:**

Form:	Aerosol
Colour:	Different according to colouring
Odour:	Characteristic
Odour threshold:	Not determined.
pH-value:	Not determined.

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 27.07.2020

Version 1

Revision: 27.07.2020

Trade name: OTTOPUR OP 950

(Contd. of page 4)

- **Change in condition**
 - Melting point/freezing point:** undetermined
 - Initial boiling point and boiling range:** Not applicable, as aerosol
- **Flash point:** Not applicable, as aerosol
- **Decomposition temperature:** Not determined.
- **Auto-ignition temperature:** Not determined.
- **Explosive properties:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
- **Explosion limits:**
 - Lower:** not applicable
 - Upper:** not applicable
- **Oxidising properties:** Not determined.
- **Vapour pressure at 20 °C:** 5,100 hPa
- **Density:** see technical datasheet
- **Vapour density:** Not applicable.
- **Evaporation rate:** Not determined.
- **Solubility in / Miscibility with**
 - Water:** insoluble- reaction with water
- **Partition coefficient: n-octanol/water:** Not determined.
- **Viscosity:** Not determined.

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
Avoid strong heating.
- **10.3 Possibility of hazardous reactions**
Danger of receptacles bursting because of high vapour pressure when heated
- **10.5 Incompatible materials:** Strong oxidizing agents, alkalis, amines, strong acids
- **10.6 Hazardous decomposition products:** see item 5.2

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
 - **Acute toxicity** Based on available data, the classification criteria are not met.
 - **LD/LC50 values relevant for classification:**
-
- 13674-84-5 tris(2-chlorisopropyl)-phosphate**
Dermal LD50 >2,000 mg/kg (rat)
- 32055-14-4 Diphenylmethandiisocyanat, Isomere und Homologe**
Oral LD50 >10,000 mg/kg (rat)
Dermal LD50 >9,400 mg/kg (rab)
Inhalative LC50/4 h 310 mg/l (rat)
- **Primary irritant effect:**
 - **Skin corrosion/irritation**
Causes skin irritation.
 - **Serious eye damage/irritation**
Causes serious eye irritation.

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 27.07.2020

Version 1

Revision: 27.07.2020

Trade name: OTTOPUR OP 950

(Contd. of page 5)

- **Respiratory or skin sensitisation**
Sensitive people may react strongly to minimal concentrations. We advise asthmatics and people who tend to diseases of the respiratory tracts against the contact with this product.
May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause an allergic skin reaction.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity**
Suspected of causing cancer.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**
May cause respiratory irritation.
- **STOT-repeated exposure**
May cause damage to organs through prolonged or repeated exposure.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- **Additional ecological information:**
- **General notes:**
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water.
Do not allow product to reach ground water, water course or sewage system.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
Observe local by-laws.
Already cured material can be disposed of with the domestic or commercial waste. Unconsumed material (fluid, paste-like) is to dispose of as hazardous waste.
- **Uncleaned packaging:**
- **Recommendation:**
Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.
Packagings that may not be cleansed are to be disposed of in the same manner as the product.

SECTION 14: Transport information

- **14.1 UN-Number**
- **ADR, IMDG, IATA** UN1950
- **14.2 UN proper shipping name**
- **ADR** 1950 AEROSOLS
- **IMDG, IATA** AEROSOLS
- **14.3 Transport hazard class(es)**
- **ADR**
- **Class** 2 5F Gases.



(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31


Printing date 27.07.2020

Version 1

Revision: 27.07.2020

Trade name: OTTOPUR OP 950

(Contd. of page 6)

· Label	2.1
<hr style="border-top: 1px dashed #000;"/>	
· IMDG, IATA	
	
· Class	2 Gases.
· Label	2.1
· 14.4 Packing group	Void
· ADR, IMDG, IATA	Void
· 14.5 Environmental hazards:	Not applicable.
· 14.6 Special precautions for user	Warning: Gases.
· Hazard identification number (Kemler code): -	-
· EMS Number:	F-D,S-U
· Stowage Code	SW1 Protected from sources of heat. SW2 Clear of living quarters.
· Segregation Code	SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
· 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	
<hr style="border-top: 1px dashed #000;"/>	
· ADR	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
· Transport category	2
· Tunnel restriction code	D
<hr style="border-top: 1px dashed #000;"/>	
· IMDG	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
· UN "Model Regulation":	UN 1950 AEROSOLS, 2.1

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- Directive 2012/18/EU
- Named dangerous substances - ANNEX I None of the ingredients is listed.
- Seveso category P3a FLAMMABLE AEROSOLS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- National regulations
- Information about limitation of use:
Employment restrictions concerning juveniles must be observed.

(Contd. on page 8)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 27.07.2020

Version 1

Revision: 27.07.2020

Trade name: OTTOPUR OP 950

(Contd. of page 7)

Employment restrictions concerning pregnant and lactating women must be observed.

· **Waterhazard class:** Water hazard class 1 (Self-assessment): slightly hazardous for water.

· **Details of international registration status:**

Listed on or in accordance with the following inventories:

ENCS - Japan not listed

NZIoC - New Zealand not listed

REACH - Europe listed

TCSI - Taiwan not listed

AICS - Australia not listed

DSL - Canada not listed

IECSC - China not listed

ECL - Korea not listed

PICCS - Philippines not listed

TSCA - USA not listed

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H220 Extremely flammable gas.

H280 Contains gas under pressure; may explode if heated.

H302 Harmful if swallowed.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation.

H351 Suspected of causing cancer.

H373 May cause damage to organs through prolonged or repeated exposure.

· **Department issuing SDS:** Tel.: 0049- (0)8684- 908- 641

· **Contact:** Tel.: 0049- (0)8684- 908- 641 (-460)

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Gas 1: Flammable gases – Category 1

Aerosol 1: Aerosols – Category 1

Press. Gas (Comp.): Gases under pressure – Compressed gas

Acute Tox. 4: Acute toxicity - oral – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Resp. Sens. 1: Respiratory sensitisation – Category 1

Skin Sens. 1: Skin sensitisation – Category 1

Carc. 2: Carcinogenicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

· *** Data compared to the previous version altered.**