OTTOSEAL® M 390

CE 0757

Hermann Otto GmbH
Krankenhausstr. 14, 83413 Fridolfing, Germany

2020

OC0390B

EN 15651 - 1, EN 15651 - 4

1 component sealant
based on hybrid polymer
for application in the facade
for pedestrian walkways

- Type F EXT-INT CC, PW EXT-INT CC
- Conditioning: Process B
- Carrier material: mortar M1
- Pre-treatment: OTTO Primer 1105

1/4-1	Fire behaviour	E
1/4-2	Release of chemicals hazardous to health and/or the environment	NPD
Water- and airtightness		
1-3	Stability under load	≤ 3 mm
1/4-4	Volume loss	≤ 10 %
1-5	Tensile behaviour, i.e. stress expansion under pretensioning after submersion in water	NF
1/4-8	Tensile properties under pretensioning in a cold climate (at -30°C)	NF
4-13	Tensile behaviour under pretensioning	NF
4-14	Tearing strength	NF
4-15	Adhesive/stress expansion under pretensioning and change to the secant module after 28 days immersed in water	NF / ≤ 50 %
4-16	Adhesive/stress expansion under pretensioning after 28 days immersed in brine	NF
1/4-20	Durability - adhesive/stress expansion at different temperatures	NF