

# Declaration of Performance

LE/DoP no. OC0390A

- 1** Identification code of the product type: OTTOSEAL® M 390
- 2** Ident. no.: Batch number, see product packaging
- 3** Designated use: 1 component sealant based on hybrid polymer; sealant for application in the facade and for pedestrian walkways, type **F EXT-INT CC 25 HM** and **PW EXT-INT 25 HM**, conditioning B, carrier material: Mortar M1, pretreatment: OTTO Primer 1105
- 4** Manufacturer: Hermann Otto GmbH  
Krankenhausstraße 14  
83413 Fridolfing, Germany
- 5** Authorised representative: -
- 6** System for evaluating reliability of performance: 3 plus 3
- 7** Harmonised standard: EN 15651 - 1: 2012-12, EN 15651 - 4: 2012-12
- 8** Notified body: ift Rosenheim GmbH (NB-no. 0757) - in its capacity as a notified test laboratory in system 3 - carried out the initial tests and wrote the test report.
- 9** Important characteristics:

Important characteristic	Performance	harmonised technical specification
Fire behaviour	Class E	EN 15651 - 1: 2012-12 EN 15651 - 4: 2012-12
Release of chemicals hazardous to health and/or the environment	evaluated	
Water- and airtightness		
a) Tensile behaviour under pretensioning	passed (NF)	
b) Stability under load	≤ 3 mm	
c) Volume loss	≤ 10 %	
d) Tearing strength	passed (NF)	
e) Tensile behaviour, i.e. stress expansion under pretensioning after submersion in water	passed (NF)	
f) Adhesive/stress expansion under pretensioning after 28 days immersed in water	passed (NF)	
g) Adhesive/stress expansion under pretensioning after 28 days immersed in brine	passed (NF)	
h) Tensile properties under pretensioning in a cold climate (at -30°C)	passed (NF)	
Durability	passed (NF)	


- 10** The performance of the product in compliance with numbers 1 and 2 corresponds to the declared performance in compliance with number 9.

The manufacturer alone is responsible for preparing the declaration of performance in compliance with number 4.

Signed on behalf of and in the name of the manufacturer by:

Fridolfing, dated 31.08.2020

  
Nikolaus Auer  
Head of Applications Technology &  
Development  
Applications Technology/Development

  
Frank Bechmann  
grad. Chemical Engineer  
Applications Technology/Development

**[gb]**