

**OTTOSEAL®****P 720**

Sustainability data sheet

**Inspections/authorisations**

- EMICODE® EC 1<sup>PLUS</sup> – very low emission



- French VOC-emission class A+

**Building certification system****QNG - Quality Seal for Sustainable Buildings****Version 1.3**

<b>Criterion</b>	Avoiding harmful substances in building materials
<b>Overview table</b>	4. Adhesives and sealants - line 4.2
<b>Building product group</b>	Adhesives and sealants processed on site based on PU, PU hybrid and SMP formulations (silane-modified polymers) in interior spaces
<b>Requirements</b>	Product documentation and declaration of contained SVHC >0.1 % and chlorinated paraffins, TCEP, PBB and PBDs ≤0.1 % and solvent-free or GISCODE PU10, PU20, PU40 (ALT) or PU50 (ALT)
<b>Classification</b>	<b>Meets the requirements, as declaration of contained SVHC &gt;0.1 % and chlorinated paraffins, TCEP, PBB und PBDE ≤0.1 % and GISCODE PU10.</b>

**QNG - Quality Seal for Sustainable Buildings****Version 1.3**

<b>Criterion</b>	Avoiding harmful substances in building materials
<b>Overview table</b>	4. Adhesives and sealants - line 4.3
<b>Building product group</b>	Adhesives and sealants based on PU, PU hybrid, MS polymer or SMP (silane-modified polymers) for creating airtightness on façades, windows and exterior doors (inside and outside)
<b>Requirements</b>	Product documentation and declaration of contained SVHC >0.1 % and chlorinated paraffins, TCEP, PBB and PBDE ≤0.1 %
<b>Classification</b>	<b>Meets the requirements, as declaration of contained SVHC &gt;0.1 % and chlorinated paraffins, TCEP, PBB und PBDE ≤0.1 %.</b>

**Version 2023**

<b>Criterion</b>	ENV 1.2 Risks for the local environment	
<b>Criteria matrix</b>	line no. 11	
<b>Product type</b>	Sealing compounds, sealants, adhesives for dot and line-formed bonding of building components on the interior: - mechanically stressed joints - baseboards - door rails - support adhesive (raised or hollow floor) - ventilation ducts  This refers to acrylic adhesives/bonding agents, silicone sealants, PU adhesives and silane-modified polymers (SMP).	
<b>Requirements</b>	Quality category 1 (low)	GISCODE PU10, PU20, RS10, DA20, DSE20, DSA20, DSO20 or DH20 and bonus points SVHC $\leq 0.1\%$
	Quality category 2	GISCODE PU10, PU20, RS10, DA20, DSE20, DSA20, DSO20 or DH20 and bonus points SVHC $\leq 0.1\%$
	Quality category 3	GISCODE PU10, PU20, RS10, DA20, DSE20, DSA20, DSO20 or DH20 and EMICODE® EC 1 <sup>PLUS</sup> and bonus points SVHC $\leq 0.1\%$
	Quality category 4 (high)	GISCODE PU10, PU20, RS10, DA20, DSE20, DSA20, DSO20 or DH20 and EMICODE® EC 1 <sup>PLUS</sup> and bonus points SVHC $\leq 0.1\%$
<b>Classification</b>	<b>Fulfills quality category 4 requirements with GISCODE PU10 and EMICODE® EC 1<sup>PLUS</sup> and SVHC <math>\leq 0.1\%</math>.</b>	

**Version 2023**

<b>Criterion</b>	ENV 1.2 Risks for the local environment	
<b>Criteria matrix</b>	line no. 13	
<b>Product type</b>	Adhesive for air tightness of facades inside and outside: e. g. PU, PU Hybrid, MS Polymer, SMP, acrylate, silicone	
<b>Requirements</b>	Quality category 1 (low)	<0.1 % halogenated propellant and bonus points SVHC $\leq 0.1\%$
	Quality category 2	<0.1 % halogenated propellant and bonus points SVHC $\leq 0.1\%$
	Quality category 3	Chlorinated paraffins (SCCPs + MCCPs + LCCPs) <0.1 % and halogenated propellant <0.1 % and EMICODE® EC 1 <sup>PLUS</sup> or VOC <1 % and bonus points SVHC $\leq 0.1\%$
	Quality category 4 (high)	Chlorinated paraffins (SCCPs + MCCPs + LCCPs) <0.1 % and halogenated propellant <0.1 % and EMICODE® EC 1 <sup>PLUS</sup> or VOC <1 % and bonus points SVHC $\leq 0.1\%$
<b>Classification</b>	<b>Fulfills quality category 4 requirements with chlorinated paraffins (SCCPs + MCCPs + LCCPs) &lt;0.1 % and halogenated propellant &lt;0.1 % and EMICODE® EC 1<sup>PLUS</sup> and SVHC <math>\leq 0.1\%</math>.</b>	

**Version 2018**

<b>Criterion</b>	ENV 1.2 Risks for the local environment	
<b>Criteria matrix</b>	line no. 13	
<b>Product type</b>	Adhesive for air tightness of facades inside and outside: e.g. PU, PU Hybrid, MS Polymer, SMP or similar.	
<b>Requirements</b>	Quality category 1 (low)	<0.1 % halogenated propellant
	Quality category 2	<0.1 % halogenated propellant
	Quality category 3	Chlorinated paraffins <0.1 % and halogenated propellant <0.1 % and EMICODE® EC 1/EC 1 <sup>PLUS</sup> or VOC <1 %
	Quality category 4 (high)	Chlorinated paraffins <0.1 % and halogenated propellant <0.1 % and EMICODE® EC 1/EC 1 <sup>PLUS</sup> or VOC <1 %
<b>Classification</b>	<b>Fulfills quality category 4 requirements with chlorinated paraffins &lt;0.1 % and halogenated propellant &lt;0.1 % and EMICODE® EC 1<sup>PLUS</sup>.</b>	

---

**BNB – Bewertungssystem Nachhaltiges Bauen (Rating System for Sustainable Building)****Version 2015**

<b>Criterion</b>	1.1.6 Risks for the local environment	
<b>Overview table</b>	6. Adhesives and sealants – line no. 9	
<b>Construction product type</b>	Adhesives and sealants for the airtightness of facades inside and outside: e.g. PU, PU hybrid, MS polymer, SMP, etc. for punctiform and linear bonding of components for the airtightness of facades, windows and external doors.	
<b>Requirements</b>	Quality category 1 (low)	Documentation and declaration of contained SVHC >0.1 %.
	Quality category 2	Declaration of contained SVHC >0.1 % and chlorinated paraffins <0.1 %. For PU adhesives additionally applies: TCEP <0.1 %.
	Quality category 3	Declaration of contained SVHC >0.1 % and chlorinated paraffins <0.1 %. For PU adhesives additionally applies: TCEP <0.1 %.
	Quality category 4	Declaration of contained SVHC >0.1 % and chlorinated paraffins <0.1 % and EMICODE® EC 1/EC 1 <sup>PLUS</sup> or VOC < 10 g/l. For PU adhesives additionally applies: TCEP <0.1 %.
	Quality category 5 (high)	Declaration of contained SVHC >0.1 % and chlorinated paraffins <0.1 % and EMICODE® EC 1/EC 1 <sup>PLUS</sup> or VOC < 10 g/l. For PU adhesives additionally applies: TCEP <0.1 %.
<b>Classification</b>	<b>Fulfills the quality category 5 requirements as declaration of contained SVHC &gt;0.1 % and chlorinated paraffins &lt;0.1 % and EMICODE® EC 1<sup>PLUS</sup> and TCEP &lt;0.1 %.</b>	

---

<b>Documentation documents</b>	All the listed documents can be downloaded from <a href="http://www.otto-chemie.com">www.otto-chemie.com</a>
	1. Technical data sheet
	2. Safety data sheet
	3. Sustainability data sheet
	4. Test certificates
	5. Environmental product declaration

---

This information is based on our knowledge at the time of the compilation (see below). The current version can be viewed on our website at: [www.otto-chemie.com](http://www.otto-chemie.com). Furthermore, the information in the documents accompanying the products is applicable.

---