# **OTTOCOLL®** S81

Sustainability data sheet

## Inspections/authorisations

Environmental Product Declarations (EPD)

Declaration number: EPD-DBC-20220179-IBF1-EN

## **Building certification system**

QNG - Quality Seal for Sustainable Buildings

Version 1.3

Criterion Avoiding harmful substances in building materials

Overview table 4. Adhesives and sealants - line 4.1

**Building product group** Adhesives and sealants (acrylates and silicones) used on site indoors

Requirements Product documentation and declaration of contained SVHC > 0.1 % and chlorinated

paraffins ≤0.1 % and declaration of biocidal active substances in silicones

Meets the requirements, as declaration of contained SVHC > 0.1 % and chlorinated paraffins ≤0.1% and declaration of biocidal active substances in silicones.

DGNB - Deutsche Gesellschaft für Nachhaltiges Bauen (German Sustainable Building Council)

Version 2023

Classification

Criterion ENV 1.2 Risks for the local environment

Criteria matrix line no. 13

**Product type** Adhesive for air tightness of facades inside and outside: e.g. PU, PU Hybrid, MS Polymer, SMP,

acrylate, silicone.

Requirements Quality category 1 (low) < 0.1 % halogenated propellant and bonus points SVHC ≤ 0.1 %

Quality category 2

< 0.1 % halogenated propellant and bonus points SVHC ≤ 0.1 % Quality category 3 Chlorinated paraffins (SCCPs + MCCPs + LCCPs) < 0.1 % and

halogenated propellant < 0.1 % and EMICODE® EC 1 PLUS or

VOC <1% and bonus points SVHC ≤0.1%

Chlorinated paraffins (SCCPs + MCCPs + LCCPs) < 0.1 % and Quality category 4 (high)

halogenated propellant < 0.1 % and EMICODE® EC 1 PLUS or

VOC <1% and bonus points SVHC ≤0.1%

Classification Fulfills quality category 4 requirements with chlorinated paraffins (SCCPs + MCCPs +

LCCPs) <0.1 % and halogenated propellant <0.1 % and VOC <1 % und SVHC ≤0.1 %.

Sustainability data sheet OTTOCOLL® S81 version: 2gb (13.03.2024 09:05 h)

Hermann Otto GmbH · Krankenhausstr. 14 · 83413 Fridolfing, GERMANY Tel.:+49 8684-908-0 · Fax: +49 8684-12-60

e-mail: info@otto-chemie.de · Internet: www.otto-chemie.com



#### DGNB - Deutsche Gesellschaft für Nachhaltiges Bauen (German Sustainable Building Council)

Version 2018

**Criterion** ENV 1.2 Risks for the local environment

Criteria matrix line no. 13

**Product type** Adhesive for air tightness of facades inside and outside: e.g. PU, PU Hybrid, MS Polymer,

SMP or similar.

**Requirements** Quality category 1 (low) <0.1 % halogenated propellant

Quality category 2 <0.1% halogenated propellant

Quality category 3 Chlorinated paraffins < 0.1% and halogenated propellant < 0.1%

and EMICODE® EC 1/EC 1 PLUS or VOC < 1 %

Quality category 4 (high) Chlorinated paraffins < 0.1 % and halogenated propellant < 0.1 %

and EMICODE® EC 1/EC 1 PLUS or VOC < 1 %

Classification Fulfills quality category 4 requirements with chlorinated paraffins < 0.1 % and

halogenated propellant < 0.1 % and VOC < 1 %.

### BNB – Bewertungssystem Nachhaltiges Bauen (Rating System for Sustainable Building)

Version 2015

Criterion 1.1.6 Risks for the local environment

Overview table 6. Adhesives and sealants – line no. 9

Construction product type

Adhesives and sealants for the airtightness of facades inside and outside: e.g. PU, PU hybrid, MS polymer, SMP, etc. for punctiform and linear bonding of components for the airtightness of

facades, windows and external doors.

**Requirements** Quality category 1 (low) Documentation and declaration of contained SVHC > 0.1 %.

Quality category 2 Declaration of contained SVHC > 0.1 % and chlorinated

paraffins < 0.1 %.

For PU adhesives additionally applies: TCEP < 0.1%.

Quality category 3

Declaration of contained SVHC > 0.1% and chlorinated

paraffins < 0.1 %.

For PU adhesives additionally applies: TCEP < 0.1 %.

Quality category 4 Declaration of contained SVHC > 0.1 % and chlorinated paraffins

<0.1 % and EMICODE® EC 1/EC 1 PLUS or VOC < 10 g/l. For PU adhesives additionally applies: TCEP < 0.1 %.

Quality category 5 (high) Declaration of contained SVHC > 0.1 % and chlorinated paraffins

<0.1 % and EMICODE® EC 1/EC 1 PLUS or VOC <10 g/l. For PU adhesives additionally applies: TCEP <0.1 %.

Classification Fulfills the quality category 3 requirements as declaration of contained SVHC > 0.1 % and

chlorinated paraffins < 0.1 %.

Documentation documents

All the listed documents can be downloaded from www.otto-chemie.com

Technical data sheet
 Safety data sheet

3. Sustainability data sheet

4. Test certificates

5. Environmental product declaration

This information is based on our knowledge at the time of the compilation (see below). The current version can be viewed on our website at: www.otto-chemie.com. Furthermore, the information in the documents accompanying the products is applicable.

Sustainability data sheet OTTOCOLL® S81 Page 2 version: 2gb (13.03.2024 09:05 h)

Hermann Otto GmbH · Krankenhausstr. 14 · 83413 Fridolfing, GERMANY

Tel.:+49 8684-908-0 · Fax: +49 8684-12-60

e-mail: info@otto-chemie.de · Internet: www.otto-chemie.com

