

OTTOSEAL®**A 225**

Sustainability data sheet

Inspections/authorisations



- French VOC-emission class A+

- Environmental Product Declarations (EPD)

Declaration number: EPD-DBC-20220148-IBF1-EN

Building certification system

DGNB – Deutsche Gesellschaft für Nachhaltiges Bauen (German Sustainable Building Council)

Version 2023

Criterion	ENV 1.2 Risks for the local environment	
Criteria matrix	line no. 13	
Product type	Adhesive for air tightness of facades inside and outside: e. g. PU, PU Hybrid, MS Polymer, SMP, acrylate, silicone.	
Requirements	Quality category 1 (low)	<0.1 % halogenated propellant and bonus points SVHC \leq 0.1 %
	Quality category 2	<0.1 % halogenated propellant and bonus points SVHC \leq 0.1 %
	Quality category 3	Chlorinated paraffins (SCCPs + MCCPs + LCCPs) <0.1 % and halogenated propellant <0.1 % and EMICODE® EC 1 ^{PLUS} or VOC < 1 % and bonus points SVHC \leq 0.1 %
	Quality category 4 (high)	Chlorinated paraffins (SCCPs + MCCPs + LCCPs) <0.1 % and halogenated propellant <0.1 % and EMICODE® EC 1 ^{PLUS} or VOC < 1 % and bonus points SVHC \leq 0.1 %
Classification	Fulfills quality category 4 requirements with chlorinated paraffins (SCCPs + MCCPs + LCCPs) <0.1 % and halogenated propellant <0.1 % and VOC < 1 % und SVHC \leq 0.1 %.	
Documentation documents	All the listed documents can be downloaded from www.otto-chemie.com	
	1. Technical data sheet	
	2. Safety data sheet	
	3. Sustainability data sheet	
	4. Test certificates	
	5. Environmental product declaration	

This information is based on our knowledge at the time of the compilation (see below). The current version can be viewed on our website at: www.otto-chemie.com. Furthermore, the information in the documents accompanying the products is applicable.