SENTINEL HOLDING
INSTITUT

SHI PRODUCT PASSPORT

Find products. Certify buildings.

SHI Product Passport No.:

1093-10-1017

OTTOCOLL® M 500

Product group: Adhesive - Assembly glue - Spezialkleber

OTTO CHEMIE
DICHTEN & KLEBEN

OTTO-CHEMIE
Krankenhausstraße 14
83413 Fridolfing

Product qualities:

- SHI Product Assessment 2024 ✓
- QNG Qualitätssiegel Nachhaltiges Gebäude ✓
- DGNB NEW CONSTRUCTION 2023 ✓
- DGNB NEW CONSTRUCTION 2018 ✓
- BNB-BN NEUBAU V2015 ✓
- EU taxonomy ✓
- BREEAM DE NEUBAU 2018 ✓

CERTIFIED SUSTAINABLE PRODUCT
SHI PRODUCT PASSPORT
SENTINEL HOLDING INSTITUT
www.sentinel-holding.eu

Köttner

Helmut Köttner
Scientific Director
Freiburg, 04 December 2025

Product:
OTTOCOLL® M 500

SHI Product Passport no.:
1093-10-1017

OTTO CHEMIE
DICHTEN & KLEBEN

Contents

SHI Product Assessment 2024	1
QNG - Qualitätssiegel Nachhaltiges Gebäude	2
DGNB New Construction 2023	3
DGNB New Construction 2018	4
BNB-BN Neubau V2015	5
EU taxonomy	6
BREEAM DE Neubau 2018	7
Product labels	8
Legal notices	9
Technical data sheet/attachments	10

The SHI Database is the first and only database for construction products whose comprehensive processes and data accuracy are regularly verified by the independent auditing company SGS-TÜV Saar

SGS

SGS TÜV SAAR

SENTINEL HOLDING
INSTITUT

Product:
OTTOCOLL® M 500

SHI Product Passport no.:
1093-10-1017

OTTO CHEMIE
DICHTEN & KLEBEN

SHI Product Assessment 2024

Since 2008, Sentinel Holding Institut GmbH (SHI) has been establishing a unique standard for products that support healthy indoor air. Experts carry out independent product assessments based on clear and transparent criteria. In addition, the independent testing company SGS regularly audits the processes and data accuracy.

Criteria	Product category	Harmful substance limit	Assessment
SHI Product Assessment	Sealants and adhesives	TVOC ≤ 300 µg/m^3 Formaldehyd ≤ 24 µg/m^3	Indoor Air Quality Certified
Valid untill: 30 September 2029			

Product:
OTTOCOLL® M 500

SHI Product Passport no.:
1093-10-1017

OTTO CHEMIE
DICHTEN & KLEBEN

QNG - Qualitätssiegel Nachhaltiges Gebäude

The Qualitätssiegel Nachhaltiges Gebäude (Quality Seal for Sustainable Buildings), developed by the German Federal Ministry for Housing, Urban Development and Building (BMWSB), defines requirements for the ecological, socio-cultural, and economic quality of buildings. The Sentinel Holding Institut evaluates construction products in accordance with QNG requirements for certification and awards the QNG ready label. Compliance with the QNG standard is a prerequisite for eligibility for the KfW funding programme. For certain product groups, the QNG currently has no specific requirements defined. Although classified as not assessment-relevant, these products remain suitable for QNG-certified projects.

Criteria	Pos. / product group	Considered substances	QNG assessment
3.1.3 Schadstoffvermeidung in Baumaterialien	4.2 On-site applied adhesives and sealants based on PU	VOC / Emissions / hazardous substances / chlorinated paraffins / polybrominated biphenyls (PBB) / polybrominated diphenyl ethers (PBDE) / SVHC	QNG ready
Verification: Sicherheitsdatenblatt 07.01.2025, Nachhaltigkeitsdatenblatt 20.03.2025			

Product:
OTTOCOLL® M 500

SHI Product Passport no.:
1093-10-1017

OTTO CHEMIE
DICHTEN & KLEBEN

DGNB New Construction 2023

The DGNB System (German Sustainable Building Council) assesses the sustainability of various types of buildings. It can be applied to both large-scale private and commercial projects as well as smaller residential buildings. The 2023 version sets high standards for ecological, economic, socio-cultural, and functional aspects throughout the entire life cycle of a building.

Criteria	No. / Relevant building components / construction materials / surfaces	Considered substances / aspects	Quality level
ENV 1.2 Local environmental impact, 03.05.2024 (3rd edition)	11 Indoor bonding and waterproofing.	VVOCs, VOCs, SVOC emissions and content of hazardous substances	Quality level 4
Verification: Sicherheitsdatenblatt 07.01.2025, EC1 Plus Zertifikat (10891/10.10.13) 01.10.2024			

Criteria	No. / Relevant building components / construction materials / surfaces	Considered substances / aspects	Quality level
ENV 1.2 Local environmental impact, 29.05.2025 (4th edition)	11 Indoor bonding and waterproofing	VVOCs, VOCs, SVOC emissions and content of hazardous substances	Quality level 4
Verification: Sicherheitsdatenblatt 07.01.2025, EC1 Plus Zertifikat (10891/10.10.13) 01.10.2024			

Product:
OTTOCOLL® M 500

SHI Product Passport no.:
1093-10-1017

OTTO CHEMIE
DICHTEN & KLEBEN

DGNB New Construction 2018

The DGNB System (German Sustainable Building Council) assesses the sustainability of various types of buildings. It can be applied to both large-scale private and commercial projects as well as smaller residential buildings.

Criteria	No. / Relevant building components / construction materials / surfaces	Considered substances / aspects	Quality level
ENV 1.2 Local environmental impact	12 Adhesive bonds on small joints under mechanical stress	Chlorinated paraffins, solvents, HC	Quality level 4
Verification: Nachhaltigkeitsdatenblatt 20.03.2025			

Product:
OTTOCOLL® M 500

SHI Product Passport no.:
1093-10-1017

OTTO CHEMIE
DICHTEN & KLEBEN

BNB-BN Neubau V2015

The Bewertungssystem Nachhaltiges Bauen (Assessment System for Sustainable Building) is a tool for evaluating public office and administrative buildings, educational facilities, laboratory buildings, and outdoor areas in Germany. The BNB was developed by the former Federal Ministry for the Environment, Nature Conservation, Building and Nuclear Safety (BMUB) and is now overseen by the Federal Ministry for Housing, Urban Development and Building (BMWSB).

Criteria	Pos. / product type	Considered substance group	Quality level
1.1.6 Risiken für die lokale Umwelt	8 Adhesives and sealants made of PU, SMP (silan-modified polymers), acrylic (including dispersion adhesives), or silicone	VOC / hazardous substances / biocides	Quality level 5
Verification: Sicherheitsdatenblatt 07.01.2025, EC1 Plus Zertifikat (10891/10.10.13) 01.10.2024, Nachhaltigkeitsdatenblatt 20.03.2025			

EU taxonomy

The EU Taxonomy classifies economic activities and products according to their environmental impact. At the product level, the EU regulation defines clear requirements for harmful substances, formaldehyde and volatile organic compounds (VOCs). The Sentinel Holding Institut GmbH labels qualified products that meet this standard.

Criteria	Product type	Considered substances	Assessment
DNSH - Pollution prevention and control		Substances according to Annex C	EU taxonomy compliant
Verification: Sicherheitsdatenblatt vom 07.01.2025 (Druckdatum)			

Product:
OTTOCOLL® M 500

SHI Product Passport no.:
1093-10-1017

OTTO CHEMIE
DICHTEN & KLEBEN

BREEAM DE Neubau 2018

BREEAM (Building Research Establishment Environmental Assessment Methodology) is a UK-based building assessment system that evaluates the sustainability of new constructions, refurbishments, and conversions. Developed by the Building Research Establishment (BRE), the system aims to assess and improve the environmental, economic, and social performance of buildings.

Criteria	Product category	Considered substances	Quality level
Hea 02 Indoor Air Quality	Interior adhesives and sealants (including flooring adhesives)	Emissions: Formaldehyde, TVOC, TSVOC, carcinogens	Exemplary quality
Verification: EMICODE EC1+-Zertifikat vom 01.10.2024			

Product:
OTTOCOLL® M 500

SHI Product Passport no.:
1093-10-1017

OTTO CHEMIE
DICHTEN & KLEBEN

Product labels

In the construction industry, high-quality materials are crucial for a building's indoor air quality and sustainability. Product labels and certificates offer guidance to meet these requirements. However, the evaluation criteria of these labels vary, and it is important to carefully assess them to ensure products align with the specific needs of a construction project.

The EMICODE® label, awarded by the German manufacturers' association "GEV – Gemeinschaft Emissionskontrollierte Verlegewerkstoffe, Klebstoffe und Bauprodukte e. V.", is primarily relevant for flooring installation materials. The EMICODE® EC1^{PLUS} label, as the premium class, sets significantly stricter emission limits than the other label variants.

Products bearing the Sentinel Holding Institute QNG-ready seal are suitable for projects aiming to achieve the "Qualitätssiegel Nachhaltiges Gebäude" (Quality Seal for Sustainable Buildings). QNG-ready products meet the requirements of QNG Appendix Document 3.1.3, "Avoidance of Harmful Substances in Building Materials." The KfW loan program Climate-Friendly New Construction with QNG may allow for additional funding.

This product is SHI Indoor Air Quality certified and recommended by Sentinel Holding Institut. Indoor-air-focused construction, renovation, and operation of buildings is made possible by transparent and verifiable criteria thanks to the Sentinel Holding concept.

Legal notices

(*) These criteria apply to the construction project as a whole. While individual products can positively contribute to the overall building score through proper planning, the evaluation is always conducted at the building level. The information was provided entirely by the manufacturer.

Find our criteria here: https://www.sentinel-holding.eu/de/Themenwelten/Pr%C3%BCfkriterien%20f%C3%BCr%20Produkte

The SHI Database is the first and only database for construction products whose comprehensive processes and data accuracy are regularly verified by the independent auditing company SGS-TÜV Saar

Publisher

Sentinel Holding Institut GmbH
Bötzinger Str. 38
79111 Freiburg im Breisgau
Tel.: +49 761 59048170
info@sentinel-holding.eu
www.sentinel-holding.eu

Technisches Datenblatt

OTTOCOLL® M 500

PREMIUM

Der extrem wasserbeständige Premium-Hybrid-Klebstoff

1K-Hybrid-Polymer STP-Klebstoff | Für Innen und Außen | M 500

Eigenschaften

- Extrem wasserbeständig - Für Klebungen mit hoher Wasserbelastung
- Sehr gute Haftung auf vielen Materialien - Ohne Vorbehandlung auf vielen Materialien verwendbar
- Natursteinverträglich - Verursacht keine Verfettung an Natursteinen
- Haftet auch auf feuchten Untergründen
- Elastisch - Gleicht Bewegungen aus
- Überstreichbar / Überlackierbar - bitte Anwendungshinweise im technischen Datenblatt beachten
- Silikonfrei
- Isocyanatfrei

Anwendungsgebiete

- Kleben von Stein, Naturstein und Keramik
- Kleben von lackiertem und emailliertem Glas
- Klebung von OTTOFLEX® Abdichtbahn / Abdicht- und Entkopplungsbahn im Überlappungsbereich sowie mit Zubehörteilen wie Dichtband, Abdichtungsecken und Dichtmanschetten (nach Anforderungen der ETAG 022 und geprüft nach AbP-Grundsätzen)
- Kleben von Spiegeln auf Keramik, Glas, Kunststoff, Edelstahl, Aluminium, Holz, Beton etc.
- Kleben von Fensterbänken, Fußbodenleisten, Zierleisten und Treppenstufen
- Kleben im Karosserie- und Fahrzeugbau, Waggon- und Containerbau, Metall- und Apparatebau, Schiffsbau
- Kleben im lebensmittelnahen Bereich
- Kleben und Montieren unterschiedlichster Materialien wie Holz, Holzwerkstoffe, Kunststoffe, Metalle und mineralische Untergründe

Normen und Prüfungen

- Entspricht den Anforderungen des Brandverhaltens nach EN 13501: Klasse E
- Unbedenklichkeitserklärung - geprüft für den Einsatz im lebensmittelnahen Bereich (ISEGA Forschungs- und Untersuchungs-Gesellschaft mbH, Aschaffenburg)
- EMICODE® EC 1 Plus - sehr emissionsarm
- Sentinal Holding Institut - Zertifiziert und ausgezeichnet mit dem SHI-Produktpass - Einstufung für DGNB, QNG, BNB, BREEAM und EU-Taxonomie
- Französische VOC-Emissionsklasse A+
- Deklaration in Baubook Österreich
- Geprüft im Verbund mit OTTOFLEX® Abdichtbahn / Abdicht- und Entkopplungsbahn zur Erteilung eines Allgemeinen

Hermann Otto GmbH
Krankenhausstr. 14 | 83413 Fridolfing, Deutschland
+49 8684 908-0 | @ info@otto-chemie.de
www.otto-chemie.de

Anwendungsberatung
+49 8684 908-4300
@ tae@otto-chemie.de

DICHTEN & KLEBEN

bauaufsichtlichen Prüfzeugnisses

Technische Daten

Hautbildungszeit bei 23 °C/50 % rLf [min]	~ 20
Aushärtung in 24 Std. bei 23 °C/50 % rLf [mm]	~ 2 - 3
Verarbeitungstemperatur von/bis [°C]	+ 5 / + 40
Viskosität bei 23 °C	pastös, standfest
Dichte bei 23 °C nach ISO 1183-1 [g/cm³]	~ 1,4
Klebstoffmenge [lfm/Kartusche]	~ 4 [1]
Shore-A-Härte nach ISO 868	~ 55
Zulässige Gesamtverformung [%]	10
Dehnspannungswert bei 100 % nach ISO 37, Typ 3 [N/mm²]	~ 1,8
Reißdehnung nach ISO 37, Typ 3 [%]	~ 230
Zugfestigkeit nach ISO 37, Typ 3 [N/mm²]	~ 3,5
Temperaturbeständigkeit von/bis [°C]	- 40 / + 90
Lagerstabilität bei 23 °C/50 % rLf für Kartusche/Beutel [Monate]	12 [2]
Lagerstabilität bei 23 °C/50 % rLf für Hobbock/Fass [Monate]	9 [2]

1) Verbrauch mit OTTO-Flachdüse (abhängig von der Klebstoffdicke)

2) ab Herstellung

Diese Werte sind nicht zur Erstellung von Spezifikationen bestimmt. Bitte wenden Sie sich vor der Erstellung von Spezifikationen an OTTO-CHEMIE.

Vorbehandlung

Die Haftflächen müssen gereinigt und jegliche Verunreinigungen, wie Trennmittel, Konservierungsmittel, Fett, Öl, Staub, Wasser, alte Kleb-/Dichtstoffe sowie andere die Haftung beeinträchtigende Stoffe entfernt werden. Reinigen von nicht-porösen Untergründen: Reinigung mit OTTO Cleaner T (keine Ablüftezeit erforderlich) und sauberem, flusenfreiem Tuch. Reinigen von porösen Untergründen: Oberflächen mechanisch, z.B. mit einer Stahlbürste oder einer Schleifscheibe, von losen Partikeln säubern.
Die Haftflächen müssen sauber, staub- und fettfrei sowie tragfähig sein.

Grundierungstabelle

Die Anforderungen an elastische Abdichtungen und Klebungen sind abhängig von den jeweiligen äußeren Einflüssen. Extreme Temperaturschwankungen, Dehn- und Scherkräfte, wiederholter Kontakt mit Wasser etc. stellen hohe Ansprüche an eine Haftverbindung. In solchen Fällen ist bei Empfehlungen (z.B. +/OTTO Primer 1216) die Verwendung des genannten Primers ratsam, um eine möglichst belastbare Verbindung zu erzielen.

Acrylglas/PMMA	+ / 1227
Acryl-Sanitär (z.B. Wannen)	1101 [1]
Aluminium blank	+
Aluminium eloxiert	+
Aluminium, pulverbeschichtet	T / 1216
Beton	1105 / 1215
Betonwerkstein	1216 [2]
Blei	T
Edelstahl	+ / 1216
Eisen	T
Epoxidharzbeschichtung	+ / 1216
Faserzement	1105 / 1215
Glas	+
Holz, lackiert (lösemittelhaltig)	+
Holz, lackiert (wässrige Systeme)	T
Holz, lasiert (lösemittelhaltig)	+
Holz, lasiert (wässrige Systeme)	+
Holz, unbehandelt	T / 1225
Keramik, glasiert	+

Keramik, unglasiert	+ / 1215 / 1216
Kunststoffprofile (Hart-PVC z.B. Vinnolit)	T / 1227
Kupfer	+ [3]
Lackiertes Glas	+ / 1216 / T
Melaminharzplatten	+ / 1216
Messing	+
Mineralwerkstoff	+ / 1216 / 1226
Naturstein (Marmor, Granit etc.)	1216 [2]
Polyester	+ / 1216
Polypropylen (PP)	-
Porenbeton	1105
Putz	1105 / 1215
PVC-hart	1217 / 1227
PVC-weich-Folien	1217
Weißblech	+ / 1216
Zink, verzinktes Eisen	1216 / 1227

1) Für die elastische Verfugung im Sanitärbereich nicht empfohlen.

2) Nur für Klebungen geeignet. Für Abdichtungen empfehlen wir OTTOSEAL® S 70.

3) Siehe "Besondere Hinweise"

+ = ohne Grundierung gute Haftung
- = nicht geeignet
T = Test/Vorversuch empfohlen

Besondere Hinweise

Vor dem Einsatz des Produktes hat der Anwender sicherzustellen, dass die Werkstoffe/Materialien in dem Kontaktbereich mit diesem und miteinander verträglich sind und sich nicht schädigen oder verändern (z. B. verfärben). Bei Werkstoffen/Materialien, die in der Folge im Bereich des Produktes verarbeitet werden, hat der Anwender im Vorfeld abzuklären, dass deren Inhaltsstoffe bzw. Ausdünstungen zu keiner Beeinträchtigung oder Veränderung (z. B. Verfärbung) des Produktes führen können. Gegebenenfalls hat der Anwender Rücksprache mit dem jeweiligen Hersteller der Werkstoffe/Materialien zu nehmen.
Farben, Lacke, Kunststoffe und andere Beschichtungsmaterialien müssen mit dem Kleb-/Dichtstoff verträglich sein.
Der Klebstoff ist erfahrungsgemäß mit einer Vielzahl von Glasbeschichtungen (z.B. Lacobel) verträglich und zeigt auch auf vielen eine gute Haftung ohne Primer. Die Prüfung sämtlicher Beschichtungen ist mit einem vertretbaren Aufwand nicht möglich und es gibt eine Vielzahl von Fällen, bei welchen die Gläser vom Glasbetrieb mit eigenen, für geeignet empfundenen und uns nicht bekannten Lacken beschichtet werden. Abgesehen davon werden wir über Änderungen und Modifikationen beschichteter Gläser und Lacke vom Glashersteller/ Beschichter nicht informiert, um diese hinsichtlich Klebstoffeignung prüfen zu können. In jedem Fall müssen die Verarbeitungshinweise des Glasherstellers beachtet werden. Sollten keine Erkenntnisse zur Verträglichkeit und Haftung auch im Hinblick auf die Haftung der Beschichtung zum Glas vorliegen, empfehlen wir Vorversuche.
Bei UV- belasteten Klebungen/ Abdichtungen von Glas empfehlen wir die Verwendung unserer hochwertigen Silikon-Kleb-/ Dichtstoffe wie OTTOSEAL® S 110 / S 120 (für Glasfalzabdichtungen), OTTOSEAL® S 10 (u.a. für Klebungen), OTTOSEAL® S 7 (für Wetterversiegelungen) oder OTTOCOLL® S 81 (für geklebtes Fenster).
Bei UV-belasteten Klebungen/ Abdichtungen von transparenten Kunststoffen wie z. B. Acrylglas empfehlen wir unseren Silikon-Dichtstoff OTTOSEAL® S 72.
Nicht für die Abdichtung/Klebung von Kupfer unter UV-/Temperatureinwirkung geeignet.
Die Farbtöne können durch Umwelteinflüsse beeinträchtigt werden (hohe Temperatur, Chemikalien, Dämpfe, UV-Strahlung). Dieses hat keinen Einfluss auf die Produkteigenschaften.

Anwendungshinweise

Um optimale Haftung und gute mechanische Eigenschaften zu erzielen, muss der Einschluss von Luft vermieden werden.
Die Zeit bis zur Aushärtung kann durch Feuchtigkeitszufuhr und höhere Temperaturen verkürzt werden.
Bei der flächigen Klebung von dampfdichten Substraten sollte der Klebstoff befeuchtet werden.
Unser Produkt kann überstrichen / überlackiert werden. Die Verträglichkeit zwischen Beschichtung und unserem Produkt muss **vor** der Anwendung durch den Anwender/Verarbeiter überprüft werden - ggf. unter Produktionsbedingungen. Unsere OTTO Anwendungstechnik unterstützt Sie gerne unverbindlich. Wird nach erfolgreicher Verträglichkeitsprüfung unser Produkt in Ausnahmefällen ganzflächig überstrichen, muss auch diese Beschichtung der elastischen Bewegung des Dichtstoffes folgen können. Anderenfalls können Rissbildungen im Anstrich oder optische Beeinträchtigungen entstehen.
Farben, Lacke, Kunststoffe und andere Beschichtungsmaterialien müssen mit dem Kleb-/Dichtstoff verträglich sein. Materialien mit alkalischen Inhaltsstoffen können Wechselwirkungen in Form von Verfärbungen verursachen.
Reinmineralische Anstriche (z.B. auf Basis Kaliwasserglas oder Kalk) sind aufgrund der Sprödigkeit des Anstrichs zum ganzflächigen Überstreichen nicht geeignet.
Eine Überarbeitung mit Beschichtungsstoffen kann je nach klimatischen Bedingungen und Anstrichart ab etwa 1 Stunde erfolgen.

In Kontakt mit oxidativ härtenden Anstrichen (z.B. Alkydharz-Lacke) können Trocknung und Aushärtung verzögert oder verhindert werden.
Wir empfehlen Vorversuche.
Beschichtungen sowie deren Ausdünstungen können zu Verfärbungen des Kleb-/ Dichtstoffes führen.
Verfärbungen von Beschichtungen durch Wechselwirkungen mit dem Kleb-/ Dichtstoff sind nicht ausgeschlossen.
Wegen der Vielzahl möglicher Einflüsse bei der Verarbeitung und der Anwendung ist vom Verarbeiter stets eine Probeverarbeitung und -anwendung vorzunehmen.
Das konkrete Aufbrauchdatum ist dem Gebindeaufdruck zu entnehmen und zu beachten.
Wir empfehlen, unsere Produkte in den ungeöffneten Originalgebinden trocken (< 60 % rLF) im Temperaturbereich von + 15° C bis + 25° C zu lagern. Werden die Produkte über längere Zeiträume (mehrere Wochen) bei höherer Temperatur/ Luftfeuchtigkeit gelagert und / oder transportiert, kann eine Verringerung der Haltbarkeit bzw. eine Veränderung der Materialeigenschaften nicht ausgeschlossen werden.
Die nachfolgend beschriebenen Hinweise gelten sowohl für die Klebung von Glasspiegeln als auch für die Klebung von lackiertem Glas.
Verarbeitung als Spiegel-Klebstoff:

Es dürfen nur Spiegel geklebt werden, deren Reflexions- und Schutzschicht der DIN EN 1036 entsprechen. Im Zweifelsfall bitte unbedingt dazu Informationen des Spiegelherstellers einholen.
Mit dem Spiegel Saint Gobain MIRALITE ® PURE kann unter bestimmten Objektbedingungen eine Unverträglichkeit nicht ausgeschlossen werden.
Für die Klebung des Saint Gobain MIRALITE ® PURE empfehlen wir unsere Silikon-Spiegel-Klebstoffe OTTOCOLL® S 16 bzw. OTTOCOLL® S 610.
Bei der Auswahl des lackierten Glases gilt es im Vorfeld die ortsübliche Belichtung, sowie die Schichtstärke und Lichtdurchlässigkeit des Lacks zu berücksichtigen. Bei manchen nicht deckenden Beschichtungen ist es möglich, dass sogar transparente Klebstoffe auf der Vorderseite erkennbar sind.
Mineralische Untergründe, wie z. B. Beton, Putz, Mauerwerk, Gipskarton, Porenbeton sowie unbehandeltes Holz müssen unbedingt mit OTTO Primer 1105 grundiert werden. Die Verwendung dieses Primers dient dabei nicht nur der Haftverbesserung, sondern auch der unbedingt notwendigen Absperrung der Alkalität. Nicht abgesperrte Alkalität kann in Kombination mit Feuchtigkeit u. U. zur Beschädigung der Spiegelrückseite führen.
Den Klebstoff bei der Klebung niemals punktförmig, sondern in senkrechten Streifen auftragen. Die Länge eines Klebestreifens soll 200 mm nicht übersteigen. Je m² Glas / Spiegel sind mindestens 3 Klebestreifen so aufzutragen, dass nach Anpressen des Glases / Spiegels die Streifenbreite 10 mm nicht überschreitet und der Abstand zwischen den Klebestreifen mindestens 200 mm beträgt, damit die für die Vulkanisation erforderliche Luftzirkulation möglich ist. Für eine optimale Tragfähigkeit ist eine Haftfläche von mindestens 10 cm²/kg Glas / Spiegel erforderlich.
Zur Vermeidung der Einsperrung des Vernetzer-Spaltprodukts ist ein Mindestabstand zwischen Glas / Spiegel und Untergrund von 1,6 mm zwingend einzuhalten. Dieser lässt sich auf zweckmäßigste Weise durch das Aufkleben von Abstandshaltern erreichen. Der hier vorgeschriebene Mindestabstand dient dem Abtransport des Vernetzer-Spaltprodukts.
Die empfohlene Klebschichtstärke beträgt 2 - 4 mm.
Die für die Klebung erforderlichen Festigkeitswerte werden frühestens nach 48 Stunden erreicht (23°C, ca. 50% rLf). Bis dahin ist eine Vorfixierung notwendig. Diese kann mit wieder entfernbaren, mechanischen Hilfen, wie z. B. Klötzen, Keilen oder einseitig wirkenden Klebebändern von vorne (Glasseite) oder mit doppelseitigen Klebebändern, z. B. OTTOTAPE Fixierband (aufgedoppelt verlegt), von hinten (Rückseite) erfolgen.
Zur äußeren Versiegelung des Glases / Spiegels in Verbindung mit Natursteinen empfehlen wir OTTOSEAL® S 70 und OTTOSEAL® S 80, in Verbindung mit anderen Materialien wie Keramik, Metall, Glas etc. empfehlen wir OTTOSEAL® S 120 und OTTOSEAL® S 125.
Zu beachten ist, dass die Versiegelung erst nach vollständiger Aushärtung des Klebstoffes und dem Entweichen der Spaltprodukte erfolgen darf. Diese Zeit beträgt etwa 7 Tage. Bei beschichteten Gläsern ohne Glasrücken sollten nur die vertikalen Glasränder versiegelt werden, um eine Beschädigung der Glasbeschichtung durch Kondenswasserbildung zu vermeiden. Bitte beachten Sie die nachfolgende Zeichnung.



Bei der Klebung an Decken und bei der Klebung an Wände (wenn die Oberkante des Glases 4 m über der Bodenfläche liegt), muss das Glas zusätzlich mechanisch z. B. durch Schrauben bzw. Einlegen in Rahmen gesichert werden.

Lieferform

	310 ml Kartusche
grau	M500-04-C02
schwarz	M500-04-C04
weiß	M500-04-C01
Stück pro Verpackungseinheit	**20**
Stück pro Palette	**1200**

Aus darstellungstechnischen Gründen können die abgebildeten Farben von den Originalfarben der Produkte abweichen.

Sicherheitshinweise

Bitte das Sicherheitsdatenblatt beachten.
Nach erfolgter Aushärtung ist das Produkt geruchlos.

Entsorgung

Hinweise zur Entsorgung siehe Sicherheitsdatenblatt.

Markenhinweise

EMICODE® ist eine eingetragene Marke der GEV e. V. (Düsseldorf)

Mängelhaftung

Die vorstehenden Informationen und unsere anwendungstechnische Beratung in Wort, Schrift und durch Versuche erfolgen nach bestem Wissen, gelten jedoch nur als unverbindliche Hinweise, auch in Bezug auf etwaige Schutzrechte Dritter. Die Angaben in dieser Druckschrift befreien den Verarbeiter nicht von einer eigenen Prüfung unserer Produkte im Hinblick auf ihre Eignung für die beabsichtigten Verfahren und Zwecke. Anwendung, Verwendung und Verarbeitung unserer Produkte und der auf Grund unserer anwendungstechnischen Beratung hergestellten Produkte erfolgen außerhalb unserer Kontrollmöglichkeiten und liegen daher ausschließlich in der Verantwortung des Verarbeiters. Unterliegt die Anwendung, für die unsere Produkte herangezogen werden, einer behördlichen Genehmigungspflicht, so ist der Anwender für die Erlangung dieser Genehmigungen verantwortlich. Wir behalten uns das Recht zur Anpassung des Produktes an den technischen Fortschritt und an neue Entwicklungen vor. Im Übrigen verweisen wir auf unsere Allgemeinen Geschäftsbedingungen, insbesondere auch bezüglich einer etwaigen Mängelhaftung. Sie finden unsere AGB unter www.otto-chemie.de.

Sicherheitsdatenblatt

gemäß Verordnung (EG) Nr. 1907/2006, Artikel 31

Druckdatum: 07.01.2025 Version: 7 (ersetzt Version 6) überarbeitet am: 07.01.2025

*

ABSCHNITT 1: Bezeichnung des Stoffs beziehungsweise des Gemischs und des Unternehmens

· **1.1 Produktidentifikator**

· **Handelsname: OTTOCOLL M 500**
· **1.2 Relevante identifizierte Verwendungen des Stoffs oder Gemischs und Verwendungen, von denen abgeraten wird**
· **Verwendung des Stoffes / des Gemisches** Dicht- Klebstoff
· **Verwendungen, von denen abgeraten wird** Angaben im technischen Datenblatt beachten

· **1.3 Einzelheiten zum Lieferanten, der das Sicherheitsdatenblatt bereitstellt**
· **Hersteller/Lieferant:**
Hermann Otto GmbH
Krankenhausstraße 14
D-83413 Fridolfing
Tel.: 0049/(0)8684/908-0
Fax.: 0049/(0)8684/908-1840

· **Auskunftgebender Bereich:**
Tel.: 0049- (0)8684- 908- 2363 (-4300)
E-Mail: alois.parzinger@otto-chemie.de
· **1.4 Notrufnummer:**
Tel: 0049 (0)89 220 61012 (Carechem 24)
Giftnotruf München Tel.: 0049- (0)89- 192 40 (24 h von Mo.-So.)
für Österreich: 0043-1-40 6-43 43 (Vergiftungsinformationszentrale der Gesundheit Österreich GmbH- 24h täglich)

ABSCHNITT 2: Mögliche Gefahren

· **2.1 Einstufung des Stoffs oder Gemischs**
· **Einstufung gemäß Verordnung (EG) Nr. 1272/2008**
Das Produkt ist gemäß CLP-Verordnung nicht eingestuft.

· **2.2 Kennzeichnungselemente**
· **Kennzeichnung gemäß Verordnung (EG) Nr. 1272/2008** entfällt
· **Gefahrenpiktogramme** entfällt
· **Signalwort** entfällt
· **Gefahrenhinweise** entfällt
· **Zusätzliche Angaben:**
Während der Verarbeitung und Aushärtung für gute Belüftung sorgen.
EUH208 Enthält Trimethoxyvinylsilan, 3-(2-Aminoethylamino)-propyltrimethoxysilan. Kann allergische Reaktionen hervorrufen.
EUH210 Sicherheitsdatenblatt auf Anfrage erhältlich.
· **2.3 Sonstige Gefahren**
Während der Verarbeitung und Aushärtung des Materials werden chemische Stoffe in die Luft freigesetzt (siehe Punkt 11). Deshalb für gute Raumbelüftung und bei Bedarf für Absaugung sorgen.
· **Ergebnisse der PBT- und vPvB-Beurteilung**
· **PBT:** Nicht anwendbar.
· **vPvB:** Nicht anwendbar.
· **Feststellung endokrinschädlicher Eigenschaften**
Dieses Produkt enthält keine Bestandteile, die gemäß REACH Artikel 57(f) oder der delegierten Verordnung (EU) 2017/2100 der Kommission oder der delegierten Verordnung (EU) 2018/605 der Kommission in Mengen von 0,1 % oder mehr endokrinschädliche Eigenschaften aufweisen.

ABSCHNITT 3: Zusammensetzung/Angaben zu Bestandteilen

· **3.2 Gemische**
· **Beschreibung:** Kleb- und Dichtstoff auf Basis Hybrid-Polymer STP

(Fortsetzung auf Seite 2)

Sicherheitsdatenblatt
gemäß Verordnung (EG) Nr. 1907/2006, Artikel 31

Druckdatum: 07.01.2025 Version: 7 (ersetzt Version 6) überarbeitet am: 07.01.2025

Handelsname: OTTOCOLL M 500

(Fortsetzung von Seite 1)

· **Gefährliche Inhaltsstoffe:**

CAS: 2768-02-7 EINECS: 220-449-8 Reg.nr.: 01-2119513215-52-xxxx	Trimethoxyvinylsilan Flam. Liq. 3, H226; Acute Tox. 4, H332; Skin Sens. 1B, H317	<2,5%
CAS: 1760-24-3 EINECS: 217-164-6 Reg.nr.: 01-2119970215-39-xxxx	3-(2-Aminoethylamino)-propyltrimethoxysilan Eye Dam. 1, H318; Aquatic Chronic 2, H411; Acute Tox. 4, H332; Skin Sens. 1, H317	<1%

· **zusätzl. Hinweise:**
Der Wortlaut der angeführten Gefahrenhinweise ist dem Abschnitt 16 zu entnehmen.
Partikelförmige Rohstoffe mit Inhalationsrisiko sind untrennbar in der Produktmasse gebunden und lösen daher keine Einstufung als inhalationsgefährdend aus. Aufgrund der physikalischen Eigenschaften des Produkts ist eine inhalative Exposition durch Partikeln nicht möglich.

ABSCHNITT 4: Erste-Hilfe-Maßnahmen

· **4.1 Beschreibung der Erste-Hilfe-Maßnahmen**
· **nach Einatmen:**
Frischluftzufuhr, gegebenenfalls Atemspende, Wärme. Bei anhaltenden Beschwerden Arzt konsultieren.
· **nach Hautkontakt:**
Sofort mit Wasser und Seife abwaschen und gut nachspülen.
Bei andauernder Hautreizung Arzt aufsuchen.
· **nach Augenkontakt:**
Augen bei geöffnetem Lidspalt mehrere Minuten unter fließendem Wasser abspülen und Arzt konsultieren. Auf Kontaklinsen prüfen und falls vorhanden entfernen.
· **nach Verschlucken:**
Kein Erbrechen herbeiführen. Sofort Arzthilfe zuziehen. Verpackung oder Etikett vorzeigen.
· **4.2 Wichtigste akute und verzögert auftretende Symptome und Wirkungen**
Keine weiteren relevanten Informationen verfügbar.
· **4.3 Hinweise auf ärztliche Soforthilfe oder Spezialbehandlung**
Keine weiteren relevanten Informationen verfügbar.

ABSCHNITT 5: Maßnahmen zur Brandbekämpfung

· **5.1 Löschmittel**
· **Geeignete Löschmittel:**
CO2, Löschpulver oder Wassersprühstrahl. Größeren Brand mit Wassersprühstrahl oder alkoholbeständigem Schaum bekämpfen.
· **5.2 Besondere vom Stoff oder Gemisch ausgehende Gefahren**
Beim Erhitzen oder im Brandfalle Bildung giftiger Gase möglich.
· **5.3 Hinweise für die Brandbekämpfung**
· **Besondere Schutzausrüstung:**
Atemschutzgerät anlegen.
Explosions- und Brandgase nicht einatmen.

ABSCHNITT 6: Maßnahmen bei unbeabsichtigter Freisetzung

· **6.1 Personenbezogene Vorsichtsmaßnahmen, Schutzausrüstungen und in Notfällen anzuwendende Verfahren**
Für ausreichende Lüftung sorgen.
· **6.2 Umweltschutzmaßnahmen:**
Nicht in die Kanalisation/Oberflächenwasser/Grundwasser gelangen lassen.
· **6.3 Methoden und Material für Rückhaltung und Reinigung:**
Kontaminiertes Material als Abfall nach Abschnitt 13 entsorgen.

(Fortsetzung auf Seite 3)

Sicherheitsdatenblatt
gemäß Verordnung (EG) Nr. 1907/2006, Artikel 31

Druckdatum: 07.01.2025 Version: 7 (ersetzt Version 6) überarbeitet am: 07.01.2025

Handelsname: OTTOCOLL M 500

(Fortsetzung von Seite 2)

· **6.4 Verweis auf andere Abschnitte**
Informationen zur persönlichen Schutzausrüstung siehe Abschnitt 8.

ABSCHNITT 7: Handhabung und Lagerung

· **7.1 Schutzmaßnahmen zur sicheren Handhabung**
Für gute Belüftung/Absaugung am Arbeitsplatz sorgen.
Siehe Punkt 8: Persönliche Schutzausrüstung.

· **7.2 Bedingungen zur sicheren Lagerung unter Berücksichtigung von Unverträglichkeiten**
· **Lagerung:**
· **Anforderung an Lagerräume und Behälter:** Eindringen in den Boden sicher verhindern.
· **Zusammenlagerungshinweise:** Getrennt von Lebensmitteln lagern.
· **Weitere Angaben zu den Lagerbedingungen:**
In gut verschlossenen Gebinden kühl und trocken lagern.
Vor Hitze und direkter Sonnenbestrahlung schützen.
· **Lagerklasse LGK gemäß TRGS 510:** 12
· **GISCode** RS10 Verlegewerkstoffe, methoxysilanhaltig, kennzeichnungsfrei (keine Grundierungen)
· **7.3 Spezifische Endanwendungen** Keine weiteren relevanten Informationen verfügbar.

ABSCHNITT 8: Begrenzung und Überwachung der Exposition/Persönliche Schutzausrüstungen

· **8.1 Zu überwachende Parameter**
· **Bestandteile mit arbeitsplatzbezogenen, zu überwachenden Grenzwerten:**
· **CAS-Nr. Bezeichnung des Stoffes % Art Wert Einheit**
· **Zusätzliche Expositionsgrenzwerte bei möglichen Verarbeitungsgefahren:**

67-56-1 Methanol

AGW Langzeitwert: 130 mg/m³, 100 ml/m³
2(II);DFG, EU, H, Y
· **Zusätzliche Hinweise:** Als Grundlage dienten die bei der Erstellung gültigen Listen.

· **8.2 Begrenzung und Überwachung der Exposition**
· **Geeignete technische Steuerungseinrichtungen** Keine weiteren Angaben, siehe Abschnitt 7.
· **Individuelle Schutzmaßnahmen, zum Beispiel persönliche Schutzausrüstung**
· **Allgemeine Schutz- und Hygienemaßnahmen:**
Die üblichen Vorsichtsmaßnahmen beim Umgang mit Chemikalien sind zu beachten.
Vor den Pausen und bei Arbeitsende Hände waschen.
Berührung mit den Augen und der Haut vermeiden.
· **Atemschutz**
Das Produkt nicht bei ungenügender Lüftung verwenden oder Schutzmaske mit entsprechendem Gasfilter (Typ ABEK nach EN 14387) tragen.
· **Handschutz** Schutzhandschuhe.
· **Handschuhmaterial**
Die Schutzhandschuhe sollten in jedem Fall auf ihre Arbeitsplatz- spezifische Eignung (z.B. Feinfühligkeit, mechanische Beständigkeit, Produktverträglichkeit, Permeationszeit)geprüft werden. Anweisungen und Informationen der Handschuhhersteller zur Anwendung, Lagerung, Pflege und zum Austausch der Handschuhe befolgen. Die Schutzhandschuhe sollten bei Beschädigung oder ersten Abnutzungserscheinungen sofort ersetzt werden. Die Auswahl eines geeigneten Handschuhs ist nicht nur vom Material, sondern auch von weiteren Qualitätsmerkmalen abhängig und von Hersteller zu Hersteller unterschiedlich. Bezugsnummer EN 374.
Empfohlenes Handschuhmaterial: z.B. Nitrilkautschuk
Empfohlene Materialstärke: > 0,4 mm
· **Durchdringungszeit des Handschuhmaterials** Durchbruchzeit: 10 - 30 min
· **Augen-/Gesichtsschutz** Schutzbrille.

(Fortsetzung auf Seite 4)

Sicherheitsdatenblatt
gemäß Verordnung (EG) Nr. 1907/2006, Artikel 31

Druckdatum: 07.01.2025 Version: 7 (ersetzt Version 6) überarbeitet am: 07.01.2025

Handelsname: OTTOCOLL M 500

(Fortsetzung von Seite 3)

· **Körperschutz:** Arbeitsschutzkleidung.

ABSCHNITT 9: Physikalische und chemische Eigenschaften

· **9.1 Angaben zu den grundlegenden physikalischen und chemischen Eigenschaften**

· **Allgemeine Angaben**	
· **Aggregatzustand**	flüssig
· **Farbe**	gemäß Produktbezeichnung
· **Geruch:**	charakteristisch
· **Schmelzpunkt/Gefrierpunkt:**	nicht anwendbar
· **Siedepunkt oder Siedebeginn und Siedebereich**	nicht anwendbar
· **Untere und obere Explosionsgrenze**	
· **untere:**	entfällt
obere:	entfällt
· **Flammpunkt:**	Nicht anwendbar (Testmethoden für Flammpunkt nicht gültig für pastöse Stoffe und hochviskose Flüssigkeiten)
· **Zersetzungstemperatur:**	Nicht bestimmt.
· **pH-Wert:**	Nicht anwendbar.
· **Viskosität:**	Nicht bestimmt.
· **Löslichkeit**	
· **Wasser:**	nicht bzw. wenig mischbar
· **Verteilungskoeffizient n-Oktanol/Wasser (log-Wert)**	Nicht bestimmt.
· **Dampfdruck:**	Nicht bestimmt.
· **Dichte und/oder relative Dichte**	
· **Dichte:**	siehe Technisches Datenblatt
· **Relative Dichte**	Nicht bestimmt.
· **Dampfdichte**	Nicht bestimmt.
· **Relative Dampfdichte**	Nicht bestimmt.
· **Partikeleigenschaften**	Nicht bestimmt

· **9.2 Sonstige Angaben**

· **Form:**	pastös
· **Zündtemperatur:**	Das Produkt ist nicht selbstentzündlich.
· **Explosive Eigenschaften:**	Das Produkt ist nicht explosionsgefährlich, jedoch ist die Bildung explosionsgefährlicher Dampf-/Luftgemische möglich.
· **Angaben über physikalische Gefahrenklassen**	
· **Aerosole**	entfällt
· **Entzündbare Flüssigkeiten**	entfällt

ABSCHNITT 10: Stabilität und Reaktivität

· **10.1 Reaktivität** Keine weiteren relevanten Informationen verfügbar.

· **10.2 Chemische Stabilität**

· **Thermische Zersetzung / zu vermeidende Bedingungen:**
Keine Zersetzung bei bestimmungsgemäßer Verwendung.
Starke Erhitzung vermeiden.

· **10.3 Möglichkeit gefährlicher Reaktionen**
Durch Kontakt mit Luftfeuchtigkeit, Wasser und protische Mittel entsteht Methanol.

· **10.4 Zu vermeidende Bedingungen** Keine weiteren relevanten Informationen verfügbar.

· **10.5 Unverträgliche Materialien:** Keine weiteren relevanten Informationen verfügbar.

(Fortsetzung auf Seite 5)

Sicherheitsdatenblatt
gemäß Verordnung (EG) Nr. 1907/2006, Artikel 31

Druckdatum: 07.01.2025 Version: 7 (ersetzt Version 6) überarbeitet am: 07.01.2025

Handelsname: OTTOCOLL M 500

(Fortsetzung von Seite 4)

· **10.6 Gefährliche Zersetzungsprodukte:** siehe Punkt 5.2

ABSCHNITT 11: Toxikologische Angaben

· **11.1 Angaben zu den Gefahrenklassen im Sinne der Verordnung (EG) Nr. 1272/2008**
· **akute Toxizität:** Aufgrund der verfügbaren Daten sind die Einstufungskriterien nicht erfüllt.
· **Einstufungsrelevante LD/LC50-Werte:**

2768-02-7 Trimethoxyvinylsilan

Oral	LD50	7.100 mg/kg (rat)
Dermal	LD50	3.200 mg/kg (rab)
Inhalativ	LC50/4 h	16,8 mg/l (rat)

1760-24-3 3-(2-Aminoethylamino)-propyltrimethoxysilan

Oral	LD50	2.995 mg/kg (rat)
Dermal	LD50	>2.000 mg/kg (rab)

· **Bei Hautkontakt:** Aufgrund der verfügbaren Daten sind die Einstufungskriterien nicht erfüllt.
· **Bei Augenkontakt:** Aufgrund der verfügbaren Daten sind die Einstufungskriterien nicht erfüllt.
· **Sensibilisierung der Atemwege/Haut**
dermal: nicht sensibilisierend
Quelle: Analogieschluss
Prüfbericht gem. OECD Guideline 406 (Guinea Pigs)
Aufgrund der verfügbaren Daten sind die Einstufungskriterien nicht erfüllt.
· **Keimzellmutagenität** Aufgrund der verfügbaren Daten sind die Einstufungskriterien nicht erfüllt.
· **Karzinogenität** Aufgrund der verfügbaren Daten sind die Einstufungskriterien nicht erfüllt.
· **Reproduktionstoxizität** Aufgrund der verfügbaren Daten sind die Einstufungskriterien nicht erfüllt.
· **Spezifische Zielorgan-Toxizität bei einmaliger Exposition**
Aufgrund der verfügbaren Daten sind die Einstufungskriterien nicht erfüllt.
· **Spezifische Zielorgan-Toxizität bei wiederholter Exposition**
Aufgrund der verfügbaren Daten sind die Einstufungskriterien nicht erfüllt.
· **Aspirationsgefahr** Aufgrund der verfügbaren Daten sind die Einstufungskriterien nicht erfüllt.
· **Sonstige Angaben (zur experimentellen Toxikologie):**
Produkt hydrolysiert unter Bildung von Methanol (CAS-Nr. 67-56-1). Methanol ist giftig beim Einatmen, Verschlucken und Berührung mit der Haut. Methanol schädigt die Organe. Methanol ist leichtentzündlich. Beim Einatmen von Aerosolnebeln können Gesundheitsschäden auftreten.
· **11.2 Angaben über sonstige Gefahren**
· **Endokrinschädliche Eigenschaften**

Keiner der Inhaltsstoffe ist enthalten.

*

ABSCHNITT 12: Umweltbezogene Angaben

· **12.1 Toxizität** Keine weiteren relevanten Informationen verfügbar
· **12.2 Persistenz und Abbaubarkeit** Keine weiteren relevanten Informationen verfügbar.
· **Sonstige Hinweise:** Produkt biologisch nicht abbaubar.
· **12.3 Bioakkumulationspotenzial** Keine weiteren relevanten Informationen verfügbar.
· **12.4 Mobilität im Boden** Keine weiteren relevanten Informationen verfügbar.
· **12.5 Ergebnisse der PBT- und vPvB-Beurteilung**
· **PBT:** Nicht anwendbar.
· **vPvB:** Nicht anwendbar.
· **12.6 Endokrinschädliche Eigenschaften**
Dieses Produkt enthält keine Bestandteile, die gemäß REACH Artikel 57(f) oder der delegierten Verordnung (EU) 2017/2100 der Kommission oder der delegierten Verordnung (EU) 2018/605 der Kommission in Mengen von 0,1 % oder mehr endokrinschädliche Eigenschaften aufweisen.
· **12.7 Andere schädliche Wirkungen**
· **Weitere ökologische Hinweise:**
· **Allgemeine Hinweise:**
Wassergefährdungsklasse 1 : schwach wassergefährdend

(Fortsetzung auf Seite 6)

Sicherheitsdatenblatt
gemäß Verordnung (EG) Nr. 1907/2006, Artikel 31

Druckdatum: 07.01.2025 Version: 7 (ersetzt Version 6) überarbeitet am: 07.01.2025

Handelsname: OTTOCOLL M 500

(Fortsetzung von Seite 5)

Nicht in das Grundwasser, in Gewässer oder in die Kanalisation gelangen lassen.

ABSCHNITT 13: Hinweise zur Entsorgung

· **13.1 Verfahren der Abfallbehandlung**
· **Empfehlung:**
Örtliche behördliche Vorschriften beachten.
Material kann nach der Aushärtung zusammen mit dem Hausmüll oder den Gewerbeabfällen entsorgt werden.
Unverbrauchtes Material (flüssig, pastös) ist als Sonderabfall zu entsorgen.

· **Verpackungen:**
· **Empfehlung:**
Restentleerte Verpackungen können einer Wiederverwertung/Recycling zugeführt werden.
Nicht reinigungsfähige Verpackungen bzw. Verpackungen mit Restinhalten sind wie der Stoff zu entsorgen.

ABSCHNITT 14: Angaben zum Transport

· **14.1 UN-Nummer oder ID-Nummer**
· **ADR, ADN, IMDG, IATA** *entfällt*
· **14.2 Ordnungsgemäße UN-Versandbezeichnung**
· **ADR, ADN, IMDG, IATA** *entfällt*
· **14.3 Transportgefahrenklassen**

· **ADR, ADN, IMDG, IATA**
· **Klasse** *entfällt*
· **14.4 Verpackungsgruppe**
· **ADR, IMDG, IATA** *entfällt*
· **14.5 Umweltgefahren:**
· **Marine pollutant:** *Nein*
· **14.6 Besondere Vorsichtsmaßnahmen für den Verwender** *Nicht anwendbar.*
· **14.7 Massengutbeförderung auf dem Seeweg gemäß IMO-Instrumenten** *Nicht anwendbar.*

· **Transport/weitere Angaben:** *Kein Gefahrgut nach obigen Verordnungen*
· **UN "Model Regulation":** *entfällt*

*

ABSCHNITT 15: Rechtsvorschriften

· **15.1 Vorschriften zu Sicherheit, Gesundheits- und Umweltschutz/spezifische Rechtsvorschriften für den Stoff oder das Gemisch**

· **Richtlinie 2012/18/EU**
· **Namentlich aufgeführte gefährliche Stoffe - ANHANG I** *Keiner der Inhaltsstoffe ist enthalten.*
· **Richtlinie 2011/65/EU zur Beschränkung der Verwendung bestimmter gefährlicher Stoffe in Elektro- und Elektronikgeräten – Anhang II**

Keiner der Inhaltsstoffe ist enthalten.
· **VERORDNUNG (EU) 2019/1148**
· **Anhang I - BESCHRÄNKTE AUSGANGSSTOFFE FÜR EXPLOSIVSTOFFE (Oberer Konzentrationsgrenzwert für eine Genehmigung nach Artikel 5 Absatz 3)**

Keiner der Inhaltsstoffe ist enthalten.
· **Anhang II - MELDEPFLICHTIGE AUSGANGSSTOFFE FÜR EXPLOSIVSTOFFE**

Keiner der Inhaltsstoffe ist enthalten.

(Fortsetzung auf Seite 7)

Sicherheitsdatenblatt
gemäß Verordnung (EG) Nr. 1907/2006, Artikel 31

Druckdatum: 07.01.2025 Version: 7 (ersetzt Version 6) überarbeitet am: 07.01.2025

Handelsname: OTTOCOLL M 500

(Fortsetzung von Seite 6)

· **Verordnung (EG) Nr. 273/2004 betreffend Drogenausgangsstoffe**

Keiner der Inhaltsstoffe ist enthalten.

· **Verordnung (EG) Nr. 111/2005 zur Festlegung von Vorschriften für die Überwachung des Handels mit Drogenaustauschstoffen zwischen der Gemeinschaft und Drittländern**

Keiner der Inhaltsstoffe ist enthalten.

· **Nationale Vorschriften:**

· **Wassergefährdungsklasse:** WGK 1 (Selbsteinstufung VwVwS): schwach wassergefährdend.

· **Angaben zum internationalen Registrierungsstatus:**

ENCS - Japan gelistet bzw. konform
AICS - Australia gelistet bzw. konform
REACH - Europe gelistet bzw. konform
NZIoC - New Zealand nicht gelistet
ECL - Korea nicht gelistet
PICCS - Philippines nicht gelistet
TCSI- Taiwan nicht gelistet
TSCA - USA gelistet bzw. konform
DSL - Canada gelistet bzw. konform
IECSC - China nicht gelistet

· **15.2 Stoffsicherheitsbeurteilung:** Eine Stoffsicherheitsbeurteilung wurde nicht durchgeführt.

ABSCHNITT 16: Sonstige Angaben

Die Angaben stützen sich auf den heutigen Stand unserer Kenntnisse, sie stellen jedoch keine Zusicherung von Produkteigenschaften dar und begründen kein vertragliches Rechtsverhältnis. Dieses Sicherheitsdatenblatt entspricht der Verordnung (EG) Nr. 1907/2006, Artikel 31 in der Fassung der Verordnung (EU) 2020/878.

· **Relevante Sätze**

H226 Flüssigkeit und Dampf entzündbar.
H317 Kann allergische Hautreaktionen verursachen.
H318 Verursacht schwere Augenschäden.
H332 Gesundheitsschädlich bei Einatmen.
H411 Giftig für Wasserorganismen, mit langfristiger Wirkung.

· **Datenblatt ausstellender Bereich:** Tel.: 0049- (0)8684- 908- 2363
· **Ansprechpartner:** Tel.: 0049- (0)8684- 908- 2363 (-4300)
· **Versionsnummer der Vorgängerversion:** 6
· **Abkürzungen und Akronyme:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
ICAO: International Civil Aviation Organisation
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flam. Liq. 3: Entzündbare Flüssigkeiten – Kategorie 3
Acute Tox. 4: Akute Toxizität – Kategorie 4
Eye Dam. 1: Schwere Augenschädigung/Augenreizung – Kategorie 1
Skin Sens. 1: Sensibilisierung der Haut – Kategorie 1
Skin Sens. 1B: Sensibilisierung der Haut – Kategorie 1B
Aquatic Chronic 2: Gewässergefährdend - langfristig gewässergefährdend – Kategorie 2

· *** Daten gegenüber der Vorversion geändert**

Konformitätserklärung für Produkte mit Muster-EPDs

Der Industrieverband Deutsche Bauchemie e.V., in dem Hermann Otto GmbH Mitglied ist, hat sogenannte Muster-Umweltproduktdeklarationen (Muster-EPD) entwickelt und durch das unabhängige Institut Bauen und Umwelt e.V. (IBU) verifizieren lassen.

Diese durch das IBU verifizierten Muster-EPDs wurden von der Deutschen Bauchemie und dem IBU veröffentlicht.

Anhand unserer Produktrezepturen wurde überprüft, ob unsere Produkte durch die Muster-EPD abgedeckt werden.

Mit dieser Erklärung bestätigen wir, dass das Produkt

OTTOCOLL® M 500

von der beigefügten Muster-EPD erfasst wird

Products based on polyurethane or silane-modified polymer, group 1
EPD-FEI-20220021-IBG1-EN

Das heißt, dass die Ökobilanzdaten und die sonstigen Inhalte der beigefügten Muster-EPD auf das oben genannte Produkt zutreffen und für die Bewertung der Nachhaltigkeit von Gebäuden, in denen das oben genannte Produkt verbaut wurde, herangezogen werden können.

Hermann Otto GmbH

Fridolfing, 25.05.2023

Hermann Otto GmbH | Krankenhausstr.14 | 83413 Fridolfing, Deutschland
Tel.: +49 8684 908-0 | Fax: +49 8684 1840
E-Mail: info@otto-chemie.de | Internet: www.otto-chemie.de

ISO 9001, ISO 14001
Zertifiziertes Integriertes Managementsystem für Qualität und Umwelt
www.tuev-sued.de/ms-zert

DICHTEN & KLEBEN

ENVIRONMENTAL PRODUCT DECLARATION

as per *ISO 14025* and *EN 15804+A2*

Owner of the Declaration	DBC, EFCC, FEICA, IVK
Programme holder	Institut Bauen und Umwelt e.V. (IBU)
Publisher	Institut Bauen und Umwelt e.V. (IBU)
Declaration number	EPD-FEI-20220021-IBG1-EN
Issue date	01.06.2022
Valid to	31.05.2027

Products based on polyurethane or silane-modified polymer, group 1

DBC - Deutsche Bauchemie e.V.

EFCC - European Federation for Construction Chemicals

FEICA - Association of the European Adhesive and Sealant Industry

IVK - Industrieverband Klebstoffe e.V.

Institut Bauen und Umwelt e.V.

www.ibu-epd.com | https://epd-online.com

ECO PLATFORM

EPD

VERIFIED

1. General Information

DBC - Deutsche Bauchemie e.V.
EFCC - European Federation for Construction Chemicals
FEICA - Association of the European Adhesive and Sealant Industry
IVK - Industrieverband Klebstoffe e.V.

Products based on polyurethane or silane-modified polymer, group 1

Programme holder
IBU – Institut Bauen und Umwelt e.V.
Hegelplatz 1
10117 Berlin
Germany

Owner of the declaration
DBC, Mainzer Landstr. 55, D-60329 Frankfurt a.M.
EFCC, 172 Boulevard du Triomphe, B-1160 Brussels
FEICA, Rue Belliard 40, B-1040 Brussels
IVK, Völklingerstr. 4, D-40219 Düsseldorf

Declaration number
EPD-FEI-20220021-IBG1-EN

Declared product / declared unit
1 kg product based on polyurethane or silane-modified polymer; density 1.25 - 1.8 g/cm³

This declaration is based on the product category rules:
Reaction resin products, 07.2014
(PCR checked and approved by the SVR)

Issue date
01.06.2022

Valid to
31.05.2027

Scope:
This verified EPD entitles the holder to bear the symbol of the Institut Bauen und Umwelt e.V. It exclusively applies for products produced in Europe and for a period of five years from the date of issue. This EPD may be used by members of DBC, EFCC, FEICA and IVK and their members provided it has been proven that the respective product can be represented by this EPD. For this purpose a guideline is available at the secretariats of the four associations. The members of the associations are listed on the respective websites.

The owner of the declaration shall be liable for the underlying information and evidence; the IBU shall not be liable with respect to manufacturer information, life cycle assessment data and evidences.
The EPD was created according to the specifications of *EN 15804+A2*. In the following, the standard will be simplified as *EN 15804*.

Verification

The standard *EN 15804* serves as the core PCR
Independent verification of the declaration and data according to *ISO 14025:2011*
☐ internally ☒ externally

Dipl. Ing. Hans Peters
(chairman of Institut Bauen und Umwelt e.V.)

Dr. Alexander Röder
(Managing Director Institut Bauen und Umwelt e.V.))

Matthias Schulz
(Independent verifier)

2. Product

2.1 Product description/Product definition

This EPD comprises reactive products based on polyurethane (PU) or silane-modified polymer (SMP) with a volatile organic copound (VOC) content ≤1 % (VOC definition according to *Decopaint Directive*) and a castor oil/-derivatives content ≤ 10%. The one- or two-component reactive PU products are manufactured using polyols and isocyanates. Reactive products based on SMP polymers are usually manufactured as a one-component system from polyols and alkoxysilane in a preliminary stage. The aqueous systems consist of (a) dispersion and are crosslinked by a dispersible isocyanate. The products fulfil manifold, often specific, functions in the construction, furnishing and repair of buildings. The product displaying the highest environmental impacts was used as a representative product for calculating the Life Cycle Assessment results (worst-case approach).

For the placing on the market in the European Union/European Free Trade Association (EU/EFTA) with the exception of Switzerland) products falling under Regulation (EU) No 305/2011 (*CPR*) need a Declaration of Performance taking into consideration either the relevant harmonised European standard or

the European Technical Assessment and the CE marking. For the application and use of the products the respective national provisions apply.

2.2 Application

Products based on polyurethane or silane-modified polymer, group 1, are used for the following applications:

Module 1: Adhesives for parquet and floor coverings
Parquet adhesives in accordance with *EN ISO 17178* for wooden and parquet floors and flooring adhesives in accordance with *EN ISO 22636* for floor coverings

Module 2: Reactive products for protecting and repairing concrete structures
Products for increasing the durability of concrete and reinforced concrete structures as well as for new concrete and for maintenance and repair work (requirements 2.1), products for structural bonding of strengthening materials to an existing concrete structure (requirements 2.2) and products for concrete injection for filling cracks, voids and interstices in concrete (requirements 2.3)

Module 3: Liquid-applied roof waterproofing kits
Reactive products for waterproofing roof constructions which are applied on site

Module 4: Reactive products for liquid-applied bridge deck waterproofing kits
Products for liquid-applied waterproofing for use on concrete bridge decks

Module 5: Screed material, floor screeds and decorative floors
Products for screed/synthetic resin screed for use in floor constructions

Module 6: Reactive products as an adhesive for tiles
Tile adhesives for internal and external tile installations on walls, floors and ceilings

Module 7: Adhesives and sealants
Reactive products for use as:
· Structural and repair adhesives
· Surface and joint sealants
Applications in accordance with the manufacturer's technical documentation/declaration of performance

Module 8: Reactive products for watertight covering kits
Products for waterproofing floors and/or walls in wet rooms inside buildings

Module 9: Reactive products for liquid-applied waterproofing
Liquid applied products for waterproofing of buildings

Module 10: Reactive products for waterproofing and/or for pre-treating mineral substrates
Applications in accordance with the manufacturer's technical documentation

Module 11*:* Liquid-applied waterproofing membranes for use beneath ceramic tiling

Module 12: One-component foam (OCF)
One component foam in a can is a one-component, self-expanding, ready to use polyurethane foam used for various construction applications. It consists of a low viscous semi-fluid in a can that leaves the can as a froth and immediately forms a polyurethane foam.
12.1 Window & External Door Sealing & Insulation:
Installing mechanically fixed external windows and doors with an OCF, as part of a system including sealants and tapes
12.2 Door Installation & Fixation:
Fixing interior doors with an OCF
12.3 General Gap Filling:
Filling of regularly and irregularly shaped spaces between at least two surfaces made of typical building materials with a one-component foam (OCF)

Module 13: Sealants for glazing
Two-component reactive sealants are to be used as the second barrier of the structural hermetic seal in insulating glass units.

Module 14: Bonded glazing sealants
One- and two-component reactive sealants are used for the bonding of insulating glass units in the window frame.

2.3 Technical Data

The density of the products is between 1,25 and 1,8 g/cm³, other relevant technical data can be found in the manufacturer's technical documentation.

Module 1: Reactive products as adhesive for parquet and floor coverings
The minimum requirements of *EN ISO 17178* and *EN ISO 22636* must be maintained.

Module 2: Reactive products for protecting and repairing concrete structures
2.1 The requirements on essential characteristics for all intended uses in accordance with *EN 1504-2*, Tables 1 and 5 must be maintained. These are:
- Permeability to CO_2 (*EN 1062-6*)
- Water vapour permeability (*EN ISO 7783-1/-2*)
- Capillary absorption and permeability to water (*EN 1062-3*)
- Adhesive strength by pull-off test (*EN 1542*)

2.2 Essential characteristics for all intended uses in accordance with *EN 1504-4*, Tables 3.1 and 3.2 (manufacturer's declaration of performance)
2.3 Requirements on essential characteristics for all intended uses in accordance with *EN 1504-5*, Table 3:
- Injectability (*EN 1771*)
- Viscosity (*EN ISO 3219*)

Further essential characteristics in accordance with the manufacturer's technical documentation/declaration of performance

Module 3: Liquid-applied roof waterproofing kits
The minimum requirements of *EAD 030350-00-0402* Liquid-applied roof waterproofing kits must be maintained. The essential characteristics are to be specified in accordance with the European Technical Assessment (ETA, specification no.).

Module 4: Reactive products for liquid-applied bridge deck waterproofing kits
The minimum requirements of *ETAG 033* Liquid-applied bridge deck waterproofing kits must be maintained. The essential characteristics are to be specified in accordance with the European Technical Assessment (ETA, specification no.).

Module 5: Screed material, floor screeds and decorative floors
The requirements on essential characteristics according to E*N 13813* 'Screed material and floor screeds – Screed materials – Properties and requirements'/ must be maintained. For synthetic resin screeds, these are:
- Bond strength (*EN 13892-8*)
- Reaction to fire (*EN 13501-1*)
Further essential characteristics in accordance with the manufacturer's technical documentation/declaration of performance

Module 6: Reactive products as an adhesive for tiles
The requirements on essential characteristics according to *EN12004*, must be maintained. These are:
-Tensile adhesion strength after dry storage (*EN 12004-2*)
-Tensile adhesion strength after water immersion (*EN 12004-2*)
-Tensile adhesion strength after heat ageing *(EN 12004-2*)
-Tensile adhesion strength after freeze/thaw cycles (*EN 12004-2*)
-Open time: Tensile strength (*EN 12004-2*)
Further essential characteristics in accordance with the manufacturer's technical documentation

Module 7: Adhesives and sealants
Performance characteristics in accordance with the manufacturer's technical documentation / declaration of performance

Module 8: Reactive products for watertight covering kits
The minimum requirements of *EAD 030352-00-0503* Liquid applied watertight covering kits for wet room floors and/or walls must be maintained. The essential characteristics are to be specified in accordance with the European Technical Assessment (ETA, specification no.).

Module 9*:* Reactive products for liquid-applied waterproofings
The minimum requirements of the test principles regarding the issuing of general building authority test certificates for liquid-applied products for waterproofing of buildings (*PG-FLK*) must be maintained. The characteristics for the proof of usability are to be specified in accordance with the test principles for granting general building authority test certificates for liquid applied polymer products for waterproofing buildings

Module 10: Reactive products for waterproofing and/or for pre-treating mineral substrates

Name	Value	Unit
Density acc. to EN ISO 2811-1	700 - 1800	kg/m³
Shore hardness A acc. to ISO 48-4	>15	
Shore hardness D acc. to ISO 48-4	>5	
Viscosity acc. to ISO 3219-2	<100	Pas

Other performance characteristics in accordance with the manufacturer's technical documentation/declaration of performance

Module 11: Liquid-applied waterproofing membranes for use beneath ceramic tiling The minimum requirements on essential characteristics according to *EN 14891* - Liquid applied water-impermeable products for use beneath ceramic tiling - Definitions, specifications and test methods- must be maintained. These are:
- Initial tensile adhesion strength
- Tensile adhesion strength after water contact
- Tensile adhesion strength after heat ageing
- Tensile adhesion strength after freeze-thaw cycles
- Waterproofing
- Crack bridging ability

Module 12: One-Component Foams
Physical data of the one-component foam must be indicated in accordance with the respective product standards; these can include, for example:

12.1 Window & External Door Sealing & Insulation
Tensile Strength E*N 17333-4*, Movement Capability *EN 17333-4*, Curing Pressure *EN 17333-2*, Thermal conductivity *EN 17333-5*, Sound Insulation *EN ISO 717-1*, Post expansion *EN 17333-2*

12.2 Door Installation & Fixation
Shear Strength *EN 17333-4*, Tensile Strength *EN 17333-4*, Compression Strength *EN 17333-4*, Curing pressure *EN 17333-2*

12.3 General Gap Filling
Sagging *EN 17333-3* Other performance characteristics in accordance with the manufacturer's technical documents/declaration of performance.

Module 13: Sealants for glazing
Reactive sealants must comply with *EN 1279-4*
Performance characteristics in accordance with the manufacturer's technical documentation/declaration of performance

Module 14: Bonded glazing sealants
Reactive sealants must comply with *RAL-GZ 716* part 2 and *ift-Guideline VE-08/4.*
Performance characteristics in accordance with the manufacturer's technical documentation/declaration of performance

2.4 Delivery status
Liquid or pasty in containers made of tinplate or plastic packed in separate or combi-containers for the required mixing ratio. Packages containing one kg of product in different types of containers. Sealants in plastic cartridges and foil packs. Typical container sizes contain 10 to 25 kg of material. For major works, vats containing approx. 200 kg or IBCs (intermediate bulk containers) containing 1 tonne or more are also used. The LCA is based on tinplate, plastic and wood packaging.

2.5 Base materials/Ancillary materials
Products based on polyurethane or silane-modified polymer with a VOC content ≤1 % and a castor oil/-

derivatives content ≤10 % usually comprise a reactive polymer and a crosslinking system. The polymer component contains polyether and/or polyester polyols. Crosslinking takes place after installation on site. In the case of two-component systems, this involves the use of pre-polymers and polymers based on typically Methylene diphenyl diisocyanate (MDI), Toluene diisocyanate (TDI), Hexamethylene diisocyanate (HDI) or Isophorone diisocyanate (IPDI). The resin mixing ratio is adjusted according to the stoichiometric requirements. Crosslinking starts directly after the components have been mixed. There are also one-component reactive polymer formulations based on PU or SMP which crosslink in the presence of moisture. They comprise prepolymers based on e.g. MDI, TDI, HDI, IPDI or those with alkoxy-silane groups in the case of SMP formulations. In formulations with aqueous dispersions, dispersible isocyanates are used for crosslinking. The formulations can contain auxiliary materials such as accelerators, catalysts, wetting agents, foam regulators and viscosity regulators for fine-tuning the product features. Typically, the products covered by this EPD contain the following ranges of base materials and auxiliaries:
Polyol component: up to approx. 50 %
Crosslinking component: up to approx. 95 %
SMP component: up to approx. 80 %
Plasticiser: ~ 0-25 %
Additives / Pigments: ~ 0-30 %
Water: ~ 0-60 %
VOC: ≤1 % according to the *Decopaint Directive* (**mandatory**)
Castor oil and derivatives: ≤10 % **(mandatory)**

These ranges are average values and the composition of products complying with the EPD can deviate from these concentration levels in individual cases. More detailed information is available in the respective manufacturer's documentation (e.g. product data sheets).
Note: For companies to declare their products within the scope of this EPD it is not sufficient to simply comply with the product composition shown above. The application of this EPD is only possible for member companies of DBC, EFCC, FEICA, and IVK member associations and only for specific formulations with a total score below the declared maximum score for a product group according to the associated guidance document.

1. substances from the "Candidate List of Substances of Very High Concern for Authorisation" (SVHC)
If this product contains substances listed in the candidate list (latest version) exceeding 0.1 percentage by mass, the relevant information can be found in the safety data sheet of the relevant product covered by this model EPD.
2. CMR substances in categories 1A and 1B
If this product contains other carcinogenic, mutagenic, reprotoxic (CMR) substances in categories 1A or 1B which are not on the candidate list, exceeding 0.1 percentage by mass, the relevant information can be found in the safety data sheet of the relevant product covered by this model EPD.
3. Biocide products added to the construction product
If this construction product contains biocide products, the active substances, information on the concentration and/or concentration range, the product type together with information on their hazardous properties are listed in the safety data sheet of the respective product.

2.6 Manufacture
The components of the formulation are usually mixed batch-wise and packaged for delivery.

2.7 Environment and health during manufacturing
As a general rule, no other environmental protection measures other than those specified by law are necessary.

2.8 Product processing/Installation
Products based on polyurethane or silane-modified polymer, are processed by trowelling/knife-coating or rolling, pouring, spraying or injection.
Precautions for safe handling and storage (e.g. air exchange, exhaust ventilation, personal protective measures, precautions required in the handling of isocyanates, conditions for safe storage) must be observed in accordance with the information on the safety data sheet.

2.9 Packaging
A detailed description of packaging is provided in section 2.4. Empty containers and clean foils can be recycled.

2.10 Condition of use
During the use phase, products based on polyurethane or silane-modified polymer are crosslinked and essentially comprise an inert three-dimensional network. They are long-lasting products which protect our buildings in the form of adhesives, coatings or sealants as well as make an essential contribution in retaining their function and long-term value.

2.11 Environment and health during use
Option 1: Products for applications outside indoor areas with permanent stays by people
During use, the reactive products lose their reactive properties and become inert. No risks are known for water, air and soil if the products are used as designated.
Option 2: Products for applications inside indoor areas with permanent stays by people
When used in indoor areas with permanent stays by people, evidence of the emission performance of construction products in contact with indoor air must be submitted according to national requirements (see chapter 7). No further influences by emissions on the environment and health are known.

2.12 Reference service life
Cured products based on polyurethane or silane-modified polymer fulfil manifold, often specific functions in the construction or refurbishment of building structures. They decisively improve the usability of building structures and significantly extend their original service lives. The anticipated reference service life depends on the specific installation situation and the exposure associated with the product. It can be influenced by weathering as well as mechanical or chemical loads.

2.13 Extraordinary effects

Fire
Even without any special fire safety features, cured products based on polyurethane or silane-modified polymer comply with at least the requirements of *EN 13501-1* standard for fire classes E and Efl. In terms of the volumes applied, they have only a marginal influence on the fire performance characteristics (e.g. smoke gas development) of the building structure in which they have been installed. As crosslinked polyurethane systems do not melt or drip, they do not contribute towards spreading fire.

Water
Cured reactive products based on polyurethane or silane-modified polymer are chemically inert and insoluble in water. They are often used to protect building structures from harmful water ingress or the effects of flooding.

Mechanical destruction
Mechanical destruction of cured reactive products based on polyurethane or silane-modified polymer does not lead to any decomposition products which are harmful to the environment or health.

2.14 Re-use phase
According to present knowledge, no environmentally harmful effects are generally anticipated in landfilling, for example, as a result of de-construction and recycling of building materials with adherent crosslinked products. If the crosslinked products can be removed from construction products without large effort, thermal recovery is a practical recycling variant on account of their energy content. Minor adhesion is not taken into consideration during disposal. It does not interfere with the disposal/recycling of the remaining components/building materials.

2.15 Disposal
Residual material which cannot be used or recycled must be combined at a specified ratio and hardened. Hardened product residue is not special waste. Non-hardened product residue is hazardous waste. Empty, dried containers (free of drops and scraped clean) are directed to the recycling process. Residue must be directed to proper waste disposal taking into consideration the local guidelines. The following waste codes according to the European List of Waste (*2000/532/EC*) can apply:
Hardened product residue:
European Waste Calalogue (EWC) code 080112 (waste paint and varnish with the exception of that mentioned in 08 01 11)
EWC code 080410 (waste adhesives and sealants other than mentioned in 08 04 09)

2.16 Further information
More information is available on the manufacturer's product or safety data sheets and on the manufacturer's websites or on request. Valuable technical information is also available on the associations' websites.

3. LCA: Calculation rules

3.1 Declared Unit
This EPD refers to the declared unit of 1 kg of product based on polyurethane or silane-modified polymer, group 1; applied into the building with a density of 1.25 - 1.8 g/cm³ in accordance with the *IBU PCR* part B for reaction resin products.
The results of the Life Cycle Assessment provided in this declaration have been selected from the product with the highest environmental impact (worst-case scenario).
Depending on the application, a corresponding conversion factor such as the density to convert volumetric use to mass must be taken into consideration.

The Declaration type is according to *EN 15804*: Cradle to gate with options, modules C1–C3, and module D (A1–A3, C, D) and additional modules.

Declared unit

Name	Value	Unit
Declared unit	1	kg
Gross density	1.25 - 1.8	g/cm³
Conversion factor to 1 kg	-	-

3.2 System boundary
Modules A1, A2 and A3 are taken into consideration in the LCA:
- A1 Production of preliminary products
- A2 Transport to the plant
- A3 Production incl. provision of energy, production of packaging as well as auxiliaries and consumables and waste treatment
- A4 Transport to site
- A5 Installation, product applied into the building during A5 phase operations and packaging disposal. This stage considers VOC emissions during the installation phase. The declared product does not contain substances in the formulation that directly emit (as) VOC, but VOCs are generated by a chemical reaction that are occurring during this phase. The end of life for the packaging material considered is described below:
  -Incineration, for materials like plastic and wood.
  -Landfill, for inert material like metals (where used).

-C1-C2-C3-D
The building deconstruction (demolition process) takes place in the C1 module which considers energy production and consumption in terms of diesel and all the emissions connected with the fuel-burning process to run the machines. After the demolition, the product is transported to the end-of-life processing (C2 module) where all the impacts related to the transport processes are considered. For precautionary principle and as a worst-case scenario, thermal treatment is the only end-of-life scenario considered. This is modelled by the incineration process (module C3) where the product ends its life cycle.
Module D accounts for potential benefits that are beyond the defined system boundaries. Credits are generated during the incineration of wastes and related electricity produced that are occurring in the A5 module.

3.3 Estimates and assumptions
For this EPD formulation and production data defined and collected by FEICA were considered. Production

waste was assumed to be disposed of by incineration without credits as a worst-case.
An average of steel and plastic containers, and wooden pallets was considered in the LCA.

3.4 Cut-off criteria
All raw materials submitted for the formulations and production data were taken into consideration.
The manufacture of machinery, plant and other infrastructure required for the production of the products under review was not taken into consideration in the LCA.
Transport of packaging materials is excluded.

3.5 Background data
Data from the *GaBi* database SP40 (2020) was used as background data.

3.6 Data quality
Representative products were applied for this EPD and the product in the group displaying the highest environmental impact was selected for calculating the LCA results. The background data sets used are less than 4 years old.
Production data and packaging are based on details provided by the manufacturer. The formulation used for evaluation refers to a specific product.
The data quality of the background data is considered to be good.

3.7 Period under review
Representative formulations are valid for 2021.

3.8 Allocation
Mass allocation has been applied when primary data have been used and implemented into the LCA model.

3.9 Comparability
Basically, a comparison or an evaluation of EPD data is only possible if all the data sets to be compared were created according to *EN 15804* and the building context, respectively the product-specific characteristics of performance, are taken into account.

The *GaBi* database SP40 (2020) was used.

4. LCA: Scenarios and additional technical information

Characteristic product properties
Information on biogenic Carbon
The packaging material contains biogenic carbon content which is presented below.

Information on describing the biogenic Carbon Content at factory gate

Name	Value	Unit
Biogenic Carbon Content in product	0	kg C
Biogenic Carbon Content in accompanying packaging	0.016	kg C

Transport to the building site (A4)

Name	Value	Unit
Transport distance	1000	km
Gross weight	34 - 40	t
Payload capacity	27	t

Assembly (A5)

Name	Value	Unit
Other resources for packaging material	0.1	kg
Material loss	0.01	kg

Material loss regards the amount of product not used during the application phase into the building. This amount is 1% of the product, impacts related to the production of this part are charged to the A5 module. This percentage is considered as waste to disposal and impacts of its end of life have been considered in the LCA model and declared in A5.

End of life (C1-C3)

Name	Value	Unit
Collected as mixed construction waste	1	kg
Incineration	1	kg

5. LCA: Results

DESCRIPTION OF THE SYSTEM BOUNDARY (X = INCLUDED IN LCA; ND = MODULE OR INDICATOR NOT DECLARED; MNR = MODULE NOT RELEVANT)

PRODUCT STAGE			CONSTRUCTION PROCESS STAGE		USE STAGE							END OF LIFE STAGE				BENEFITS AND LOADS BEYOND THE SYSTEM BOUNDARIES
Raw material supply	Transport	Manufacturing	Transport from the gate to the site	Assembly	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	De-construction demolition	Transport	Waste processing	Disposal	Reuse-Recovery-Recycling-potential
A1	**A2**	**A3**	**A4**	**A5**	**B1**	**B2**	**B3**	**B4**	**B5**	**B6**	**B7**	**C1**	**C2**	**C3**	**C4**	**D**
X	X	X	X	X	ND	ND	MNR	MNR	MNR	ND	ND	X	X	X	ND	X

RESULTS OF THE LCA - ENVIRONMENTAL IMPACT according to EN 15804+A2: 1 kg of product based on polyurethane or silane modified polymer, group 1

Core Indicator	Unit	A1-A3	A4	A5	C1	C2	C3	D
GWP-total	[kg CO_2-Eq.]	4.79E+0	5.27E-2	1.80E-1	2.79E-4	1.24E-2	2.21E+0	-9.50E-1
GWP-fossil	[kg CO_2-Eq.]	4.81E+0	5.22E-2	9.38E-2	2.66E-4	1.18E-2	2.21E+0	-9.47E-1
GWP-biogenic	[kg CO_2-Eq.]	-3.57E-2	1.52E-4	8.62E-2	1.24E-5	5.42E-4	8.82E-5	-2.23E-3
GWP-luluc	[kg CO_2-Eq.]	4.50E-3	4.22E-4	4.84E-5	6.39E-9	2.79E-7	2.08E-5	-6.66E-4
ODP	[kg CFC11-Eq.]	6.76E-9	6.27E-18	6.76E-11	2.84E-20	1.24E-18	2.62E-16	-9.93E-15
AP	[mol H^+-Eq.]	1.02E-2	1.56E-4	1.29E-4	3.60E-6	3.73E-5	1.31E-3	-1.33E-3
EP-freshwater	[kg P-Eq.]	1.93E-5	1.59E-7	1.98E-7	5.75E-11	2.51E-9	4.40E-8	-1.23E-6
EP-marine	[kg N-Eq.]	2.67E-3	6.96E-5	3.50E-5	1.63E-6	1.72E-5	6.31E-4	-3.43E-4
EP-terrestrial	[mol N-Eq.]	2.93E-2	7.80E-4	4.11E-4	1.79E-5	1.89E-4	7.26E-3	-3.68E-3
POCP	[kg NMVOC-Eq.]	9.47E-3	1.38E-4	7.20E-3	4.91E-6	3.39E-5	1.62E-3	-9.87E-4
ADPE	[kg Sb-Eq.]	8.18E-6	3.74E-9	8.22E-8	8.06E-12	3.52E-10	4.65E-9	-1.56E-7
ADPF	[MJ]	1.05E+2	6.94E-1	1.11E+0	3.81E-3	1.66E-1	5.87E-1	-1.61E+1
WDP	[m^3 world-Eq deprived]	1.34E+0	4.66E-4	2.69E-2	5.27E-7	2.30E-5	2.17E-1	-9.86E-2

Caption	GWP = Global warming potential; ODP = Depletion potential of the stratospheric ozone layer; AP = Acidification potential of land and water; EP = Eutrophication potential; POCP = Formation potential of tropospheric ozone photochemical oxidants; ADPE = Abiotic depletion potential for non-fossil resources; ADPF = Abiotic depletion potential for fossil resources; WDP = Water (user) deprivation potential

RESULTS OF THE LCA - INDICATORS TO DESCRIBE RESOURCE USE according to EN 15804+A2: 1 kg of product based on polyurethane or silane modified polymer, group 1

Indicator	Unit	A1-A3	A4	A5	C1	C2	C3	D
PERE	[MJ]	6.67E+0	3.90E-2	6.65E-1	1.20E-5	5.25E-4	8.23E-2	-3.52E+0
PERM	[MJ]	5.85E-1	0.00E+0	-5.85E-1	0.00E+0	0.00E+0	0.00E+0	0.00E+0
PERT	[MJ]	7.26E+0	3.90E-2	7.99E-2	1.20E-5	5.25E-4	8.23E-2	-3.52E+0
PENRE	[MJ]	8.33E+1	6.95E-1	1.63E+0	3.81E-3	1.67E-1	2.21E+1	-1.61E+1
PENRM	[MJ]	2.20E+1	0.00E+0	-5.20E-1	0.00E+0	0.00E+0	-2.15E+1	0.00E+0
PENRT	[MJ]	1.05E+2	6.95E-1	1.11E+0	3.81E-3	1.67E-1	5.87E-1	-1.61E+1
SM	[kg]	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0
RSF	[MJ]	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0
NRSF	[MJ]	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0
FW	[m^3]	4.03E-2	4.52E-5	7.22E-4	2.16E-8	9.41E-7	5.11E-3	-4.08E-3

Caption	PERE = Use of renewable primary energy excluding renewable primary energy resources used as raw materials; PERM = Use of renewable primary energy resources used as raw materials; PERT = Total use of renewable primary energy resources; PENRE = Use of non-renewable primary energy excluding non-renewable primary energy resources used as raw materials; PENRM = Use of non-renewable primary energy resources used as raw materials; PENRT = Total use of non-renewable primary energy resources; SM = Use of secondary material; RSF = Use of renewable secondary fuels; NRSF = Use of non-renewable secondary fuels; FW = Use of net fresh water

RESULTS OF THE LCA – WASTE CATEGORIES AND OUTPUT FLOWS according to EN 15804+A2: 1 kg of product based on polyurethane or silane modified polymer, group 1

Indicator	Unit	A1-A3	A4	A5	C1	C2	C3	D
HWD	[kg]	1.12E-5	3.23E-8	1.12E-7	3.70E-13	1.62E-11	3.34E-10	-6.41E-9
NHWD	[kg]	1.66E-1	1.06E-4	4.75E-2	3.90E-7	1.70E-5	1.11E-2	-7.44E-3
RWD	[kg]	2.34E-3	8.60E-7	2.54E-5	4.09E-9	1.79E-7	2.37E-5	-1.20E-3
CRU	[kg]	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0
MFR	[kg]	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0
MER	[kg]	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0
EEE	[MJ]	0.00E+0	0.00E+0	2.12E-1	0.00E+0	0.00E+0	0.00E+0	0.00E+0
EET	[MJ]	0.00E+0	0.00E+0	3.86E-1	0.00E+0	0.00E+0	0.00E+0	0.00E+0

Caption	HWD = Hazardous waste disposed; NHWD = Non-hazardous waste disposed; RWD = Radioactive waste disposed; CRU = Components for re-use; MFR = Materials for recycling; MER = Materials for energy recovery; EEE = Exported electrical energy; EEE = Exported thermal energy

RESULTS OF THE LCA – additional impact categories according to EN 15804+A2-optional: 1 kg of product based on polyurethane or silane modified polymer, group 1

Indicator	Unit	A1-A3	A4	A5	C1	C2	C3	D
PM	[Disease Incidence]	ND	ND	ND	ND	ND	ND	ND
IRP	[kBq U235-Eq.]	ND	ND	ND	ND	ND	ND	ND
ETP-fw	[CTUe]	ND	ND	ND	ND	ND	ND	ND
HTP-c	[CTUh]	ND	ND	ND	ND	ND	ND	ND
HTP-nc	[CTUh]	ND	ND	ND	ND	ND	ND	ND
SQP	[-]	ND	ND	ND	ND	ND	ND	ND
Caption	PM = Potential incidence of disease due to PM emissions; IR = Potential Human exposure efficiency relative to U235; ETP-fw = Potential comparative Toxic Unit for ecosystems; HTP-c = Potential comparative Toxic Unit for humans (cancerogenic); HTP-nc = Potential comparative Toxic Unit for humans (not cancerogenic); SQP = Potential soil quality index							

Potential Human exposure efficiency relative to U235, Disclaimer 1 – This impact category deals mainly with the eventual impact of low dose ionizing radiation on human health of the nuclear fuel cycle. It does not consider effects due to possible nuclear accidents, occupational exposure or radioactive waste disposal in underground facilities. Potential ionizing radiation from the soil, radon and (from) some construction materials is also not measured by this indicator.

ADP minerals & metals, ADP fossil, WDP, ETF-fw, HTP-c, HTP-nc, SQP, Disclaimer 2 – The results of this environmental impact indicator shall be used with care as the uncertainties on these results are high or as there is limited experience with the indicator.

Additional environmental impact indicators (suggested by *EN15804*, table 4) are not declared in the EPD. The results of this environmental impact indicator shall be used with care as the uncertainties on these results are high and as there is limited experience with the indicator (see ILCD classification in EN 15804, table 5). For this reason, results based on these indicators are not considered suitable for a decision-making process and are thus not declared in the EPD.

6. LCA: Interpretation

The majority of impacts are associated with the production phase (A1-A3). The most significant contribution to the production phase impacts is the upstream production of raw materials as the main driver. Another substantial contributor in the production phase, in the category of Abiotic depletion potential for nonfossil resources (ADPminerals& metals), is the steel sheet used as a packaging material. Emissions associated with the manufacturing of products also have some influence on the Formation potential of tropospheric ozone (POCP) in the production phase. In all EPDs, CO_2 is the most important contributor to Global Warming Potential (GWP). For the Acidification Potential (AP), NOx and SO_2 contribute the largest share. In some cases, HCl in water also impacts AP due to the use of TiO_2 as a pigment.
The majority of life cycle energy consumption takes place during the production phase (A1-A3). Significant contributions to Primary Energy Demand – Non-renewable (PENRT) come from the energy resources used in the production of raw materials. The largest contributor to Primary Energy Demand – Renewable (PERT) impacts comes from the consumption of renewable energy resources required for the generation and supply of electricity. It should be noted that Primary Energy Demand – Renewable (PERT) generally represents a small percentage of the production phase primary energy demand with the bulk of the demand coming from non-renewable energy resources.
Transportation to the construction site (A4) and the installation process (A5) make a low contribution to all impacts.
The installation phase influences mainly the Photochemical ozone formation indicator, due to the emission of VOC during the operations. These emissions are not directly related to the pre-products in the resins, but they are related to the reaction products between pre-products and air components (water and oxygen).
The end-of-life phases influence climate change indicators, due to the incineration processes occurring in the C3 module, the process used for modelling the thermal treatment process of the resin.

7. Requisite evidence

VOC
Special tests and evidence have not been carried out or provided within the framework of drawing up this Model EPD. Some member states require special documentation on VOC emissions into indoor air for specific areas of application. This documentation, as well as documentation for voluntary VOC labelling, has to be provided separately and is specific for product in question.

Evidence pertaining to VOC emissions shall show
- either an attestation of compliance with,
- or documentation of test data that are required in any of the existing regulations or in any of the existing voluntary labelling programs for low-emitting products, as far as these

(1) include limits for the parameters TVOC, TSVOC, carcinogens, formaldehyde, acetaldehyde, LCI limits for individual substances (including but not limited to the European list of harmonized LCIs), and the R value;
(2) base their test methods on *EN 16516*;
(3) perform testing and apply the limits after 28 days of storage in a ventilated test chamber, under the conditions specified in *EN 16516*; some regulations

and programs also have limits after 3 days, on top of the 28 days limits;
(4) express the test results as air concentrations in the European Reference Room, as specified in *EN 16516*.

Examples of such regulations are the *Belgian Royal Decree C-2014/24239*, or the *German AgBB/* ABG. Examples of such voluntary labelling programs are *EMICODE*, *Blue Angel* or *Indoor Air Comfort*.

Relevant test results shall be produced either by an *ISO 17025* accredited commercial test lab or by a qualified internal test lab of the manufacturer.
Examples for the applied limits after 28 days of storage in a ventilated test chamber are:

- TVOC: 1000 µg/m³
- TSVOC: 100 µg/m³
- Each carcinogen: 1 µg/m³
- Formaldehyde: 100 µg/m³
- LCI: different per substance involved
- R value: 1 (meaning that, in total, 100 % of the combined LCI values must not be exceeded).

Informative Annexes (2 tables):
Table 1 shown below is an overview of the most relevant regulations and specifications as of October 2021, as regards requirements after 3 days of storage in a ventilated test chamber.
Table 2 provides an overview of the most relevant regulations and specifications as of October 2021, as regards requirements after 28 days of storage in a ventilated test chamber. Some details may be missing in the table due to lack of space. Values given represent maximum values/limits.

	TVOC µg/m³	Sum of carcinogens. C1A,CA2 µg/m³	Formaldehyde µg/m³	Acetaldehyde µg/m³	Sum of Form- and Acetaldehyde
German AgBB/ABG regulation	10 000	10	-/-	-/-	-/-
Belgian regulation	10 000	10	-/-	-/-	-/-
EMICODE EC1	1 000	10	50	50	50 ppb
EMICODE EC1 *PLUS*	750	10	50	50	50 ppb

	TVOC µg/m³	TSVOC µg/m³	Each carcinogen C1A,CA2 µg/m³	Formalde-hyde µg/m³	Acetalde-hyde µg/m³	LCI	R value	Specials	Sum of non-LCI & non-identified µg/m³
Belgian regulation	1000	100	1	100	200	Belgian list	1	Toluene 300 µg/m³	-/-
French regulations class A+	1000	-/-	-/-	10	200	-/-	-/-	List of 8 VOCs, 4 CMR	-/-
French regulations class A	1500	-/-	-/-	60	300	-/-	-/-	List of 8 VOCs, 4 CMR	-/-
French regulations class B	2000	-/-	-/-	120	400	-/-	-/-	List of 8 VOCs, 4 CMR	-/-
French regulations class C	>2000	-/-	-/-	>120	>400	-/-	-/-	List of 8 VOCs, 4 CMR	-/-
German DIBt/AgBB regulation	1000	100	1	100	300	German AgBB list	1	-/-	100
EMICODE EC1	100	50	1	(after 3 days)	(after 3 days)	-/-	-/-	-/-	-/-
EMICODE EC1 *PLUS*	60	40	1	(after 3 days)	(after 3 days)	German AgBB list	1	-/-	40
Finnish M1, sealants	20	-/-	1	10	300	EU LCI list	-/-	Ammonia, odour	-/-
Finnish M1, adhesives	200 µg/m²h	-/-	5 µg/m²h	50 µg/m²h	300	EU LCI list	-/-	Ammonia, odour	-/-

8. References

ETAG 033
Liquid applied bridge deck waterproofing kits

ISO 48-4

ISO 48-4:2018, Rubber, vulcanized or thermoplastic - Determination of hardness- Part 4: Indentation hardness by durometer method (Shore hardness)

EN ISO 717-1
EN ISO 717-1:2020 Acoustics - Rating of sound insulation in buildings and of building elements - Part 1: Airborne sound insulation

EN 1062-3
EN 1062-3:2008-04, Paints and varnishes - Coating materials and coating systems for exterior masonry and concrete - Part 3: Determination of liquid water permeability

EN 1062-6
EN 1062-6:2002-10, Paints and varnishes - Coating materials and coating systems for exterior masonry and concrete - Part 6: Determination of carbon dioxide permeability

EN 1279-4
EN 1279-4:2002 Glass in building - Insulating glass units - Part 4: Methods of test for the physical attributes of edge seals

EN 1504-2
EN 1504-2:2004-12, Products and systems for the protection and repair of concrete structures - Definitions, requirements, quality control and evaluation of conformity - Part 2: Surface protection systems for concrete

EN 1504-4
EN 1504-4:2004-11, Products and systems for the protection and repair of concrete structures - Definitions, requirements, quality control and evaluation of conformity- Part 4: Structural bonding

EN 1504-5
EN 1504-5:2004-12, Products and systems for the protection and repair of concrete structures - Definitions, requirements, quality control and evaluation of conformity - Part 5: Concrete injection

EN 1542
EN 1542:1999-07, Products and systems for the protection and repair of concrete structures - Test methods - Measurement of bond strength by pull-off

EN 1771
EN 1771:2004-11, Products and systems for the protection and repair of concrete structures - Test methods - Determination of injectability and splitting test

ISO 2811-1
ISO 2811-1:2016, Paints and varnishes - Determination of density - Part 1: Pycnometer method

EN ISO 3219
EN ISO 3219:1994-10, Plastics - Polymers/resins in the liquid state or as emulsions or dispersions - Determination of viscosity using a rotational viscometer with defined shear rate

ISO 3219-2
ISO 3219-2:2021, Rheology - Part 2: General principles of rotational and oscillatory rheometry

EN ISO 7783
EN ISO 7783:2019-02, Paints and varnishes - Determination of water-vapour transmission properties - Cup method

EN 12004
EN12004:2012, Adhesives for ceramic tiles

EN 12004-1
EN 12004-1:2017, Adhesives for ceramic tiles – Part 1: Requirements, assessment and verification of constancy of performance, classification and marking

EN 12004-2
EN 12004-2:2017, Adhesives for ceramic tiles - Part 2: Test methods

EN 13501-1
EN 13501-1:2018, Fire classification of construction products and building elements - Part 1: Classification using data from reaction to fire tests

EN 13813
EN 13813:2002-10, Screed material and floor screeds - Screed materials - Properties and requirements

EN 13892-8
EN 13892:2003-02, Methods of test for screed materials - Part 8: Determination of bond strength

ISO 14025
DIN EN ISO 14025:2011-10, Environmental labels and declarations — Type III environmental declarations — Principles and procedures

EN 14891
EN 14891:2012-04, Liquid applied water impermeable products for use beneath ceramic tiling - Definitions, specifications and test methods

EN 15804
EN 15804:2019+A2, Sustainability of construction works — Environmental Product Declarations — Core rules for the product category of construction products

EN 16516
EN 16516:2017
Construction products - Assessment of release of dangerous substances - Determination of emissions into indoor air

EN ISO 17025
EN ISO 17025:2018-03
General requirements for the competence of testing and calibration laboratories

EN ISO 17178
EN ISO 17178:2020-06, Adhesives - Adhesives for bonding parquet to subfloor - Test methods and minimum requirements

EN 17333-2
EN 17333-2:2020+AC:2020, Characterisation of one component foam - Part 2: Expansion characteristics

EN 17333-3
EN 17333-3:2020, Characterisation of one component foam - Part 3: Application

EN 17333-4
EN 17333-4:2020, Characterisation of one component foam - Part 4: Mechanical strength

EN 17333-5
EN 17333-5:2020, Characterisation of one component foam - Part 5: Insulation

EN ISO 22636
EN ISO 22636:2020, Adhesives - Adhesives for floor coverings - Requirements for mechanical and electrical performance

EAD 030350-00-0402
EAD 030350-00-0402:2018-08**,** Liquid Applied Roof Waterproofing Kits

EAD 030352-00-0503
EAD 030352-00-0503:2019-01, Liquid applied watertight covering kits for wet room floors and/or walls

2000/532/EC
Commission decision dated 3 May 2000 replacing decision 94/3/EC on a waste directory in accordance with Article 1 a) of Council Directive 75/442/EEC on waste and Council decision 94/904/EC on a directory of hazardous waste in terms of Article 1, paragraph 4 of Directive 91/689/EEC on hazardous waste

Belgian Royal Decree C-2014/24239
Belgisch Staatsblad 8 MEI 2014, p. 60603. — Koninklijk besluit tot vaststelling van de drempelniveaus voor de emissies naar het binnenmilieu van bouwproducten voor bepaalde geoogde gebruiken

Blue Angel
Environmental label organised by the federal government of Germany www.blauer-engel.de

CPR
CPR Regulation (EU) No 305/2011 of the European Parliament and of the Council of 9 March 2011 laying down harmonised conditions for the marketing of construction products and repealing Council Directive 89/106/EEC

Decopaint Directive
Directive 2004/42/CE of the European Parliament and the council of 21 April 2004 on the limitation of emissions of volatile organic compounds due to the use of organic solvents in certain paints and varnishes and vehicle refinishing products and amending Directive 1999/13/EC

EMICODE
EMICODE, GEV – Gemeinschaft Emissionskontrollierte Verlegewerkstoffe, Klebstoffe und Bauprodukte e. V. (pub.).www.emicode.de

GaBi 10 software & documentation
Data base for Life Cycle Engineering LBP, University of Stuttgart and Sphera, documentation of GaBi 10 data sets http://documentation.gabi-software.com/, 2020

German AgBB
Committee for Health-related Evaluation of Building Products: health-related evaluation of emissions of volatile organic compounds (VOC and SVOC) from building products; status: June 2012 www.umweltbundesamt.de/produkte/bauprodukte/agbb.htm

IBU 2021
Institut Bauen und Umwelt e.V.: General Instructions for the EPD programme of Institut Bauen und Umwelt e.V. EPD programme. Version 2.0. Berlin: Institut Bauen und Umwelt e.V., 2021 www.ibu-epd.com

ift-Guideline VE-08/4
ift-Guideline VE-08/4:2017, Beurteilungsgrundlage für geklebte Verglasungssysteme

Indoor Air Comfort
Product certification by Eurofins, Hamburg, Germany www.eurofins.com

PCR Part A
Product Category Rules for Building-Related Products and Services, Part A: Calculation Rules for the Life Cycle Assessment and Requirements on the Project report, Version 1.1, Institut Bauen und Umwelt e.V., 2021-01

PCR Part B
Product Category Rules for Construction Products, Part B: Reaction resin products, Institut Bauen und Umwelt e.V., 2019-01

RAL-GZ 716
RAL-GZ 716:2019-04 part 2, Kunststoff-Fensterprofilsysteme - Gütesicherung

REACH
Directive (EG) No. 1907/2006 of the European Parliament and of the Council dated 18 December 2006 on the registration, evaluation, approval and restriction of chemical substances (REACH), for establishing a European Agency for chemical substances, for amending Directive 1999/45/EC and for annulment of Directive (EEC) No. 793/93 of the Council, Directive (EC) No. 1488/94 of the Commission, Guideline 76/769/EEC of the Council and Guidelines 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC of the Commission.

Publisher
Institut Bauen und Umwelt e.V.
Hegelplatz 1
10117 Berlin
Germany

Tel +49 (0)30 3087748- 0
Fax +49 (0)30 3087748- 29
Mail info@ibu-epd.com
Web **www.ibu-epd.com**

Programme holder
Institut Bauen und Umwelt e.V.
Hegelplatz 1
10117 Berlin
Germany

Tel +49 (0)30 - 3087748- 0
Fax +49 (0)30 – 3087748 - 29
Mail info@ibu-epd.com
Web **www.ibu-epd.com**

Author of the Life Cycle Assessment
Sphera Solutions GmbH
Hauptstraße 111- 113
70771 Leinfelden-Echterdingen
Germany

Tel +49 711 341817-0
Fax +49 711 341817-25
Mail info@sphera.com
Web **www.sphera.com**

Owner of the Declaration
Industrieverband Klebstoffe e.V
Völklinger Straße 4
40219 Düsseldorf
Germany

Tel +49 (0)211 67931-10
Fax +49 (0)211 67931-33
Mail info@klebstoffe.com
Web **www.klebstoffe.com**

FEICA - Association of the European Adhesive and Sealant Industry
Avenue E. van Nieuwenhuyse 2
B-1160 Brussels
Belgium

Tel +32 (0)267 673 20
Fax +32 (0)267 673 99
Mail info@feica.eu
Web **www.feica.eu**

EFCC - European Federation for Construction Chemicals
Boulevard du Triomphe 172
1160 Brussels
Belgium

Tel +32289720-39
Fax +32289720-37
Mail info@efcc.be
Web **www.efcc.eu**

Deutsche Bauchemie e.V.
Mainzer Landstr. 55
60329 Frankfurt
Germany

Tel +49 (0)69 2556-1318
Fax +49 (0)69 2556-1319
Mail info@deutsche-bauchemie.de
Web **www.deutsche-bauchemie.de**

Declaration of conformity for products with Model EPDs

The Association of Deutsche Bauchemie e.V., of which Hermann Otto GmbH is a member, has developed so-called Model Environmental Product Declarations (Model EPDs) and had them independently verified by the Institut Bauen und Umwelt e.V. (IBU).

These IBU verified Model EPDs have been made publicly available by Deutsch Bauchemie and IBU.

Based on the product formulations it was checked if our products were covered by the Model EPDs.

This Declaration confirms that the product

OTTOCOLL® M 500

is covered by the attached Model EPD

Products based on polyurethane or silane-modified polymer, group 1
EPD-FEI-20220021-IBG1-EN

This means that the Life Cycle Assessment data and the remaining content of the attached Model EPD apply to the above mentioned product and may thus be used for the evaluation of the sustainability of buildings where the product is applied.

Hermann Otto GmbH

Fridolfing, 25.05.2023

Hermann Otto GmbH | Krankenhausstr.14 | 83413 Fridolfing, Germany
Tel.: +49 8684 908-0 | Fax: +49 8684 1840
e-mail: info@otto-chemie.de | Internet: www.otto-chemie.de

ISO 9001, ISO 14001
Certified Integrated Quality and Environmental Management System
www.tuv-sud.com/ms-cert

SEALING & BONDING

ENVIRONMENTAL PRODUCT DECLARATION

as per *ISO 14025* and *EN 15804+A2*

Owner of the Declaration	DBC, EFCC, FEICA, IVK
Programme holder	Institut Bauen und Umwelt e.V. (IBU)
Publisher	Institut Bauen und Umwelt e.V. (IBU)
Declaration number	EPD-FEI-20220021-IBG1-EN
Issue date	01.06.2022
Valid to	31.05.2027

Products based on polyurethane or silane-modified polymer, group 1

DBC - Deutsche Bauchemie e.V.

EFCC - European Federation for Construction Chemicals

FEICA - Association of the European Adhesive and Sealant Industry

IVK - Industrieverband Klebstoffe e.V.

Institut Bauen und Umwelt e.V.

www.ibu-epd.com | https://epd-online.com

ECO PLATFORM

EPD

VERIFIED

1. General Information

DBC - Deutsche Bauchemie e.V.
EFCC - European Federation for Construction Chemicals
FEICA - Association of the European Adhesive and Sealant Industry
IVK - Industrieverband Klebstoffe e.V.

Products based on polyurethane or silane-modified polymer, group 1

Programme holder
IBU – Institut Bauen und Umwelt e.V.
Hegelplatz 1
10117 Berlin
Germany

Owner of the declaration
DBC, Mainzer Landstr. 55, D-60329 Frankfurt a.M.
EFCC, 172 Boulevard du Triomphe, B-1160 Brussels
FEICA, Rue Belliard 40, B-1040 Brussels
IVK, Völklingerstr. 4, D-40219 Düsseldorf

Declaration number
EPD-FEI-20220021-IBG1-EN

Declared product / declared unit
1 kg product based on polyurethane or silane-modified polymer; density 1.25 - 1.8 g/cm³

This declaration is based on the product category rules:
Reaction resin products, 07.2014
(PCR checked and approved by the SVR)

Issue date
01.06.2022

Valid to
31.05.2027

Scope:
This verified EPD entitles the holder to bear the symbol of the Institut Bauen und Umwelt e.V. It exclusively applies for products produced in Europe and for a period of five years from the date of issue. This EPD may be used by members of DBC, EFCC, FEICA and IVK and their members provided it has been proven that the respective product can be represented by this EPD. For this purpose a guideline is available at the secretariats of the four associations. The members of the associations are listed on the respective websites.

The owner of the declaration shall be liable for the underlying information and evidence; the IBU shall not be liable with respect to manufacturer information, life cycle assessment data and evidences.
The EPD was created according to the specifications of *EN 15804+A2*. In the following, the standard will be simplified as *EN 15804*.

Verification

The standard *EN 15804* serves as the core PCR
Independent verification of the declaration and data according to *ISO 14025:2011*
☐ internally ☒ externally

Dipl. Ing. Hans Peters
(chairman of Institut Bauen und Umwelt e.V.)

Dr. Alexander Röder
(Managing Director Institut Bauen und Umwelt e.V.))

Matthias Schulz
(Independent verifier)

2. Product

2.1 Product description/Product definition
This EPD comprises reactive products based on polyurethane (PU) or silane-modified polymer (SMP) with a volatile organic copound (VOC) content ≤1 % (VOC definition according to *Decopaint Directive*) and a castor oil/-derivatives content ≤ 10%. The one- or two-component reactive PU products are manufactured using polyols and isocyanates. Reactive products based on SMP polymers are usually manufactured as a one-component system from polyols and alkoxysilane in a preliminary stage. The aqueous systems consist of (a) dispersion and are crosslinked by a dispersible isocyanate. The products fulfil manifold, often specific, functions in the construction, furnishing and repair of buildings. The product displaying the highest environmental impacts was used as a representative product for calculating the Life Cycle Assessment results (worst-case approach).

For the placing on the market in the European Union/European Free Trade Association (EU/EFTA) with the exception of Switzerland) products falling under Regulation (EU) No 305/2011 (*CPR*) need a Declaration of Performance taking into consideration either the relevant harmonised European standard or

the European Technical Assessment and the CE marking. For the application and use of the products the respective national provisions apply.

2.2 Application

Products based on polyurethane or silane-modified polymer, group 1, are used for the following applications:

Module 1: Adhesives for parquet and floor coverings
Parquet adhesives in accordance with *EN ISO 17178* for wooden and parquet floors and flooring adhesives in accordance with *EN ISO 22636* for floor coverings

Module 2: Reactive products for protecting and repairing concrete structures
Products for increasing the durability of concrete and reinforced concrete structures as well as for new concrete and for maintenance and repair work (requirements 2.1), products for structural bonding of strengthening materials to an existing concrete structure (requirements 2.2) and products for concrete injection for filling cracks, voids and interstices in concrete (requirements 2.3)

Module 3: Liquid-applied roof waterproofing kits
Reactive products for waterproofing roof constructions which are applied on site

Module 4: Reactive products for liquid-applied bridge deck waterproofing kits
Products for liquid-applied waterproofing for use on concrete bridge decks

Module 5: Screed material, floor screeds and decorative floors
Products for screed/synthetic resin screed for use in floor constructions

Module 6: Reactive products as an adhesive for tiles
Tile adhesives for internal and external tile installations on walls, floors and ceilings

Module 7: Adhesives and sealants
Reactive products for use as:
· Structural and repair adhesives
· Surface and joint sealants
Applications in accordance with the manufacturer's technical documentation/declaration of performance

Module 8: Reactive products for watertight covering kits
Products for waterproofing floors and/or walls in wet rooms inside buildings

Module 9: Reactive products for liquid-applied waterproofing
Liquid applied products for waterproofing of buildings

Module 10: Reactive products for waterproofing and/or for pre-treating mineral substrates
Applications in accordance with the manufacturer's technical documentation

Module 11*:* Liquid-applied waterproofing membranes for use beneath ceramic tiling

Module 12: One-component foam (OCF)
One component foam in a can is a one-component, self-expanding, ready to use polyurethane foam used for various construction applications. It consists of a low viscous semi-fluid in a can that leaves the can as a froth and immediately forms a polyurethane foam.
12.1 Window & External Door Sealing & Insulation:
Installing mechanically fixed external windows and doors with an OCF, as part of a system including sealants and tapes
12.2 Door Installation & Fixation:
Fixing interior doors with an OCF
12.3 General Gap Filling:
Filling of regularly and irregularly shaped spaces between at least two surfaces made of typical building materials with a one-component foam (OCF)

Module 13: Sealants for glazing
Two-component reactive sealants are to be used as the second barrier of the structural hermetic seal in insulating glass units.

Module 14: Bonded glazing sealants
One- and two-component reactive sealants are used for the bonding of insulating glass units in the window frame.

2.3 Technical Data

The density of the products is between 1,25 and 1,8 g/cm³, other relevant technical data can be found in the manufacturer's technical documentation.

Module 1: Reactive products as adhesive for parquet and floor coverings
The minimum requirements of *EN ISO 17178* and *EN ISO 22636* must be maintained.

Module 2: Reactive products for protecting and repairing concrete structures
2.1 The requirements on essential characteristics for all intended uses in accordance with *EN 1504-2*, Tables 1 and 5 must be maintained. These are:
- Permeability to CO_2 (*EN 1062-6*)
- Water vapour permeability (*EN ISO 7783-1/-2*)
- Capillary absorption and permeability to water (*EN 1062-3*)
- Adhesive strength by pull-off test (*EN 1542*)

2.2 Essential characteristics for all intended uses in accordance with *EN 1504-4*, Tables 3.1 and 3.2 (manufacturer's declaration of performance)
2.3 Requirements on essential characteristics for all intended uses in accordance with *EN 1504-5*, Table 3:
- Injectability (*EN 1771*)
- Viscosity (*EN ISO 3219*)

Further essential characteristics in accordance with the manufacturer's technical documentation/declaration of performance

Module 3: Liquid-applied roof waterproofing kits
The minimum requirements of *EAD 030350-00-0402* Liquid-applied roof waterproofing kits must be maintained. The essential characteristics are to be specified in accordance with the European Technical Assessment (ETA, specification no.).

Module 4: Reactive products for liquid-applied bridge deck waterproofing kits
The minimum requirements of *ETAG 033* Liquid-applied bridge deck waterproofing kits must be maintained. The essential characteristics are to be specified in accordance with the European Technical Assessment (ETA, specification no.).

Module 5: Screed material, floor screeds and decorative floors
The requirements on essential characteristics according to E*N 13813* 'Screed material and floor screeds – Screed materials – Properties and requirements'/ must be maintained. For synthetic resin screeds, these are:
- Bond strength (*EN 13892-8*)
- Reaction to fire (*EN 13501-1*)
Further essential characteristics in accordance with the manufacturer's technical documentation/declaration of performance

Module 6: Reactive products as an adhesive for tiles
The requirements on essential characteristics according to *EN12004*, must be maintained. These are:
-Tensile adhesion strength after dry storage (*EN 12004-2*)
-Tensile adhesion strength after water immersion (*EN 12004-2*)
-Tensile adhesion strength after heat ageing *(EN 12004-2*)
-Tensile adhesion strength after freeze/thaw cycles (*EN 12004-2*)
-Open time: Tensile strength (*EN 12004-2*)
Further essential characteristics in accordance with the manufacturer's technical documentation

Module 7: Adhesives and sealants
Performance characteristics in accordance with the manufacturer's technical documentation / declaration of performance

Module 8: Reactive products for watertight covering kits
The minimum requirements of *EAD 030352-00-0503* Liquid applied watertight covering kits for wet room floors and/or walls must be maintained. The essential characteristics are to be specified in accordance with the European Technical Assessment (ETA, specification no.).

Module 9*:* Reactive products for liquid-applied waterproofings
The minimum requirements of the test principles regarding the issuing of general building authority test certificates for liquid-applied products for waterproofing of buildings (*PG-FLK*) must be maintained. The characteristics for the proof of usability are to be specified in accordance with the test principles for granting general building authority test certificates for liquid applied polymer products for waterproofing buildings

Module 10: Reactive products for waterproofing and/or for pre-treating mineral substrates

Name	Value	Unit
Density acc. to EN ISO 2811-1	700 - 1800	kg/m³
Shore hardness A acc. to ISO 48-4	>15	
Shore hardness D acc. to ISO 48-4	>5	
Viscosity acc. to ISO 3219-2	<100	Pas

Other performance characteristics in accordance with the manufacturer's technical documentation/declaration of performance

Module 11: Liquid-applied waterproofing membranes for use beneath ceramic tiling The minimum requirements on essential characteristics according to *EN 14891* - Liquid applied water-impermeable products for use beneath ceramic tiling - Definitions, specifications and test methods- must be maintained. These are:
- Initial tensile adhesion strength
- Tensile adhesion strength after water contact
- Tensile adhesion strength after heat ageing
- Tensile adhesion strength after freeze-thaw cycles
- Waterproofing
- Crack bridging ability

Module 12: One-Component Foams
Physical data of the one-component foam must be indicated in accordance with the respective product standards; these can include, for example:

12.1 Window & External Door Sealing & Insulation
Tensile Strength E*N 17333-4*, Movement Capability *EN 17333-4*, Curing Pressure *EN 17333-2*, Thermal conductivity *EN 17333-5*, Sound Insulation *EN ISO 717-1*, Post expansion *EN 17333-2*

12.2 Door Installation & Fixation
Shear Strength *EN 17333-4*, Tensile Strength *EN 17333-4*, Compression Strength *EN 17333-4*, Curing pressure *EN 17333-2*

12.3 General Gap Filling
Sagging *EN 17333-3* Other performance characteristics in accordance with the manufacturer's technical documents/declaration of performance.

Module 13: Sealants for glazing
Reactive sealants must comply with *EN 1279-4*
Performance characteristics in accordance with the manufacturer's technical documentation/declaration of performance

Module 14: Bonded glazing sealants
Reactive sealants must comply with *RAL-GZ 716* part 2 and *ift-Guideline VE-08/4.*
Performance characteristics in accordance with the manufacturer's technical documentation/declaration of performance

2.4 Delivery status
Liquid or pasty in containers made of tinplate or plastic packed in separate or combi-containers for the required mixing ratio. Packages containing one kg of product in different types of containers. Sealants in plastic cartridges and foil packs. Typical container sizes contain 10 to 25 kg of material. For major works, vats containing approx. 200 kg or IBCs (intermediate bulk containers) containing 1 tonne or more are also used. The LCA is based on tinplate, plastic and wood packaging.

2.5 Base materials/Ancillary materials
Products based on polyurethane or silane-modified polymer with a VOC content ≤1 % and a castor oil/-

derivatives content ≤10 % usually comprise a reactive polymer and a crosslinking system. The polymer component contains polyether and/or polyester polyols. Crosslinking takes place after installation on site. In the case of two-component systems, this involves the use of pre-polymers and polymers based on typically Methylene diphenyl diisocyanate (MDI), Toluene diisocyanate (TDI), Hexamethylene diisocyanate (HDI) or Isophorone diisocyanate (IPDI). The resin mixing ratio is adjusted according to the stoichiometric requirements. Crosslinking starts directly after the components have been mixed. There are also one-component reactive polymer formulations based on PU or SMP which crosslink in the presence of moisture. They comprise prepolymers based on e.g. MDI, TDI, HDI, IPDI or those with alkoxy-silane groups in the case of SMP formulations. In formulations with aqueous dispersions, dispersible isocyanates are used for crosslinking. The formulations can contain auxiliary materials such as accelerators, catalysts, wetting agents, foam regulators and viscosity regulators for fine-tuning the product features. Typically, the products covered by this EPD contain the following ranges of base materials and auxiliaries:
Polyol component: up to approx. 50 %
Crosslinking component: up to approx. 95 %
SMP component: up to approx. 80 %
Plasticiser: ~ 0-25 %
Additives / Pigments: ~ 0-30 %
Water: ~ 0-60 %
VOC: ≤1 % according to the *Decopaint Directive* (**mandatory**)
Castor oil and derivatives: ≤10 % **(mandatory)**

These ranges are average values and the composition of products complying with the EPD can deviate from these concentration levels in individual cases. More detailed information is available in the respective manufacturer's documentation (e.g. product data sheets).
Note: For companies to declare their products within the scope of this EPD it is not sufficient to simply comply with the product composition shown above. The application of this EPD is only possible for member companies of DBC, EFCC, FEICA, and IVK member associations and only for specific formulations with a total score below the declared maximum score for a product group according to the associated guidance document.

1. substances from the "Candidate List of Substances of Very High Concern for Authorisation" (SVHC)
If this product contains substances listed in the candidate list (latest version) exceeding 0.1 percentage by mass, the relevant information can be found in the safety data sheet of the relevant product covered by this model EPD.
2. CMR substances in categories 1A and 1B
If this product contains other carcinogenic, mutagenic, reprotoxic (CMR) substances in categories 1A or 1B which are not on the candidate list, exceeding 0.1 percentage by mass, the relevant information can be found in the safety data sheet of the relevant product covered by this model EPD.
3. Biocide products added to the construction product
If this construction product contains biocide products, the active substances, information on the concentration and/or concentration range, the product type together with information on their hazardous properties are listed in the safety data sheet of the respective product.

2.6 Manufacture
The components of the formulation are usually mixed batch-wise and packaged for delivery.

2.7 Environment and health during manufacturing
As a general rule, no other environmental protection measures other than those specified by law are necessary.

2.8 Product processing/Installation
Products based on polyurethane or silane-modified polymer, are processed by trowelling/knife-coating or rolling, pouring, spraying or injection.
Precautions for safe handling and storage (e.g. air exchange, exhaust ventilation, personal protective measures, precautions required in the handling of isocyanates, conditions for safe storage) must be observed in accordance with the information on the safety data sheet.

2.9 Packaging
A detailed description of packaging is provided in section 2.4. Empty containers and clean foils can be recycled.

2.10 Condition of use
During the use phase, products based on polyurethane or silane-modified polymer are crosslinked and essentially comprise an inert three-dimensional network. They are long-lasting products which protect our buildings in the form of adhesives, coatings or sealants as well as make an essential contribution in retaining their function and long-term value.

2.11 Environment and health during use
Option 1: Products for applications outside indoor areas with permanent stays by people
During use, the reactive products lose their reactive properties and become inert. No risks are known for water, air and soil if the products are used as designated.
Option 2: Products for applications inside indoor areas with permanent stays by people
When used in indoor areas with permanent stays by people, evidence of the emission performance of construction products in contact with indoor air must be submitted according to national requirements (see chapter 7). No further influences by emissions on the environment and health are known.

2.12 Reference service life
Cured products based on polyurethane or silane-modified polymer fulfil manifold, often specific functions in the construction or refurbishment of building structures. They decisively improve the usability of building structures and significantly extend their original service lives. The anticipated reference service life depends on the specific installation situation and the exposure associated with the product. It can be influenced by weathering as well as mechanical or chemical loads.

2.13 Extraordinary effects

Fire
Even without any special fire safety features, cured products based on polyurethane or silane-modified polymer comply with at least the requirements of *EN 13501-1* standard for fire classes E and Efl. In terms of the volumes applied, they have only a marginal influence on the fire performance characteristics (e.g. smoke gas development) of the building structure in which they have been installed. As crosslinked polyurethane systems do not melt or drip, they do not contribute towards spreading fire.

Water
Cured reactive products based on polyurethane or silane-modified polymer are chemically inert and insoluble in water. They are often used to protect building structures from harmful water ingress or the effects of flooding.

Mechanical destruction
Mechanical destruction of cured reactive products based on polyurethane or silane-modified polymer does not lead to any decomposition products which are harmful to the environment or health.

2.14 Re-use phase
According to present knowledge, no environmentally harmful effects are generally anticipated in landfilling, for example, as a result of de-construction and recycling of building materials with adherent crosslinked products. If the crosslinked products can be removed from construction products without large effort, thermal recovery is a practical recycling variant on account of their energy content. Minor adhesion is not taken into consideration during disposal. It does not interfere with the disposal/recycling of the remaining components/building materials.

2.15 Disposal
Residual material which cannot be used or recycled must be combined at a specified ratio and hardened. Hardened product residue is not special waste. Non-hardened product residue is hazardous waste. Empty, dried containers (free of drops and scraped clean) are directed to the recycling process. Residue must be directed to proper waste disposal taking into consideration the local guidelines. The following waste codes according to the European List of Waste (*2000/532/EC*) can apply:
Hardened product residue:
European Waste Calalogue (EWC) code 080112 (waste paint and varnish with the exception of that mentioned in 08 01 11)
EWC code 080410 (waste adhesives and sealants other than mentioned in 08 04 09)

2.16 Further information
More information is available on the manufacturer's product or safety data sheets and on the manufacturer's websites or on request. Valuable technical information is also available on the associations' websites.

3. LCA: Calculation rules

3.1 Declared Unit
This EPD refers to the declared unit of 1 kg of product based on polyurethane or silane-modified polymer, group 1; applied into the building with a density of 1.25 - 1.8 g/cm³ in accordance with the *IBU PCR* part B for reaction resin products.
The results of the Life Cycle Assessment provided in this declaration have been selected from the product with the highest environmental impact (worst-case scenario).
Depending on the application, a corresponding conversion factor such as the density to convert volumetric use to mass must be taken into consideration.

The Declaration type is according to *EN 15804*: Cradle to gate with options, modules C1–C3, and module D (A1–A3, C, D) and additional modules.

Declared unit

Name	Value	Unit
Declared unit	1	kg
Gross density	1.25 - 1.8	g/cm³
Conversion factor to 1 kg	-	-

3.2 System boundary
Modules A1, A2 and A3 are taken into consideration in the LCA:
- A1 Production of preliminary products
- A2 Transport to the plant
- A3 Production incl. provision of energy, production of packaging as well as auxiliaries and consumables and waste treatment
- A4 Transport to site
- A5 Installation, product applied into the building during A5 phase operations and packaging disposal. This stage considers VOC emissions during the installation phase. The declared product does not contain substances in the formulation that directly emit (as) VOC, but VOCs are generated by a chemical reaction that are occurring during this phase. The end of life for the packaging material considered is described below:
  -Incineration, for materials like plastic and wood.
  -Landfill, for inert material like metals (where used).

-C1-C2-C3-D
The building deconstruction (demolition process) takes place in the C1 module which considers energy production and consumption in terms of diesel and all the emissions connected with the fuel-burning process to run the machines. After the demolition, the product is transported to the end-of-life processing (C2 module) where all the impacts related to the transport processes are considered. For precautionary principle and as a worst-case scenario, thermal treatment is the only end-of-life scenario considered. This is modelled by the incineration process (module C3) where the product ends its life cycle.
Module D accounts for potential benefits that are beyond the defined system boundaries. Credits are generated during the incineration of wastes and related electricity produced that are occurring in the A5 module.

3.3 Estimates and assumptions
For this EPD formulation and production data defined and collected by FEICA were considered. Production

waste was assumed to be disposed of by incineration without credits as a worst-case.
An average of steel and plastic containers, and wooden pallets was considered in the LCA.

3.4 Cut-off criteria
All raw materials submitted for the formulations and production data were taken into consideration.
The manufacture of machinery, plant and other infrastructure required for the production of the products under review was not taken into consideration in the LCA.
Transport of packaging materials is excluded.

3.5 Background data
Data from the *GaBi* database SP40 (2020) was used as background data.

3.6 Data quality
Representative products were applied for this EPD and the product in the group displaying the highest environmental impact was selected for calculating the LCA results. The background data sets used are less than 4 years old.
Production data and packaging are based on details provided by the manufacturer. The formulation used for evaluation refers to a specific product.
The data quality of the background data is considered to be good.

3.7 Period under review
Representative formulations are valid for 2021.

3.8 Allocation
Mass allocation has been applied when primary data have been used and implemented into the LCA model.

3.9 Comparability
Basically, a comparison or an evaluation of EPD data is only possible if all the data sets to be compared were created according to *EN 15804* and the building context, respectively the product-specific characteristics of performance, are taken into account.

The *GaBi* database SP40 (2020) was used.

4. LCA: Scenarios and additional technical information

Characteristic product properties
Information on biogenic Carbon
The packaging material contains biogenic carbon content which is presented below.

Information on describing the biogenic Carbon Content at factory gate

Name	Value	Unit
Biogenic Carbon Content in product	0	kg C
Biogenic Carbon Content in accompanying packaging	0.016	kg C

Transport to the building site (A4)

Name	Value	Unit
Transport distance	1000	km
Gross weight	34 - 40	t
Payload capacity	27	t

Assembly (A5)

Name	Value	Unit
Other resources for packaging material	0.1	kg
Material loss	0.01	kg

Material loss regards the amount of product not used during the application phase into the building. This amount is 1% of the product, impacts related to the production of this part are charged to the A5 module. This percentage is considered as waste to disposal and impacts of its end of life have been considered in the LCA model and declared in A5.

End of life (C1-C3)

Name	Value	Unit
Collected as mixed construction waste	1	kg
Incineration	1	kg

5. LCA: Results

DESCRIPTION OF THE SYSTEM BOUNDARY (X = INCLUDED IN LCA; ND = MODULE OR INDICATOR NOT DECLARED; MNR = MODULE NOT RELEVANT)

PRODUCT STAGE			CONSTRUCTION PROCESS STAGE		USE STAGE							END OF LIFE STAGE				BENEFITS AND LOADS BEYOND THE SYSTEM BOUNDARIES
Raw material supply	Transport	Manufacturing	Transport from the gate to the site	Assembly	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	De-construction demolition	Transport	Waste processing	Disposal	Reuse-Recovery-Recycling-potential
A1	**A2**	**A3**	**A4**	**A5**	**B1**	**B2**	**B3**	**B4**	**B5**	**B6**	**B7**	**C1**	**C2**	**C3**	**C4**	**D**
X	X	X	X	X	ND	ND	MNR	MNR	MNR	ND	ND	X	X	X	ND	X

RESULTS OF THE LCA - ENVIRONMENTAL IMPACT according to EN 15804+A2: 1 kg of product based on polyurethane or silane modified polymer, group 1

Core Indicator	Unit	A1-A3	A4	A5	C1	C2	C3	D
GWP-total	[kg CO_2-Eq.]	4.79E+0	5.27E-2	1.80E-1	2.79E-4	1.24E-2	2.21E+0	-9.50E-1
GWP-fossil	[kg CO_2-Eq.]	4.81E+0	5.22E-2	9.38E-2	2.66E-4	1.18E-2	2.21E+0	-9.47E-1
GWP-biogenic	[kg CO_2-Eq.]	-3.57E-2	1.52E-4	8.62E-2	1.24E-5	5.42E-4	8.82E-5	-2.23E-3
GWP-luluc	[kg CO_2-Eq.]	4.50E-3	4.22E-4	4.84E-5	6.39E-9	2.79E-7	2.08E-5	-6.66E-4
ODP	[kg CFC11-Eq.]	6.76E-9	6.27E-18	6.76E-11	2.84E-20	1.24E-18	2.62E-16	-9.93E-15
AP	[mol H^+-Eq.]	1.02E-2	1.56E-4	1.29E-4	3.60E-6	3.73E-5	1.31E-3	-1.33E-3
EP-freshwater	[kg P-Eq.]	1.93E-5	1.59E-7	1.98E-7	5.75E-11	2.51E-9	4.40E-8	-1.23E-6
EP-marine	[kg N-Eq.]	2.67E-3	6.96E-5	3.50E-5	1.63E-6	1.72E-5	6.31E-4	-3.43E-4
EP-terrestrial	[mol N-Eq.]	2.93E-2	7.80E-4	4.11E-4	1.79E-5	1.89E-4	7.26E-3	-3.68E-3
POCP	[kg NMVOC-Eq.]	9.47E-3	1.38E-4	7.20E-3	4.91E-6	3.39E-5	1.62E-3	-9.87E-4
ADPE	[kg Sb-Eq.]	8.18E-6	3.74E-9	8.22E-8	8.06E-12	3.52E-10	4.65E-9	-1.56E-7
ADPF	[MJ]	1.05E+2	6.94E-1	1.11E+0	3.81E-3	1.66E-1	5.87E-1	-1.61E+1
WDP	[m^3 world-Eq deprived]	1.34E+0	4.66E-4	2.69E-2	5.27E-7	2.30E-5	2.17E-1	-9.86E-2

Caption	GWP = Global warming potential; ODP = Depletion potential of the stratospheric ozone layer; AP = Acidification potential of land and water; EP = Eutrophication potential; POCP = Formation potential of tropospheric ozone photochemical oxidants; ADPE = Abiotic depletion potential for non-fossil resources; ADPF = Abiotic depletion potential for fossil resources; WDP = Water (user) deprivation potential

RESULTS OF THE LCA - INDICATORS TO DESCRIBE RESOURCE USE according to EN 15804+A2: 1 kg of product based on polyurethane or silane modified polymer, group 1

Indicator	Unit	A1-A3	A4	A5	C1	C2	C3	D
PERE	[MJ]	6.67E+0	3.90E-2	6.65E-1	1.20E-5	5.25E-4	8.23E-2	-3.52E+0
PERM	[MJ]	5.85E-1	0.00E+0	-5.85E-1	0.00E+0	0.00E+0	0.00E+0	0.00E+0
PERT	[MJ]	7.26E+0	3.90E-2	7.99E-2	1.20E-5	5.25E-4	8.23E-2	-3.52E+0
PENRE	[MJ]	8.33E+1	6.95E-1	1.63E+0	3.81E-3	1.67E-1	2.21E+1	-1.61E+1
PENRM	[MJ]	2.20E+1	0.00E+0	-5.20E-1	0.00E+0	0.00E+0	-2.15E+1	0.00E+0
PENRT	[MJ]	1.05E+2	6.95E-1	1.11E+0	3.81E-3	1.67E-1	5.87E-1	-1.61E+1
SM	[kg]	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0
RSF	[MJ]	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0
NRSF	[MJ]	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0
FW	[m^3]	4.03E-2	4.52E-5	7.22E-4	2.16E-8	9.41E-7	5.11E-3	-4.08E-3

Caption	PERE = Use of renewable primary energy excluding renewable primary energy resources used as raw materials; PERM = Use of renewable primary energy resources used as raw materials; PERT = Total use of renewable primary energy resources; PENRE = Use of non-renewable primary energy excluding non-renewable primary energy resources used as raw materials; PENRM = Use of non-renewable primary energy resources used as raw materials; PENRT = Total use of non-renewable primary energy resources; SM = Use of secondary material; RSF = Use of renewable secondary fuels; NRSF = Use of non-renewable secondary fuels; FW = Use of net fresh water

RESULTS OF THE LCA – WASTE CATEGORIES AND OUTPUT FLOWS according to EN 15804+A2: 1 kg of product based on polyurethane or silane modified polymer, group 1

Indicator	Unit	A1-A3	A4	A5	C1	C2	C3	D
HWD	[kg]	1.12E-5	3.23E-8	1.12E-7	3.70E-13	1.62E-11	3.34E-10	-6.41E-9
NHWD	[kg]	1.66E-1	1.06E-4	4.75E-2	3.90E-7	1.70E-5	1.11E-2	-7.44E-3
RWD	[kg]	2.34E-3	8.60E-7	2.54E-5	4.09E-9	1.79E-7	2.37E-5	-1.20E-3
CRU	[kg]	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0
MFR	[kg]	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0
MER	[kg]	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0
EEE	[MJ]	0.00E+0	0.00E+0	2.12E-1	0.00E+0	0.00E+0	0.00E+0	0.00E+0
EET	[MJ]	0.00E+0	0.00E+0	3.86E-1	0.00E+0	0.00E+0	0.00E+0	0.00E+0

Caption	HWD = Hazardous waste disposed; NHWD = Non-hazardous waste disposed; RWD = Radioactive waste disposed; CRU = Components for re-use; MFR = Materials for recycling; MER = Materials for energy recovery; EEE = Exported electrical energy; EEE = Exported thermal energy

RESULTS OF THE LCA – additional impact categories according to EN 15804+A2-optional: 1 kg of product based on polyurethane or silane modified polymer, group 1

Indicator	Unit	A1-A3	A4	A5	C1	C2	C3	D
PM	[Disease Incidence]	ND	ND	ND	ND	ND	ND	ND
IRP	[kBq U235-Eq.]	ND	ND	ND	ND	ND	ND	ND
ETP-fw	[CTUe]	ND	ND	ND	ND	ND	ND	ND
HTP-c	[CTUh]	ND	ND	ND	ND	ND	ND	ND
HTP-nc	[CTUh]	ND	ND	ND	ND	ND	ND	ND
SQP	[-]	ND	ND	ND	ND	ND	ND	ND
Caption	PM = Potential incidence of disease due to PM emissions; IR = Potential Human exposure efficiency relative to U235; ETP-fw = Potential comparative Toxic Unit for ecosystems; HTP-c = Potential comparative Toxic Unit for humans (cancerogenic); HTP-nc = Potential comparative Toxic Unit for humans (not cancerogenic); SQP = Potential soil quality index							

Potential Human exposure efficiency relative to U235, Disclaimer 1 – This impact category deals mainly with the eventual impact of low dose ionizing radiation on human health of the nuclear fuel cycle. It does not consider effects due to possible nuclear accidents, occupational exposure or radioactive waste disposal in underground facilities. Potential ionizing radiation from the soil, radon and (from) some construction materials is also not measured by this indicator.

ADP minerals & metals, ADP fossil, WDP, ETF-fw, HTP-c, HTP-nc, SQP, Disclaimer 2 – The results of this environmental impact indicator shall be used with care as the uncertainties on these results are high or as there is limited experience with the indicator.

Additional environmental impact indicators (suggested by *EN15804*, table 4) are not declared in the EPD. The results of this environmental impact indicator shall be used with care as the uncertainties on these results are high and as there is limited experience with the indicator (see ILCD classification in EN 15804, table 5). For this reason, results based on these indicators are not considered suitable for a decision-making process and are thus not declared in the EPD.

6. LCA: Interpretation

The majority of impacts are associated with the production phase (A1-A3). The most significant contribution to the production phase impacts is the upstream production of raw materials as the main driver. Another substantial contributor in the production phase, in the category of Abiotic depletion potential for nonfossil resources (ADPminerals& metals), is the steel sheet used as a packaging material. Emissions associated with the manufacturing of products also have some influence on the Formation potential of tropospheric ozone (POCP) in the production phase. In all EPDs, CO_2 is the most important contributor to Global Warming Potential (GWP). For the Acidification Potential (AP), NOx and SO_2 contribute the largest share. In some cases, HCl in water also impacts AP due to the use of TiO_2 as a pigment.
The majority of life cycle energy consumption takes place during the production phase (A1-A3). Significant contributions to Primary Energy Demand – Non-renewable (PENRT) come from the energy resources used in the production of raw materials. The largest contributor to Primary Energy Demand – Renewable (PERT) impacts comes from the consumption of renewable energy resources required for the generation and supply of electricity. It should be noted that Primary Energy Demand – Renewable (PERT) generally represents a small percentage of the production phase primary energy demand with the bulk of the demand coming from non-renewable energy resources.
Transportation to the construction site (A4) and the installation process (A5) make a low contribution to all impacts.
The installation phase influences mainly the Photochemical ozone formation indicator, due to the emission of VOC during the operations. These emissions are not directly related to the pre-products in the resins, but they are related to the reaction products between pre-products and air components (water and oxygen).
The end-of-life phases influence climate change indicators, due to the incineration processes occurring in the C3 module, the process used for modelling the thermal treatment process of the resin.

7. Requisite evidence

VOC
Special tests and evidence have not been carried out or provided within the framework of drawing up this Model EPD. Some member states require special documentation on VOC emissions into indoor air for specific areas of application. This documentation, as well as documentation for voluntary VOC labelling, has to be provided separately and is specific for product in question.

Evidence pertaining to VOC emissions shall show
- either an attestation of compliance with,
- or documentation of test data that are required in any of the existing regulations or in any of the existing voluntary labelling programs for low-emitting products, as far as these

(1) include limits for the parameters TVOC, TSVOC, carcinogens, formaldehyde, acetaldehyde, LCI limits for individual substances (including but not limited to the European list of harmonized LCIs), and the R value;
(2) base their test methods on *EN 16516*;
(3) perform testing and apply the limits after 28 days of storage in a ventilated test chamber, under the conditions specified in *EN 16516*; some regulations

and programs also have limits after 3 days, on top of the 28 days limits;
(4) express the test results as air concentrations in the European Reference Room, as specified in *EN 16516*.

Examples of such regulations are the *Belgian Royal Decree C-2014/24239*, or the *German AgBB/* ABG. Examples of such voluntary labelling programs are *EMICODE*, *Blue Angel* or *Indoor Air Comfort*.

Relevant test results shall be produced either by an *ISO 17025* accredited commercial test lab or by a qualified internal test lab of the manufacturer.
Examples for the applied limits after 28 days of storage in a ventilated test chamber are:

- TVOC: 1000 µg/m³
- TSVOC: 100 µg/m³
- Each carcinogen: 1 µg/m³
- Formaldehyde: 100 µg/m³
- LCI: different per substance involved
- R value: 1 (meaning that, in total, 100 % of the combined LCI values must not be exceeded).

Informative Annexes (2 tables):
Table 1 shown below is an overview of the most relevant regulations and specifications as of October 2021, as regards requirements after 3 days of storage in a ventilated test chamber.
Table 2 provides an overview of the most relevant regulations and specifications as of October 2021, as regards requirements after 28 days of storage in a ventilated test chamber. Some details may be missing in the table due to lack of space. Values given represent maximum values/limits.

	TVOC µg/m³	Sum of carcinogens. C1A,CA2 µg/m³	Formaldehyde µg/m³	Acetaldehyde µg/m³	Sum of Form- and Acetaldehyde
German AgBB/ABG regulation	10 000	10	-/-	-/-	-/-
Belgian regulation	10 000	10	-/-	-/-	-/-
EMICODE EC1	1 000	10	50	50	50 ppb
EMICODE EC1 *PLUS*	750	10	50	50	50 ppb

	TVOC µg/m³	TSVOC µg/m³	Each carcinogen C1A,CA2 µg/m³	Formalde-hyde µg/m³	Acetalde-hyde µg/m³	LCI	R value	Specials	Sum of non-LCI & non-identified µg/m³
Belgian regulation	1000	100	1	100	200	Belgian list	1	Toluene 300 µg/m³	-/-
French regulations class A+	1000	-/-	-/-	10	200	-/-	-/-	List of 8 VOCs, 4 CMR	-/-
French regulations class A	1500	-/-	-/-	60	300	-/-	-/-	List of 8 VOCs, 4 CMR	-/-
French regulations class B	2000	-/-	-/-	120	400	-/-	-/-	List of 8 VOCs, 4 CMR	-/-
French regulations class C	>2000	-/-	-/-	>120	>400	-/-	-/-	List of 8 VOCs, 4 CMR	-/-
German DIBt/AgBB regulation	1000	100	1	100	300	German AgBB list	1	-/-	100
EMICODE EC1	100	50	1	(after 3 days)	(after 3 days)	-/-	-/-	-/-	-/-
EMICODE EC1 *PLUS*	60	40	1	(after 3 days)	(after 3 days)	German AgBB list	1	-/-	40
Finnish M1, sealants	20	-/-	1	10	300	EU LCI list	-/-	Ammonia, odour	-/-
Finnish M1, adhesives	200 µg/m²h	-/-	5 µg/m²h	50 µg/m²h	300	EU LCI list	-/-	Ammonia, odour	-/-

8. References

ETAG 033
Liquid applied bridge deck waterproofing kits

ISO 48-4

ISO 48-4:2018, Rubber, vulcanized or thermoplastic - Determination of hardness- Part 4: Indentation hardness by durometer method (Shore hardness)

EN ISO 717-1
EN ISO 717-1:2020 Acoustics - Rating of sound insulation in buildings and of building elements - Part 1: Airborne sound insulation

EN 1062-3
EN 1062-3:2008-04, Paints and varnishes - Coating materials and coating systems for exterior masonry and concrete - Part 3: Determination of liquid water permeability

EN 1062-6
EN 1062-6:2002-10, Paints and varnishes - Coating materials and coating systems for exterior masonry and concrete - Part 6: Determination of carbon dioxide permeability

EN 1279-4
EN 1279-4:2002 Glass in building - Insulating glass units - Part 4: Methods of test for the physical attributes of edge seals

EN 1504-2
EN 1504-2:2004-12, Products and systems for the protection and repair of concrete structures - Definitions, requirements, quality control and evaluation of conformity - Part 2: Surface protection systems for concrete

EN 1504-4
EN 1504-4:2004-11, Products and systems for the protection and repair of concrete structures - Definitions, requirements, quality control and evaluation of conformity- Part 4: Structural bonding

EN 1504-5
EN 1504-5:2004-12, Products and systems for the protection and repair of concrete structures - Definitions, requirements, quality control and evaluation of conformity - Part 5: Concrete injection

EN 1542
EN 1542:1999-07, Products and systems for the protection and repair of concrete structures - Test methods - Measurement of bond strength by pull-off

EN 1771
EN 1771:2004-11, Products and systems for the protection and repair of concrete structures - Test methods - Determination of injectability and splitting test

ISO 2811-1
ISO 2811-1:2016, Paints and varnishes - Determination of density - Part 1: Pycnometer method

EN ISO 3219
EN ISO 3219:1994-10, Plastics - Polymers/resins in the liquid state or as emulsions or dispersions - Determination of viscosity using a rotational viscometer with defined shear rate

ISO 3219-2
ISO 3219-2:2021, Rheology - Part 2: General principles of rotational and oscillatory rheometry

EN ISO 7783
EN ISO 7783:2019-02, Paints and varnishes - Determination of water-vapour transmission properties - Cup method

EN 12004
EN12004:2012, Adhesives for ceramic tiles

EN 12004-1
EN 12004-1:2017, Adhesives for ceramic tiles – Part 1: Requirements, assessment and verification of constancy of performance, classification and marking

EN 12004-2
EN 12004-2:2017, Adhesives for ceramic tiles - Part 2: Test methods

EN 13501-1
EN 13501-1:2018, Fire classification of construction products and building elements - Part 1: Classification using data from reaction to fire tests

EN 13813
EN 13813:2002-10, Screed material and floor screeds - Screed materials - Properties and requirements

EN 13892-8
EN 13892:2003-02, Methods of test for screed materials - Part 8: Determination of bond strength

ISO 14025
DIN EN ISO 14025:2011-10, Environmental labels and declarations — Type III environmental declarations — Principles and procedures

EN 14891
EN 14891:2012-04, Liquid applied water impermeable products for use beneath ceramic tiling - Definitions, specifications and test methods

EN 15804
EN 15804:2019+A2, Sustainability of construction works — Environmental Product Declarations — Core rules for the product category of construction products

EN 16516
EN 16516:2017
Construction products - Assessment of release of dangerous substances - Determination of emissions into indoor air

EN ISO 17025
EN ISO 17025:2018-03
General requirements for the competence of testing and calibration laboratories

EN ISO 17178
EN ISO 17178:2020-06, Adhesives - Adhesives for bonding parquet to subfloor - Test methods and minimum requirements

EN 17333-2
EN 17333-2:2020+AC:2020, Characterisation of one component foam - Part 2: Expansion characteristics

EN 17333-3
EN 17333-3:2020, Characterisation of one component foam - Part 3: Application

EN 17333-4
EN 17333-4:2020, Characterisation of one component foam - Part 4: Mechanical strength

EN 17333-5
EN 17333-5:2020, Characterisation of one component foam - Part 5: Insulation

EN ISO 22636
EN ISO 22636:2020, Adhesives - Adhesives for floor coverings - Requirements for mechanical and electrical performance

EAD 030350-00-0402
EAD 030350-00-0402:2018-08**,** Liquid Applied Roof Waterproofing Kits

EAD 030352-00-0503
EAD 030352-00-0503:2019-01, Liquid applied watertight covering kits for wet room floors and/or walls

2000/532/EC
Commission decision dated 3 May 2000 replacing decision 94/3/EC on a waste directory in accordance with Article 1 a) of Council Directive 75/442/EEC on waste and Council decision 94/904/EC on a directory of hazardous waste in terms of Article 1, paragraph 4 of Directive 91/689/EEC on hazardous waste

Belgian Royal Decree C-2014/24239
Belgisch Staatsblad 8 MEI 2014, p. 60603. — Koninklijk besluit tot vaststelling van de drempelniveaus voor de emissies naar het binnenmilieu van bouwproducten voor bepaalde geoogde gebruiken

Blue Angel
Environmental label organised by the federal government of Germany www.blauer-engel.de

CPR
CPR Regulation (EU) No 305/2011 of the European Parliament and of the Council of 9 March 2011 laying down harmonised conditions for the marketing of construction products and repealing Council Directive 89/106/EEC

Decopaint Directive
Directive 2004/42/CE of the European Parliament and the council of 21 April 2004 on the limitation of emissions of volatile organic compounds due to the use of organic solvents in certain paints and varnishes and vehicle refinishing products and amending Directive 1999/13/EC

EMICODE
EMICODE, GEV – Gemeinschaft Emissionskontrollierte Verlegewerkstoffe, Klebstoffe und Bauprodukte e. V. (pub.).www.emicode.de

GaBi 10 software & documentation
Data base for Life Cycle Engineering LBP, University of Stuttgart and Sphera, documentation of GaBi 10 data sets http://documentation.gabi-software.com/, 2020

German AgBB
Committee for Health-related Evaluation of Building Products: health-related evaluation of emissions of volatile organic compounds (VOC and SVOC) from building products; status: June 2012 www.umweltbundesamt.de/produkte/bauprodukte/agbb.htm

IBU 2021
Institut Bauen und Umwelt e.V.: General Instructions for the EPD programme of Institut Bauen und Umwelt e.V. EPD programme. Version 2.0. Berlin: Institut Bauen und Umwelt e.V., 2021 www.ibu-epd.com

ift-Guideline VE-08/4
ift-Guideline VE-08/4:2017, Beurteilungsgrundlage für geklebte Verglasungssysteme

Indoor Air Comfort
Product certification by Eurofins, Hamburg, Germany www.eurofins.com

PCR Part A
Product Category Rules for Building-Related Products and Services, Part A: Calculation Rules for the Life Cycle Assessment and Requirements on the Project report, Version 1.1, Institut Bauen und Umwelt e.V., 2021-01

PCR Part B
Product Category Rules for Construction Products, Part B: Reaction resin products, Institut Bauen und Umwelt e.V., 2019-01

RAL-GZ 716
RAL-GZ 716:2019-04 part 2, Kunststoff-Fensterprofilsysteme - Gütesicherung

REACH
Directive (EG) No. 1907/2006 of the European Parliament and of the Council dated 18 December 2006 on the registration, evaluation, approval and restriction of chemical substances (REACH), for establishing a European Agency for chemical substances, for amending Directive 1999/45/EC and for annulment of Directive (EEC) No. 793/93 of the Council, Directive (EC) No. 1488/94 of the Commission, Guideline 76/769/EEC of the Council and Guidelines 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC of the Commission.

Publisher
Institut Bauen und Umwelt e.V.
Hegelplatz 1
10117 Berlin
Germany

Tel +49 (0)30 3087748- 0
Fax +49 (0)30 3087748- 29
Mail info@ibu-epd.com
Web **www.ibu-epd.com**

Programme holder
Institut Bauen und Umwelt e.V.
Hegelplatz 1
10117 Berlin
Germany

Tel +49 (0)30 - 3087748- 0
Fax +49 (0)30 – 3087748 - 29
Mail info@ibu-epd.com
Web **www.ibu-epd.com**

Author of the Life Cycle Assessment
Sphera Solutions GmbH
Hauptstraße 111- 113
70771 Leinfelden-Echterdingen
Germany

Tel +49 711 341817-0
Fax +49 711 341817-25
Mail info@sphera.com
Web **www.sphera.com**

Owner of the Declaration
Industrieverband Klebstoffe e.V
Völklinger Straße 4
40219 Düsseldorf
Germany

Tel +49 (0)211 67931-10
Fax +49 (0)211 67931-33
Mail info@klebstoffe.com
Web **www.klebstoffe.com**

FEICA - Association of the European Adhesive and Sealant Industry
Avenue E. van Nieuwenhuyse 2
B-1160 Brussels
Belgium

Tel +32 (0)267 673 20
Fax +32 (0)267 673 99
Mail info@feica.eu
Web **www.feica.eu**

EFCC - European Federation for Construction Chemicals
Boulevard du Triomphe 172
1160 Brussels
Belgium

Tel +32289720-39
Fax +32289720-37
Mail info@efcc.be
Web **www.efcc.eu**

Deutsche Bauchemie e.V.
Mainzer Landstr. 55
60329 Frankfurt
Germany

Tel +49 (0)69 2556-1318
Fax +49 (0)69 2556-1319
Mail info@deutsche-bauchemie.de
Web **www.deutsche-bauchemie.de**

OTTOCOLL® M 500

Nachhaltigkeitsdatenblatt

Prüfungen/Zulassungen

- EMICODE® EC 1 PLUS – sehr emissionsarm

- Französische VOC-Emissionsklasse A+

- Deklaration in Baubook Österreich

  Informationen unter: www.baubook.info

- Umweltproduktdeklaration (EPD)

  Deklarationsnummer: EPD-FEI-20220021-IBG1-EN

Gebäudezertifizierungssysteme

QNG - Qualitätssiegel Nachhaltiges Gebäude

Version 1.3

Kriterium	Schadstoffvermeidung in Baumaterialien
Übersichtstabelle	4. Kleb- und Dichtstoffe - Zeile 4.2
Bauproduktgruppe	Bauseitig verarbeitete Kleb- und Dichtstoffe auf Basis von PU-, PU-Hybrid- und SMP-Rezepturen (silanmodifizierte Polymere) in Innenräumen
Anforderungen	Produktdokumentation und Deklaration enthaltener SVHC > 0,1 % und Chlorparaffine, TCEP, PBB und PBDE ≤ 0,1 % und lösemittelfrei oder GISCODE PU10, PU20, PU40 (ALT) bzw. PU50 (ALT)
Einstufung	**Erfüllt die Anforderungen, da Deklaration enthaltener SVHC > 0,1 % und Chlorparaffine, TCEP, PBB und PBDE ≤ 0,1 % und lösemittelfrei.**

Hermann Otto GmbH · Krankenhausstr. 14 · 83413 Fridolfing, DEUTSCHLAND
Tel.:+49 8684-908-0 · Fax: +49 8684-12-60
E-Mail: info@otto-chemie.de · Internet: www.otto-chemie.de

DICHTEN & KLEBEN

DGNB – Deutsche Gesellschaft für Nachhaltiges Bauen

Version 2023

Kriterium	ENV 1.2 Risiken für die lokale Umwelt	
Kriterienmatrix	Zeile 11	
Produkttyp	Dichtungsmassen, Dichtstoffe, Klebstoffe für punkt- und linienförmige Verklebungen von Bauteilen im Innnenraum: - mechanisch belastete Fugen - Sockelleisten - Türschienen - Stützenkleber (Doppel- oder Hohlboden) - Lüftungskanäle Gemeint sind Acrylklebstoffe/-kleber, Silikondichtstoffe, PU-Kleber und silanmodifizierte Polymere (SMP)	
Anforderungen	Qualitätsstufe 1 (niedrig)	GISCODE PU10, PU20, RS10, DA20, DSE20, DSA20, DSO20 oder DH20 und Bonuspunkte SVHC ≤ 0,1 %
	Qualitätsstufe 2	GISCODE PU10, PU20, RS10, DA20, DSE20, DSA20, DSO20 oder DH20 und Bonuspunkte SVHC ≤ 0,1 %
	Qualitätsstufe 3	GISCODE PU10, PU20, RS10, DA20, DSE20, DSA20, DSO20 oder DH20 und EMICODE® EC 1PLUS und Bonuspunkte SVHC ≤ 0,1 %
	Qualitätsstufe 4 (hoch)	GISCODE PU10, PU20, RS10, DA20, DSE20, DSA20, DSO20 oder DH20 und EMICODE® EC 1PLUS und Bonuspunkte SVHC ≤ 0,1 %
Einstufung	**Erfüllt die Anforderungen an Qualitätsstufe 4, da GISCODE RS10 und EMICODE® EC 1PLUS und SVHC ≤ 0,1 %.**	

DGNB – Deutsche Gesellschaft für Nachhaltiges Bauen

Version 2018

Kriterium	ENV 1.2 Risiken für die lokale Umwelt	
Kriterienmatrix	Zeile 11	
Produkttyp	Dichtungsmassen, Dichtstoffe, Klebstoffe für punkt- und linienförmige Verklebungen von Bauteilen im Innenraum. Gemeint sind PU-Kleber und silanmodifizierte Polymere (SMP).	
Anforderungen	Qualitätsstufe 1 (niedrig)	GISCODE PU20 oder RS10
	Qualitätsstufe 2	GISCODE PU20 oder RS10
	Qualitätsstufe 3	GISCODE PU20 oder RS10 und EMICODE® EC 1 oder EC 1 PLUS
	Qualitätsstufe 4 (hoch)	GISCODE PU20 oder RS10 und EMICODE® EC 1 oder EC 1 PLUS
Einstufung	**Erfüllt die Anforderungen an Qualitätsstufe 4, da GISCODE RS10 und EMICODE® EC 1 PLUS.**	

DGNB – Deutsche Gesellschaft für Nachhaltiges Bauen

Version 2018

Kriterium	ENV 1.2 Risiken für die lokale Umwelt	
Kriterienmatrix	Zeile 12	
Produkttyp	Dichtungsmassen, Dichtstoffe, Klebstoffe für punkt- und linienförmige Verklebungen von Bauteilen im Innenraum und Lüftungskanälen im Gebäudeinneren. Gemeint sind Acrylatdichtstoffe/-kleber, Silikondichtstoffe und SMP-(Hybrid-Dichtstoffe).	
Anforderungen	Qualitätsstufe 1 (niedrig)	–
	Qualitätsstufe 2	Keine im SDB deklarierten Chlorparaffine
	Qualitätsstufe 3	Chlorparaffine < 0,1 %
	Qualitätsstufe 4 (hoch)	Chlorparaffine < 0,1 %, Lösemittel < 1 % und KWS-Weichmacher < 0,1 %
Einstufung	**Erfüllt die Anforderungen an Qualitätsstufe 4, da Chlorparaffine < 0,1 %, Lösemittel < 1 % und KWS-Weichmacher < 0,1 %.**	

Hermann Otto GmbH · Krankenhausstr. 14 · 83413 Fridolfing, DEUTSCHLAND
Tel.:+49 8684-908-0 · Fax: +49 8684-12-60
E-Mail: info@otto-chemie.de · Internet: www.otto-chemie.de

DICHTEN & KLEBEN

BNB – Bewertungssystem Nachhaltiges Bauen

Version 2015

Kriterium	1.1.6 Risiken für die lokale Umwelt	
Übersichtstabelle	6. Kleb- und Dichtstoffe – Zeile 8	
Bauprodukttyp	Kleb- und Dichtstoffe aus PU, SMP (silanmodifizierte Polymere), Acrylat (einschließlich Dispersionsklebstoffe) oder Silikon für punkt- und linienförmige Verklebungen und Abdichtungen im Innenraum inkl. TGA.	
Anforderungen	Qualitätsniveau 1 (niedrig)	Dokumentation, Deklaration enthaltener SVHC > 0,1 % und Deklaration biozider Wirkstoffe (sofern eingesetzt).
	Qualitätsniveau 2	Deklaration biozider Wirkstoffe (sofern eingesetzt) und Deklaration enthaltener SVHC > 0,1 % und Chlorparaffine < 0,1 %. Für PU-Klebstoffe gilt zusätzlich: GISCODE PU10 oder PU20 und TCEP < 0,1 %.
	Qualitätsniveau 3	Deklaration biozider Wirkstoffe (sofern eingesetzt) und Deklaration enthaltener SVHC > 0,1 % und Chlorparaffine < 0,1 %. Für PU-Klebstoffe gilt zusätzlich: GISCODE PU10 oder PU20 und TCEP < 0,1 %.
	Qualitätsniveau 4	Keine amin- oder oximvernetzenden Silikone. Zusätzlich gilt: RAL-UZ 123 oder EMICODE® EC 1/EC 1 PLUS und Chlorparaffine < 0,1 % und Deklaration biozider Wirkstoffe (sofern eingesetzt) und Deklaration enthaltener SVHC > 0,1 %. Für PU-Klebstoffe gilt zusätzlich: TCEP < 0,1 %.
	Qualitätsniveau 5 (hoch)	Keine amin- oder oximvernetzenden Silikone. Zusätzlich gilt: RAL-UZ 123 oder EMICODE® EC 1/EC 1 PLUS und Chlorparaffine < 0,1 % und Deklaration biozider Wirkstoffe (sofern eingesetzt) und Deklaration enthaltener SVHC > 0,1 %. Für PU-Klebstoffe gilt zusätzlich: TCEP < 0,1 %.
Einstufung	**Erfüllt die Anforderungen an Qualitätsniveau 5, da kein amin- oder oximvernetzendes Silikon und EMICODE® EC1 PLUS und Deklaration der bioziden Wirkstoffe (sofern eingesetzt) und Deklaration enthaltener SVHC > 0,1 % und Chlorparaffine < 0,1 %.**	
Dokumentations-unterlagen	Alle aufgeführten Dokumente stehen auf www.otto-chemie.de zum Download bereit 1. Technisches Datenblatt 2. Sicherheitsdatenblatt 3. Nachhaltigkeitsdatenblatt 4. Prüfzeugnisse 5. Umweltproduktdeklaration	

Diese Angaben basieren auf unserem Wissen zum Zeitpunkt der Erstellung (siehe unten). Die aktuelle Version ist auf unserer Website unter www.otto-chemie.de einsehbar. Darüber hinaus gelten die Angaben in den produktbegleitenden Dokumenten.

Hermann Otto GmbH · Krankenhausstr. 14 · 83413 Fridolfing, DEUTSCHLAND
Tel.:+49 8684-908-0 · Fax: +49 8684-12-60
E-Mail: info@otto-chemie.de · Internet: www.otto-chemie.de

DICHTEN & KLEBEN

Gemeinschaft Emissionskontrollierte Verlegewerkstoffe, Klebstoffe und Bauprodukte e.V.

GEV
EMICODE®

Lizenzerteilung zur Führung des EMICODE

Lizenzierungs-Nummer:	10891/10.10.13
Für den Artikel	OTTOCOLL® M 500
der Firma	Hermann Otto GmbH
wird auf Antrag vom	01.10.2019

unter Bezugnahme auf die Einstufung gemäß den nach § 10 der GEV-Zeichensatzung festgelegten Richtlinien

namens der Gemeinschaft Emissionskontrollierte Verlegewerkstoffe, Klebstoffe und Bauprodukte e.V. für den oben genannten Artikel nach § 5 Abs. 4 der GEV-Zeichensatzung die Lizenz zur Führung des GEV-Zeichens

GEV-EMICODE®
EC 1 PLUS
sehr emissionsarm

erteilt. Damit erfüllt dieser Artikel die rückseitig aufgeführten Kriterien.
Die Firma ist ordentliches Mitglied der GEV.

OM098 01.10.2024
gültig bis 01.10.2029

Der Geschäftsführer
Gemeinschaft Emissionskontrollierte Verlegewerkstoffe,
Klebstoffe und Bauprodukte e.V.
Völklinger Straße 4 · D-40219 Düsseldorf

Hinweise zu den Voraussetzungen über die Vergabe der Lizenz für den EMICODE

Das gemäß vorseitiger Lizenz eingestufte Produkt hat nach der Satzung und den Richtlinien des Technischen Beirats der GEV u.a. den folgenden Kriterien zu genügen:

- Das Produkt entspricht allen gesetzlichen Bestimmungen, insbesondere denen des Chemikalienrechtes und seiner Verordnungen.
- Das Produkt ist nach der Definition der TRGS 610 lösemittelfrei, sofern es sich nicht um ein Oberflächenprodukt handelt. Soweit es einer Produktgruppe nach GISCODE zuzuordnen ist, wird diese angegeben.
- Für das Produkt wird ein Sicherheitsdatenblatt nach lokalem Recht in der jeweils aktuellen Fassung erstellt.
- Krebserregende, erbgutverändernde oder fruchtschädigende Stoffe der Klassen 1A und 1B werden dem Produkt bei der Herstellung nicht zugesetzt.
- Die Prüfung des Produktes erfolgt nach der definierten „GEV-Prüfmethode“. Die VOC-Bestimmung wird dabei in einer Prüfkammer nach dem Tenax-Thermodesorptions-Verfahren mit nachgeschalteter GC/MS-Analyse durchgeführt.
- Die Einstufung in EMICODE-Klassen erfolgt entsprechend den nachstehenden Bezeichnungen und TVOC/TSVOC-Konzentrationsbereichen. Zur Produktkennzeichnung ist die zutreffende EMICODE-Klasse zu verwenden:

1) Verlegewerkstoffe, Klebstoffe und Bauprodukte

Parameter	EC 1PLUS	EC 1	EC 2
	max. zulässige Konzentration [µg/m³]		
TVOC nach 3 Tagen	≤ 750	≤ 1000	≤ 3000
TVOC nach 28 Tagen	≤ 60	≤ 100	≤ 300
TSVOC nach 28 Tagen	≤ 40	≤ 50	≤ 100
R-Wert basierend auf AgBB-NIK-Werten nach 28 Tagen	≤ 1	-	-
Summe der nicht bewertbaren VOC	≤ 40	-	-
Formaldehyd nach 3 Tagen	≤ 50	≤ 50	≤ 50
Acetaldehyd nach 3 Tagen	≤ 50	≤ 50	≤ 50
Summe von Form- und Acetaldehyd	≤ 0,05 ppm	≤ 0,05 ppm	≤ 0,05 ppm
Summe von flüchtigen K1A/K1B Stoffen nach 3 Tagen	< 10	< 10	< 10
Jeder flüchtige K1A/K1B Stoff nach 28 Tagen	< 1	< 1	< 1

2) Oberflächenbehandlungsmittel für Parkett, mineralische Böden und elastische Bodenbeläge

Parameter	EC 1PLUS	EC 1	EC 2
	max. zulässige Konzentration [µg/m³]		
Summe TVOC + TSVOC nach 28 Tagen	≤ 100 davon max. 40 SVOC	≤ 150 davon max. 50 SVOC	≤ 400 davon max. 100 SVOC
Formaldehyd nach 3 Tagen	≤ 50	≤ 50	≤ 50
Acetaldehyd nach 3 Tagen	≤ 50	≤ 50	≤ 50
Jeder flüchtige K1A/K1B Stoff nach 3 Tagen	< 10	< 10	< 10
Jeder flüchtige K1A/K1B Stoff nach 28 Tagen	< 1	< 1	< 1