

Permanently
sealed

More information
from specialist suppliers

Heat and steam
leave it cold

The OTTOFLEX system consists of

Adhesive primer
Deep Primer
Primer
Protective Coating
Slurry Seal Coating
Sealing Strip
Sealing Tape
Project Sealing Tape
Floor Sealing Sleeve
Exterior Corner Tapes
Interior Corner Tapes
Wall Sealing Sleeve
Flexible Sealing Sleeve

Supplier's stamp

Index: 9999599-GB-01.10.2014
© Hermann Otto GmbH 2014

Notes:

The information in the present document corresponds to the status quo on going to print, refer to the index. With a new edition this edition becomes invalid. Due to the many possible influences during and after application, the customer always has to carry out trials first. Please observe the respective technical data sheet! This information is available on the Internet at www.otto-chemie.com. Errors and typographical errors are excepted.

Find out about the other OTTO products for sealing and bonding at www.otto-chemie.com

**OTTO
CHEMIE**

Sealants • Adhesives

Hermann Otto GmbH · Krankenhausstr. 14 · 83413 Fridolfing, GERMANY
Tel.: 0049-8684-908-0 · Fax: 0049-8684-1260
E-Mail info@otto-chemie.de · www.otto-chemie.com

OTTO accessories
for professionals

Cleaner
Primer
Back-up foam rods/
back-filling material
Hand-operated guns
Smoothing Agent
Fugenboy
Silicone remover



**The sauna and
steam bath silicone**

**OTTO
CHEMIE**
Sealants • Adhesives

Much more than hot air

OTTOSEAL® S73

Damp and hot with hardly ever a possibility to get fresh air in through a window?


The sauna and steam bath silicone OTTOSEAL® S73 can be used under the most extreme conditions.

In saunas it braves tropical heat and humidity through its high resistance to steam.

Mould is being held back by the fungicide it contains and with its high

resistance to chemical cleaning substances and to scratching OTTOSEAL® S73 stands up against frequent cleaning and disinfection with chemical solutions.

The best choice for natural stone saunas and steam baths.



The most important features at a glance

Characteristics:

- 1-component acetate-curing silicone sealant
- Very good steam and humidity resistance
- High resistance to notches, tension and tearing
- Very fast curing
- Excellent weathering, ageing and UV-resistance
- Contains fungicides
- Very good resistance towards essential oils

Fields of application:

Elastic jointing in steam rooms and saunas in connection with various materials such as natural stone, ceramic, sanitary-acryl, fibre-reinforced plastic

Standards and tests:

Conform to LEED® IEQ-credits 4.1 (Indoor Environmental Quality) adhesives and sealants

Fulfills DGNB-characteristics 06 (DGNB e.V. = German Organisation for sustainable building)

Suitable for applications according to IVD instruction sheet no. 31 (IVD = German industry association sealants)

French VOC-emission class A+

Certified according to GOS

