OTTO Accumulator gun 2K AP 400 |



The Accumulator gun for 2-component systems

2K AP 400

Characteristics

- > Powerful accumulator gun for 2-component products
- Specifically for using 490 ml side-by-side plastic cartridges with a mixing ratio of 10:1 in the MIXPAC™ C-, F- and BlueLine system or ACF system
- Includes 2 Li-lon batteries, 18 volts / 2.0 Ah with state of charge indicator
- Quick charger with state of charge indicator (charge time approx. 30 minutes)
- Practical side loader in a lightweight skeleton design with exchangeable retaining bridges to securely hold the cartridge systems
- > Exchangeable plunger for other mixing ratios (1:1, 2:1, 4:1 and 10:1)
- > For easy transport in a practical carrying bag
- > Conform to RoHS
- > CE-compliant

Standards and tests

- Machinery Directive: 2006/42/EC
- > EMV guideline: 2014/30/EU
- > RoHS directive 2011/65/EU
- > Applied standards for these guidelines can be found in the declaration of conformity at the end of the operating instructions

Technical properties

Mixture ratio	10:1
Thrust force [kN]	5
Advance rate [mm/min.]	20 - 230
Length [mm]	477
Width [mm]	114
Height [mm]	283
Weight [kg]	3,74

Important information

Please read the enclosed operating instructions with the safety instructions before commissioning.

Packaging

Order unit (OU)	Order code
1 piece	2KAP400

Disposal

Hermann Otto GmbH

Krankenhausstr. 14 | 83413 Fridolfing, Germany & +49 8684 908-0 | @ info@otto-chemie.de www.otto-chemie.com

*\text{\text{\$\text{\$\text{\$\text{\$}}}}} Application advice \text{\$\text{\$\text{\$\text{\$\text{\$}}}} +49 8684 908-4300 \text{\$\text{\$\text{\$\text{\$\text{\$\text{\$}}}}\$ tae@otto-chemie.de







For disposal instructions, see imprint and operating instructions.