

# OTTO Flexi tape

## The glazing tape for insulating glass

PE flexible foam tape

For indoor and outdoor application

FLB

### Characteristics

- ▶ Reinforced for tensile strength
- ▶ Closed-cell
- ▶ Resistant to aging
- ▶ Compatible with OTTO silicone sealants
- ▶ Available with or without removable strip

### Fields of application

- ▶ Used as a glazing tape for insulating glass in accordance with the Rosenheim specifications

### Standards and tests

- ▶ French VOC-emission class A+

### Technical properties

Temperature resistance from/ to [°C] - 40 / + 80

Water absorption [vol. %]  $\leq 1,0$  <sup>1</sup>

Thermal conductivity according to DIN EN 12667 [W/mK]  $\leq 0,04$

Compression hardness in accordance with ISO 3386-1 with compression of 25% [kPa]  $\leq 35$

Compression hardness in accordance with ISO 3386-1 with compression of 40% [kPa]  $\leq 65$

Compression hardness in accordance with ISO 3386-1 with compression of 50% [kPa]  $\leq 95$

Storage temperature from/to [°C] + 5 / + 20

Shelf life at 23 °C/50 % RH [months] 12

1) after 7 days

These data are not suitable for the issue of specifications.  
Please contact OTTO-CHEMIE before issuing specifications.

### Packaging

#### OTTO Flexi tape with peel-off foil



Hermann Otto GmbH  
Krankenhausstr. 14 | 83413 Fridolfing, Germany  
☎ +49 8684 908-0 | @ info@otto-chemie.de  
www.otto-chemie.com

💡 Application advice  
☎ +49 8684 908-4300  
@ tae@otto-chemie.de

**OTTO**  
CHEMIE  
SEALING & BONDING

Dimensions	Colour	Order unit (OU)	Packaging unit (PU)	Order code
6 x 2 mm	anthracite	75 x 20 m pc.	75 x 20 m pc.	On request
6 x 2 mm	white	75 x 20 m pc.	75 x 20 m pc.	On request
8 x 2 mm	anthracite	75 x 20 m pc.	75 x 20 m pc.	On request
8 x 2 mm	white	75 x 20 m pc.	75 x 20 m pc.	On request
9 x 2 mm	anthracite	5 x 20 m pc.	75 x 20 m pc.	FLBM-9x2-C67
9 x 2 mm	white	5 x 20 m pc.	75 x 20 m pc.	FLBM-9x2-C01
9 x 3 mm	anthracite	5 x 20 m pc.	75 x 20 m pc.	FLBM-9x3-C67
9 x 3 mm	white	5 x 20 m pc.	75 x 20 m pc.	FLBM-9x3-C01
9 x 4 mm	anthracite	5 x 10 m pc.	150 x 10 m pc.	FLBM-9x4-C67
9 x 4 mm	white	150 x 10 m pc.	150 x 10 m pc.	On request
9 x 5 mm	anthracite	150 x 10 m pc.	150 x 10 m pc.	On request
9 x 5 mm	white	150 x 10 m pc.	150 x 10 m pc.	On request
9 x 6 mm	anthracite	100 x 10 m pc.	100 x 10 m pc.	On request
9 x 6 mm	white	100 x 10 m pc.	100 x 10 m pc.	On request
12 x 2 mm	anthracite	5 x 20 m pc.	75 x 20 m pc.	FLBM-12x2-C67
12 x 2 mm	white	75 x 20 m pc.	75 x 20 m pc.	On request
12 x 3 mm	anthracite	5 x 20 m pc.	75 x 20 m pc.	FLBM-12x3-C67
12 x 3 mm	white	75 x 20 m pc.	75 x 20 m pc.	On request
12 x 4 mm	anthracite	5 x 10 m pc.	150 x 10 m pc.	FLBM-12x4-C67
12 x 4 mm	white	150 x 10 m pc.	150 x 10 m pc.	On request
12 x 5 mm	anthracite	120 x 10 m pc.	120 x 10 m pc.	On request
12 x 5 mm	white	120 x 10 m pc.	120 x 10 m pc.	On request
15 x 2 mm	anthracite	5 x 20 m pc.	75 x 20 m pc.	FLBM-15x2-C67
15 x 2 mm	white	75 x 20 m pc.	75 x 20 m pc.	On request
15 x 3 mm	anthracite	75 x 20 m pc.	75 x 20 m pc.	On request
15 x 3 mm	white	75 x 20 m pc.	75 x 20 m pc.	On request
50 x 5 mm	anthracite	35 x 10 m pc.	35 x 10 m pc.	On request
50 x 5 mm	white	35 x 10 m pc.	35 x 10 m pc.	On request

#### OTTO Flexi tape SP without peel-off foil

Dimensions	Colour	Order unit (OU)	Packaging unit (PU)	Order code
6 x 2 mm	anthracite	70 x 20 m pc.	70 x 20 m pc.	On request
6 x 2 mm	white	70 x 20 m pc.	70 x 20 m pc.	On request
8 x 2 mm	anthracite	70 x 20 m pc.	70 x 20 m pc.	On request
8 x 2 mm	white	70 x 20 m pc.	70 x 20 m pc.	On request
9 x 2 mm	anthracite	5 x 20 m pc.	70 x 20 m pc.	FLBO-9x2-C67
9 x 2 mm	white	70 x 20 m pc.	70 x 20 m pc.	On request
9 x 3 mm	anthracite	5 x 20 m pc.	70 x 20 m pc.	FLBO-9x3-C67
9 x 3 mm	white	70 x 20 m pc.	70 x 20 m pc.	On request
9 x 4 mm	anthracite	140 x 10 m pc.	140 x 10 m pc.	On request
9 x 4 mm	white	140 x 10 m pc.	140 x 10 m pc.	On request
9 x 5 mm	anthracite	140 x 10 m pc.	140 x 10 m pc.	On request
9 x 5 mm	white	140 x 10 m pc.	140 x 10 m pc.	On request
9 x 6 mm	anthracite	140 x 10 m pc.	140 x 10 m pc.	On request
9 x 6 mm	white	140 x 10 m pc.	140 x 10 m pc.	On request
12 x 2 mm	anthracite	5 x 20 m pc.	70 x 20 m pc.	FLBO-12x2-C67
12 x 2 mm	white	70 x 20 m pc.	70 x 20 m pc.	On request
12 x 3 mm	anthracite	5 x 20 m pc.	70 x 20 m pc.	FLBO-12x3-C67
12 x 3 mm	white	70 x 20 m pc.	70 x 20 m pc.	On request
12 x 4 mm	anthracite	140 x 10 m pc.	140 x 10 m pc.	On request
12 x 4 mm	white	140 x 10 m pc.	140 x 10 m pc.	On request
12 x 5 mm	anthracite	100 x 10 m pc.	100 x 10 m pc.	On request
12 x 5 mm	white	100 x 10 m pc.	100 x 10 m pc.	On request
15 x 2 mm	anthracite	70 x 20 m pc.	70 x 20 m pc.	On request

15 x 2 mm	white	70 x 20 m pc.	70 x 20 m pc.	On request
15 x 3 mm	anthracite	70 x 20 m pc.	70 x 20 m pc.	On request
15 x 3 mm	white	70 x 20 m pc.	70 x 20 m pc.	On request
50 x 5 mm	anthracite	35 x 10 m pc.	35 x 10 m pc.	On request
50 x 5 mm	white	35 x 10 m pc.	35 x 10 m pc.	On request

Disposal

Product residues can be disposed of along with industrial waste as mixed plastics. Packaging materials (cardboard boxes, foils) are recyclable and hence should be recycled.

Warranty information

The above information and our technical application advice, whether verbal, in writing or by means of tests, are provided to the best of our knowledge, but are non-binding, including with regard to any third-party property rights. The information in this publication does not exempt the processor from carrying out their own tests on our products with regard to their suitability for the intended processes and purposes. The application, use and processing of our products and the products manufactured on the basis of our technical application advice are beyond our control and are therefore the sole responsibility of the processor. If the application for which our products are used is subject to an official authorisation requirement, the user is responsible for obtaining these authorisations. We reserve the right to adapt the product to technical progress and new developments. For the rest, we refer to our General Terms and Conditions, in particular with regard to any liability for defects. You can find our GTC at [www.otto-chemie.de](http://www.otto-chemie.de).