

OTTO Spray primer

The contact adhesive for installing the window tape



Contact adhesive for the pre-treatment of wall reveal

For indoor and outdoor application

SPRÜHPR

Characteristics

- ▶ Spray primer or contact adhesive with high adhesive strength
- ▶ Fast-drying
- ▶ Universally usable

Fields of application

- ▶ Pre-treatment of the wall reveal for the OTTO window tapes
- ▶ Bonding of EPDM rails

Technical properties

Temperature resistance from/ - 40 / + 110
to [°C]

Processing temperature from/ + 5 / + 40
to [°C]

Consumption [g/m²] 70 - 80

Open time [minutes] 3 - 4

VOC content [g/l] 544

These data are not suitable for the issue of specifications.
Please contact OTTO-CHEMIE before issuing specifications.

Pretreatment

The reveal must be cleaned of dirt and mortar residues

Important information

The materials to be bonded must be dry and free of dust and grease. Then spray the primer onto the surfaces to be bonded. A distance of 30 cm is ideal. The adhesive sheets should preferably be applied without overlap. After 2 - 4 minutes, press or roll the two surfaces firmly together. For overlapping application, at least double the open time of 3 - 4 minutes. In the case of a very porous substrate, check whether there is sufficient contact between the two adhesive layers. If necessary, spray on an additional layer.

If necessary, protect adjacent areas from undesired primer application.

Application information

Due to the many possible influences during and after application, the customer always has to carry out trials first. Please observe the recommended shelf life which is printed on the packaging.

Packaging

Container	Order unit (OU)	Packaging unit (PU)	Order code
500 ml aerosol can	1 piece	12 pieces	SPRÜHPR83

Hermann Otto GmbH
Krankenhausstr. 14 | 83413 Fridolfing, Germany
☎ +49 8684 908-0 | @ info@otto-chemie.de
www.otto-chemie.com

Application advice
☎ +49 8684 908-4300
@ tae@otto-chemie.de



SEALING & BONDING



Disposal

Product residues can be disposed of along with industrial waste as mixed plastics. Packaging materials (cardboard boxes, foils) are recyclable and hence should be recycled.

Warranty information

The above information and our technical application advice, whether verbal, in writing or by means of tests, are provided to the best of our knowledge, but are non-binding, including with regard to any third-party property rights. The information in this publication does not exempt the processor from carrying out their own tests on our products with regard to their suitability for the intended processes and purposes. The application, use and processing of our products and the products manufactured on the basis of our technical application advice are beyond our control and are therefore the sole responsibility of the processor. If the application for which our products are used is subject to an official authorisation requirement, the user is responsible for obtaining these authorisations. We reserve the right to adapt the product to technical progress and new developments. For the rest, we refer to our General Terms and Conditions, in particular with regard to any liability for defects. You can find our GTC at www.otto-chemie.de.